

July 2024

MTA - NEW YORK CITY TRANSIT

3 Stone Street

New YORK, N.Y. 10004

BID RECEPTION DESK

WWW.MTA.INFO/NYCT/PROCURE/NYCTPROC.HTM

THIS PACKAGE CONTAINS THE QUALIFIED PRODUCTS LIST (QPL) ITEMS FOR THE BELOW STATED PROCUREMENT UNIT WHICH INCLUDES THE NYCT STOCK NUMBER, ITEM DESCRIPTIONS, AND ESTIMATED USAGE.

QUALIFIED PRODUCTS LIST (QPL)

Bus Parts

PROCUREMENT UNIT: 400

Bus Parts: Items including, but are not limited to, the following:

Brake lining, undercarriage, wheels, muffler & exhaust system, front & rear parts, steering & related parts, cooling & heating, system, fuel injection, transmission, windows & bus body parts.

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
43-20-6155	BEARING, .8750" X 1.8750" X 5.000", SINGLE ROW RADIAL, PLAIN, WITH TWO SHIELDS, EXTRA LIGHT, RETAINER TYPE	WABCO FAFNIR	560667 S9-KDD	120	140
59-50-2705	MAT, RUBBER, INSULATING, 36" WIDE X 22' LONG, WITH A TOLERANCE IN LENGTH OF (-0 INCHES TO + 24 INCHES), TO BE MANUFACTURED IN ACCORDANCE WITH NYCT STANDARD SPECIFICATION FOR TRACK AND STRUCTURES MATERIALS SECTION 31 LATEST EDITION NOTE: DELIVERIES TO STOREROOMS #28, 62, 67 & 69 SHALL BE MADE ON OPEN TOP EQUIPMENT ON TUESDAYS, WEDNESDAYS AND OR THURSDAYS BETWEEN 8:00 AM AND 3:00 PM ONLY	BILTRITE CORPORATION RAVASCO TRANSMISSION PACKING P NYCTA	6123-75-22 T1C2 US-NYCT SECTION 31, 2/11/15	1731	75
61-12-3160	BOTTLE, PLASTIC (HDPE), 32 OZ. CAPACITY NECK, FINISHING SIZE TO BE 28MM/410 OR 28MM/400, NECK HEIGHT TO BE 3/8" TO 1/2", NATURAL COLOR, BOTTLE TO BE USED WITH TRIGGER ACTION SPRAYERS OBTAINED UNDER STOCK #61-46-5820 AND MUST BE COMPATIBLE WITH ALL OF THEM	IMPACT PRODUCTS INC. CONTICO INT. INC. DELTA NYCTA	5032WG 932CG B32DR2N1-A PALLET SPEC.	15832	9883
61-12-3310	BROOM, 100% CORN, 1-1/8" DIAMETER WOOD HANDLE, TOTAL LEGTH OF BROOM TO BE 57" +/- 1", BROOM BODY 11-14" WIDE 10"-17" LONG, HANDLE LENGTH 42" +/- 1", MUST MEET NYC DEPARTMENT OF PURCHASE SPECIFICATION 6-B-4: 66, TYPE A.	NIB NYSPSP GREENWOOD MOP & BROOM, INC.	330T 563	1901	1105
61-12-3405	BROOM, LOBBY, 38"-39" OVERALL LENGTH, 100% CORN AND YUCCA FIBERS WITH 8" - 9" WIDTH AND 8-1/2" TO 11" TRIM, 7-8 OZ OF CORN AND FIBERS ATTACHED TO HANDLE BY WIRE, BROOM MUST HAVE 3 ROWS OF TWINE STITCHING, PACKAGED 6 - 12 BROOMS PER BOX	OCEDAR CRYSTAL LAKE MANUFACTURING INC	6201-6 CRYSTAL LAKE #12102	3340	1954

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-12-6205	BROOM, PUSH, WITH OUT HANDLE, 18" LONG METAL BLOCK, HAS 3-1/4" TRIM LENGTH, FIBERS ARE HORSEHAIR, TAMPICO, AND PATENT FIBER, HAS AN ADJUSTABLE METAL THREADED SOCKET WHICH CAN ACCEPT 3/8" THREADED STUD HANDLES (16 TURNS PER INCH) ATTENTION USERS: HANDLES CAN BE OBTAINED UNDER COMMODITY NUMBERS; 61-24-3115, 61-24-3105, AND 61-24-3125.	MILWAUKEE DUSTLESS BRUSH CO. NYCTA	214180 PALLET SPEC	142	94
61-12-6210	BROOM, PUSH (WITHOUT HANDLE), 18" WIDE WOODEN BLOCK, FIBER SECTIION NOMINAL 2-1/2" WIDE X NOMINAL 18-1/2" LONG, X 3" TRIM LENGTH; FIBERS ARE HORSEHAIR AND ACRYLONITRILE/POLYSTYRENE; BLOCK HAS TWO BORED AND THREADED 3/4" HOLES FOR ACCEPTING 3/4" THREADED STUD HANDLE (OBTAINED UNDER STOCK #61-24-3205)	NIB NYSPPS	412	281	164
61-13-2845	BRUSH, PAINT, FLAT,100% CHINA BRISTLE (HOG'S HAIR), BRISTLE SECTION IS 3/4" TO 7/8" WIDE X NOMINALLY 5/16" THICK X 1-1/2" +/- 1/4" TRIM LENGTH, BRUSH HANDLE LENGTH (NOT INCLUDING NOMINAL 2" FERRULE), TO BE 8-5/8" +/- 2/8", "NYCT", STOCK # AND MANUFACTURER'S NAME AND PART NUMBER TO BE STAMPED ON THE HANDLE	KIRSCHNER LINZER BRUSH	310 9081	10741	7583
61-13-3445	BRUSH, OVAL SASH; FOR RAILCAR APPEARANCE PURPOSES ONLY (PAINTING/ TOUCHUP OF RAILCAR INTERIORS/EXTERIORS); TRIM LENGTH IS 2-1/8" +/- 1/8"; WIDTH OF BRISTLE SECTION (MEASURED AT BRISTLE TIPS) IS 1-1/8" +/- 1/8"; HANDLE IS 8" +/- 3/8" LONG (INCLUDING FERRULE); HANDLE IS TO BE STAMPED WITH "NYCT", "61-13-3445", AND MANUFACTURER'S NAME AND PART #'S MOST DO NOT SHED BRISTLES ONTO NEWLY PAINTED SURFACE DURING PAINTING WITH TWO-COMPONENT POLYURETHANE PAINT AND WHEN CLEANED WITH PAINT THINNERS	KIRSCHNER	320CA	119	97

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-13-3710	BRUSH, VARNISH, 2" WIDE BRISTLE SECTION; BRISTLES ARE A 70 +/- 5% CHINESE BRISTLE AND 30 +/- 5% OXHAIR BLEND; BRISTLE THICKNESS IS NOMINAL 9/16"; BRISTLE LENGTH (TRIM) IS 2" +/- 3/8" LONG; HANDLE (WOOD OR PLASTIC CONSTRUCTION) IS NOMINALLY 5-1/8" LONG (MEASURED FROM FERRULE TO HANDLE'S END).	LINZER BRUSH	TYPE-1435	457	271
61-13-6005	BRUSH, WIRE, 3 X 19 ROWS OF WIRE STRAND SETS; TO HAVE CURVED PLASTIC OR WOOD BLOCK THAT IS 13-3/4" +/- 1/8" LONG X 1" +/- 1/8" WIDE X 3/4" +/- 1/8" HIGH, WIRE STRAND SECTION TAKES UP 5-1/2" TO 6-1/2" OF TOTAL BLOCK LENGTH; WIRE STRANDS TO BE 0.013" TO 0.014" THICK WITH A MINIMUM OF 22 (2 X 11) WIRE STRANDS PER WIRE STRAND SET; WIRE STRANDS TO HAVE 1-1/8" +/- 1/8" TRIM LENGTH WIRE STRANDS TO BE MADE OF UNS G10590 OR G10640 CARBON STEEL WIRE (SEE ASTM A510-91) EXCEPT MIN. MN CONTENT CAN BE 0.45%; WIRE STRANDS' MAX. PB CONTENT TO BE 0.005%; MFG'S NAME, PART #, "NYCT" + STOCK # TO APPEAR ON BRUSH	SOLO-HORTON ASTM NYCTA	W210 A510-91 PALLET SPEC.	2717	1798
61-13-6060	BRUSH, WIRE, 1 X 17 ROWS, STEEL WIRE STRANDS WITH MINIMUM 98.2% IRON, TO BE LEAD FREE; WIRE STRANDS TO BE .0125" TO .0135" THICK; 36 (2 X 18) WIRE STRANDS PER HOLE (WIRE STRAND SET); WIRE STRAND LENGTH OUT OF BRUSH TO BE 1-3/16" +/- 1/16"; WOOD BLOCK (SHOE HANDLE) TO BE ABOUT 10-3/8" LONG X 1" X 7/16"; MANUFACTURER'S NAME & PART NUMBER TO APPEAR ON BRUSH ALONG WITH "NYCT" PLUS STOCK NUMBER	PFERD INC.	A67757	36	70

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-13-6065	BRUSH, WIRE, 2X MINIMUM 15 ROWS OF WIRE STRAND SETS; TO HAVE A TAPERED WOODEN BLOCK THAT IS NOMINALLY 10" LONG X 5/8" WIDE X 7/8" THICK; WIRE STRAND SECTION TAKES UP 4-5/8" TO 5" OF TOTAL BLOCK LENGTH; WIRE STRANDS TO BE 0.012" TO 0.013" THICK WITH A MINIMUM OF 26 (2X13) WIRE STRANDS PER WIRE STRAND SET; WIRE STRANDS TO HAVE 1-1/16" TO 1-1/8" TRIM LENGTH; WIRE STRANDS TO BE MADE OF UNS G10590 OR G10600 CARBON STEEL (SEE ASTM A-510) EXCEPT THAT MINIMUM MN CONTENT CAN BE 0.44%; WIRE STRAND'S MAXIMUM PB CONTENT 0.002%; MFG'S NAME, PART #, "NYCT", & STOCK # TO APPEAR ON BRUSH	E. GORNELL & SONS GORDON BRUSH MFG. CO., INC. ASTM	162 567120 510	268	116
61-13-6075	BRUSH, WIRE, HAS 4 ROWS OF WIRE STRAND SETS, THE OUTSIDE 2 ROWS HAVING 16 SETS AND THE INSIDE 2 ROWS HAVING 17 SETS; TO HAVE A WOODEN "SHOE" HANDLE BLOCK THAT IS 9-7/8" TO 10" LONG, 1-1/8" WIDE, AND 3/4" THICK; BRISTLE SECTION TAKES UP 4-5/8" TO 5" OF TOTAL BLOCK LENGTH; WIRE STRANDS TO BE .012" TO .013" THICK WITH A MINIMUM OF 24 (2 X 12) WIRE STRANDS PER WIRE STRAND SET; WIRE STRANDS TO HAVE 1" TO 1-1/4" TRIM LENGTH, WIRE STRANDS TO BE MADE OF USN G10590 OR G10600 CARBON STEEL (ASTM A-510) EXCEPT THAT MINIMUM MN CONTENT CAN BE 0.43%; MAXIMUM PB CONTENT OF WIRE TO BE 0.005%; MFG'S NAME TO APPEAR ON BRUSH; MFG'S PART # MUST APPEAR ON CARTONS BRUSHES ARE SHIPPED IN	OSBORN ASTM	54018 A-510	1267	735
61-13-6105	BRUSH, BRASS WIRE; 3 X 13 ROWS; BRASS (63-78% COPPER, 22-36% ZINC) WIRE STRANDS TO BE 0.006" TO 0.0065" THICK; 70-80 WIRE STRANDS (2 X 35-40) PER HOLE (WIRE STRAND SET); WIRE STRAND LENGTH TO BE 0.5" +/- 1/16"; WOODEN BLOCK TO BE NOMINALLY 7" LONG X 9/16" WIDE X 5/16" HIGH; MANUFACTURER'S NAME, PART #, "NYCT" AND STOCK # TO APPEAR ON BRUSH	GORDON BRUSH MFG. CO., INC. KIRSCHNER	321112 K383	7103	5114

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-16-4290	MAT, OIL ABSORBENT, POLYPROPYLENE BASED; 30" +/- 1/6" WIDE X 150' LONG ROLLS; AS MEASURED BY ASTM 828, TO HAVE MINIMUM TENSILE STRENGTHS OF 2.3 LB/IN (DRY MACHINE DIRECTION), 1.75 LB/IN (WET [SAE 10W] MACHINE DIRECTION), 2.54 LB/IN (DRY CROSS DIRECTION), 2.15 LB/IN (WET [SAE 10W] CROSS DIRECTION); AS MEASURED BY FED SPEC UUT591D, TO HAVE MINIMUM ABSORPTIONS OF 1.67 G SAE 10W OIL/SQ IN MAT AND 1.13 G #2 DIESEL FUEL/SQ IN MAT; AS MEASURED BY ASTM D1117-80, TO HAVE MAXIMUM ABSORBENCY TIMES OF 180 SECONDS (SAE 10W OIL) AND 5 SECONDS (#2 DIESEL FUEL); EACH ROLL PACKAGED IN TRANSPARENT PLASTIC WRAPPER WITH MANUFACTURER'S NAME AND PART NUMBER, STOCK #, AND PO# APPEARING ON WRAPPER (ON PAPER)	SORBENT PRODUCTS CO ASTM ASTM NYCTA FED. SPEC.	ENV150 828 D1117-80 PALLET SPEC UUT591D	351	184
61-16-4291	BAG, FILTER, FOR USE IN WATER FILTRATION SYSTEM FOR TREATMENT OF RAILCAR AIR CONDITIONER CONDENSER WASHING EFFLUENT IN ORDER TO MEET SEWER DISCHARGE CODES. USED IN 4 X 16 BAG FILTER TANK. 7" DIAMETER X 24" LONG. 50 MICRON POLYPROPYLENE BAG. 50 BAGS PER CASE. 8 CASES PER PALLET	SABO INDUSTRIAL CORP.	247RCRS50	450	700
61-24-3810	HANDLE, MOP, 54" LONG, FIBERGLASS, WITH OUT MOPHEAD, HAS A SPRING-ACTIVATED, JAW-LIKE PLASTIC GRIPPER TO HOLD MOP HEAD; GRIPPER CONSTRUCTION TO BE SUCH THAT A DIRTY MOP HEAD CAN BE REMOVED FROM IT BY STEPPING ON IT AND TWISTING HANDLE FROM TOP (MANUAL HANDLING OF MOP HEAD UNNECESSARY)	IMPACT PRODUCTS INC. NYCTA	#61 PALLET SPEC	3420	1674

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-24-4000	KIT, ABRASIVE PAD CLEANING, TO CONSIST OF: 1)A 9" LONG X 3-3/4" WIDE PLASTIC APPLICATOR HEAD WITH PLASTIC STUDED GRIPS AND THAT HAS A MOVEABLE THREADED RECEPACLE THAT ACCEPTS 3/4" DIAMETER STUD ON HANDLES OBTAINED UNDER STOCK #'S 61-24-3205-3215(HANDLE NOT IN KIT) 2) ONE 4-1/2" X 10" X 7/8" MINERAL-IMPREGNATED POLYESTER FIBER CLEANING PAD THAT HAS AN ABRASIVENESS INDEX OF 10.71+/- 1.07 AS MEASURED BY ASTM 1015-86(REAPPROVED 1991) AS MODIFIED PER NOTE 2 BELOW; AND 3) ONE 4-1/2" X 10" X 7/8" MINERAL-IMPREGNATED NYLON + POLYESTER SCRUBBING PAD THAT HAS AN ABRASIVENESS INDEX OF 15.82 +/- 1.58 AS MEASURED BY ASTM F1015-86 (REAPPROVED 1991) AS MODIFIED PER NOTE 2 BELOW. NOTE: PART # DESIGNATION IN MFG'S PART # FIELD SHALL BE KIT PART # = APPLICATOR HEAD PART # + CLEANING PAD PART # + SCRUBBING PAD PART #. NOTE 2: ASTM F1015-86 (REAPPROVED 1991) MODIFIED TO USE A 5-LB WEIGHT, NOTRHT BROS. "TRYMER 190" ISOCYANURATE FOAM AND RESULTS ARE NOT TO BE ROUNDED TO NEAREST INTERGER. 24" X 24" SPECIMENS ARE TO BE CONSTRUCTED BY TAPING TOGETHER THE BACK SIDE OF SUFFICIENT PADS + THEN ATTACHING THEM TO A PLYWOOD SUBSTRATE USING CONTACT ADHESIVE	MINNESOTA, MINING & MANUFACTUR MINNESOTA, MINING & MANUFACTUR	6472=DOODLEBUGPADHOLDR+8440+85 F1015-86 (REAPPROVED 1991)	2104	1770
61-28-4001	APPLICATOR HEAD, FOR CLEANING/ABRASIVE PADS, PLASTIC; 10-7/8" LONG X 5" WIDE WITH VELCRO PADS; HAS A MOVABLE THREADED RECEPACLE TO ACCEPT 3/4" DIAMETER STUD ON HANDLES OBTAINED UNDER STOCK #'S 61-24-3205 & 61-24-3215	MINNESOTA, MINING & MANUFACTUR	261	0	10

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-28-4002	PAD, CLEANING AND POLISHING, MINERAL IMPREGNATED SYNTHETIC FIBER; PAD IS 6" X 12" X 1/4" THICK; PAD HAS AN ABRASIVENESS INDEX OF 6.43 +/- .64 AS MEASURED BY ASTM F1015-86 (REAPPROVED 1991) AS MODIFIED AS FOLLOWS: (1) USES A 5-LB WEIGHT AND NORTH BROS. "TRYMER 190" ISO CYANURATE FOAM (2) RESULTS ARE NOT TO BE ROUNDED OFF TO NEAREST INTEGER (3) 24" X 24" SPECIMENS ARE TO BE CONSTRUCTED BY TAPING TOGETHER SUFFICIENT PADS AND THEN ATTACHING THEM TO A PLYWOOD SUBSTRATE USING CONTACT ADHESIVE); FOR USE WITH APPLICATOR HEAD AVAILABLE UNDER STOCK # 61-28-4001; PACKAGED 50 SHEETS PER CASE	MINNESOTA, MINING & MANUFACTUR	048011-16064-1 (TYPE T)	0	0
61-28-4003	PAD, POLISHING, MINERAL-IMPREGNATED SYNTHETIC FIBER; PAD IS 6" X 12" X 3/4" THICK; PAD HAS AN ABRASIVENESS INDEX OF 6.39 +/- .64 AS MEASURED BY ASTM F 1015-86 (REAPPROVED 1991) AS MODIFIED AS FOLLOWS: (1) USES A 5-LB WEIGHT AND NORTH BROS. "TRYMER 190" ISOCYANURATE FOAM, 2)RESULTS ARE NOT TO BE ROUNDED OFF TO NEAREST INTEGER, 3)24" X 24" SPECIMENS ARE TO BE CONSTRUCTED BY TAPING TOGETHER SUFFICIENT PADS AND THEN ATTACHING THEM TO A PLYWOOD SUBSTRATE USING CONTACT ADHESIVE; FOR USE WITH APPLICATOR HEAD AVAILABLE UNDER STOCK NUMBER 61-28-4001; PACKAGED 50 SHEETS/CASE	MINNESOTA, MINING & MANUFACTUR	048011-90573-0 (SUPER POLISH)	0	0
61-31-0210	BASE, MAGNETIC, RUBBER MATERIAL. TO BE USED WITH CORRESPONDING D-CELL LED FLAGGING LANTERNS. TO BE MANUFACTURED IN ACCORDANCE WITH SECTION 82A	EFLARE NYCTA	939-EFRAILMAGBASE SECTION 82A 5/24/18	2934	1990

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-31-0940	LANTERN, FLAGGING, WITH AMBER LED BULB OR CLUSTER, D-CELL BATTERY OPERATED, CLEAR GLOBE, WITH LOW BATTERY LED WARNING LIGHT. TO BE USED WITH CORRESPONDING MAGNETIC BASE. TO BE MANUFACTURED IN ACCORDANCE WITH SECTION 82A	EFLARE NYCTA	939-RB610A-NYCT SECTION 82A 5/24/18	4490	3146
61-31-0942	LANTERN, FLAGGING, WITH GREEN LED BULB OR CLUSTER, D-CELL BATTERY OPERATED, CLEAR GLOBE, WITH LOW BATTERY LED WARNING LIGHT. TO BE USED WITH CORRESPONDING MAGNETIC BASE. TO BE MANUFACTURED IN ACCORDANCE WITH SECTION 82A	EFLARE NYCTA	939-RB610G-NYCT SECTION 82A 5/24/18	1117	1039
61-31-0944	LANTERN, FLAGGING, WITH RED LED BULB OR CLUSTER, D-CELL BATTERY OPERATED, CLEAR GLOBE, WITH LOW BATTERY LED WARNING LIGHT. TO BE USED WITH CORRESPONDING MAGNETIC BASE. TO BE MANUFACTURED IN ACCORDANCE WITH SECTION 82A	EFLARE NYCTA	939-RB610R-NYCT SECTION 82A 5/24/18	1753	1294
61-36-2670	MAT, OIL ABSORBENT, POLYPROPYLENE & POLYESTER; TO HAVE NON-POROUS BACKING; TO COME IN 36" X 100' LONG ROLLS; MINIMUM ROLL THICKNESS TO BE .07"; TO HAVE MINIMUM DRY TENSILE STRENGTHS AS MEASURED BY ASTM D828/829 OF 55 LB/IN CROSS DIRECTION AND 95 LB/IN IN MACHINE DIRECTION; MINIMUM OIL (SAE 10) ABSORBENCY AS MEASURED BY FED. SPECIFICATION UUT591D TO BE .75 G/IN 2; MINIMUM #2 DIESEL FUEL ABSORBENCY AS MEASURED BY FED. SPECIFICATION UUT591D TO BE .55 G/IN 2; MAXIMUM #2 DIESEL FUEL ABSORBENCY TIME AS MEASURED BY ASTM D117-80 TO BE 40 SECONDS; EACH ROLL TO BE PACKAGED IN A TRANSPARENT PLASTIC WRAPPER WITH MANUFACTURER'S NAME & PART #, STOCK #, & PO # APPEARING ON A STICKER ON THE WRAPPER 100 FT PER ROLL 100 FT PER ROLL	CHEMTEX	PBRNP	149	76

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-41-1010	PAD, SCRUBBING, ABRASIVE, MINERAL-IMPREGNATED NYLON + POLYESTER; TO BE 4-1/2" X 10" X 7/8"; TO HAVE AN ABRASIVENESS INDEX OF 15.8 +/- 1.58 AS MEASURED BY ASTM F1015-86 (REAPPROVED 1991) AS MODIFIED PER NOTE 1 BELOW; PACKAGED 5 PADS PER BOX; USED AS A REPLACEMENT PAD IN CONJUNCTION WITH THE ABRASIVE PAD CLEANING KIT OBTAINED UNDER STOCK # 61-24-4000. NOTE 1: ASTM F1015-86 (REAPPROVED 1991) MODIFIED TO USE 5-LB WEIGHT, NORTH BROS. "TRYMER 190" ISOCYANURATE FOAM, AND RESULTS ARE NOT TO BE ROUNDED TO NEAREST INTERGER; 24" X 24" SPECIMENS ARE TO BE CONSTRUCTED BY TAPING TOGETHER THE BACK SIDES OF SUFFICIENT # OF PADS AND THEN ATTACHING THEM TO A PLYWOOD SUBSTRATE USING CONTACT ADHESIVE	MINNESOTA, MINING & MANUFACTUR ASTM	8541 F1015-86 (REAPPROVED 1991)	586	360
61-41-1080	PAD, SCRUBBING, ABRASIVE; MINERAL-IMPREGNATED SYNTHETIC FIBER; TO BE 3.5" X 5" X 1" (THICKNESS); TO HAVE AN ABRASIVENESS INDEX OF 21.17 +/- 2.12 AS MEASURED BY ASTM F1015-86 (REAPPROVED 1991) AS MODIFIED BY NOTE 1 BELOW; PACKAGED 40 PADS/CASE; NOTE 1- F1015-86 (REAPPROVED 1991) MODIFIED TO USE 5 LB. WEIGHT, NORTH BROS. "TRYMER 190" ISOCYANURATE FOAM AND RESULTS NOT TO BE ROUNDED TO NEAREST INTEGER; NOTE 2 - 24" X 24" SPECIMENS FOR TEST VIA THE ASTM TEST METHOD ARE TO BE CONSTRUCTED BY TAPING THE BACKSIDE OF A SUFFICIENT # OF PADS AND THEN ATTACHING THEM TO A PLYWOOD SUBSTRATE USING CONTACT ADHESIVE 40 PADS/CASE	MINNESOTA, MINING & MANUFACTUR ASTM	9030 F1015-86 (REAPPROVED 1991)	1	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-41-2270	BUCKET, MOPPING, 35 QUART, YELLOW, PLASTIC; BUCKET COMES WITH A MOSTLY PLASTIC DOWNWARD PRESSURE WRINGER THAT CAN HANDLE 24-32 OZ. MOP HEADS; BUCKET HAS 3" REPLACABLE CASTERS, CASTERS NOT TO SIT IN A METAL FRAME UNDERCARRIAGE, MANUFACTURER'S NAME TO APPEAR ON BUCKET AND WRINGER, PICTOGRAM OF SLIPPING MAN TO APPEAR ON BUCKET, ONE BUCKET AND ONE WRINGER PACKAGED PER BOX. NOTE: IN MANUFACTURER'S PART NUMBER FIELD, THE DESIGNATION SHALL BE MOPPING SET PART NUMBER(=BUCKET PART NUMBER/WRINGER PART NUMBER)	CONTINENTAL MFG. RUBBERMAID NYCTA	335-37YW(=335-3YW/SW7) 7577-88 (=7570-88/7575-88) PALLET SPEC	606	507
61-41-2271	BUCKET, MOPPING, 26 QUART PLASTIC BUCKET COMES WITH SIDEWARD PRESSURE WRINGER. BUCKET HAS 3" CASTERS; BUCKET MUST BE BLUE OR YELLOW, PACKAGED ONE BUCKET AND ONE WRINGER PER BOX; NOTE: IN THE MANUFACTURERS PART NUMBER FIELD, THE DESIGNATION IS MOPPING SET PART NUMBER=(BUCKET PART NUMBER/WRINGER PART NUMBER); NO ASSEMBLY TO BE REQUIRED	RUBBERMAID NYCTA	7480(=7470/612788) PALLET SPEC	267	80
61-41-3705	PAN, DUST, HOODED PAN IS CAPABLE OF SWINGING TO AN UPRIGHT POSITION, PAN IS 11" TO 12" WIDE AT MOUTH, 11-1/2" TO 12-1/2" LONG FROM DEEPEST POINT TO EDGE, 4-1/2" TO 5-1/2" HIGH, MADE OF 20-26 GAGE GALVANIZED STEEL, DUSTPAN HAS A 30" TO 32" LONG WOODEN SWING HANDLE.	CORCRAFT/DEPT. OF CORRECT.SERV NYCTA	M04-531000 PALLET SPEC	107	60
61-41-3740	PAN, DUST, PLASTIC, PLASTIC PAN IS CAPABLE OF SWINGING TO AN UPRIGHT POSITION; PAN IS NOMINALLY 10-1/2" TO 11" DEEP; 4-1/2" TO 5" HIGH AT HIGHEST POINT AND 12"-12-1/2" WIDE; FIBERGLASS SWING HANDLE ITSELF 25"-26" TALL; TOP OF HANDLE TO BE ABOUT 31" FROM BOTTOM OF PAN	IMPACT PRODUCTS INC. NYCTA	2602 PALLET SPEC	2125	1589

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
61-44-2154	WIPER, WHITE CREPED CELLULOSE AND POLYESTER, 12" X 16.5" SHEETS; PRODUCT PROVIDED MUST BE SONTARA AMERICA SONTARA EC CREPED PR922"; VENDOR MUST PROVIDE A LETTER FROM SONTARA AMERICA STATING THAT VENDOR IS AN AUTHORIZED DISTRIBUTOR/CONVERTER AND IS SUPPLYING NYCT WITH GENUINE SONTARA AMERICA "SONTARA EC CREPED PR922" UNDER THE PO. 250 SHEETS/BOX 250 SHEETS/BOX 250 SHEETS/BOX	SONTARA AMERICA NYCTA	SONTARA EC CREPED PR922 PALLET SPEC	29399	19208
61-44-4617	COVER, PAINT ROLLER, 7" LONG, HAS NOMINAL 3/16" HIGH 100% ACRYLIC NAP; CORE INTERNAL DIAMETER IS NOMINALLY 1-7/16"; POLYPROPYLENE CORE; FOR USE WITH ALL PAINTS, INCLUDING TWO-COMPONENT POLYURETHANE PAINT	LINZER BRUSH	RC 100	540	2269
61-44-4627	FRAME, PAINT ROLLER, 7", 5-WIRE CAGE TYPE, CAGE IS 7" LONG X NOMINALLY 1-1/2" IN DIAMETER, TOTAL LENGTH OF FRAME IS 13 TO 13-1/2", HANDLE IS BENT AT A NOMINAL 115-120 DEGREE ANGLE, FRAME IS FOR USE WITH 6' EXTENSION POLE (STOCK # 61-24-3215) AND 7" PAINT ROLLER FRAME COVERS (STOCK #'S 61-44-4617, 4616, 4615), THE INTERIOR OF ITS 5-1/2" LONG PLASTIC GRIP IS THREADED TO ACCEPT 6' EXTENSION POLE, COMES WITHOUT COVER, FRAME MUST NOT BREAK WHEN USED WITH 6' EXTENSION POLE AND 7" PAINT ROLLER COVERS	CHARLES E. GREEN & SON'S	167250AR-#1	8557	10937
69-02-2500	OIL, KEROSENE, REFINED PETROLEUM DISTILLATE, UNDYED. TO BE A HOMOGENEOUS MIXTURE OF HYDROCARBONS, TO BE FREE FROM WATER, INORGANIC ACIDIC AND BASIC COMPOUNDS. MUST MEET ASTM D 3699-90 STANDARD SPECIFICATION NO. N 1-K/2-K GRADE. EXCEPT THAT COPPER STRIP CORROSION (ASTM D130) CAN ALSO BE MEASURED AT 2 HRS & 212 DEGREES F (INSTEAD OF 3 HRS & 212 DEGREES F) AND HAVE A RATING OF 1A; SULFUR CONTENT MUST NOT EXCEED 0.05% BY WEIGHT; PACKED	SPRAGUE DAVID WEBER OIL CO. NYCTA NYCTA	KEROSENE (UNDYED) ULTRA LOW SULFUR KEROSENE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	IN 55 GALLON NON-RETURNABLE DRUMS. CERTIFICATE OF ANALYSIS TO INCLUDE SULFUR CONTENT MUST BE PROVIDED FOR EACH BATCH. THIS PRODUCT MUST BE RECEIVED BY NYCT TRANSIT WITHIN 24 MONTHS OF THE DATE OF MANUFACTURER				
69-05-0660	GRAPHITE, FLAKED; BULK DRY; 85% TO 95% OF FLAKES CAN PASS THROUGH A 200 MESH SCREEN; PACKAGED IN 25-LB PAILS; CERTIFICATE OF ANALYSIS COVERING PERCENTAGE OF FLAKES THAT PASS THROUGH OR CAUGHT BY 200 MESH SCREEN TO BE PROVIDED FOR EACH BATCH SHIPPED	ASBURY GRAPHITE NYCTA NYCTA	NAT FLAKE GRAPHITE:99+CARBN 32 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	25
69-05-0700	LUBRICANT, GRAPHITE IN AEROSOL 16-OZ. CANS(9 OZ NET WEIGHT), 12 CANS PER CASE; FOR OUTSIDE MIRROR JOINTS & BRAKE SHOE ROLLERS & CAMS; MUST BE CFC FREE; MUST HAVE A DRYING TIME 3 TO 5 MINUTES AND SOLID CONTENT 2.75% TO 4.75%. CERTIFICATE OF ANALYSIS WHICH INCLUDES SOLID CONTENT & CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH BATCH SHIPPED. NOTE: FLASHPOINT REQUIREMENT OF NYCT SPECIFICATIONS IS NOT APPLICABLE 12 CANS PER CSE	MIRACLE POWER PROD NYCTA NYCTA	DGF 123 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	26	3
69-05-0702	LUBRICANT, FOR ROLLER DRIVE AND CONVEYOR CHAINS, AEROSOL, 12 OZ. NET WEIGHT IN A 16 OUNCE CAN. MINERAL OIL BASED; USED TO LUBRICATE RABBIT ON DROP TABLE ALSO FOR CONVEYOR CHAINS, HOIST CHAINS, LINK AND ROLLER ASSEMBLIES. PENETRATES, LUBRICATES AND PROTECTS MOVING PARTS. DOES NOT CONTAIN SILICONE. NON-DRYING FILM. FLASHPOINT > 370 DEGREES F., VOC CONTENT 15% BY WEIGHT; 1.09 LB/GAL. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES, LIGHTWEIGHT NITRILE GLOVES.	CRC INDUSTRIES, INC. NYCTA NYCTA	FOOD GRADE CHAIN LUBE 03055 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	1

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-05-0705	COMPOUND, LAPPING, 320 GRIT, SILICON CARBIDE, GREASE MIX, ONE POUND CAN. 1 LB CAN	HENKEL CORPORATION NYCTA NYCTA NYCTA	CLOVER SILICON CARBIDE 39510 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S NYCTA MARKING	17	10
69-10-1725	GREASE, ELECTRIC MOTOR BEARING, NLGI # 2 GRADE, HIGH TEMPERATURE, LITHIUM COMPLEX BASED, MINIMUM FLASHPOINT TO BE 475 DEGREES F (246 DEGREES C); BASE OIL VISCOSITY @ 40 DEGREES C TO BE 115 CST +/- 11.5 CST VIA ASTM D445; BASE OIL VISCOSITY INDEX TO BE APPROXIMATELY 95 VIA ASTM D2270; MINIMUM DROPPING POINT TO BE 210 DEGREES C, VIA ASTM D2265; WORKED (60 STROKES) PENETRATION @ 25 DEGREES C TO 265-295 VIA ASTM D217; FOUR BALL WEAR TEST SCAR (ASTM D2266) RESULTS FOR [10 KG, 1800 RPM, 75 DEGREES C] AND [40 KG, 1200 RPM, 75 DEGREES C] TO BE MAXIMUM OF 0.28 MM AND 0.45 MM RESPECTIVELY; MUST PASS RUST PROTECTION TESTING (ASTM D1743); PACKAGED IN 120-LB DRUMS, CERTIFICATE OF ANALYSIS COVERING DROPPING POINT AND WORKED PENETRATION TO ACCOMPANY EACH BATCH SHIPPED. IN 120LB DRMS	NYCTA EXXON MOBIL CORP. NYCTA	CCSS-001, REV I, 3-9-11, LABEL UNIREX N2 CCSS-003 REV E 9/11/17 RESTR S	19	9
69-10-1735	GREASE, ELECTRIC MOTOR BEARING, NLGI #2 GRADE, HIGH TEMPERATURE, LITHIUM COMPLEX BASED, MINIMUM FLASHPOINT TO BE 475 DEGREES F (246 DEGREES C); BASE OIL VISCOSITY @ 40 DEGREES C TO BE 115 CST +/- 11.5 CST VIA ASTM D445; BASE OIL VISCOSITY INDEX TO BE APPROXIMATELY 95 VIA ASTM D2270; MINIMUM DROPPING POINT TO BE 210 DEGREES C, VIA ASTM D2265; WORKED (60 STROKES) PENETRATION @ 25 DEGREES C TO 265-295 VIA ASTM D217; FOUR BALL WEAR TEST SCAR (ASTM D2266) RESULTS FOR {10 KG, 1800 RPM, 75 DEGREES C} AND [40 KG, 1200 RPM, 75 DEGREES C] TO BE MAXIMUM OF 0.28 MM AND 0.45 MM RESPECTIVELY; MUST PASS RUST PROTECTION TESTING (ASTM D1743); PACKAGED IN 13.7 - 14.1 OZ TUBES.	EXXON MOBIL CORP. NYCTA NYCTA	UNIREX N2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	743	680

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	CERTIFICATE OF ANALYSIS COVERING DROPPING POINT AND WORKED PENETRATION TO ACCOMPANY EACH BATCH SHIPPED.				
69-10-1915	GREASE, FOR BEARINGS; 14.5 OZ. CARTRIDGES. USED FOR LUBRICATING TURNTABLE BEARINGS AND PBM SWIVEL JOINT ON STINGRAY STANDARD TURNTABLE POWER WASHER TANK. NLGI GRADE #2, VISCOSITY 3300 SUS @ 100F & 190 SUS @ 210F, DROPPING POINT 500F, POUR POINT 10F, WORKED PENETRATION 265-295 @ 60 STROKES. 40 CARTRIDGES PER CARTON. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF COMPLIANCE FOR EACH BATCH. C OF A TO INCLUDE WORKED PENETRATION. PPE REQUIRED CHEMICAL SAFETY GLASSES, NITRILE OR NEOPRENE GLOVES 14 OZ CART	LUBRIPLATE LUBRICANTS CO. NYCTA NYCTA	LUBRIPLATE NO 1444 #L0227-098 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	40	0
69-10-2403	GREASE, EXTREME PRESSURE, MULTI-PURPOSE, LITHIUM BASED; FOR BEARINGS; MUST HAVE #2 NLGI CONSISTENCY GRADE, PENETRATION (WORKED 60 STROKES) 265-295, DROPPING POINT MINIMUM OF 355 DEGREES F, PACKED IN 14 OZ. CARTRIDGE. 14OZ PER CTDG	PHILLIPS 66 LUBRICANTS NYCTA NYCTA	DYNALIFE 220 #2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	118	200
69-10-3130	GREASE, SILICONE, FOR MASKING ELECTRIC MOTORS PRIOR TO APPLYING VARNISH; MUST MEET THE REQUIREMENTS OF COMMERCIAL ITEM DESCRIPTION A-A-59173 TYPE II. PACKAGED IN 30LB(5 GALLON) CONTAINERS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS/ CERTIFICATE OF COMPLIANCE FOR EACH BATCH. CERTIFICATE OF ANALYSES TO INCLUDE: PENETRATION, BLEEDING, EVAPORATION RATE MUST BE PROVIDED FOR EACH BATCH 30 LB/CONTAINER 30 LB/CONTAINER	SYNCO CHEMICAL COMMERCIAL ITEM NYCTA NYCTA	SYNCOSIL SILICONE GREASE A-A-59173-II CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	510	330

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-3140	GREASE, DI-ELECTRIC, NON-CURING SILICONE, FOR USE TO SEAL, LUBRICATE, PROTECT AND INSULATE ELECTRICAL CONNECTORS AND COMPONENTS; CERTIFICATE OF ANALYSIS AND COMPLIANCE MUST CONTAIN PERCENT SOLIDS IN THE RANGE OF 13 TO 15 AND DENSITY BETWEEN 5.80 TO 5.95 PPG; PACKAGED IN 16 OZ. CAN WITH NET FILL OF 10 OZ; 12 CANS PER BOX	CRC INDUSTRIES, INC. NYCTA NYCTA	DI-ELECTRIC GREASE (03082) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-10-3161	GREASE, HIGH GRADE, SOAP BASE, THICKENED, RUST AND OXIDATION INHIBITOR TYPE GREASE. FOR LUBRICATING JOURNAL BEARINGS ON R10- TO R62 CARS, IN 120 LB NON-RETURNABLE DRUMS. MUST BE SUPPLIED IN MANUFACTURER SEALED DRUMS. CERTIFICATE OF ANALYSIS FOR EACH BATCH TO BE SUPPLIED PRIOR TO SHIPMENT AND TO ACCOMPANY EACH SHIPMENT 120 LB PER DRUM	EXXON MOBIL CORP. NYCTA NYCTA ASSOC. OF AMERICAN RAILROAD	ARAPEN RB 320 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S M-942-88	4320	2280
69-10-3163	GREASE, EXTREME PRESSURE, (RAIL CURVE) NLGI GRADE O. TO BE MANUFACTURED IN ACCORDANCE WITH NYCTA SPECIFICATIONS SECTION 48 TRACK AND STRUCTURES MATERIALS WITH THE VARIABILITY IN CONSISTENCE FROM 355 TO 370 OR 370 AND 385 UPON TA ORDER REQUEST. VENDOR WILL SUPPLY PRODUCT IN 35 LB. PLASTIC PAILS LINED WITH A 4 MILL MIN. THICKNESS LINER SEALED INSIDE LID. VENDOR WILL AFFIX TA COMMODITY NUMBER 69-10-3163 TO LID AND SHELL. VENDOR WILL SUPPLY ORDERS OF A MINIMUM AMOUNT OF 1750 LB. TO DESIGNATED LOCATION IN THE 5 BOROUGHES. VENDOR WILL REQUEST 48 HOURS IN ADVANCE DELIVERY APPOINTMENT. VENDOR WILL BE GOVERNED BY RESULTS OF RANDOM TESTING THROUGHOUT THE LIFE OF CONTRACT. VENDOR WILL REMOVE ANY PRODUCT THAT FAILS TO MEET SPECIFICATIONS. VENDOR WILL BE RESPONSIBLE FOR OFF LOADING SHIPMENT. VENDOR WILL SUPPLY	SUMMIT LUBRICANTS DAVID WEBER OIL CO. NYCTA NYCTA	ABBALUBE NYC#5 RAIL CURVE GREASE CURVEGARD O CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	TWO LB. SAMPLE FOR TESTING BY T.A. PRIOR TO BEING AWARDED BID				
69-10-3165	GREASE, WHEEL FLANGE & R142A BRAKE HANGER; LITHIUM SOAP THICKENED; CONTAINS EP ADDITIVES AND MOLYBDENUM DISULFIDE; NLGI GRADE O; WORKED PENETRATION (60X) VIA W1 2.040 TO BE 355 TO 385 MM/10; CERTIFICATE OF COMPLIANCE & ANALYSIS COVERING WORKED PENETRATION TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 18 KG (39.6 LB) PAILS 18 KG PER PAIL 18 KG PER PAIL	SOPUS PRODUCTS NYCTA NYCTA	SHELGADUSRAILS2 WHEELFLANGGRES CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-10-3200	GREASE, RAILCAR BRAKE CYLINDER, NLGI GRADE #1.5; BASE OIL IS A BLEND OF MINERAL OIL AND SYNTHETIC HYDROCARBON FLUID WITH LITHIUM COMPLEX THICKENER; GREASE TO HAVE GOOD CONTINUOUS PERFORMANCE AT TEMPERATURES RANGING FROM -40 DEGREES F TO 300 DEGREES F; MINIMUM FLASH POINT 290 DEGREES F; MINIMUM DROPPING POINT VIA ASTM D 2265 TO BE 250 DEGREES C; TYPICAL WORKED (X60) PENETRATION TO BE 310. 1MM VIA ASTM D217; BASE OIL VISCOSITY @ 40 DEGREES C TO BE 100 TO 135 CST; BASE OIL VISCOSITY @ 100 DEGREES C TO BE 13.1 TO 15.9 CST; BASE OIL VISCOSITY INDEX TO BE 145 TO 155; TIMKEN OK LOAD VIA ASTM D2509 TO BE 50 TO 70 LBS; PACKAGED IN 120-LB DRUMS; CERTIFICATE OF ANALYSIS COVERING BASE OIL VISCOSITY @ 40 DEGREES C AND CERTIFICATE OF CONFORMANCE/COMPLIANCE TO BE SUPPLIED PRIOR TO SHIPMENT AND MUST ACCOMPANY EACH SHIPMENT 120 LB PER DRUM	ESSO IMPERIAL OIL EXXON MOBIL CORP. NYCTA NYCTA	EPIC EP 102 EPIC EP 102 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	840	120

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-3202	GREASE, RAILCAR BRAKE CYLINDER, NLGI GRADE # 1.5; BASE OIL IS A BLEND OF MINERAL OIL AND SYNTHETIC HYDROCARBON FLUID WITH LITHIUM COMPLEX THICKENER; GREASE TO HAVE GOOD CONTINUOUS PERFORMANCE AT TEMPERATURES RANGING FROM -40 DEGREES F TO 300 DEGREES F; MINIMUM FLASH POINT 290 DEGREES F; MINIMUM DROPPING POINT VIA ASTM D 2265 TO BE 250 DEGREES C; TYPICAL WORKED (X60) PENETRATION TO BE 310. 1MM VIA ASTM D217; BASE OIL VISCOSITY @40 DEGREES C TO BE 100 TO 135 CST; BASE OIL VISCOSITY @ 100 DEGREES C TO BE 13.1 TO 15.9 CST; BASE OIL VISCOSITY INDEX TO BE 145 TO 155; TIMKEN OK LOAD VIA ASTM D2509 TO BE 50 TO 70 LBS; PACKAGED IN 16-KG PAILS; CERTIFICATE OF ANALYSIS COVERING BASE OIL VISCOSITY @ 40 DEGREES C AND CERTIFICATE OF CONFORMANCE/COMPLIANCE TO BE SUPPLIED PRIOR TO SHIPMENT AND MUST ACCOMPANY EACH SHIPMENT	EXXON MOBIL CORP. NYCTA NYCTA	EPIC EP 102 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-10-3400	GREASE, LITHIUM BASED, EP-2, WITH MOLYBDENUM DISULFIDE; TO HAVE A WORKED(X60 STROKES) PENETRATION OF 265 TO 295 MM/10; TO HAVE A MINIMUM 4-BALL WELD POINT AS MEASURED VIA ASTM D2596 OF 315 KG; MAXIMUM 4-BALL WEAR TEST SCAR DIAMETER AS MEASURED VIA ASTM D2596 TO BE 0.55 MM; MUST PASS ASTM D1743 RUST AND PROTECTION TEST; MINIMUM DROPPING POINT TO BE 520 DEGREES F; CERTIFICATE OF ANALYSIS COVERING WORKED PENETRATION AND DROPPING POINT TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 120-LB OR 121.2-LB DRUMS; SPECIAL NOTE: EXCEPTION TO CCSS-001 REV I, SECTION 6.1A IN THAT GREASE TO BE RECEIVED BY NYCT WITHIN 36 MONTHS OF MANUFACTURE 120 LB DRMS	EXXON MOBIL CORP. CITGO NYCTA NYCTA	"MOBILGREASE XHP 222 SPECIAL LITHOPLEX MP GREASE #2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4	4

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-3402	GREASE, LITHIUM BASED, EP-2, WITH MOLYBDENUM DISULFIDE; TO HAVE A WORKED (X60) STROKES)PENETRATION OF 265 TO 295 MM/10; TO HAVE A MINIMUM 4-BALL WELD POINT AS MEASURED VIA ASTM D2596 OF 315 KG; MAXIMUM 4-BALL WEAR TEST SCAR DIAMETER AS MEASURED VIA ASTM D2596 TO BE 0.55 MM; MUST PASS ASTM D1743 RUST PROTECTION TEST; MINIMUM DROPPING POINT TO BE 520 DEGREES F; CERTIFICATE OF ANALYSIS COVERING WORKED PENETRATION AND DROPPING POINT TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 400-LB DRUMS; SPECIAL NOTE: EXCEPTION TO CCSS-001 REV I, SECTION 6.1 IN THAT GREASE TO BE RECEIVED BY NYCT WITHIN 36 MONTHS OF MANUFACTURE	EXXON MOBIL CORP. CITGO NYCTA NYCTA	GREASE XHP222 SPECIAL LITHOPLEX MP GREASE #2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
	400 LB DRMS				
69-10-3405	GREASE, MULTIPURPOSE, LITHIUM BASED, EXTREME PRESSURE, NLGI #2; FOR BEARINGS, GEARS, COUPLINGS, AND HEAVY DUTY APPLICATIONS; HAS GOOD RESISTANCE TO WEAR, RUSTING, AND OXIDATION; MINIMUM FLASH POINT TO BE 400 DEGREES F; WORKED PENETRATION (60X) @77 DEGREES F AS MEASURED BY ASTM D217 TO BE 260-300 MM/10; MINIMUM DROPPING POINT AS MEASURED BY ASTM D2265 TO BE 350 DEGREES F; BASE OIL VISCOSITY @40 DEGREES C AS MEASURED BY ASTM D445 TO BE 145-180 CST; AS MEASURED BY ASTM D2596, FOUR BALL LWI (LOAD WEAR INDEX) TO BE 35-50 KG AND FOUR BALL WELD POINT TO BE A MINIMUM OF 250 KG; FOUR BALL WEAR TO BE 0.40 TO 0.52 MM AS MEASURED BY ASTM D2266; TIMKEN OK LOAD TO BE 40-50 LBS AS MEASURED BY ASTM D2509; OIL SEPARATION AS MEASURED BY ASTM D1742 TO BE A MAXIMUM OF 5%; WATER WASHOUT LOSS @ 175 DEGREES F TO BE 6% MAXIMUM AS MEASURED BY ASTM D1264; COPPER CORROSION AS MEASURED BY ASTM D4048 TO BE 1B OR BETTER, CERTIFICATE OF ANALYSIS INCLUDING WORKED PENETRATION AND DROPPING POINT TO BE PROVIDED FOR EACH BATCH SHIPPED;	CHEVRON PHILLIPS 66 LUBRICANTS EXXON MOBIL CORP. NYCTA NYCTA	CHEVRON MULTIFAK EP2 DYNALIFE 150 #2 MOBILUX EP 2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	20640	16080

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	PACKAGED IN 120 LB DRUMS 120 LB/DRUM 120 LB/DRUM				
69-10-3406	GREASE, LITHIUM BASED, EP-1; TO HAVE AN UNWORKED PENETRATION OF 310 TO 340 AS MEASURED VIA ASTM D217, TO HAVE A WORKED (60X) PENETRATION OF 310 TO 340 AS MEASURED VIA ASTM D217; TO HAVE A MINIMUM DROPPING POINT OF 190 DEGREES CENTIGRADE AS MEASURED VIA ASTM D2265; PACKAGED IN 14 OZ. TUBE. CERTIFICATE OF ANALYSIS COVERING PENETRATION (WORKED AND UNWORKED AS MEASURED BY ASTM D217) AND DROPPING POINT (MEASURED BY ASTM D2265) TO BE PROVIDED FOR EACH BATCH DELIVERED 14 OZ/TUBE	EXXON MOBIL CORP. NYCTA NYCTA	MOBILUX EP-1 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	53	25
69-10-3986	GREASE, WHITE LITHIUM BASED, AEROSOL, MULTIPURPOSE; MUST HAVE #2 NLGI CONSISTENCY GRADE; DROPPING POINT 370-390 DEGREES F MINIMUM; SPECIFIC GRAVITY TO BE 0.90 TO 0.94; 10.75 OZ. NET WEIGHT AEROSOL CANS. CERTIFICATE OF ANALYSIS INCLUDING SPECIFIC GRAVITY & CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. PPE REQUIRED; CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE OR PVC GLOVES 16 OZ/CAN 16 OZ/ CAN	ITW PERMATEX NYCTA NYCTA	WHITE LITHIUM GREASE 81981 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	876	229

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-4785	GREASE, E/M KRONAPLATE, ALL-SEASON, IN TWO (2) GALLON CANS 2-(2)G PER CAN	LONE STAR LUBRICANTS CADILLAC OIL COMPANY NYCTA NYCTA	LS-333R RLI-100AW CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	3000	2000
69-10-4855	GREASE, LUBRIPLATE NO. 5555, PETROLEUM LUBRICATING GREASE. SEMI-FLUID, MILD EXTREME PRESSURE, WATER REPELLENT FLUID LUBRICANT FORMULATING FROM ANHYDROUS CALCIUM SOAP, MINERAL OIL AND ADDITIVES. FLASH POINT >330 DEG F. NLGI GRADE:00. LOW TEMPERATURE APPLICATION OF -65 DEG F. COLOR: OFF WHITE. PRODUCTS MUST HAVE MINIMUM EFFECTIVE LIFE OF 30 MONTHS FROM "BEST PERFORMANCE USE BY DATE" AT TIME OF RECEIVING INTO STORE ROOM ORDER IN MULTIPLE OF 4 GALLONS PER CARTON. 4 GAL PER CTN	LUBRIPLATE LUBRICANTS CO. NYCTA NYCTA	L0109-007 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	192	0
69-10-4917	GREASE, SILICONE, BASED LUBRICANT, FOR COMPRESSORS, LUBRICATION BETWEEN RUBBER AND METAL PARTS IN PNEUMATIC SYSTEMS, HELPS ENSURE POSITIVE SEALING BY SLIGHTLY SWELLING RUBBER O-RINGS AND SEALS, SUPPLIED IN 5.3 OZ TUBES, PENETRATION (WORKED 60 STROKES) 260-300; % BLEED (24 HOURS/150C) 5.0% MAX; EVAPORATION (24 HOURS/150C) 2.5% MAX. VENDOR TO SUPPLY A CERTIFICATE OF ANALYSIS AND A CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO THE NYCT MANAGER OF INSPECTIONS AND TESTING BEFORE SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, WORKED PENETRATION, % EVAPORATION, % BLEED 5 OZ TUBE/PKG	FUCHS LUBRICANTS NYCTA NYCTA	PST-455 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1698	862

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-4955	LUBRICANT, GREASE, EXTREME PRESSURE FORMULATED #2, LITHIUM-BASED, PACKAGED IN 14 OZ/397 GRAM CARTRIDGES, USED ON VARIOUS APPLICATIONS ON THE FUJITEC, SCHINDLER, KONE ESCALATORS. USED ON NOVA ARTIC BUS JOINT RACEWAY 14 OZ PER CART	EXXON MOBIL CORP. NYCTA NYCTA	MOBILUX EP2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	661	311
69-10-5060	GREASE, LUBRICANT, POLGLYCOL BASE OIL, LITHIUM-COMPLEX, NLGI #2, FOR NEW FLYER XCELSIOR MAN KING PIN LUBRICATION AND OTHER AREAS WHERE THIS GREASE IS APPLICABLE. THIS IS AN OEM-SPECIFIED GREASE. ANY ALTERNATE OR REPLACEMENT GREASE MUST BE OEM APPROVED BEFORE IT CAN BE ADDED UNDER THIS STOCK NUMBER. 20 CARTRIDGES PER CASE	FUCHS LUBRICANTS NYCTA NYCTA	RENOLITH LX-OTP 2 CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	522	551
69-10-5167	GREASE, HIGH TEMPERATURE BALL & ROLLER BEARING; NLGI #2; POLYUREA BASED (6-10%) TO HAVE A WORKED (X60) PENETRATION OF 275-295 MM/10 @ 25 DEGREES C (VIA ASTM D217); TO HAVE A MINIMUM DROPPING POINT OF 215 DEGREES C AS MEASURED BY ASTM D2265; MUST PASS STATIC BEARING RUST TEST WITH 10% SYNTHETIC SEA WATER(ASTM D5969). PACKAGED IN 14 OZ. TUBES; CERTIFICATE OF ANALYSIS COVERING DROPPING POINT AND WORKED PENETRATION TO ACCOMPANY EACH BATCH SHIPPED; FOR USE IN CAR WASHER PUMP, MIXER, COMPRESSOR AND DRYER MOTORS 14 OZ/ TUBE 14 OZ/ TUBE 14 OZ/ TUBE	CHEVRON NYCTA NYCTA	SRI GREASE 2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	62	24

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-10-5195	GREASE, SYNTHETIC BASE OIL; FOR LUBRICATING R32 THROUGH R68A DOOR SYSTEMS; PACKAGED IN 35 LB. CONTAINERS; MUST MEET ALL REQUIREMENTS OF NYCT 7127-FACIL-00; CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS FOR EACH BATCH MUST BE PROVIDED TO THE MANAGER OF TESTING AND ANALYSIS PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS MUST INCLUDE WORKED PENETRATION AND DROPPING POINT VALUES. (NOTE: FOR THE R142, R142A & R143 RAIL CARS USE COMMODITY #69-10-5196)	EXXON MOBIL CORP. NYCTA NYCTA NYCTA	MOBILTEMP SHC 32 7127-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1050	315
	35 LB/CONTAINER				
69-10-5196	GREASE, SYNTHETIC BASE; FOR LUBRICATING R142, R142A, & R143 DOOR OPERATOR SCREW DRIVES ONLY; HAS LITHIUM SOAP THICKENER; TO HAVE OXIDATION STABILITY, ANTI-WEAR, AND EXTREME PRESSURE PROPERTIES; NLGI #1; WORKED PENETRATION (60X) VIA ASTM D1403 TO BE 310-340; MINIMUM DROPPING POINT VIA ASTM D2265 TO BE 400 DEGREES F; BASE OIL VISCOSITY VIA ASTM D445 TO BE 37.8 TO 46.2 CST @ 40 DEGREES C AND 6 TO 8 CST @ 100 DEGREES C; PACKAGED IN 5LB CONTAINERS; CERTIFICATES OF CONFORMANCE AND ANALYSIS FOR EACH BATCH MUST BE PROVIDED TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING; CERTIFICATE OF ANALYSIS MUST INCLUDE WORKED PENETRATION AND DROPPING POINT; (NOTE: FOR RAILCARS REQUIRING DOOR SYSTEM LUBRICATION OTHER THAN R142S, R142AS, AND R143S, USE STOCK # 69-10-5195)	SYNTECH LTD. NYCTA NYCTA	NS-3844-TG CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	85	55
	5 LB/CONTAINER				

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-0105	FLUID, CUTTING, METALWORKING FLUID CONCENTRATE (FOR BRIDGEPORT MILLING MACHINES), CONTAINS A BIOSTABLE MICROBIAL CONTROL PACKAGE, RUST INHIBITOR PACKAGE, MUST BE SOLUBLE IN WATER, USED ON ALL METALS EXCEPT MAGNESIUM; MUST HAVE SPECIFIC GRAVITY @ 60 DEGREES F 1.04-1.06., PH OF CONCENTRATE 9.3-9.9, TOTAL CHLORINE, WT%, 50 PPM MAXIMUM; PACKAGED IN 5 GAL. PAIL. CERTIFICATE OF ANALYSIS TO INCLUDE SPECIFIC GRAVITY AND PH OF CONCENTRATE MUST BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING MATERIAL	MILACRON CO NYCTA NYCTA	CIMSTAR 60XL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-0675	OIL, STEAM CYLINDER AND WORM GEAR; AGMA STANDARD 9005-D94, LUBRICANT NO 7,7 COMP.(COMPOUNDED WITH ACIDLESS TALLOW OIL); VISCOSITY RANGES FROM 414 CST TO 508 CST @40 DEGREES C; TO BE PACKAGED IN MANUFACTURER SEALED 55 GALLON DRUMS; DISTRIBUTOR OR BLENDER REPACKAGED MATERIAL IS NOT ACCEPTABLE. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND SPECIFIC GRAVITY MUST BE PROVIDED FOR EACH BATCH	CHEVRON PRODUCT COMPANY ANSI NYCTA NYCTA	CYLINDER OIL W ISO 460 9005-D94 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-0677	OIL, WORM GEAR + CYLINDER; TO HAVE A VISCOSITY RANGE OF 125 TO 150 SUS @ 210 DEGREES F; TO HAVE A VISCOSITY OF 380 CST +/- 10% @ 40 DEGREES C; PACKAGED IN 5-GAL PAILS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C TO BE PROVIDED FOR EACH BATCH DELIVERED 5 GAL PER CAN	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL 600 W CYLINDER OIL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1025	FLUID, CUTTING, COOLANT, METAL WORKING FLUID, SYNTHETIC, WATER SOLUBLE. USED IN CUTTING, FORMING AND GRINDING OPERATIONS FOR STAINLESS STEEL, CAST IRON, ALL FERROUS AND NON-FERROUS METALS. DOES NOT CONTAIN SULPHUR OR CHLORINE. NON-GUMMING AND NON-CORROSIVE. PH 8 TO 9. SUPPLIED IN ONE-GALLON CONTAINERS. SIX CONTAINERS PER CASE. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND LIGHTWEIGHT NITRILE OR VITON GLOVES. CERTIFICATE OF ANALYSIS TO INCLUDE PH. 1 GAL/CONTAINER	SENTINEL LUBRICANTS CORP. NYCTA NYCTA	CF51 MWF 13260 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1050	OIL, CUTTING, SULFURIZED, LIGHT GRADE, MUST MEET REQUIREMENTS UNDER NYC 30-C-1:67 SPECIFICATION FOR CUTTING OIL TYPE III; PACKAGED IN ONE GALLON CONTAINER; CERTIFICATE OF ANALYSES TO INCLUDE VISCOSITY AND % SULFUR & CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH BATCH SHIPPED 1 GAL CTR	CASTOLEUM CORP. NYCTA NYC SPEC NYCTA NYCTA	TRIZOL #2080 "NU-CLEAR" 30-C-1:67 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	52	37
69-12-1185	OIL, SAE GRADE 10W-30; USED TO LUBRICATE FORKLIFTS, CRANE CAR DIESEL ENGINES (DEUTZ "913" ENGINES) AND VARIOUS OTHER EQUIPMENT; VISCOSITY @ 100 DEGREES C TO BE 9.3 TO 12.49 CST; VISCOSITY @ -25 DEGREES C TO BE A MAXIMUM OF 7000 CP; PER ASTM D892 FOAMING TEST, FOAMING/SETTLING MAXIMUMS FOR SEQUENCE II TO BE 20 ML/ 0 ML; PACKAGED IN 5 GAL CANS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 100 DEGREES C+ -25 DEGREES C AND FOAM SEQUENCE II, TO BE PROVIDED FOR EACH BATCH SHIPPED	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DELVAC 1300 SUPER 10W-30 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	120	70

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1410	OIL, GEAR CASE, SAE GRADE 80W-90; FOR RAILCAR TRACTION MOTOR GEAR CASES; MAXIMUM POUR POINT TO BE -10 DEGREES F; VISCOSITY @ 100 DEGREES C TO BE 13.5 TO 24.0 CST; MINIMUM FLASH POINT TO BE 329 DEGREES F; MAXIMUM CHANNELING POINT VIA FTMS 791C NO. 3456 TO BE -35 DEGREES C; PACKAGED BY ORIGINAL MANUFACTURER IN SEALED 120 LB DRUMS; DRUM LABEL MUST INCLUDE FILLING DATE AND BATCH NUMBER; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 100 DEGREES C TO BE PROVIDED FOR EACH BATCH SHIPPED; VENDOR'S NOTE: 120-LB DRUMS TO BE DELIVERED WRAPPED ON 40" X 48" NON-RETURNABLE PALLETS 120 LB/ DRUM	CHEVRON EXXON MOBIL CORP. PHILLIPS 66 LUBRICANTS CITGO NYCTA NYCTA	DELO EP-5 80W-90 MOBILUBE HD PLUS 80 W 90 MP GEAR LUBE SAE 80W-90 PREMIUM GEAR OIL MP 80W-90 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	176640	105120
69-12-1414	OIL, HYDRAULIC, ISO 46, ZINC FREE FORMULATION. FOR USE IN R162 ONE-TON CRANE CARS. SUPPLIED IN 55-GALLON DRUM. VISCOSITY 42-50 CST @40C, 6.12-7.4 CST @ 100C; VISCOSITY INDEX 101; POUR POINT -22F MIN.; OXIDATION STABILITY GREATER THAN 18,000 HOURS. MEETS DENISON HF-0, HF-2; MAG CINCINNATI MACHINE P-70 (ISO 46); EATON-VICKERS 35VQ25 PUMP TEST. VENDOR TO SUPPLY A CERTIFICATE OF ANALYSIS AND A CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO THE NYCT MANAGER OF INSPECTIONS AND TESTING BEFORE SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURER, VISCOSITY, POUR POINT. THIS OIL IS NOT COMPATIBLE WITH ZINC/CALCIUM FLUIDS AND OEM RECOMMENDED CHANGE-OUT PROCEDURES INCLUDING DRAIN AND FLUSH REQUIREMENTS NEED TO BE ADHERED TO IF CHANGING FROM OR TO THIS OIL. PPE REQUIRED: CHEMICAL SPLASH GOGGLES AND NITRILE GLOVES	CHEVRON NYCTA NYCTA	CLARITY HYDAULIC OIL AW ISO 46 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1416	OIL, GEAR CASE, SYNTHETIC, SAE GRADE 75W-90; FOR USE IN R255 LOCOMOTIVE GEAR CASES; MAXIMUM POUR POINT TO BE -40 DEGREES C; VISCOSITY @ 100 DEGREES C TO BE 14.3 TO 17.5 MM^2/SEC; MINIMUM FLASH POINT VIA ASTM D92 CLEVELAND OPEN CUP TO BE 195 DEGREES C; PACKAGED IN 105-LB DRUMS; BATCH NUMBER TO APPEAR ON DRUM/DRUM LABEL; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 100 DEGREES C TO BE PROVIDED FOR EACH BATCH SHIPPED	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DELVAC 1 GEAR OIL 75W-90 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1481	OIL, AIR TOOL AND SPINDLE; PROVIDES OXIDATION RESISTANCE AND RUST/CORROSION PREVENTION; MINIMUM FLASH POINT TO BE 350 DEGREES F; MAXIMUM POUR POINT TO BE 0 DEGREES F; VISCOSITY @ 40 DEGREES C TO BE 9 TO 11 CST; MAXIMUM TOTAL ACID NUMBER AS MEASURED VIA ASTM D 974 TO BE 0.1 MG KOH/G OIL; COPPER STRIP CORROSION AS MEASURED VIA ASTM D 130 (3 HRS., @ 100 DEGREES C) TO BE 1A; MUST PASS ASTM D 665 RUST CHARACTERISTICS TEST, PROCEDURE A; COMPATIBLE WITH BUNA AND VITON RUBBER; PACKAGED IN 1-GALLON CONTAINERS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C TO BE PROVIDED FOR EACH BATCH SHIPPED	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL VELOCITE OIL NO. 6 CCSS-001, REV I, 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S	43	13
69-12-1491	OIL, HEAVY HYDRAULIC, ISO GRADE 150; USED IN AXLE LATHE AND RAILCAR WHEEL BORER HYDRAULIC SYSTEMS; API GRAVITY TO BE 26.8 TO 30; VISCOSITY @ 40 DEGREES C TO BE 135 TO 165 CST; MAXIMUM COLOR VIA ASTM D1500 TO BE 5; MINIMUM FLASH POINT TO BE 420 DEGREES F; MAXIMUM NEUTRALIZATION NUMBER VIA ASTM D664 TO BE 0.2 MG KOH/G OIL; MUST PASS ASTM D665 PROCEDURE A (DISTILLED WATER) RUST TEST; PACKAGED IN 55-GALLON DRUMS; CERTIFICATE OF ANALYSIS INCLUDING VISCOSITY AND API GRAVITY TO BE PROVIDED FOR EACH BATCH SHIPPED. 55 GAL/ DRUM 55 GAL/ DRUM	CITGO CHEVRON EXXON MOBIL CORP. NYCTA NYCTA	PACEMAKER 150 REGAL R&O 150 TERESSTIC 150 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	55 GAL/ DRUM				
69-12-1492	OIL, WAY, ISO GRADE 68, USED FOR LUBRICATION OF THE HORIZONTAL & VERTICAL RAM, TABLE MAIN SHAFT OF CAR WHEEL BORER MACHINES; API GRAVITY VIA ASTM D287 TO BE 18 TO 29; VISCOSITY @ 40 DEGREES C TO BE 61.2 TO 74.8 CST; VISCOSITY @ 100 DEGREES F TO BE 317 TO 389 SUS; MINIMUM FLASH POINT TO BE 330 DEGREES F; MINIMUM FIRE POINT TO BE 360 DEGREES F; MAXIMUM NEUTRALIZATION NUMBER VIS ASTM D664 TO BE 1.7 MG KOH/G OIL; MAXIMUM RATIO OF STATIC TO KINETIC FRICTION VIA CINCINNATI MACHINE STICK-SLIP TEST TO BE 0.8; MUST PASS CINCINNATI. MACHINE THERMAL STABILTIY TEST; PACKAGED IN 55 GAL DRUMS; CERTIFICATE OF ANAYLSIS THAT INCLUDE VISCOSITY @ 40 DEG C AND API GRAVITY TO BE PROVIDED FOR EACH BATCH SHIPPED. 55 GAL/DRUM	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL VACTRA OIL #2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	110
69-12-1493	OIL, HYDRAULIC, ISO GRADE 46, ANTI-WEAR, PROVIDES PROTECTION AGAINST RUST AND OXIDATION; CONTAINS ZINC; API GRAVITY @ 60 DEGREES F TO BE 28 TO 34; VISCOSITY @ 40 DEGREES C TO BE 41.4 TO 50.6 CST; MINIMUM VISCOSITY INDEX TO BE 90; MINIMUM FLASH POINT TO BE 385 DEGREES F; MAXIMUM POUR POINT TO BE -10 DEGREES F; MAXIMUM NEUTRALIZATION NUMBER TO BE 1.5 MG KOH/G OIL; MUST PASS ASTM D665, PROCEDURE A RUST TEST; PACKAGED IN 55-GALLON DRUMS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C AND API GRAVITY TO BE PROVIDED FOR EACH BATCH SHIPPED 55 GAL/ DRUM	CHEVRON EXXON MOBIL CORP. PHILLIPS 66 LUBRICANTS EXXON MOBIL CORP. NYCTA NYCTA	CHEVRON RANDO HD 46 DTE-25 MEGAFLOW AW HYDRAULIC OIL 46 NUTO H-46 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	220	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
69-12-1494	OIL, HEAVY-MEDIUM HYDRAULIC, ISO GRADE 68, ANTI-WEAR, ZINC CONTENT 225-750 PPM; USED IN HYDRAULIC SYSTEMS OF VARIOUS PIECES OF EQUIPMENT; API GRAVITY TO BE 27.5 - 32; VISCOSITY @ 40 DEGREES C TO BE 61.2 TO 74.8 CST; MINIMUM VISCOSITY INDEX TO BE 90; MINIMUM FLASHPOINT TO BE 395 DEGREES F; MUST PASS ASTM D 665 RUST TEST; PACKAGED IN 55 GAL DRUMS; CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH 55 GAL/ DRUM 55 GAL/ DRUM 55 GAL/ DRUM	CHEVRON/TEXACO CHEVRON/TEXACO GULF/NU-TIER EXXON MOBIL CORP. EXXON MOBIL CORP. D A LUBRICANTS NYCTA NYCTA	CHEVRON HYDRAULIC OIL AW ISO 68 CHEVRON RANDO HD 68 GULF HARMONY AW HYD 68 MOBIL DTE 26 NUTO H 68 PRESURFLO 68 CCSS-001, REV I, 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S	6	0		55
69-12-1495	OIL, HYDRAULIC, FOR VOITH L2R4 TRANSMISSION ON VAKTRAK VACUUM TRAIN, ISO GRADE 32, IN 55 GALLON DRUMS. MUST MEET REQUIREMENTS OF NYCT SPECIFICATION 7126-FACIL-00. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH 55 GAL/DRUMS	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DTE 24 7126-FACIL-00 CCSS-003 REV E 9/11/17 RESTR S		0		55
69-12-1496	OIL, HYDRAULIC, ISO GRADE 32, PACKAGED IN 55 GALLON DRUMS. MUST CONTAIN A VISCOSITY INDEX IMPROVER COPOLYMER ADDITIVE TO GIVE A HIGH VISCOSITY INDEX WITHOUT EXCESSIVE LOSS OF VISCOSITY FROM MECHANICAL SHEARING AND MUST ALSO CONTAIN A ZINC TYPE ANTI-WEAR ADDITIVE. API GRAVITY (ASTM D1298 OR D4052) = 30-35; FLASHPOINT (ASTM D92) = 325F MIN.; VISCOSITY (ASTM D445) @ 40C = 28.8 TO 35.2 CST, @ 100C=6.0-7.0 CST; VISCOSITY INDEX (ASTM D2270) = 144 MIN.; POUR POINT (ASTM D97) IS -35F MAX; COPPER CORROSION (ASTM D130) @212F = 1B; TOTAL ACID NUMBER (ASTM D664) = 0.6 MG KOH/G OIL MAX; MUST PASS ASTM D665B RUST TEST; OXIDATION STABILITY (ASTM D943) IS 1500+ HOURS; EMULSION (ASTM D1401 @ 130F SEPARATION TIME = 30 MINUTES (MAX); FOAMING	CHEVRON PRODUCT COMPANY EXXON MOBIL CORP. NYCTA NYCTA	RANDO HDZ 32 UNIVIS N32 CCSS-001, REV I, 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S		0		0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	TENDENCY/STABILITY (ASTM D892) SEQUENCE II = 25/0 -50/0; % ZINC = 0.0238-0.40; DIELECTRIC STRENGTH (ASTM D877) = 30 KV MIN. MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF DENISON'S HF-0, VICKERS M-2950-5 AND CINCINNATI - MILACRON P68 SPECIFICATIONS. CERTIFICATION OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH				
69-12-1497	OIL, HYDRAULIC, ISO GRADE 22 PARAFFINIC BASED; USED TO LUBRICATE SEFAC "M225BF" HYDRAULIC JACK SYSTEMS; VISCOSITY @ 40 DEGREES C TO BE 19.8-24.2 CST, VISCOSITY @ 100 DEGREES C, TO BE 4.5-5.5 CST, VISCOSITY INDEX TO BE APPROXIMATELY 165; API GRAVITY TO BE 35-40; MINIMUM FLASH POINT TO BE 392 DEGREES F; MAXIMUM POUR POINT TO BE -30 DEGREES F; COPPER CORROSION VIA ASTM D130, 3 HRS @ 100 DEGREES C TO BE 1B; FOAM SEQUENCE I TENDENCY & STABILITY VIA ASTM D892 TO BE 0 ML AND 0 ML RESPECTIVELY; TIME TO 3 ML EMULSION AT 54 DEGREES C VIA ASTM D1401 TO BE 10 MIN; PACKAGED IN 5 GAL PAILS; CERTIFICATE OF ANALYSIS THAT INCLUDES VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH THAT IS SHIPPED.	EXXON MOBIL CORP. NYCTA NYCTA	DTE 10 EXCEL 22 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1501	OIL, HYDRAULIC, BIODEGRADABLE, FOR USE ON TAMPERS. FOR HYDRAULIC SYSTEMS OPERATING WITH OIL TEMPERATURES IN THE RANGE OF 0 DEG. F. TO 180 DEG. F. VEGETABLE OIL BASED WITH ADDITIVIES THAT PROVIDE HIGH PERFORMANCE, EXCELLENT PROTECTION AGAINST RUST, OUTSTANDING LOAD CARRYING, ANTI-WEAR PROPERTIES, CORROSION RESISTANCE PROPERTIES. API GRAVITY 22.1; VISCOSITY 37 +/- 3.7 CST AT 40 DEG. C, VISCOSITY 8.4 +/-0.84 CST AT 100 DEG. C; POUR POINT -18 DEG. F. MEETS REQUIREMENTS OF DENISON HF-0 AND TP30283 VANE PUMP	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL EAL224H CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	TESTS, VICKERS V-104C AND 35VQ25, 12 STAGE RATING IN THE FZG GEAR TEST; MEETS ASTM D665 FOR RUST PROTECTION. CERTIFICATION OF ANALYSIS FOR EACH BATCH TO BE PROVIDED WHICH INCLUDES VISCOSITY. PACKAGED IN 55-GALLON DRUMS				
69-12-1514	OIL, HYDRAULIC ELEVATOR, ISO 32, PETROLEUM BASED, TO BE SHIPPED IN RESEALABLE 5 GALLON PAILS; USED ON HYDRAULIC ELEVATORS 5 GAL/PAIL	EXXON MOBIL CORP. NYCTA NYCTA	583195-00/NUTO H 32 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	3960	2290
69-12-1519	OIL, HYDRAULIC, ISO 100 GRADE, ANTI-WEAR, ASHLESS (ZINC-FREE); FOR NILFISK/ALTO/KEW 5003 V STEAM CLEANER/ PRESSURE WASHER & OTHER EQUIPMENT; VISCOSITY INDEX TO BE 140-155; MAXIMUM POUR POINT TO BE -32 DEGREES F; VISCOSITY @ 40 DEGREES C TO BE 90 TO 110 CST; VISCOSITY @ 100 DEGREES C TO BE 12.6 TO 15.4 CST; OXIDATION STABILITY TO BE > 5,000 HRS TO 2.0 MG KOH/G ACID NUMBER AS MEASURED BY ASTM D943; PACKAGED IN 5-GAL PAIL; CERTIFICATE OF ANALYSIS COVERING VISCOSITY (@ 40 DEGREES C @ 100 DEGREES C), VISCOSITY INDEX & POUR POINT TO BE PROVIDED FOR EACH BATCH SHIPPED; FOR HIGH PRESSURE, HIGH TEMPERATURE HYDRAULIC SYSTEMS THAT OPERATE IN HIGH MOISTURE ENVIRONMENT 5 GAL PAILS	CHEVRON NYCTA NYCTA	CLARITY HYDRAULIC OIL AW 100 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	15	0
69-12-1521	OIL, FOR VACUUM PUMPS IN ROBINAIR 178002K/178012K REFRIGERANT RECOVERY MACHINES; VISCOSITY @ 40 DEGREES C TO BE 27.9 TO 34.3 CST; VISCOSITY @ 100 DEGREES C TO BE 4.5 TO 5.5 CST; MINIMUM VISCOSITY INDEX TO BE 94; API GRAVITY TO BE NOMINALLY 33.2; MINIMUM FLASH POINT TO BE 410 DEGREES F; MAXIMUM POUR POINT TO BE 8 DEGREES F; PACKAGED IN 1-GAL BOTTLES. CERTIFICATES OF ANALYSIS	LUBRICATION TECHNOLOGIES OLYMPIC NYCTA NYCTA	ROBINAIR PREMIUMHI VACUUMPUMPO VACUUM PUMP OIL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	15	17

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	INCLUDING VISCOSITY AND API GRAVITY TO ACCOMPANY EACH BATCH THAT IS SHIPPED. NOTE TO USERS: SAME PRODUCT IN 1 QT CANS AVAILABLE UNDER STOCK #69-12-1532 1 GAL/ BOTTLE				
69-12-1524	AEROSOL LUBRICANT, POLYDIMETHYLSILOXANE SILICONE-BASED, IN 9-16 OZ CANS. 3% SILICONE BY WEIGHT MIN; VOC BY WEIGHT 60% MAX; KINEMATIC VISCOSITY(D-445)200-400 CST@40 DEG. C; POUR POINT(D97)-40 DEG. F MAX. CERTIFICATE OF CONFORMANCE/ COMPLIANCE AND CERTIFICATE OF ANALYSIS TO INCLUDE SILICONE CONTENT AND VISCOSITY MUST ACCOMPANY EACH SHIPMENT. 9-16 OZ CAN/CSE	STATE CHEMICAL CASTOLEUM CORP. NYCTA NYCTA ASTM ASTM NY STATE DEPT OF ENVIRON CONS.	SPW (SPECIAL PURPOSE WAX 43040 TRIZOL SILICONE SPRAY LUBRICAN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S D1640 D3539 PART 235-3	3382	2688
69-12-1526	LUBRICANT, PENETRANT, RUST PREVENTIVE, MOISTURE DISPLACER AND CLEANER, AEROSOL, USED FOR FREEING AND LUBRICATING RUSTED PARTS AND MACHINERY; SPECIFIC GRAVITY TO BE 0.8 TO 1.2 (CORRESPONDS TO DENSITY OF 6.67 LBS/GAL TO 10.0 LBS/GAL); FLASH POINT MINIMUM TO BE 110 DEGREES F; PACKAGED IN 11-OZ CANS, 12 CANS PER CASE; CERTIFICATE OF CONFORMANCE TO BE PROVIDED FOR EACH BATCH SHIPPED 12 CANS/CSE	CRC INDUSTRIES, INC. WD-40 COMPANY NYCTA NYCTA	#3005 AEROSOL 336 MULTI-PURP WD-40 11 OZ CAN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	27617	17831
69-12-1527	LUBRICANT, SILICONE, AEROSOL; 16 OZ. CAN (NET WEIGHT 10 OZ.). COMES WITH MOVABLE PLASTIC STRAW APPLICATOR PERMANENTLY AFFIXED TO SPRAY NOZZLE. CONTAINS 2.0 TO 5.1% SILICONE. DRYING TIME (FOR A 1.25 MM THICK FILM) TO BE 175 SECONDS MAXIMUM. CERTIFICATE OF ANALYSIS TO INCLUDE % SILICONE/% SOLIDS CONTENT. C OF A AND CERTIFICATE OF CONFORMANCE TO BE PROVIDED TO THE NYCT MANAGER OF INSPECTION AND TESTING PRIOR TO SHIPPING MATERIAL.	CRC INDUSTRIES, INC. NYCTA NYCTA	FOOD GRADE SILICONE 03040 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	3113	1704

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	16 OZ CANS				
69-12-1532	OIL, FOR VACUUM PUMPS IN ROBINAIR 178002K/178012K REFRIGERANT RECOVERY MACHINES; VISCOSITY @ 40 DEGREES C TO BE 27.9 TO 34.3 CST; VISCOSITY @ 100 DEGREES C TO BE 4.5 TO 5.5 CST; MINIMUM VISCOSITY INDEX TO BE 94; API GRAVITY TO BE NOMINALLY 33.2; MINIMUM FLASH POINT TO BE 410 DEGREES F, MAXIMUM POUR POINT TO BE 8 DEGREES F; PACKAGED IN 1 QT CANS; CERTIFICATES OF ANALYSIS INCLUDING VISCOSITY AND API GRAVITY TO ACCOMPANY EACH BATCH THAT IS SHIPPED. NOTE TO USERS: SAME PRODUCT IN 1 GAL BOTTLES AVAILABLE UNDER STOCK #69-12-1521 1 QT CANS	LUBRICATION TECHNOLOGIES OLYMPIC NYCTA NYCTA	ROBINAIR PREMIUMHI VACUUMPUMPO VACUUM PUMP OIL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	249	189
69-12-1534	OIL, COMPRESSOR, HIGHLY REFINED, WAX AND WATER FREE, NAPHTHENIC MINERAL OIL BLEND, USED FOR LUBRICATION, IN REFRIGERATION AND RAILCAR AIR CONDITIONING SYSTEMS. UNSUITABLE FOR REFRIGERANT SYSTEMS USING HFC REFRIGERANTS, SUCH AS R-134A. MUST MEET THE FOLLOWING REQUIREMENTS: API GRAVITY 21-27; VISCOSITY @ 40 DEGREES C- 61-75 CST; FLASH POINT 340 DEGREES F MINIMUM; POUR POINT-25 DEGREES F MAXIMUM; FLOC POINT -50 DEGREES F MAXIMUM; WATER CONTENT 35 PPM MAXIMUM;DIELECTRIC STRENGTH 25KV MINIMUM. PACKAGED IN ONE-GALLON PLASTIC CONTAINERS, SIX CONTAINERS TO A CASE. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH. 1 GAL/CTR 1 GAL/CTR	CHEVRON PRODUCT COMPANY NYCTA NYCTA	CAPELLA WF 68 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	517	338

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1537	OIL, FOR LUBRICATING RAIL CAR AIR CONDITIONER COMPRESSORS; ISO VISCOSITY. GRADE 32; MUST BE COMPATIBLE WITH R-22 REGRIGERANT. PACKAGED IN ONE (1) GALLON CANS, SIX CANS TO A CASE 6 CANS/CSE	CHEVRON PRODUCT COMPANY SONNEBORN, LLC NYCTA/MABSTOA NYCTA NYCTA	CAPELLA WF 32 SUNISO 3GS 7090-FACIL-99 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	1
69-12-1546	OIL, SEMI-SYNTHETIC, MECHANICAL PUMP FLUID. FOR USE IN VACUUM PUMP THAT IS USED TO EVACUATE MOISTURE FROM RAILCAR A/C SYSTEM. VISCOSITY @ 40C IS 48 CST, POUR POINT IS -16C. PACKAGED IN 1-GALLON CONTAINER 1 GAL/CTR	CAMBRIDGE MILL PRODUCTS NYCTA NYCTA	CMP19 ULTRA HT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1548	LUBRICANT, PENETRANT, RUST PREVENTATIVE, MOISTURE DISPLACER AND CLEANER, AEROSOL 3 OZ. CAN. USED FOR FREEING AND LUBRICATING RUSTED PARTS AND MACHINERY. PACKAGED IN 3 OZ. CANS 12 CANS/CSE. PETROLEUM DISTILLATE/HYDROCARBON BLEND WITH CARBON DIOXIDE PROPELLANT. FLASH POINT = 120F MINIMUM; SPECIFIC GRAVITY = 0.78 - 0.82; BOILING POINT = 300F MINIMUM 12 CANS/CSE	WD-40 COMPANY NYCTA NYCTA	WD-40 (3-OZ CAN)#49000 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	36295	23278
69-12-1576	OIL, COMPRESSOR, DIESTER BASED, ISO 68 GRADE, FOR ROTARY SCREW TYPE COMPRESSORS; MINIMUM FLASH POINT TO BE 235 DEGREES C; VISCOSITY @ 40 DEGREES C TO BE 61.2 TO 74.8 CST; VISCOSITY @ 100 DEGREES C TO BE 7.0 TO 10.5 CST, SPECIFIC GRAVITY TO BE 0.850 TO .965; MAXIMUM POUR POINT TO BE -32 DEGREES F; COPPER CORROSION AS MEASURED VIA ASTM D130 TO BE 1A; MINIMUM AUTOIGNITION TEMPERATURE TO BE 405 DEGREES C AS MEASURED VIA ASTM E659; TYPICAL CONRADSON CARBON RESIDUE VIA ASTM D189 TO BE 0.02%; EVAPORATION (22 HRS @ 99 DEGREES C VIA ASTM D972) TO BE LESS THAN 1.0%; DEMULSIBILITY @ 54 DEGREES C	SUMMIT INDUSTRIAL PRODUCTS INC NYCTA NYCTA	DSL68 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	ML OIL/WATER/EMULSION (MINUTES) TO BE 40/37/3 (<60) OR BETTER AS MEASURED VIA ASTM D1401; MAXIMUM 4 BALL WEAR @ 1200 RPM, 75 DEGREES C, 40KG, 1 HOUR TO BE 0.85MM AS MEASURED VIA ASTM D2266; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C, FLASHPOINT, & POUR POINT TO ACCOMPANY EACH BATCH SHIPPED; PACKAGED IN 55 GALLON DRUMS.				
69-12-1577	OIL, SYNTHETIC DIESTER COMPRESSOR OIL, SAE 20W40, FOR INGERSOLL-RAND RECIPROCATING AIR COMPRESSORS (MODELS "242-50", "25T2", "5HE", "2475N5", "5BP"); MUST HAVE VISCOSITY OF 90-110 CST @ 100 DEGREES F, VISCOSITY INDEX 128, DEMULSIBILITY @ 130 DEGREES F ML OIL/EMULSION 40/40/0(60) MINIMUM, FOUR BALL WEAR, 1200 RPM, 167 DEGREES F, 40KG, 1HR.MM 0.32, SPECIFIC GRAVITY 0.9-1.1, POUR POINT -50 DEGREES F. MAXIMUM, FLASH POINT 450 DEGREES F. MINIMUM, PACKED IN 1 LITER CONTAINERS. CERTIFICATE OF ANALYSES TO INCLUDE VISCOSITY AND POUR POINT & CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH BATCH IN SHIPMENT MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. 1 LITER CTR 1 LITER CTR	INGERSOLL-RAND NYCTA NYCTA	ALL SEASON T30 SELECT(38436721 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1578	OIL, COMPRESSOR, MINERAL BASED, ISO VISCOSITY GRADE 100 (VISCOSITY TO BE 90 TO 110 CST @40 DEGREES C); MUST PASS SYNTHETIC SEA WATER TEST (ASTM D665) RUST & OXIDATION INHIBITED; POUR POINT MAXIMUM TO BE -10 DEGREES F; API GRAVITY TO BE NOMINALLY 31; MAXIMUM ACID NUMBER AS MEASURED BY ASTM D974 TO BE 0.18 MG KOH/G OF OIL; FOR USE IN CAR WASHER BLOWER COMPRESSORS; CERTIFICATE OF ANALYSIS TO ACCOMPANY EACH BATCH SHIPPED; PACKAGED IN 5 GALLON PAILS 5 GAL/PLS	CHEVRON NYCTA NYCTA	REGAL R&0 ISO 100 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	5 GAL/PLS				
69-12-1585	OIL, DIESTER BASED, FOR RECIPROCATING TYPE AIR COMPRESSORS(INGERSOLL-RAND "XLE"); ISO GRADE 100; VISCOSITY @ 40 DEGREES C TO BE 90-110 CST; VISCOSITY @ 100 DEGREES C TO BE 9.4 TO 14; VISCOSITY INDEX TO BE A MINIMUM OF 60; POUR POINT MAXIMUM TO BE -25 DEGREES F; FLASH POINT MINIMUM TO BE 460 DEGREES F; SPECIFIC GRAVITY TO BE 0.85 TO 0.98; EVAPORATION LOSS(22 HOURS @ 210 DEGREES F VIA ASTM D972) TO BE LESS THAN 1%; COPPER STRIP CORROSION VIA ASTM D130 TO BE 1A OR 1B; DEMULSIBILITY @ 130 DEGREES F VIA ASTM 1401 TO BE 39/38/3 (<60)ML OIL/WATER/EMULSION(MINUTES) OR BETTER; MAXIMUM TOTAL ACID NUMBER VIA ASTM D664 TO BE 0.2 MG KOH/G; MUST PASS RUST TEST(48 HOURS VIA ASTM D665A); FOUR-BALL WEAR @ 1200 RPM, 165 DEGREES F, 40 KG, 1 HOUR VIA ASTM D2266 TO BE A MAXIMUM OF 1.0 MM; PACKAGED IN 55-GALLON DRUMS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C, POUR POINT, FLASH POINT, COPPER CORROSION, AND DEMULSIBILITY @ 130 DEGREES F TO BE PROVIDED FOR EACH BATCH SHIPPED	ULTRACHEM INC. SUMMIT INDUSTRIAL PRODUCTS INC NYCTA NYCTA	CHEMLUBE 501 DSL100 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1615	OIL, SYNTHETIC COMPRESSOR, FOR USE IN ATLAS COPCO GA55 ROTARY SCREW TYPE AIR COMPRESSORS, IN 5 GALLON CONTAINERS. SYNTHETIC BASED LUBRICANT; KINEMATIC VISCOSITY @40C; IS 34.3-46 CENTISTOKES (ASTM D445) VISCOSITY INDEX 133 (ASTM D2270); POUR POINT -10F (ASTM D97; PASSES ASTM D665B RUST TEST. ALLOWS FOR SERVICE DRAIN INTERVALS UP TO 8,000 HOURS OR TWO YEARS. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE GLOVES 5 GAL/CTR	ATLAS COPCO AIRPOWER NYCTA NYCTA	ROTO EXTENDED DUTY FLUID CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	45	40

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1630	OIL, COMPRESSOR, SYNTHETIC, ALKYL BENZENE, USED FOR LUBRICATION, IN REFRIGERATION AND RAILCAR AIR CONDITIONING SYSTEMS. SUITABLE FOR REFRIGERANT SYSTEMS USING HCFC-BASED REFRIGERANTS. MUST MEET THE FOLLOWING REQUIREMENTS: COLOR 4.0 MAXIMUM; GRAVITY 29.5 - 31.5 API; VISCOSITY @ 100 DEGREES F 290-310 SUS; FLASH POINT 310 DEGREES F MINIMUM; POUR POINT - 30 DEGREES MAXIMUM; FLOC POINT < -80 DEGREES F; DIELECTRIC STRENGTH > 25KV. PACKAGED IN ONE-GALLON PLASTIC CONTAINERS, SIX CONTAINERS TO A CASE. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH. SAFETY COMMENTS: USE PERSONAL PROTECTIVE EQUIPMENT IN ACCORDANCE WITH THE MSDS. WEAR CHEMICAL SPLASH GOGGLES & NITRILE GLOVES	SHRIEVE CHEMICAL PRODUCTS NYCTA NYCTA	ZEROL 300 CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1705	OIL, PARAFFINIC BASED FOR RECIPROCATING COMPRESSORS, ISO GRADE 68; CONTAINS RUST AND OXIDATION INHIBITORS; VISCOSITY @ 40 DEGREES C TO BE 61-75; MINIMUM VISCOSITY INDEX TO BE 90; MINIMUM FLASH POINT TO BE 395 DEGREES F; MAXIMUM POUR POINT TO BE -5 DEGREES F; MAXIMUM NEUTRALIZATION NUMBER TO BE 0.2; CORROSION CLASSIFICATION AS MEASURED BY ASTM D130 (3 HRS @ 212 DEGREES F) TO BE 1A OR 1B (SLIGHT TARNISH); TO BE PACKAGED IN ORIGINAL MANUFACTURER SEALED 55 GALLON DRUMS (OIL REPACKAGED FROM BULK IS NOT ACCEPTABLE); MUST PASS ASTM D665 RUST PREVENTION TEST 24 HRS, DISTILLED WATER), CERTIFICATE OF ANALYSIS COVERING VISCOSITY & POUR POINT TO ACCOMPANY EACH BATCH SHIPPED 55 GAL DRMS 55 GAL DRMS	PHILLIPS 66 LUBRICANTS CITGO CHEVRON PRODUCT COMPANY EXXON MOBIL CORP. NYCTA NYCTA	MULTIPURPOSE R&O OIL 68 PACEMAKER T68 REGAL R&O 68 TERRESTIC 68 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	7645	4400

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1708	OIL, FOR USE IN SOME SIMMONS WHEEL TRUING MACHINE BEARINGS AND GEARS; TO HAVE A VISCOSITY RANGE OF 400 TO 600 SUS @ 100 DEGREES F; TO HAVE A VISCOSITY OF 100 CST +/- 10% @ 40 DEGREES C; PACKAGED IN 55 GAL DRUMS; CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C TO BE PROVIDED FOR EACH BATCH DELIVERED. 55 GAL/ DRUM	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DTE OIL HEAVY CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1709	OIL, FOR CAR WASHER PUMPS, PARAFINIC BASED; ISO VISCOSITY GRADE 46 (VISCOSITY 41.4 TO 50.6 @ 40 DEGREES C); TIME TO 3 ML EMULSION AT 54 DEGREES C PER ASTM D1401 TO BE 15 MINUTES (MAXIMUM); API GRAVITY TO BE APPROXIMATELY 32.2, ZINC CONTENT TO BE APPROXIMATELY .008%; PACKAGED IN 5 GAL PAILS; CERTIFICATE OF ANALYSIS TO ACCOMPANY EACH BATCH SHIPPED 5 GAL/ PAIL	EXXON MOBIL CORP. NYCTA NYCTA	DTE OIL MEDIUM CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1720	LUBRICANT/RUST PREVENTATIVE FOR RAILCAR DOOR HANGERS, IN ONE QUART BOTTLES. APPLIED TO R68 DOOR HANGERS BY BRUSH OR WIPER. BLEND OF SYNTHETIC AND MINERAL OILS WITH MOLYBDENUM AND POLYTETRAFLUOROETHYLENE, SOLVENT FREE. PPE RQUIRED FOR USE; CHEMICAL SPLASH GOGGLES, NITRILE GLOVES. 1 QT/ BOTTLE	FLUORAMICS INC NYCTA NYCTA	HINDERRUST R2.0 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	498	269
69-12-1753	OIL, GEAR, AGMA #6EP, ISO VISCOSITY GRADE 320 (VISCOSITY OF 288 TO 352 CST @ 40 DEGREES C); PARAFINIC BASED; API GRAVITY TO BE 25 TO 30; FOR LUBRICATING CAR WASHER PUMP GEARS; PACKAGED IN 5-GAL PAILS; CERTIFICATE OF ANALYSIS TO BE PROVIDED FOR EACH BATCH SHIPPED 5 GAL/ PAILS	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL GEAR 600 XP 320 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1755	OIL, GEAR, ISO GRADE 220. FOR GEAR BOXES ON WHEEL TRUING MACHINES AND OTHER EQUIPMENT OPERATING UNDER HEAVY OR SHOCK LOADS. FORMULATED FROM HIGH-QUALITY OILS WITH HIGH OXIDATION STABILITY AND WATER SEPARATING CHARACTERISTICS WITH ADDITIVES TO PROVIDE EXTREME PRESSURE AND WEAR PROTECTION, RUST AND CORROSION PROTECTION, INCREASED OXIDATION STABILITY AND RESISTANCE TO FOAMING. MUST MEET THE FOLLOWING REQUIREMENTS: API GRAVITY 25 MINIMUM; DENSITY AT 15.6 DEGREES C 0.89 KG/L; FLASH POINT 255 DEGREES C MINIMUM; POUR POINT -24 DEGREES C MAXIMUM; VISCOSITY AT 40 DEGREES C-205-235 CST; VISCOSITY INDEX 95 MINIMUM; DEMULSIBILITY AT 82 DEGREES C 30 MINUTES MAXIMUM; COPPER STRIP CORROSION-1B MAXIMUM. MUST PASS RUST PROTECTION TEST AND FZG FOUR SQUARE GEAR TEST -12 STAGES MINIMUM. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND API GRAVITY MUST BE PROVIDED FOR EACH BATCH. PACKAGED IN 38-LB DRUMS. 38 LB/ DRUM	EXXON MOBIL CORP. NYCTA NYCTA	MOBILGEAR 600XP 220 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	456	684
69-12-1770	OIL, GEAR, ISO GRADE 100. FOR GEAR BOXES ON SIMMONS WHEEL TRUING MACHINES, (NOT INCLUDING #54 SERIES). EXTREME PRESSURE (3 EP); RESISTANT TO OIL OXIDATION, AND FOAMING/EMULSION FORMATION; TO PROVIDE RUST/CORROSION PROTECTION; MUST MEET THE FOLLOWING REQUIREMENTS: MINIMUM API GRAVITY TO BE 25; POUR POINT MAXIMUM TO BE -27 DEGREES C; VISCOSITY @ 40 DEGREES C TO BE 90-110 CST; PACKAGED IN 38 LB. PAILS; CERTIFICATE OF ANALYSIS COVERING BATCH(ES) DELIVERED TO BE PROVIDED; CERTIFICATE OF ANALYSIS TO COVER API GRAVITY, POUR POINT, VISCOSITY AT 40 DEGREES C. 38 LB PER EA	EXXON MOBIL CORP. NYCTA NYCTA	MOBILGEAR 600 XP 100 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1772	OIL, GEAR, #4 EP; ISO VISCOSITY GRADE 150 (VISCOSITY OF 135 TO 165 CST @ 40 DEGREES C); API GRAVITY TO BE APPROXIMATELY 26.65; FOR LUBRICATING CAR WASHER MIXER GEARS; PACKAGED IN 38-LB. PAILS); CERTIFICATE OF ANALYSIS TO BE PROVIDED FOR EACH BATCH SHIPPED 38 LB/ PAIL	EXXON MOBIL CORP. NYCTA EXXON MOBIL CORP.	MOBIL GEAR 600 XP 150 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-1811	OIL, SYNTHETIC, LUBRICATING, ISO320, USED ON ESCALATOR EXTERNAL GEARBOXES. TO BE SUPPLIED IN 5 GALLON PLASTIC PAILS. ASTM D445 VISCOSITY @40 DEGREES C:288-352 CST; @ 100 DEGREES C; 34.5-42.4 CST. ASTM D2270 VISCOSITY INDEX:154-190. ASTM D1401 WATER EMULSION TIME TO 37ML WATER @ A MINIMUM TEMPERATURE OF 82 DEGREES C: 25 MINUTES MAX 5 GAL/PAIL	MOBIL OIL CO NYCTA NYCTA	SHC632 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	535	290
69-12-1815	OIL, SYNTHETIC, DIESTER BASED COMPRESSOR; ISO GRADE 68; OXIDATION RESISTANT, FOR USE IN RECIPROCATING COMPRESSORS & OTHER APPLICATIONS; VISCOSITY @ 100 DEGREE C TO BE 7.4 CST +/- 0.74 CST; VISCOSITY @ 40 DEGREE C TO BE 68 CST +/- 6.8 CST; MINIMUM VI TO BE 64; DEMULSIBILITY @ 54 DEGREES C VIA ASTM D1401 (ML OIL/WATER/EMULSION) TO BE A MAXIMUM OF 3 ML EMULSION @ 30 MIN; 4-BALL WEAR@ 1200 RPM, 75 DEGREE C, 40KG, 1 HR, TO BE MAXIMUM 0.5MM; SPECIFIC GRAVITY TO BE 0.92 TO 0.96; MAXIMUM POUR POINT TO BE -30 DEGREE C; MINIMUM FLASH POINT TO BE 230 DEGREE C; CERT OF ANALYSES COVERING VISCOSITY @ 40 DEGREE C AND POUR POINT AS WELL AS A CERT OF CONFORMANCE TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 5-GAL PAILS. 5 GAL PAILS	CHEVRON NYCTA NYCTA	CETUS DE ISO 68 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	10	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1822	OIL, LIGHT MACHINE, PARAFFINIC BASED, ISO VISCOSITY GRADE 32, TO CONTAIN RUST AND OXIDATION INHIBITORS, MUST BE SEVERELY HYDROTREATED OR SEVERELY SOLVENT REFINED, MAXIMUM POUR POINT -20 DEGREES F; API GRAVITY TO BE 31-34; MINIMUM FLASH POINT TO BE 390 DEGREES F; VISCOSITY @ 40 DEGREES C TO BE 32 CST +/- 3.2 CST; VISCOSITY @ 100 DEGREES C TO BE 5.2 TO 5.7 CST; MINIMUM VISCOSITY INDEX TO BE 98; MUST PASS RUST TEST ASTM D665B; MAXIMUM TOTAL ACID NUMBER VIA ASTMD 974 TO BE 0.16 MG KOH/G OIL; OXIDATION STABILITY VIA ASTM D943 TO BE MINIMUM 3000 HOURS; TO HAVE FOAM STABILITY OF 0 ML VIA ASTM D892, SEQUENCE II; TO HAVE 3 ML OR LESS EMULSION AFTER 30 MINUTES @ 54 DEGREES C VIA ASTM D1401; COLOR VIA ASTM D1500 TO BE L0.5 TO 1.5; PACKAGED IN 5-GAL PAILS; CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE TO ACCOMPANY EACH BATCH SHIPPED; CERTIFICATE OF ANALYSIS TO INCLUDE API GRAVITY, VISCOSITY @ 40 DEGREES C, AND POUR POINT 5 GAL/PAIL	CHEVRON PRODUCT COMPANY NYCTA NYCTA	REGAL R&O 32 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2	0
69-12-1828	OIL, SYNTHETIC POLYOLESTER, FOR ROBINAIR COMPRESSORS IN REFRIGERANT/RECOVERY UNITS, MODELS 178002K/178012K; MUST HAVE VISCOSITY OF 20-25 CST@40 DEGREES CENTIGRADE; MINIMUM VISCOSITY INDEX TO BE 116; MAXIMUM TOTAL ACID NUMBER TO BE 0.05 MG KOH/G OIL; MAXIMUM WATER CONTENT 50 PPM; SPECIFIC GRAVITY 0.9-1.1, MAXIMUM POUR POINT TO BE -45 DEGREES F; MINIMUM FLASH POINT TO BE 490 DEGREES F; PACKED IN 5 GAL. PAILS. CERTIFICATE OF ANALYSES (TO INCLUDE VISCOSITY) & CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH SHIPMENT	ULTRACHEM INC. NYCTA NYCTA	RPOE22 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-1855	OIL, COMPRESSOR, PAO(POLYALPHAOLEFIN) BASED; ISO GRADE 46; FOR USE ON R156 LOCOMOTIVE AIR COMPRESSORS; VISCOSITY @ 40 DEGREES C TO BE 41.4 TO 50.6 CST; MINIMUM VISCOSITY INDEX TO BE 127; DEMULSIBILITY @ 54 DEGREES C AS MEASURED BY ASTM D 1401 TO BE 40/40/0 (30 MINUTES) OR BETTER; MINIMUM FLASH POINT TO BE 440 DEGREES F; MAXIMUM POUR POINT TO BE -30 DEGREES F; SPECIFIC GRAVITY TO BE 0.82 TO 0.90; CERTIFICATE OF ANALYSIS COVERING VISCOSITY AND POUR POINT AND CERTIFICATE OF COMPLIANCE TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKED IN 55 GAL DRMS	SENTINEL LUBRICANTS CORP. SUMMIT INDUSTRIAL PRODUCTS INC NYCTA NYCTA	SC0-10/20 SH-46 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	220	0
69-12-1877	OIL, LUBRICANT, SYNTHETIC, METALLIC ENGINE/CRANKCASE OIL. ENGINEERED TO PERFORM SATISFACTORILY FOR 40,000 MILES OR MORE/2,000 HOURS OR MORE BEFORE OIL CHANGE IS REQUIRED. MEETS OR EXCEEDS API STANDARDS AND MIL STANDARD SPECIFICATIONS. COMPLETELY COMPATABLE WITH ALL VEHICLES WITH NO ADDITIONAL ADDITIVES NEEDED. SUPPLIED IN 55 GALLON DRUM	SENTINEL LUBRICANTS CORP. NYCTA NYCTA	SENTINEL'S SUPER 5W40 LE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	3
69-12-1920	LUBRICANT, SYNTHETIC POLYOL ESTER, FOR USE IN REFRIGERATION AND AIR CONDITIONING COMPRESSORS USING HFC REFRIGERANTS; VISCOSITY @40 AND @ 100 DEGREES CENTIGRADE RESPECTIVELY. PACKAGED IN TWELVE QUART CANS PER BOX IS 66.6-72.3 CST AND 9.3-9.8 CST	LUBRIZOL CPI ENGINEERING SERVI NYCTA NYCTA	EMKARATE RL 68H CCSS-001 REV I 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S	0	8

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-2172	OIL, DIESEL ENGINE, SAE 10W-30 GRADE; SYNTHETIC BASED; MUST MEET API CJ-4 SERVICE CATEGORY; KINEMATIC VISCOSITY @ 100 DEGREES C TO BE 9.3 MM^2/SEC TO 12.5 MM^2/SEC; CERTIFICATE OF ANALYSIS COVERING KINEMATIC VISCOSITY MUST BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 55-GALLON DRUMS	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DELVAC EXTREME 10W-30 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2176	OIL, ENGINE, SAE GRADE 30; USED FOR 100-HOUR BREAK IN FOR KNORR AIR COMPRESSORS; VISCOSITY @ 100 DEGREES C TO BE 9.3 TO 12.49 CST; FOR FOAM TEST (ASTM D892)SEQUENCE II, MUST HAVE MAXIMUM VALUES OF 20/0 ML; PACKAGED IN 55 GAL DRMS	EXXON MOBIL CORP. NYCTA NYCTA	MOBIL DELVAC 1630 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2188	OIL, RE-REFINED, LUBRICATING, API CK-4, SAE 15W-40 FORMULATED WITH A LUBRIZOL ADDITIVE, IN BULK, FOR DIESEL ENGINES DDC SERIES 50, 60, CATERPILLAR C-13. CUMMINS ISB, ISL AND VOLVO D13. MUST MEET DETROIT DIESEL 93K222, CATERPILLAR ECF-3, CUMMINS CES20086 AND VOLVO VDS-4.5 SPECIFICATIONS. THE OIL MUST BE FORMULATED FROM RE-REFINED OIL STOCK AND THE FORMULATED OIL MUST CONTAIN AT LEASE 55% RE-REFINED OIL.	SAFETY-KLEEN STSTEMS PHILLIPS 66 LUBRICANTS ADVANCED LUBRICATION SPECIALTI NYCTA NYCTA	ECOPOWER 15W 40 CK-4 FIREBIRD HD EC DIESEL MOTOR OI TECHSELECT SYNTHETIC BLEND HD CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2189	OIL, RE-REFINED, LUBRICATING, API CK-4, SAE 15W-40, FORMULATED WITH LUBRIZOL ADDITIVE, IN 55 GALLON DRUMS, FOR DIESEL ENGINES, DDC SERIES 50, 60, CATERPILLAR C-13. CUMMINS ISB, ISL AND VOLVO D13. MUST MEET DETROIT DIESEL 93K222, CATERPILLAR ECF-3, CUMMINS CES20086 AND VOLVO VDS-4.5 SPECIFICATIONS. THE OIL MUST BE FORMULATED FROM RE-REFINED OIL STOCK AND THE FORMULATED OIL MUST CONTAIN AT LEAST 55% RE-REFINED OIL. 55 GAL DRMS	SAFETY-KLEEN STSTEMS PHILLIPS 66 LUBRICANTS ADVANCED LUBRICATION SPECIALTI NYCTA NYCTA	ECOPOWER 15W 40 CK-4 FIREBIRD HD EC DIESEL MOTOR OI TECHSELECT SYNTHETIC BLEND HD CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	55 GAL DRMS				
69-12-2191	OIL, LUBRICATING, API CJ-4, SAE 15W-40, FORMULATED WITH A LUBRIZOL ADDITIVE PACKAGE, IN BULK, FOR DIESEL ENGINES, DDC SERIES 50, 60, CATERPILLAR C-13, CUMMINS ISB AND ISL. MUST MEET DETROIT DIESEL 93K218, CATERPILLAR ECF-3 AND CUMMINS CES20081 SPECIFICATIONS. THE OIL MUST BE FORMULATED FROM VIRGIN OIL STOCK ONLY. BIDDERS MUST PROVIDE 1) PROOF THAT THE PRODUCT MEETS THE ABOVE REFERENCED SPECIFICATIONS. (2)PRODUCT DATA SHEET CONTAINING TYPICAL PROPERTIES. (3)PRODUCT MSDS SHEETS. (4)AN A2LA-ACCREDITED INDEPENDENT LABORATORY REPORT (LESS THAN 6 MONTHS OLD) SHOWING THAT THE OIL HAS A HT/HS APPARENT VISCOSITY @ 150 DEGREE C AND AFTER 90 CYCLES SHEAR TEST OF 3.9 CP MINIMUM WHEN TESTED PER ASTM D7109 AND D4683. (5) AN AFFIDAVIT FROM A PRINCIPAL OFFICER OF MANUFACTURER CERTIFYING THAT IF AWARDED THE FORMULA INCLUDING THE ADDITIVE PACKAGE WILL REMAIN UNCHANGED THROUGHOUT THE TERM OF THE CONTRACT. FAILURE TO PROVIDE NYCT THE REQUIRED INFORMATION ALONG WITH THE BID QUOTATION WILL RESULT IN DETERMINATION THAT THE BIDDER IS NON-RESPONSIVE.	CONOCOPHILLIPS CORPORATION NYCTA NYCTA NYCTA	FLEET SUPREME EC (LUBRIZOL ADD CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV D 12/2/15 RESTR S CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2192	OIL, LUBRICATING, API CJ-4, SAE 15W-40, FORMULATED WITH A LUBRIZOL ADDITIVE PACKAGE, IN 55 GALLON DRUMS, FOR DIESEL ENGINES, DDC SERIES 50, 60, CATERPILLAR C-13, CUMMINS ISB AND ISL. MUST MEET DETROIT DIESEL 93K218, CATERPILLAR ECF-3 AND CUMMINS CES20081 SPECIFICATIONS. THE OIL MUST BE FORMULATED FROM VIRGIN OIL STOCK ONLY. BIDDERS MUST PROVIDE: 1) PROOF THAT THE PRODUCT MEETS THE ABOVE REFERENCED SPECIFICATIONS. (2)PRODUCT DATA SHEET CONTAINING TYPICAL PROPERTIES. (3) PRODUCT MSDS SHEETS. (4) AN	CONOCOPHILLIPS CORPORATION NYCTA NYCTA	FLEET SUPREME EC (LUBRIZOL ADD CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	A2LA-ACCREDITED INDEPENDENT LABORATORY REPORT (LESS THAN 6 MONTHS OLD) SHOWING THAT THE OIL HAS A HT/HS APPARENT VISCOSITY @ 150 DEGREE C AND AFTER 90 CYCLES SHEAR TEST) OF 3.9 CP MINIMUM WHEN TESTED PER ASTM D7109 AND D4683. (5)AN AFFIDAVIT FROM A PRINCIPAL OFFICER OF MANUFACTURER CERTIFYING THAT IF AWARDED THE FORMULA INCLUDING THE ADDITIVE PACKAGE WILL REMAIN UNCHANGED THROUGHOUT THE TERM OF THE CONTRACT. FAILURE TO PROVIDE NYCT THE REQUIRED INFORMATION ALONG WITH THE BID QUOTATION WILL RESULT IN A DETERMINATION THAT THE BIDDER IS NON-RESPONSIVE.				
69-12-2212	OIL, HEAVY DUTY HYPOID GEAR; SAE GRADE 85W-140; API GL-5 LEVEL PERFORMANCE; FOR USE IN SHOP FORKLIFTS AND SHOP CRANES; VISCOSITY @ 40 DEGREES C TO BE 360 CST +/- 36 CST; VISCOSITY @ 100 DEGREES C TO BE 25 CST +/- 2.5 CST; MINIMUM VISCOSITY INDEX TO BE 91; MAXIMUM POUR POINT TO BE 15 DEGREES F; SPECIFIC GRAVITY TO BE ABOUT 0.9 (CORRESPONDS TO API GRAVITY OF ABOUT 25 TO 26); CERTIFICATE OF ANALYSIS COVERING VISCOSITY @ 100 DEGREES C TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 5-GAL PAILS 5 GAL/PAIL	NU-TIER GULF EXXON MOBIL CORP. NYCTA NYCTA	GULF MLTIPURPSE GEAR LUB 85W-1 MOBILUBE HD PLUS 85W-140 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	1
69-12-2220	OIL, WORM GEAR, MINERAL OIL BASED; ISO VISCOSITY GRADE 680, AGMA GRADE 8 COMPOUNDED. (3% TO 10% NATURAL OR SYNTHETIC FATTY OILS); VISCOSITY AT 40 DEGREES C TO BE 612-748 CST; API GRAVITY TO BE APPROXIMATELY 24.8 CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS INCLUDING VISCOSITY AND API GRAVITY TO BE PROVIDED TO NYCT MANAGER OF INSPECTIONS AND TESTING ANALYSIS PRIOR TO SHIPMENT FOR EACH BATCH; FOR USE IN WHEEL TRUING MACHINE WORM GEARS; PACKAGED IN 5-GAL PAILS	CHEVRON NYCTA NYCTA	CYLINDER OIL W ISO 680 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	5 GAL PAIL				
69-12-2480	OIL, HYDRAULIC, ELEVATOR, ISO 68, PETROLEUM BASED, TO BE SHIPPED IN RESEALABLE 5 GALLON PAILS AND TO BE LABELED "ISO 68 - USE ON HYDRAULIC ELEVATORS" 5 GAL/PAIL	EXXON MOBIL CORP. NYCTA NYCTA	NU TO H 68 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	360
69-12-2515	LUBRICANT, SILICONE, WATER-BASED, EMULSION, MINIMUM OF 5% USDA GRADE H1 SILICONE, FLASH POINT OF AT LEAST 140 DEGREES F, MUST MEET REQUIREMENTS OF NYCT SPECIFICATION 7119-FACIL-00, PACKAGED IN 5 GALLON CONTAINERS 5 GAL/CTR	ITW PRO BRANDS NYCTA NYCTA NYCTA	LPS HEAVY-DUTY SILICONE 7119-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	7	6
69-12-2549	LUBRICANT, ANTI-SEIZE, COPPER; TO HAVE A BROOKFIELD VISCOSITY(TD@5RPM@25 DEGREES C), OF 135,000 TO 235,000 MPAS; FOR USE ON STAINLESS STEEL AND OTHER ALLOYS; PACKAGED IN 8 OZ. BRUSH TOP JAR; CERTIFICATE OF ANALYSIS TO ACCOMPANY SHIPMENT	PERMATEX, INC. NYCTA NYCTA	COPPER ANTI-SEIZE LUBRICANT091 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2550	LUBRICANT, DRY FILM; MULTI-PURPOSE; CONTAINS MOLYBDENUM DISULFIDE; MUST HAVE EFFECTIVE TEMPERATURE RANGE OF -20 DEGREES F TO 750 DEGREES F., NON-VOLATILE CONTENT 19%-25%; MUST PREVENT RUST ON METAL PARTS; PACKAGED IN 5-1/4 AEROSOL CAN WITH WARRANTY FOR TWO YEARS FROM THE SHIPMENT DATE. CERTIFICATE OF CONFORMANCE & CERTIFICATE OF ANALYSES INCLUDING % NON-VOLATILE AND SPECIFIC GRAVITY MUST BE PROVIDED FOR EACH BATCH SHIPPED 5.25 AEROS	VALSPAR CORPORATION NYCTA NYCTA	DRI-SLIDE MULTI-PURPOSE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-2590	LUBRICANT, RUBBER LUBRICANT LIQUID EMULSION, IN 475-ML CONTAINERS; 6 CONTAINERS/BOX. USED TO AID THE ATTACHMENT/INSERTION OF RUBBER/SOFT PLASTIC PARTS WHERE THERE IS A TIGHT FIT. ESPECIALLY FOR USE ON R142A CURRENT COLLECTOR ASSEMBLY. PROVIDES A WATER BASED EMULSIVE FILM THAT TEMPORARILY MAKES RUBBER SURFACES SLIPPERY. WHEN PRODUCT DRIES, THE FILM DISAPPEARS. DOES NOT CONTAIN ANY SILICONES OR PETROLEUM DISTILLATES. NON-FLAMMABLE. TOTAL SOLIDS 18% TO 22% BY WEIGHT; SPECIFIC GRAVITY 0.97 TO 1.03; PH 7.5 TO 9.5; VISCOSITY 100 - 200 CPS (BROOKFIELD #2 SPINDLE @ 100 RPM). TO BE STORED AT TEMPERATURES BETWEEN 36 DEGREES F AND 86 DEGREES F. DO NOT ALLOW PRODUCT TO FREEZE. SHELF LIFE IS TWO YEARS FROM THE DATE OF MANUFACTURE. CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO BE PROVIDED TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPMENT. C OF A TO INCLUDE VISCOSITY AND PH 6 PT/BOX	INTERNATIONAL PRODUCTS CORP. NYCTA NYCTA	P-80 #P-5391-06 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	41	16
69-12-2605	OIL, 3 IN 1, NAPHTHENIC BASED, FOR CLEANING, LUBRICATING AND PROVIDING RUST PREVENTION FOR VARIOUS SHOP MACHINERY AND RAILCAR PARTS; SPECIFIC GRAVITY TO BE 0.8 TO 1.0; MINIMUM FLASH POINT VIA ASTM D92 TO BE 285 DEGREES F; MAXIMUM POUR POINT VIA ASTM D97 TO BE -5 DEGREES F; MINIMUM BOILING POINT VIA ASTM D1120 TO BE 570 DEGREES F; VISCOSITY @ 40 DEGREES C TO BE 32-38 CST; VISCOSITY @ 100 DEGREES C TO BE 4.2 TO 6.2 CST; MAXIMUM WATER CONTENT VIA ASTM D1533 TO BE 0.0023%; COPPER CORROSION AS MEASURED VIA ASTM D130 TO BE 1A; EVAPORATION RATE @ 760 DEGREES F VIA ASTM D86 TO BE ABOUT 90%; PACKAGED IN 4-OZ CONTAINERS; CERTIFICATE OF COMPLIANCE AND CERTIFICATE OF ANALYSIS TO ACCOMPANY EACH BATCH SHIPPED; 24 CONTAINERS PER BOX	MCGEE INDUSTRIES CASTOLEUM CORP. NYCTA NYCTA	MCLUBE 31MP TRIZOL GP #1011 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	23662	14752

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	4 OZ CTR				
69-12-2640	OIL, RAW, CASTOR, USED TO LUBRICATE RAILCAR WHEELS AND AXLES; APPLIED BY BRUSH; MUST MEET REQUIREMENTS OF ASTM D960-79 STANDARD EXCEPT FOR COLOR (CAN BE 3, MAXIMUM ON GARDNER SCALE)AND LOSS ON HEATING REQUIREMENTS: PACKAGED IN 5 GALLON CANS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/ COMPLIANCE FOR EACH BATCH MUST BE SUPPLIED PRIOR TO SHIPMENT AND MUST ACCOMPANY EACH SHIPMENT 5GAL CAN/PKG	WELCH, HOLME & CLARK NYCTA NYCTA ASTM	#1 INDUSTRIAL CASTOR OIL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S D960-79	140	90
69-12-2648	OIL, WHITE, MINERAL, PARAFFINIC BASED; CLEAR, FOR USE IN CAR WASHER PUMPS AND OTHER EQUIPMENT; VISCOSITY @ 40 DEGREES C TO BE 27 CST TO 32 CST; MAXIMUM POUR POINT TO BE -20 DEGREES C; PACKAGED IN 5-GAL PAILS; CERFIFICATE OF ANALYSIS COVERING VISCOSITY @ 40 DEGREES C TO BE PROVIDED FOR EACH BATCH SHIPPED	NYE LUBRICANTS, INC. NYCTA NYCTA	NYOIL CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-2981	OIL, HYDRAULIC, ISO GRADE 32. FOR HYDRAULIC SYSTEMS, OPERATING AT HIGH SPEEDS, TEMPERATURES AND PRESSURES. FORMULATED FROM HIGH-QUALITY REFINED PARAFFIN BASE WITH INHIBITORS FOR WEAR, RUST AND OXIDATION, INCLUDING ZINC TYPE ADDITIVES TO PROVIDE EXTREME-PRESSURE AND WEAR PROTECTION, RUST AND CORROSION PROTECTION, INCREASED OXIDATION STABILITY AND RESISTANCE TO FOAMING. MUST MEET THE FOLLOWING REQUIREMENTS; API GRAVITY 29-35; FLASH POINT 385 DEGREES F MINIMUM, POUR POINT -20 DEGREES F MAXIMUM; VISCOSITY AT 40 DEGREES C29-33CST; VISCOSITY INDEX 95-120; OXIDATION STABILITY 2500 + HOURS; EMULSION SEPARATION TIME AT 130 DEGREES F 30 MINUTES MAXIMUM; FOAMING TENDENCY/ STABILITY TEST 20/0 ML MAXIMUM. MUST PASS COPPER STRIP	CITGO PHILLIPS 66 LUBRICANTS NYCTA NYCTA	A/W HYDRAULIC OIL 32 MEGAFLOW AW HYDRAULIC OIL 32 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	300	165

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	CORROSION TEST. MUST MEET OR EXCEED PERFORMANCE REQUIREMENTS OF CINCINNATI MACHINE'S P-68 SPECIFICATION. PACKAGED IN 5-GAL CONTAINERS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTION AND TESTING PRIOR TO SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE API GRAVITY AND VISCOSITY. 5 GAL CTR 5 GAL CTR				
69-12-3100	OIL, PENETRATING, USED TO LOOSEN METALLIC PARTS DUE TO CORROSION. MUST HAVE 16.5-25 CST VISCOSITY @ 40 DEGREES C. 0.85-1.0 SPECIFIC GRAVITY @ 20 DEGREES C. MINIMUM 160 DEGREES C FLASH POINT. MAXIMUM -40 DEGREES C POUR POINT. PACKAGED IN 1-GALLON CANS. CERTIFICATE OF COMPLIANCE AND CERTIFICATE OF ANALYSIS FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT 1 GAL/CAN	CHESTERTON CASTOLEUM CORP. NYCTA NYCTA NYCTA	690 FG LUBRICANT TRIZOL PENETRATING LUBR. #PL11 7097-FACIL-99 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	210	131
69-12-3110	OIL, PENETRATING, SYNTHETIC BASED; NON-SOLVENT AND NON-PROPELLENT, COMPLETELY BIODEGRADABLE; USED WITH ALL METALS, RUBBER, VINYL AND PLASTIC IN THE TEMPERATURE RANGE FROM -80 DEGREES F TO +380 DEGREES F; MUST HAVE 18-25 CST VISCOSITY @ 100 DEGREES F., 0.8-1.1 SPECIFIC GRAVITY @ 60 DEGREES F, ACID NUMBER 0.10 MG/G MAXIMUM; PACKED 14 OZ PRESSURED CAN; CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND SPECIFIC GRAVITY MUST BE PROVIDED FOR EACH BATCH TO NYCT MANAGER OF TESTING ANALYSIS BEFORE SHIPPING MATERIAL	SUPERIOR NYCTA NYCTA	SLIP 2000 SYNTHETIC LUBRICANT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-3175	SOLVENT, PENETRATING, USED TO PENETRATE RUSTED METAL PARTS; BOLTS AND MACHINERY; SPECIFIC GRAVITY TO BE 0.8 TO 1.25; MINIMUM 130 DEGREE F FLASH POINT AS MEASURED BY ASTM D92; MINIMUM 300 DEGREE F BOILING POINT AS MEASURED BY ASTM D1120; PACKAGED IN 4-OZ CANS; CERTIFICATE OF ANALYSIS (COVERING SPECIFIC GRAVITY, FLASH POINT, AND BOILING POINT) AS WELL AS CERTIFICATE OF COMPLIANCE TO BE PROVIDED FOR EACH BATCH SHIPPED 4 OZ/CAN	RADIATOR SPECIALTY CASTOLEUM CORP. NYCTA NYCTA	LIQUID WRENCH NO 1 #L1-04 TRIZOL PENETRATING SOLVNT TPS1 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	38246	25407
69-12-3185	SOLVENT, PENETRATING, LOW VISCOSITY, INDUSTRIAL STRENGTH, FOR USE TO LOOSEN AND FREE SEIZED, BOUND OR FROZEN FASTENERS; MUST COMPLY WITH ALL CURRENT VOC REGULATIONS; PACKAGED IN 16 OZ VOLUME WITH A NET WEIGHT OF 13 OZ; 12 CANS PER BOX	CRC INDUSTRIES, INC. NYCTA NYCTA	KNOCK'ER LOOSE SOLVENT 03020 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1274	474
69-12-3400	LUBRICANT, SYNTHETIC HYDROCARBON, ALKYL BENZENE, ISO GRADE 68 VISCOSITY, FOR USE IN REFRIGERANT RECOVERY UNITS, MUST MEET THE REQUIREMENTS OF NYCT SPEC. 7134-FACIL-01, PACKED IN 10 OZ. (NET WEIGHT), SCREW CAP PLASTIC CONTAINERS, 12 CONTAINERS IN A BOX. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS/CERTIFICATE OF COMPLIANCE FOR EACH BATCH SHIPPED. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, SPECIFIC GRAVITY, FLASH POINT, % WATER, TOTAL ACID NUMBER, FLOC POINT 12 CTR/BOX	SYN OILS & LUBRICANTS OF TEXAS NYCTA NYCTA NYCTA	RF 300/ISO 68 7134-FACIL-01 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-3500	OIL, LINSEED, BOILED; MUST MEET THE REQUIREMENTS OF ASTM D 260 TYPE I REGULAR BOILED; PACKAGED IN FIVE GALLON CONTAINERS. CERTIFICATE OF COMPLIANCE AND ANALYSIS FOR EACH BATCH MUST BE SUPPLIED PRIOR TO SHIPMENT TO THE MANAGER OF INSPECTIONS & TESTING AND MUST ALSO ACCOMPANY EACH SHIPMENT; CERTIFICATE OF ANALYSIS TO INCLUDE COLOR (GARDNER), APPEARANCE, ACID VALUE AND IODINE VALUE 5 GAL CTRS	CARGILL INC. ADM NYCTA NYCTA ASTM	BOILED LINSEED OIL SCIBOIL/DGMDLINSEDOILW/DRI0010 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S D 260	0	0
69-12-3502	CONCENTRATE, FLUID, METAL WORKING, SYNTHETIC, CLEAR, IN 5 GALLON PAILS. FOR MACHINING AND GRINDING OPERATIONS OF FERROUS METALS (CAST IRON, NODULAR IRON, CARBON STEELS, HIGH SPEED STEELS, HIGH ALLOY STEELS, STAINLESS STEELS, TOOL STEELS, TITANIUM). NOT TO BE USED WITH ALUMINUM ALLOYS, MAGNESIUM OR ALLOYED MAGNESIUM. FOR MODERATE TO HEAVY DUTY OPERATIONS. MUST BE MIXED WITH WATER FOR USE (ADD CONCENTRATE TO WATER). TYPICAL OPERATING RANGE 5% (1:20) TO 10% (1:10). PROVIDES GOOD FERROUS CORROSION CONTROL, BACTERIA AND MOLD CONTROL. USE DOES NOT PRODUCE OILY MIST OR SMOKE. HAS LOW CARRY-OFF ON PARTS OR CHIPS. PH CONCENTRATE IS 9.6-10.2; SPECIFIC GRAVITY 1.0514-1.0614. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS FOR EACH BATCH. C OF A TO INCLUDE PH AND SPECIFIC GRAVITY. 5 GAL/PAILS	CIMCOOL NYCTA NYCTA	CIMTECH 500 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	2

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
69-12-3525	LUBRICANT, PASTE METALWORKING, NON-CORROSIVE, FREE OF HALOGENS, HEAVY METALS AND SILICONE; MUST HAVE 20-25 CST VISCOSITY @ 100 DEGREES F, 0.8-1.0 SPECIFIC GRAVITY @ 77 DEGREES F, PACKED IN 12 OZ. JARS, 12 PER CASE. 12 OZ JARS/PKG	ORELUBE CORP. NYCTA NYCTA	BOELUBE 70305 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2	0
69-12-3535	LUBRICANT, PENETRATING OIL, CONTAINS PTFE ADDITIVE, DESIGNED FOR USE IN WIRE PULLING TO ENSURE SMOOTH AND EASILY PULL OF CABLES; PACKAGED IN 32 OZ. SQUEEZE BOTTLE AND TWELVE BOTTLES PER BOX	IDEAL INDUSTRIES NYCTA NYCTA	YELLOW77PLUS WIRE PULL LUBRICA CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-3550	LUBRICANT, FOR ROLL UP DOORS ASSEMBLIES AND OVERHEAD DOOR ASSEMBLIES. PREVENTS FRICTION AND WEAR. USED TO LUBRICATE AND PROTECT CABLES, CHAINS, BEARINGS, ROLLERS, DOOR TRACKS AND DOOR HINGES. 11 OZ NET WEIGHT IN 16 OZ. AEROSOL CAN. 12 CANS PER CASE. FLASH POINT 170F(TCC) MINIMUM, VOC 2.67 LBS/GAL OR 39.1 WEIGHT %, CARBON DIOXIDE PROPELLANT. NOT FOR USE ON PLASTIC. DO NOT USE NEAR AN OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION. USE CAUTION AROUND ENERGIZED EQUIPMENT. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES, NEOPRENE OR NITRILE GLOVES.	CRC INDUSTRIES, INC. NYCTA NYCTA	ROLL-UP DOOR LUBRICANT #03029 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
69-12-5196	OIL, SYNTHETIC HYBRID BASE OIL, FOR LUBRICATING R142, R142A, AND R143 DOOR OPERATOR DRIVE SCREWS ONLY; PACKAGED IN 35LB. CONTAINERS, OIL CONSISTS OF MULTI-FLUID, EXHIBITS EXCELLENT ANTI-WEAR AND EXTREME PRESSURE PROPERTIES AND OXIDATION STABILITY, DESIGNATED FOR GOOD MECHANICAL LUBRICITY AND LONG LIFE CHARACTERISTICS;CAPABLE OF OPERATING IN TEMPERATURE RANGES FROM -40F TO 300F; ISO GRADE IS 46(NOMINAL); VISCOSITY(ASTM 445 @ 40C) IS BETWEEN THE RANGE OF 40 TO 55 CST; VISCOSITY	SYNTECH LTD. NYCTA NYCTA	NS-2716-F CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	280	385

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	(ASTM D445 @ 100C) IS BETWEEN THE RANGE OF 6.2 TO 8.2 CST; VISCOSITY INDEX (ASTM D2270) IS 117 (NOMINAL); CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS FOR EACH BATCH MUST BE PROVIDED TO THE NYCT MANAGER OF TESTING AND ANALYSIS PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS MUST INCLUDE ISO GRADE; VISCOSITY (ASTM 445 @ 40C AND 100C IN CST); AND VISCOSITY INDEX IN 35LB CTRS				
69-14-2262	OIL, HYDRAULIC, SAE 10W-20, ISO 46, BIODEGRADABLE BASE OIL, VISCOSITY @ 40 DEGREES C IS 42.75 - 52.25 CST; VISCOSITY @ 100 DEGREES C IS 8.64-10.56 CST; POUR POINT IS -40 DEGREE C MINIMUM; FLASHPOINT IS 240 DEGREES C MINIMUM; FOR USE IN TAMPER CARS; PACKAGED IN 55 GALLON DRUMS. CERTIFICATE OF ANALYSIS SUPPLIED FOR EACH BATCH MUST INCLUDE VISCOSITY 55 GAL/ DRUMS	SENTINEL LUBRICANTS CORP. NYCTA NYCTA	BIOSYNHO46 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	110	110
70-02-1022	ABSORBENT & ENCAPSULATING COMPOUND, FOR OIL AND DIESEL FUEL, PEAT BASED WITH OIL DIGESTING MICROBES, (NOT FOR USE WITH WATER BASED PRODUCTS), 18-20 POUND BAG 18-20LB/BAG	AMERICAN PRODUCTS NYCTA NYCTA	HTP CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	125	120
70-02-1023	FLOCCULATING/SEPARATING AGENT, FOR USE IN WATER FILTRATION SYSTEM FOR TREATMENT OF RAILCAR AIR CONDITIONER CONDENSER WASHING EFFLUENT IN ORDER TO MEET SEWER DISCHARGE CODES. AGENT ALLOWS THE SUSPENDED SOLIDS, METALS, TO BE REMOVED FROM SOLUTION. SEPARATING AGENT IS SUPPLIED IN 5 POUND WATER SOLUBLE POLYMER FILM PACKETS. 30 POUNDS PER CASE. 24 CASES PER PALLET	WYO-BEN, INC. NYCTA NYCTA	CLEARTREAT 2300GRP-5 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	39	138

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	24 CSE/PLT				
70-02-1040	ABSORBENT, OIL, GREASE, WATER ABSORBING COMPOUND, INCINERABLE BASE OF NATURAL AND/OR RECYCLED ORGANIC MATERIALS; RECYCLED NEWSPRINT. MINIMUM ABSORBENCY = 1.4 ML/G; SAE NO. 10 OIL, 0.4ML/G WATER. PARTICLE SIZE = 98% GREATER THAN NO. 60 US MESH SCREEN, 17% LESS THAN NO. 6 US MESH SCREEN. TESTED IN ACCORDANCE WITH COMMERCIAL ITEM DESCRIPTION A-A-1979. LESS THAN 3.5% ASH. SHIPPED IN 22 LB. BAGS, PALLETIZED 1188 LBS PER PALLET. ** CERTIFICATE OF COMPLIANCE AND CERTIFICATE OF ANALYSIS FOR EACH BATCH TO ACOMPANY EACH SHIPMENT** 22 LB/ BAG	ABSORPTION CORPORATION NYCTA NYCTA	SPILL-SORB CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-04-0121	ADHESIVE, POLYURETHANE, TWO-COMPONENT ADHESIVE FOR USE WITH NORAMENT RUBBER FLOORING SYSTEMS. IT SHALL HAVE: VISCOSITY (BY THE BROOKFIELD RVF VISCOMETER) PART A(RESIN) 55,000-85,000 CPS, PART B(CATALYST) 400-900 CPS; POTLIFE A & B 45-60 MINUTES; VOC A & B <0.1 LBS PER GALLON; % SOLIDS BY WEIGHT A & B>99; FLASH POINT A & B> 200 DEGREES F. IT SHALL HAVE FREEZE THAW STABILITY AND A GOOD RESISTANCE TO MOISTURE AND MANY CHEMICALS; KIT=1 GALLON OF A RESIN & 14 OZ. OF B CATALYST. CERTIFICATE OF ANALYSES & CERTIFICATE OF CONFORMANCE/COMPLIANCE MUST ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSES MUST CONTAIN VISCOSITY FOR A & B; POTLIFE FOR A & B MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 8 MONTHS. IN 2 PART KIT	NORA SYSTEMS INC NYCTA NYCTA	NORA 310 (PARTS A & B) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	37	10

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-04-0127	ADHESIVE, TWO-COMPONENT POLYURETHANE, FOR USE WITH NORAMENT RUBBER FLOORING SYSTEMS. IT SHALL HAVE VISCOSITY (BY THE BROOKFIELD RVF VISCOMETER) PART A (RESIN) 55,000-85,000 CPS, PART B (CATALYST) 400-900 CPS; POTLIFE A & B 45-60 MINUTES; VOC A & B < 0.1LBS PER GALLON; % SOLIDS BY WEIGHT A & B > 99; FLASH POINT A & B > 200 DEGREES F. IT SHALL HAVE FREEZE THAW STABILITY AND A GOOD RESISTANCE TO MOISTURE AND MANY CHEMICALS; KIT=1 QUART(27 OZ. OF RESIN AND 3.1 OZ. OF CATALYST). CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE/COMPLIANCE MUST BE PROVIDED TO THE NYCT MANAGER OF INSPECTION AND TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS MUST CONTAIN VISCOSITY FOR A & B; POTLIFE FOR A & B AND MUST BE SUPPLY WITHIN 30 DAYS OF MANUFACTURER DATE	NORA SYSTEMS INC NYCTA NYCTA	NORA 310 (PARTS A & B) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-04-1031	SEALANT, SILICONE RUBBER, RTV, BLACK, ONE-COMPONENT GENERAL PURPOSE PASTE, IN 10.1 OUNCE CARTRIDGES, FOR USE ON SUBWAY CARS AND HOUSE MAINTENANCE. MUST MEET REQUIREMENTS OF MILITARY SPECIFICATION MIL-A-46106. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO BE SUPPLIED TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE: HARDNESS, ELONGATION, TENSILE STRENGTH, PEEL STRENGTH 10.1 OZ CART	DOW-CORNING MOMENTIVE PERFORMANCE MATERIAL NYCTA NYCTA MIL SPEC	732 MULTIPURPOSE BLACK RTV 103-BLACK-CRTRG CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46106	982	394

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-04-1042	ADHESIVE/SEALANT, HIGH PERFORMANCE ELASTOMERIC MUST EXHIBIT EXCELLENT ADHESION TO SUBSTRATES INCLUDES METALS, GLASS, PLASTICS AND NON-METALS; FAST CURING, MUST NOT CONTAIN ISOCYANATES, CERTIFICATE OF COMPLIANCE INCLUDES PROPERTIES OF VISCOSITY, ADHESION, CURE RATE, SAG, UV APPEARANCE AND SKIN TIME MUST BE PROVIDED TO NYCT MANAGER OF TESTING PRIOR TO SHIPPING, PACKAGED IN 10.1 OZ CARTRIDGES	MANUS PRODUCTS, INC. NYCTA NYCTA	MANUS-BOND 75-AM CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-04-1044	ADHESIVE, SEALANT, 1-COMPONENT, ELASTOMERIC, WHITE, 290 ML CARTRIDGE, 12 PER CASE. USED FOR FLOORING INSTALLATION ON R46 RAILCARS. BONDS FLOORS, INTERIOR/EXTERIOR PANELS, METALS, GLASS, PLASTICS, FIBERGLASS, GLASS, STONE, CERAMIC AND WOOD. GIVES HIGH STRENGTH BONDS TO REPLACE RIVETS AND MECHANICAL FASTENERS. DOES NOT CONTAIN ISOCYANATES. TENSILE STRENGTH 250-270 PAI; SHSORE D HARDNESS 50-60; TACK FREE @73 DEGREES F & 50% RELATIVE HUMIDITY 10-30 MINUTES. PPE REQUIRED: CHEMICAL SPLASH GOOGLES AND POLYETHYLENE OR PVA GLOVES. RAILCAR WINDOWS AND DOORS ARE TO BE OPENED FOR VENTILATION DURING THE APPLICATION OF THIS PRODUCT. BLOWER FANS MY BE USED IN THE VICINITY OF THE WORK AREA TO PROVIDE INCREASED AIR DILLUTION. 290 ML CART 12 PER CASE	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	HYBRID ADHESIVE SEALANT 760 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	9	9
70-04-1342	COMPOUND, RETAINING, FAST CURING ANAEROBIC RESIN FOR BONDING GAPS UP TO 0.004" IN CYLINDRICAL MATING PARTS (SHAFTS, BEARINGS, PINS, CAPS & PLUGS). COLOR GREEN IN 10CC. CERTIFICATE OF ANALYSIS TO INCLUDE: VISCOSITY AND SHEAR STRENGTH. IN 10CC TBE	HERNON MFG HENKEL CORPORATION PERMABOND LLC SAF-T-LOK NYCTA NYCTA MIL SPEC	CYLINLOCK 822 LOCTITE 609 RETAIN COMP #60921 PERMABOND HL 138 R01 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-R-46082B TYPE I	119	29

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-04-1344	COMPOUND, RETAINING FAST CURING ANAEROBIC RESIN FOR BONDING GAPS UP TO 0.004" IN CYLINDRICAL MATING PARTS (SHAFTS, BEARINGS, PINS, CAPS & PLUGS). COLOR GREEN IN 250 ML BOTTLES. CERTIFICATE OF ANALYSIS TO INCLUDE: VISCOSITY AND SHEAR STRENGTH IN 250 ML BTLS	HERNON MFG HENKEL CORPORATION SAF-T-LOK NYCTA NYCTA MILITARY	CYLINLOCK 822 LOCTITE 609 RETAIN COMP #60941 R01 #20141 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-R-46082B TYPE 1	22	45
70-04-1426	ADHESIVE, STRUCTURAL, 2 PART EPOXY, NON-FLAMMABLE, GRAY, FOR USE ON RUBBER, WOOD, PLASTICS AND MASONRY PRODUCTS; VISCOSITY OF BASE 75.000-150.000, ACCELERATOR 40.000-80.000 CPS; WEIGHT PER GALLON OF BASE 11.1-11.6 ACCELERATOR 10.5-11.0 LBS; WORK LIFE OF MIXED PRODUCT 90 MIN MINIMUM, OVERLAP SHEAR STRENGTH AT 75 DEGREE F 3200 PSI MINIMUM, DUROMETER HARDNESS 50-65, T-PEEL STRENGTH 25 PIW MINIMUM; MUST PASS SMOKE DENSITY (ASTM E-662) AND FLAME SPREAD (ASTM E-162) TESTS: PACKAGED IN A KIT, WHICH CONSISTS OF ONE-GALLON ACCELERATOR AND 2/3 GALLON BASE. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE TO BE PROVIDED FOR EACH BATCH TO THE MANAGER OF INSPECTIONS AND TESTING BEFORE SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE WEIGHT PER GALLON AND VISCOSITY FOR BASE AND ACCELERATOR. IN 2 PART KIT	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	SCOTCHWELD 2216 B/A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-04-1710	ADHESIVE, INSTANT, SUPERBONDER, MEDIUM VISCOSITY (65-125 CPS), FOR BONDING METAL, PLASTIC AND VINYL PARTS, GAP FILLING ABILITY UP TO 0.005", CLEAR, IN 1 OZ. BOTTLES, FOR R62 CARS. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. CERTIFICATE OF ANALYSIS TO INCLUDE: VISCOSITY AND TENSILE SHEAR 1 OZ BOTTLES	ND INDUSTRIES SAF-T-LOK PERMABOND GSA SPEC. NYCTA NYCTA	31428 INSTANT SUPERGLUE IB 100 INSTANT BONDER PERMABOND 102 A-A-3097 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	3554	1949
70-04-1810	ADHESIVE, EPOXY, TWO-COMPONENT, FAST CURING, HIGH STRENGTH, FOR PERMANENT BONDING METALS, CERAMICS, CONCRETE, WOOD, GLASS AND MOST PLASTICS, COLORLESS LIQUID; PACKAGED IN ONE OUNCE KIT, WHICH CONSISTS OF EPOXY RESIN AND HARDENER. SPECIFIC GRAVITY OF RESIN BETWEEN 1.15-1.19, OF HARDENER 1.02-1.06; VISCOSITY OF RESIN-16,000-35,000. VISCOSITY OF HARDENER-10,000-28,000 MPAS, EPOXY RESIN AND HARDENER SHALL HAVE A MIXING RATIO OF 1:1; TENSILE SHEAR STRENGTH OF CURED ADHESIVE SHALL BE A MINIMUM OF 1490 PSI; SPEED OF CURE FOR SETUP OF FIXTURE/GEL TIME 4-10 MINUTES AND WITHIN 1 HOUR FOR FULL CURE. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS WHICH INCLUDES VISCOSITY FOR EACH BATCH AND TENSILE STRENGTH IS TO BE PROVIDED TO NYCT MANAGER OF TESTING AND ANALYSIS PRIOR TO SHIPPING MATERIAL. "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS". IN 1 OUNCE KIT	HENKEL CORPORATION NYCTA NYCTA	LOCTITE EA 9017 (A&B) #1324007 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1085	745

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-07-2016	ANTIFREEZE SOLUTION, RV TYPE, PROPYLENE GLYCOL/WATER MIXTURE (ABOUT 30% PROPYLENE GLYCOL, 70% WATER); PH TO BE ABOUT 9.2; FREEZING POINT MAXIMUM TO BE 10 DEGREES F; 1-GALLON CONTAINERS; FOR CORROSION PROTECTION OF GREENLEAF DEICER SPRAYERS OBTAINED UNDER STOCK # 61-46-5850	PRESTONE PRODUCTS CORPORATION NYCTA NYCTA	RV ANTIFREEZE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-11-1950	COMPOUND, CAULKING, ACRYLIC LATEX WITH SILICONE USED FOR CAULKING AND SEALING WINDOWS AND DOORS FRAMES. MUST MEET ASTM C-920, SUPPLIED IN 10.1 OZ CARTRIDGES. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 10.1 OZ CRTRDGS	RED DEVIL ASTM NYCTA NYCTA	LIFETIME ADHESIVE SEALANT(0856) C-920 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	210	83
70-11-1977	ADHESIVE, SEALANT, SILICONE RUBBER, RTV, ONE COMPONENT THIXOTROPIC PASTE, GENERAL PURPOSE SEALING AND BONDING, CLEAR/TRANSLUCENT, 10.1 TO 10.3 FLUID OZ. CARTRIDGE. CERTIFICATE OF ANALYSIS TO INCLUDE: HARDNESS, % ELONGATION, TENSILE STRENGTH AND PEEL STRENGTH 10.1 TO 10.3 OZ	DOW CORNING MOMENTIVE AMER IND NYCTA NYCTA MIL SPEC	732 RTV 108 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46106B	4817	2461
70-11-1980	ADHESIVE, SEALANT, SILICONE RUBBER, RTV, ONE COMPONENT THIXOTROPIC PASTE, GENERAL PURPOSE SEALING AND BONDING, ALUMINUM, IN 10.1 TO 10.3 FLUID OUNCE CARTRIDGES. CERTIFICATE OF ANALYSIS TO INCLUDE: HARDNESS, ELONGATION, TENSILE STRENGTH AND PEEL STRENGTH. 10.1 TO 10.3 OZ	DOW CORNING MOMENTIVE AMER IND NYCTA NYCTA MIL SPEC	732 ALUMINUM RTV 109 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46106	330	151

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-11-1982	ADHESIVE, RTV SEALANT, USED ON R142 CARS TO ADHERE/SEAL A STEEL PLATE ON THE END CAP ON TRACTION MOTOR. WHITE SILICONE. WITHSTANDS EXTREME TEMPERATURE CYCLING, 300 ML CARTRIDGE. TACK FREE TIME 45 MIN MAXIMUM; DUROMETER HARDNESS(SHORE A) 14 MINIMUM; TENSILE STRENGTH 0.8 N/MM2 MINIMUM; BREAKING ELONGATION 275% MINIMUM. CERTIFICATE OF ANALYSIS/CERTIFICATE OF COMPLIANCE TO BE PROVIDED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE TACK FREE TIME, HARDNESS, TENSILE STRENGTH, ELONGATION. 300 ML CARTRIDG	HENKEL CORPORATION NYCTA NYCTA	LOCTITE SI WH #59475 SUPERFLEX CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			52	36
70-11-1984	SEALANT, ADHESIVE, ONE-COMPONENT SILICONE RUBBER, ROOM TEMPERATURE VULCANIZING (RTV); FOR USE IN OVERHAUL OF RAILCAR HVAC UNITS; MINIMUM CURED TENSILE STRENGTH TO BE 600 PSI; CURE TIME TO BE 24 HOURS; CURED SHORE A HARDENESS TO BE 22-37; PACKAGED IN 5.4-OZ. TUBES; CERTIFICATE OF ANALYSIS COVERING CURED TENSILE STRENGTH TO BE PROVIDED FOR EACH BATCH SHIPPED	MOMENTIVE PERFORMANCE MATERIAL NYCTA NYCTA	RTV 157 CCSS-001, REV I, 3-9/11 LABEL CCSS-003 REV E 9/11/17 RESTR S			0	0
70-13-1320	ADHESIVE, MULTI-PURPOSE, FAST DRYING, FOR BONDING POROUS AND NON-POROUS MATERIALS SUCH AS CERAMICS, MARBLE, GLASS, METAL, LEATHER, FABRIC, PAPER LABELS. TRANSPARENT IN 1.0 OZ TUBES. MUST MEET REQUIREMENTS OF COMMERCIAL ITEM DESCRIPTION A-A-529A, EXCEPT SOLIDS CONTENT TO BE BETWEEN 17-20%, VISCOSITY TO BE WITHIN THE RANGE OF 5500-6500 CPS. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND % SOLIDS. IN 1.0 OZ TUBES	ITW DEVCON COMMERCIAL ITEM NYCTA NYCTA	DUCO CEMENT 6245 A-A-529A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			0	54

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-13-1930	ADHESIVE, FAST DRYING NITRILE RUBBER BASE, STRONG FLEXIBLE BONDS, USE BETWEEN RUBBER AND GASKETING MATERIALS WITH VARIOUS SUBSTRATES. BRUSH OR FLOW APPLICATION COLOR DARK BROWN IN 5 OZ. TUBES. VISCOSITY OF 1500-3200 CPS AT 80 DEG F, SOLID CONTENT 33-39% AFTER 24 HOURS AT 160 DEG F, WEIGHT 7.4-7.8 LBS/GAL, BONDING RANGE UP TO 15 MIN FOR 10 MIL WET FILM TWO SURFACES. CERTIFICATE OF ANALYSIS WHICH INCLUDES VISCOSITY AND %SOLIDS IS TO BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING MATERIAL. IN 5 OZ TUBES	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	NITRILE HIGH PERFORMANCE 847 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	79	60
70-13-2415	ADHESIVE, RUBBER AND GASKET, CONTACT CEMENT, USED ON GE MAIN CONTTROL GROUP, LINE BREAKERS AND KNIFE SWITCHES, 5 OZ. TUBE, CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND % SOLIDS FOR EACH BATCH MUST BE PROVIDED TO NYCT MANAGER OF INSPECTION & TESTING FOR EACH BATCH PRIOR TO SHIPPING MATERIAL 36 IN A CASE	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA NYCTA	SCOTCH-WELD NEOPRENE 1300 7130-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1763	1120
70-13-2500	ADHESIVE, ALL-PURPOSE RUBBER BASED (POLYCHLOROPRENE-TYPE) STRONG HEAT RESISTANCE BOND. USE TO BOND RUBBER, METAL, WOOD AND LAMINATES. GRAYISH IN COLOR, BRUSH APPLICATION IN 1 PINT CANS. MUST MEET REQUIREMENTS OF NYCT SPECIFICATION 7084-FACIL-99. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE: BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, VISCOSITY, % SOLIDS, HEAT RESISTANCE, TACK SET TIME	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA NYCTA	NEOPRENE HIGH PERFORMANCE 1357 7084-FACIL-99 REV. A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	638	326

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	1 PINT CANS				
70-13-3593	KIT, FLOOR PATCHING, EPOXY WITH COARSE AGGREGATE; KIT CONSISTS OF A 5-GALLON PAIL CONTAINING 35-40 LBS. OF COARSE AGGREGATE MIXED WITH ONE GALLON OF RESIN & A SEPARATE ONE (1)QUART CAN OF HARDENER. MUST BE IMPACT AND SLIP RESISTANT; MUST HARDEN WITHIN 7-9 HOURS AND HAVE A MINIMUM SHORE D HARDNESS OF 60 AND/OR BARCOL HARDNESS MINIMUM OF 30, POT LIFE 30-60 MINUTES; YIELDS 21 SQUARE FEET OF 1/4" THICK PATCHING LAYER; CERTIFICATE OF ANALYSIS, WHICH INCLUDES HARDNESS DATA & CERTIFICATE OF CONFORMANCE, MUST BE PROVIDED FOR EACH BATCH SHIPPED. IN 3 PART KIT IN 3 PART KIT	NPI FOR GARON NYCTA NYCTA	GARON TREFLITE 40015 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1520	885
70-13-3596	COMPOUND, PATCHING, THREE-COMPONENT, 100% SOLIDS EPOXY MORTAR. FOR APPLICATION IN TEMPERATURES AS LOW AS -10F, INDOORS OR OUTDOORS. SUPPLIED IN 2-GALLON PAIL. TENSILE STRENGTH 8,900 PSI; FLEXURAL STRENGTH 15,000 PSI, COMPRESSIVE STRENGTH 11,00 PSI. SET TIME: FOR RECOATING 1 TO 2 HOURS, FOR LIGHT TRAFFIC 2 TO 4 HOURS, FULL CURE 1 TO 3 DAYS. LIQUID PORTIONS A&B MUST BE MIXED TOGETHER FIRST AT NORMAL ROOM TEMPERATURE(70F). SOLID PORTION C MUST BE ADDED AT APPLICATION LOCATION. APPLIED 1/4"-1/8" THICKNESS WITH TROWELL. PPE REQUIRED: CHEMICAL SPLASH GOOGLES AND NEOPRENE GLOVES. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS.	NPI FOR GARON NYCTA NYCTA	GARON ARTIC FREEZITE 47082 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	46	43

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-15-0810	WIPES, DISPOSABLE HAND SANITIZER, OF AT LEAST 60% ALCOHOL BY VOLUME CONTAINED IN EACH PRE-MOISTENED WIPE. WIPES MUST BE EASY TO USE, NO WATER, SOAP, OR TOWEL REQUIRED. FRAGRANCE AND DYE FREE. WIPES MUST CONTAIN MOISTURIZERS. THE WIPE MUST BE INDIVIDUALLY WRAPPED. 100 WIPES PER BOX. MINIMUM SHELF LIFE AT TIME OF RECEIPT IS EIGHTEEN MONTHS 100 WIPES/BOX 100 WIPES/BOX	VERIDIEN CORPORATION SAFETEC OF AMERICA, INC GOJO INDUSTRIES, INC. NICE-PAK PRODUCTS, INC. NYCTA NYCTA	25500 VIRAGUARD ANTIMICROBIAL 34400 PAWS 9022-10 PURELL HAND WIPE D43600 SANI-HANDS WIPES CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	33675	14524
70-15-0812	WIPES, HAND SANITIZING, MINIMUM 70% ETHANOL CONTENT BY WEIGHT IN EACH PREMOISTENED WIPE; EACH WIPE IS 9 INCHES X 7 INCHES; CERTIFICATE OF ANALYSIS COVERING ETHANOL CONTENT BY WEIGHT TO ACCOMPANY EACH BATCH SHIPPED; PACKAGED 40 WIPES PER CANISTER	GRIFFIN WOW NYCTA NYCTA	DERMAFRESH HANDSNTZR WIPES2350 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	67
70-15-0830	WIPES, DISINFECTANT, DISPOSABLE, TEXTURED SURFACE, MADE OF CLOTH MATERIAL, PRE-SATURATED WITH DISINFECTANT SOLUTION, SUPPLIED IN RESEALABLE CANISTERS. WIPES MUST BE EPA REGISTERED FOR EFFECTIVENESS AGAINST INFLUENZA A. CANISTERS MUST DISPENSE INDIVIDUAL PERFORATED WIPES AND SHALL CONTAIN BETWEEN 150 AND 160 WIPES. INDIVIDUAL WIPE DIMENSIONS: MIN OF 6" X 6" TO A MAX OF 12" X 12". MINIMUM SHELF LIFE AT TIME OF RECEIPT IS EIGHTEEN MONTHS. 150/160 PER CAN	VERIDIEN CORPORATION WEXFORD LABS, INC JOHNSON DIVERSEY, INC NYCTA NYCTA	10160 VIRAGUARD HOSP. TOWELETT 3130M-6, 3130M-12 CLEAN-CIDE 4599516 OXIVIR TB WIPES CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	19	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-15-0834	WIPE, DISINFECTANT, DISPOSABLE, TEXTURED SURFACE, MADE OF CLOTH MATERIAL, PRE-SATURATED WITH DISINFECTANT SOLUTION: ISOPROPYL ALCOHOL/QUATERNARY AMMONIUM CHLORIDE COMPOUNDS, SUPPLIED IN RESEALABLE CANISTERS; WIPES MUST BE EPA REGISTERED FOR EFFECTIVENESS AGAINST INFLUENZA A. MEETS CDC AND OSHA GUIDELINES. EFFECTIVE AGAINST BACTERIA, ENVELOPED & NON-ENVELOPED VIRUSES, BLOODBORNE PATHOGENS. CANISTERS MUST DISPENSE INDIVIDUAL PERFORATED WIPES. EACH CANISTER SHALL CONTAIN 65 WIPES. INDIVIDUAL WIPE DIMENSIONS: 7.5" X 15", 6 CANISTERS PER CASE. MINIMUM SHELF LIFE AT TIME OF RECEIPT IS EIGHTEEN MONTHS.	NICE-PAK PRODUCTS, INC. NYCTA NYCTA	SUPER SANI-CLOTH WIPES #Q86984 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	72
70-15-1274	ALCOHOL, ISOPROPYL: TO BE MINIMUM 68% ISOPROPYL ALCOHOL BY WEIGHT (THE REMAINDER BEING DIONIZED WATER) SOLUTION (MINIMUM 73% ISOPROPYL ALCOHOL BY VOLUME); FOR INDUSTRIAL USES INCLUDING RAILCAR FLOOR/SUBFLOOR PREPARATION FOR INSTALLATION OF RUBBER FLOORING; PACKAGED IN 1-GALLON CONTAINERS; BATCH # TO APPEAR ON CONTAINER; CERTIFICATE OF ANALYSIS COVERING % ISOPROPYL ALCOHOL CONTENT TO ACCOMPANY EACH BATCH SHIPPED; MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 1 GAL CONTAINER	TECHSPRAY, L.P. NYCTA NYCTA	1608-G CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	485	1390
70-15-1276	ALCOHOL, ISOPROPYL; TO BE MINIMUM 68% ISOPROPYL ALCOHOL BY WEIGHT (THE REMAINDER BEING DEIONIZED WATER) SOLUTION (MINIMUM 73% ISOPROPYL ALCOHOL BY VOLUME); UNIVERSAL CLEANER AND DISINFECTANT; USED FOR INDUSTRIAL APPLICATIONS; REMOVES LIGHT OILS, MOST TYPES OF INKS, PASTES AND CONTAMINANTS ASSOCIATED WITH SOLDERING AND PRINTING; PACKAGED IN 1-PINT BOTTLES. "NYCT STORAGE REQUIREMENT: STORE WITH FLAMMABLE LIQUIDS" IN 2-INCH HIGH	TECHSPRAY, L.P. NYCTA NYCTA	1608-P CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	43239	28063

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	LETTERING MUST APPEAR ON EACH BOX; BATCH # TO APPEAR ON CONTAINER; CERTIFICATE OF ANALYSIS COVERING % ISOPROPYL ALCOHOL CONTENT TO ACCOMPANY EACH BATCH SHIPPED; MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 1 PINT BOTTLES				
70-15-3016	DEICER, LIQUID, 30% MAGNESIUM CHLORIDE SOLUTION, SPECIFIC GRAVITY TO BE ABOUT 1.3; PACKAGED IN 55 GAL DRUMS IN 55 GAL DRMS	PARTSMASTER MELTSNOW COM NYCTA NYCTA	CHINOOK ANTI-ICING AGENT MAGNESIUM CHLORIDE AQ. SLTN 30 CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	220	110
70-17-0250	CLEANER, ORGANIC SOLVENT BLEND, ALL- PURPOSE, USED TO REMOVE GREASE FROM MOTOR PARTS; MUST BE CLEAR, WATER-WHITE; PACKAGED IN ONE-GALLON CAN; VOC PACKAGED 6.5 LBS PER GALLON MAXIMUM; SPECIFIC GRAVITY 0.747 TO 0.783 6.5 LBS PER GAL	PPG INDUSTRIES NYCTA NYCTA	CFX436 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	28	29
70-17-0505	CLEANER, DEGREASER, ALL PURPOSE, WATER-BASED GREEN LIQUID. USED FOR CLEANING R142A AND R143 CURRENT COLLECTORS: DILUTE 1 PART CLEANER TO 1 PART WATER; SPRAY ON OR APPLY WITH SOFT BRISTLE BRUSH; SCRUB LIGHTLY WITH WET CLOTH OR SOFT BRISTLE BRUSH; RINSE SURFACES THOROUGHLY. DELIVERED IN NON-RETURNABLE 55 GALLON DRUMS. NON-TOXIC, BIODEGRADABLE, NON-ABRASIVE, NON-BUTYL, NON-PHOSPHATE, NON-FLAMMABLE, FREE RINSING. CONTAINS EMULSIFIERS, WATER SOLUBLE SOLVENTS, BIODEGRADABLE DETERGENTS. PH(CONCENTRATE) 8.5-9.5. DENSITY 8.42 LBS/GAL +/- 1.0. WEAR CHEMICAL SPLASH GOGGLES AND LATEX GLOVES WHEN USING PRODUCT. IN 55 GAL DRUMS	ZEP MANUFACTURING COMPANY NYCTA NYCTA	ZEP Z-GREEN #184886 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	9	6

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-0512	CLEANER, DEGREASER, DEODORIZER, CITRUS INDUSTRIAL STRENGTH CLEANER, USED TO DEGREASE MOTORS IN BOILER ROOM. TO BE SUPPLIED IN CLEARLY LABELED 55 GALLON PAILS	FOSTER & CO. NYCTA NYCTA	17-88 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-0515	CLEANER, DEGREASER USED FOR CLEANING SHOP FLOORS AND THE WALLS AND FLOORS OF INSPECTION PITS. CAN BE APPLIED USING FLOOR CLEANING MACHINES, PRESSURE WASHERS OR MOPS. SUPPLIED READY FOR USE(PRE-DILUTED 50% SOLUTION) IN 5-GALLON PAILS. PH 10-11. LOW ODOR, LOW FOAM, NON-EMULSIFYING. SOLUTION MUST BE SUITABLE FOR DISCHARGE THROUGH OIL/WATER SEPARATOR(SOLUTION SEPARATES WATER AND OIL INTO TWO PHASES WITHIN MINUTES). NON-SOLVENT BASED. DOESN'T CONTAIN HYDROCARBONS OR D'LIMONENE. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES. CERTIFICATE OF ANALYSIS TO INCLUDE PH	COSCO ENTERPRISES, INC. NYCTA NYCTA	FO 2276 ODORLESS RTU CCSS-001 REV I, 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-0610	CLEANER, DEGREASER, FOR REMOVAL OF GREASE, RUBBER RESIDUES, WAX, ADHESIVE. PACKAGED IN 5 GALLON CONTAINERS. CONTAINS D-LIMONENE, TECHNICAL GRADE, ALIPHATIC HYDROCARBONS. FLASH POINT MUST BE ABOVE 140 DEGREES FAHRENHEIT. MUST MEET NYSDEC VOC REGULATIONS FOR LIQUID GENERAL PURPOSE DEGREASERS WITH A MAXIMUM ALLOWABLE VOC CONTENT OF 4% BY WEIGHT. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, FLASH POINT. CERTIFICATE OF CONFORMANCE/COMPLIANCE TO INCLUDE VOC CONTENT. NON-EMPTY CONTAINERS OF THIS MATERIAL OR RAGS/WIPERS USED WITH	CRC INDUSTRIES, INC. CHEMTRONICS NYCTA NYCTA	CITRUS DEGREASER HF#14175 MAX-KLEEN CITRUS HF # ES591 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	THIS MATERIAL MUST NOT NEED TO BE DISPOSED OF AS HAZARDOUS WASTE. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE GLOVES 5 GAL CONTAINER				
70-17-0611	CLEANER, DEGREASER, FOR REMOVAL OF GREASE, RUBBER RESIDUES, WAX, ADHESIVE. 53-55 GALLONS PACKAGED IN 55 GALLON DRUMS. CONTAINS D-LIMONENE, TECHNICAL GRADE, ALIPHATIC HYDROCARBONS. FLASH POINT MUST BE ABOVE 140 DEGREES FAHRENHEIT. MUST MEET NYSDEC VOC REGULATIONS FOR LIQUID GENERAL PURPOSE DEGREASERS WITH A MAXIMUM ALLOWABLE VOC CONTENT OF 4% BY WEIGHT. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, FLASH POINT. CERTIFICATE OF CONFORMANCE/COMPLIANCE TO INCLUDE VOC CONTENT. NON-EMPTY CONTAINERS OF THIS MATERIAL OR RAGS/WIPERS USED WITH THIS MATERIAL MUST NOT NEED TO BE DISPOSED OF AS HAZARDOUS WASTE. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE GLOVES 55 GAL DRUMS	CRC INDUSTRIES, INC. CHEMTRONICS NYCTA NYCTA	CITRUS DEGREASER HF #14176 MAX-KLEEN CITRUS HF # ES5591 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-0612	CLEANER, DEGREASER, FOR REMOVAL OF GREASE, RUBBER RESIDUES, WAX, ADHESIVE. CLEANING RAILCAR PARTS. PACKAGED IN 1-GALLON CONTAINERS. CONTAINS D-LIMONENE, TECHNICAL GRADE, ALIPHATIC HYDROCARBONS. FLASH POINT MUST BE ABOVE 140 DEGREES FAHRENHEIT. MUST MEET NYSDEC VOC REGULATIONS FOR LIQUID GENERAL PURPOSE DEGREASERS WITH A MAXIMUM ALLOWABLE VOC CONTENT OF 4% BY WEIGHT. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE	CHEMTRONICS NYCTA NYCTA	MAX-KLEEN CIRTUS HF #ES191 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	OF CONFORMANCE/ COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, FLASH POINT. CERTIFICATE OF CONFORMANCE/COMPLIANCE TO INCLUDE VOC CONTENT. NON-EMPTY CONTAINERS OF THIS MATERIAL OR RAGS/WIPERS USED WITH THIS MATERIAL MUST NOT NEED TO BE DISPOSED OF AS HAZARDOUS WASTE. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE GLOVES				
70-17-0823	CLEANER, TO REMOVE RUST FROM RAILCAR STAINLESS STEEL SURFACES (EXTERIORS AND DOORS). FOR MANUAL APPLICATION. READY TO USE FORMULA SUPPLIED IN ONE QUART PLASTIC BOTTLES. TWELVE ACID RESISTANT TRIGGER ACTION SPRAYERS SUPPLIED IN EACH CASE. DILUTE OXALIC ACID BASED FORMULATION. MINIMUM 14% ACTIVE INGREDIENT CONTENT. APPLY BY NON-ATOMIZING SPRAY, BRUSH OR SCRUB PAD. ALLOW A DWELL TIME OF 2 MINUTES OR MORE. FOR SEVERE SOIL BUILD-UP, LIGHTLY AGITATE THE HEAVY SOILED SURFACE WITH A BRUSH OR SCRUB PAD. RINSE THE ENTIRE AREA THOROUGHLY WITH WATER. PRIOR TO CLEANING INTERIOR DOORS, AND TO PREVENT WATER BUILD UP ON INTERIOR PASSENGER DOORS, PLACE ABSORBENT PADS (2 OR MORE) AGAINST THE DOORS TO ABSORB EXCESS WATER. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES. CERTIFICATE OF ANALYSIS TO INCLUDE % ACTIVE INGREDIENTS. 12 EA PER CSE 1 QUART BOTTLE	COSCO ENTERPRISES, INC. NYCTA NYCTA	FO 479HD RTU CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	657	299

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-0850	CLEANER, FLOOR, AND ALL PURPOSE, IN 1.5 OZ PAPER PACKETS. CONCENTRATED POWDER PRODUCT TO BE USED AT A DILUTION RATE OF 1 PACKET PER 4 GALLONS OF WATER; USED TO CLEAN CONCRETE AND TILE SURFACES ON STATIONS. 1.5 OZ PACKETS	PROCTOR & GAMBLE NYCTA NYCTA	84893355 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	10945	8787
70-17-0855	CLEANER, FLOOR AND MULTIPURPOSE, IN 3-4 OZ PLASTIC PACKETS WITH TEAR OPEN STRIP. CONCENTRATED LIQUID PRODUCT TO BE USED AT DILUTION RATE OF 1 PACKET PER 4 GALLONS OF WATER; USED TO CLEAN CONCRETE AND TILE SURFACES ON STATIONS 3- 4 OZ PACKETS	PROCTOR & GAMBLE NYCTA NYCTA	84895469 SPIC & SPAN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	198281	83585
70-17-0904	CLEANER/POLISH, STAINLESS STEEL, LIQUID EMULSION, CONTAINING ALIPHATIC HYDROCARBONS, MINERAL OIL, EMULSIFIERS AND/OR ORGANOMODIFIED POLYMERIC EMULSION, SPECIFIC GRAVITY 0.92 TO 1.09, PH 8.0 TO 10.8, FLASH POINT GREATER THAN 140 DEGREES F. FOR USE IN CLEANING/POLISHING STAINLESS STEEL. PACKAGED IN 1-GALLON CONTAINERS. CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURER, APPEARANCE, SPECIFIC GRAVITY, PH 1 GAL CTRS	TMA NYCTA NYCTA	NUSHEEN MLTISRFC CLEANER&POLI CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	492	272
70-17-0913	DISINFECTANT, QUATERNARY AMMONIUM CHLORIDE TYPE, MINIMUM ACTIVE INGREDIENT CONTENT TO BE 4% OF WHICH A MINIMUM OF 2% MUST BE QUATERNARY AMMONIUM CHLORIDE COMPOUND, PH TO BE BETWEEN 6 AND 10, SPECIFIC GRAVITY BETWEEN 0.998 AND 1.040. PRODUCT MUST BE REGISTERED BY EPA SPECIFICALLY FOR USE AGAINST INFLUENZA A VIRUSES. THESE REGISTERED DISINFECTANT PRODUCTS ARE	NATIONAL CHEMICAL LAB OF PA. NYCTA NYCTA	LEMON QUAT DISINFECTANT 0235 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	26074	14212

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	FOR USE ON HARD, NON-POROUS SURFACES SUCH AS BUS AND SUBWAY DOOR KNOBS, HANDLES, FLOORS, SEATS, HANDHOLDS, ETC. PACKAGED IN 1 GALLON CONTAINERS. EACH CONTAINER LABEL TO BEAR EPA REGISTRATION NUMBER AND DILUTION INSTRUCTIONS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE: COLOR, ODOR, SPECIFIC GRAVITY, PH, % QUATERNARY AMMONIUM CHLORIDE, % ACTIVE INGREDIENTS 1 1 GAL CTRS				
70-17-0940	CLEANER, ANTI-STATIC, LIQUID, FOR CLEANING PLASTIC, GLASS AND STAINLESS STEEL SURFACES, USED ESPECIALLY FOR RAIL CAR LIGHT LENSES AND OTHER INTERIOR RAILCAR SURFACES TO PREVENT DUST AND DIRT FROM ADHERING, PACKAGED IN 30 GAL DRUMS. 30 GAL DRUMS	DIAMOND CHEMICAL COSCO ENTERPRISES, INC. NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	F.O. 1143 FO 1143 TA501 LENS CLEANER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-0972	CLEANER, LIQUID, TUNER AND CONTROL, WITH NEEDLE, PACKAGED IN 16-19 OZ. NET WEIGHT SPRAY CANS	ITW CHEMTRONICS, INC TECH SPRAY, INC. NYCTA NYCTA	ELECTRO-WASH VZ (ES6119) PRECISION V FLUX REMOVER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4124	2415
70-17-0980	HEAT SHIELD COMPOUND, PASTE, IN A ONE QUART CAN. PREVENTS WELDING, BRAZING, SOLDERING HEAT DAMAGE. ABSORBS AND DISSIPATES HEAT TO ELIMATE DAMAGE AND DISCOLORATION. CONTAINS NO ASBESTOS. [SAFETY COMMENTS: WEAR CHEMICAL SPLASH GOGGLES & NITRILE/NEOPRENE GLOVES	LA-CO INDUSTRIES, INC. NYCTA NYCTA	ANTI-HEAT 24002 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-17-0982	HEAT SHIELD COMPOUND, PASTE, IN A 10 OR 11 OUNCE TUBE. PREVENTS WELDING, BRAZING, SOLDERING HEAT DAMAGE. ABSORBS AND DISSIPATES HEAT TO ELIMINATE DAMAGE AND DISCOLORATION. PROTECTS PAINTED OR FINISHED SURFACES FROM DISCOLORATION DUE TO ADJACENT SOLDERING, BRAZING OR WELDING. PREVENTS BUCKLING OF LIGHT GAUGE METALS DURING WELDING. CONTAINS NO ASBESTOS. SAFETY COMMENTS: WEAR CHEMICAL SPLASH GOGGLES & NEOPRENE GLOVES. 24 TUBES/CASE	LA-CO INDUSTRIES, INC. NU-CALGON NYCTA NYCTA	BLOC-IT-HEAT ABSORB PASTE 1151 THERMO TRAP PASTE #4371-36 CCSS-001 REV I 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S			37	25
70-17-1025	CLEANER, STEAM CLEANING SOLUTION, NON-EMULSIFYING FORMULA (RUN OFF WATER SOLUTION MUST SEPARATE INTO TWO PHASES WITHIN MINUTES), FOR CLEANING ENGINES, BRAKE PARTS, OTHER PARTS AND INSPECTION PITS WITH PRESSURE WASHING EQUIPMENT. PACKAGED IN 5-GALLON PAILS. NON-SOLVENT BASED, DOESN'T CONTAIN HYDROCARBONS OR D'LIMONENE. ALL METAL SAFE. USE 1 PART CLEANER TO 5-10 PARTS WATER. PH <12. PH WHEN DILUTED MUST MEET NYC SEWER DISCHARGE CODES OF PH BETWEEN 5 AND 11. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND LATEX GLOVES (FOR USE WITH PURESAFE) AND NITRILE OR BUTYL RUBBER GLOVES (FOR USE WITH MEGAPOWER 2289). CERTIFICATE OF ANALYSIS TO INCLUDE PH 5 GAL PAILS	DIAMOND CHEMICAL COSCO ENTERPRISES, INC. GRIGNARD COMPANY NYCTA NYCTA	MEGAPOWER 2289 MEGAPOWER 2289 PURESAFE STEAM CLEANER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			29	3
70-17-1032	CLEANER, HAND, WATER BASED LIQUID, ANTI-BACTERIAL, FOR USE AS EMPLOYEE LAVATORY HAND SOAP, IN 16 OZ, PUMP BOTTLE, CONTAINS BENZALKONIUM CHLORIDE, AN ANTI-MICROBIAL AGENT, TO HELP REDUCE BACTERIA; CONTAINS NO ALKALIES, ABRASIVES OR SOLVENTS THAT MAY BE HARSH TO THE SKIN; DOES NOT CONTAIN TRICLOSAN. FORTIFIED WITH EMOLLIENTS FOR SKIN SOFTENING TO KEEP HANDS SMOOTH, PH BETWEEN 5.5-6.0. VISCOSITY BETWEEN 1600-4000 CPS. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND PH MUST BE	ZEP INC. NYCTA NYCTA	ACCLAIM W/BENZALKCHLORIDE 3149 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			938	817

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	PROVIDED FOR EACH BATCH TO NYCT MANAGER OF TESTING & ANALYSIS BEFORE SHIPPING MATERIAL 17OZ/500ML/BTL 17OZ/500ML/BTL				
70-17-1034	CLEANER, HAND, WATER BASED LIQUID, WHITE LOTION. FOR USE AS EMPLOYEE LAVATORY HAND SOAP, IN A PLASTIC QUART CONTAINER. CLEANS AND MOISTURIZES. PH BETWEEN 6.5-7.5. PACKAGED 12 QUARTS TO A CASE. TO BE USED WITH METAL HAND CLEANER DISPENSER UNITS OBTAINABLE UNDER STOCK #61-18-2233	ZEP INC. NYCTA NYCTA	VELVET LOTION SOAP #95801 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	64874	38660
70-17-1143	DEFOAMER, FOR USE WITH MOTOR CLEANER IN SPRAY WASH TANK AND STEAM CLEANING OPERATION TO CONTROL FOAM LEVEL; LIQUID, ACTIVE INGREDIENT CONTENT 1.7% MINIMUM, PH TO BE 6.0 TO 8.0; SPECIFIC GRAVITY 1.00 TO 1.03; SUPPLIED IN 5 GALLON PAILS, CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/ COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, COLOR, PH, SPECIFIC GRAVITY, % ACTIVE INGREDIENT CONTENT MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS 5 GALLON PAILS	NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	TA1039 KNOCK-OUT DEFOAMER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	400	135
70-17-1170	CLEANER, LIQUID, WATER BASED BIOSURFACANT, CONSISTING OF BIODEGRADABLE WETTING AGENTS AND SURFACTANTS. FOR CLEANING GREASY/OILY/ DIRTY PARTS IN DIP/AGITATING AND SPRAY WASH TANKS; NON-FOAMING; LOW ODOR; SAFE FOR USE ON ALL TYPES OF METALS. DOES NOT CONTAIN CAUSTICS, PHOSPHATES, ETHERS OR TERPENES, PH BETWEEN 8 AND 10; SPECIFIC GRAVITY BETWEEN 0.98 AND 1.04; 25% MINIMUM ACTIVE INGREDIENT CONTENT. PACKAGED IN 5 GALLON	SYNTHETIC LABS INC MOON CHEMICAL PRODUCTS NYCTA NYCTA	BIOSOLVE ENVIROCLEAN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-1305	CONTAINERS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE: COLOR, ODOR, SPECIFIC GRAVITY, PH, % ACTIVE INGREDIENTS 5 GALLON PAILS 1 GAL BOTTLES	COLGATE-PALMOLIVE NYCTA NYCTA	FABULOSOALLPRPSCLNRLIQLAV15305 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	22967	16277
70-17-1310	CLEANER, AND POLISH, STAINLESS STEEL, AEROSOL, MINERAL OIL EMULSION; MUST MEET NYSDEC VOC REGULATIONS FOR METAL POLISHERS/CLEANERS WITH MAXIMUM ALLOWABLE VOC OF 30% BY WEIGHT; NON-FLAMMABLE ACCORDING TO ASTM D-3065 USA FLAME PROJECTION TEST; PH (OF CONCENTRATE) IS 7 TO 11; SPECIFIC GRAVITY (OF CONCENTRATE) IS 0.85 TO 1.10; PACKAGED 16.0 TO 21.5 OUNCES NET WEIGHT IN A 20 OR 24 OZ. AEROSOL CAN. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, VOC CONTENT, PH (OF CONCENTRATE), SPECIFIC GRAVITY (OF CONCENTRATE) MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS IN 20-24 OZ CAN IN 20-24 OZ CAN	AMREP, INC. APOLLO INDUSTRIES SPRAYON PRODUCTS MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	"MISTY 142" 17.5 OZ IN 20 OZ C APOLLO BRIGHT SHINE S/S #2390 CD 885 STSTEELCLNR S00885 STAINLESS STEEL CLNR 48011-140 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1546	964

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-1311	CLEANER, STAINLESS STEEL; CLEANING & POLISHING TOWELS; WITH CITRUS SCENT; 9.75" X 10.50" TOWELS, 30 TOWELS PER CONTAINER, 6 CONTAINERS PER CASE, 1 CONTAINER = 1 EACH. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS	ITW PRO BRANDS NYCTA NYCTA	SCRUBS STSTEEL CLNR TOWELS 919 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	18	6
70-17-1312	POLISH, FOR POLYCARBONATE ON FIND SYSTEM ON R160 CARS. CLEAR PLASTIC POLISH TO REDUCE FINE OR HAIRLINE SCRATCHES. RESTORES OPTIC CLARITY TO CLEAR PLASTICS. PROVIDES A STATIC FREE COATING THAT REPELS DUST. LIQUID IN AN EIGHT OUNCE BOTTLE	MEGUIAR'S USA NYCTA NYCTA	M10 PLASTIC POLISH M1008 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	8	0
70-17-1328	CLEANER, ALL PURPOSE, COLLOIDAL. SUPPLIED IN 55-GALLON DRUMS. SAFE FOR USE ON COPPER COMPONENTS. TO BE USED TO CLEAN RAILCAR A/C COILS, CONDENSERS, EVAPORATORS. NON-TOXIC, NON-FLAMMABLE, NON-CAUSTIC, BIODEGRADABLE. PH IN THE 9.9 TO 10.9 RANGE AND SPECIFIC GRAVITY OF 1.001 - 1.02. IT MUST NOT HAVE A FLASH POINT AND MUST NOT CONTAIN PHOSPHATES, PETROLEUM DISTILLATES, GLYCOL ETHERS, TERPENES. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (WHICH INCLUDES SPECIFIC GRAVITY & PH). AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH. 55 GALLON DRUMS 55 GALLON DRUMS	NATIONAL CHEMICAL LAB OF PA. GEMTEK PRODUCTS NYCTA NYCTA	COLLOIDAL CLEANER #5222 SC-1000 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	8580	4235
70-17-1483	CLEANER, FOR COILS, CONDENSERS, DOOR OPERATORS, LIQUID, MILD ALKALINE. MUST CONTAIN MINIMUM ACTIVE INGREDIENT CONTENT OF 11% INCLUDING, BUT NOT LIMITED TO CARBONATES, SALTS OF ORGANIC ACIDS, LOW FOAMING SURFACTANTS, MAXIMUM PH OF CONCENTRATE TO BE 10.0, SPECIFIC GRAVITY 1.05-1.15. MUST NOT HAVE AN OBJECTIONABLE ODOR ESPECIALLY WHEN HEATED. CAN BE USED AS IS OR IN UP TO 1-10 PART DILUTION WITH WATER DEPENDING UPON SOIL CONDITIONS. PRODUCT MUST BE	COSCO ENTERPRISES, INC. DIAMOND CHEMICAL PENETONE NYCTA NYCTA	MEGAPOWER COIL/CONDENSER CLNR M MEGAPOWER COIL/CONDENSER CLNR M PENBLITZ 208LM CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	8	4

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	FREE RINSING AND BE ABLE TO BE USED IN STEAM JENNY/PRESSURE WASHERS AND IN DIP TANKS. IN 55 GALLON NON-RETURNABLE PLASTIC DRUMS. CERTIFICATE OF ANALYSIS(COF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH OF CONCENTRATE AND SPECIFIC GRAVITY 1N 55 GAL DRUMS 1N 55 GAL DRUMS				
70-17-1496	CLEANER, COMPOUND, LIQUID, INTERIOR GRAFFITI REMOVER, IN ONE GALLON PLASTIC CONTAINERS, 4 OR 6 GALLONS TO A CARTON WITH STOCK NUMBER ON CARTON IN 1 GAL CTRS	DIAMOND CHEMICAL NATIONAL CHEMICAL LAB OF PA. NYCTA NYCTA NYCTA	F.O. 1120 NCL 333 GRAFFITI REMOVER 0001-2000 DATED OCT 2000 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-1515	CLEANER, GRAFFITI REMOVER, LIQUID WITH CITRUS ODOR. HEAVY DUTY FOR CLEANING OF STATIONS. PH 4 MIN. 110 DEGREE F TCC (TAG CLOSED CUP), D-LIMONENE BASED INCLUDING SURFACTANTS, BUILDERS, AUXILIARIES AND WATER AS NECESSARY FOR HEAVY DUTY GRAFFITI REMOVAL, TO BE DELIVERED ON 40" X 48" PALLETS, SPECIAL NOTE: THIS PRODUCT IS EXEMPT FROM PH GUIDELINE IN CCSS-003. TO BE SUPPLIED IN ONE(1) GALLON PLASTIC CONTAINERS. IN 1 GAL CTRS	PENETONE NYCTA NYCTA NYCTA	CITRIKLEEN GR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC	165	123
70-17-1517	REMOVER, GRAFFITI, PREMOISTENED TOWELS, D'LIMONENE BASED, TWO 12" X 16.75" TOWELS PER PACKET, FLASH POINT OF GRAFFITI REMOVER SOLUTION IS ABOVE 140 DEGREES F. 50 PACKETS PER CASE. CERTIFICATE OF ANALYSIS TO INCLUDE FLASH POINT MUST BE PROVIDED TO NYCT MANAGER OF INSPECTION & TESTING FOR EACH BATCH PRIOR TO SHIPMENT "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT	GETEX CORPORATION NYCTA NYCTA	GRAFFITI FREE GENIE WIPES CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1506	1201

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	IS 9 MONTHS". 50 PACKETS/CSE				
70-17-1520	REMOVER, GUM, GRAFFITI, STICKER ADHESIVES; LIQUID; 100% ACTIVE INGREDIENT CONTENT CONSISTING OF D'LIMONENE/TERPENES, METHYL PYRROLIDONE AND SUCH OTHER INGREDIENTS FOR THE REMOVAL OF GUM, GRAFFITI PAINT, MARKING INK, STICKER ADHESIVES FROM PAINTED AND UNPAINTED METAL, STAINLESS STEEL, FIBERGLASS, MELAMINE, GLASS, PLASTIC RUBBER, CEMENT, MARBLE, CERAMIC, TERRAZZO SURFACES. SHALL NOT CONTAIN ABRASIVES, CAUSTICS, INSOLUBLE MATERIAL. FLASH POINT TO BE A MINIMUM OF 120 DEGREES F; SPECIFIC GRAVITY TO BE 0.86 TO 0.94. PACKAGED IN 5 GALLON CONTAINERS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE; COLOR, ODOR, SPECIFIC GRAVITY, FLASH POINT, % ACTIVE INGREDIENTS 5 GAL CTRS	COSCO-FO NATIONAL CHEMICAL LAB OF PA. NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	ENVIROSOLV LR-V GUM REMOVER #4159 TA503 GUM REMOVER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	790	475
70-17-1521	REMOVER, GUM, GRAFFITI, STICKER ADHESIVES; LIQUID; 100% ACTIVE INGREDIENT CONTENT CONSISTING OF D'LIMONENE/TERPENES, METHYL PYRROLIDONE AND SUCH OTHER INGREDIENTS FOR THE REMOVAL OF GUM, GRAFFITI PAINT, MARKING INK, STICKER ADHESIVES FROM PAINTED AND UNPAINTED METAL, STAINLESS STEEL, FIBERGLASS, MELAMINE, GLASS, PLASTIC, RUBBER, CEMENT, MARBLE, CERAMIC, TERRAZZO SURFACES. SHALL NOT CONTAIN ABRASIVES, CAUSTICS, INSOLUBLE MATERIAL. FLASH POINT TO BE A MINIMUM OF 120 DEGREES F; SPECIFIC GRAVITY TO BE 0.86 TO 0.94. PACKAGED IN 1 GALLON CONTAINERS. CERTIFICATE OF ANALYSIS AND CERTIFICATE CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH	COSCO-FO NATIONAL CHEMICAL LAB OF PA. NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	ENVIROSOLV LR-V GUM REMOVER #4159 TA503 GUM REMOVER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2085	2319

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE; COLOR, ODOR, SPECIFIC GRAVITY, FLASH POINT, % ACTIVE INGREDIENTS 1 GAL CTRS				
70-17-1565	CLEANER, HIGHLY CONCENTRATED SOLUTION WITH CHELATED AGENT, FOR USE IN MEMBRANE CLEANING, PACKAGED IN 5 GALLON CONTAINERS	DYNATEC SYSTEMS, INC. NYCTA NYCTA	MEMCLEEN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-17-1584	GRAFFITI REMOVER, LIQUID, NON FLAMMABLE, ZERO VOC, NON-VISCOUS, NO/LOW ODOR, NON CAUSTIC, IN 5 GALLON CONTAINER. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NITRILE GLOVES	THIS STUFF WORKS NYCTA NYCTA	TSW9 PLASTI-MASTER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	985	1296
70-17-1632	REMOVER, GRAFFITI, IN ONE GALLON PLASTIC CONTAINERS, 4 GALLONS TO A CARTON, WITH STOCK NUMBER ON CARTON. 4 GLL TO A CA	COSCO ENTERPRISES, INC. DIAMOND CHEMICAL NYCTA NYCTA NYCTA	F0974 FO974 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S SMD 30-2-83	17	21
70-17-1670	CLEANER, DRAIN, POWDERED HYDROXIDE BASED; MUST CONTAIN 60-70% HYDROXIDE (AS MEASURED BY ASTM D514) AND 2-4% ALUMINUM (AS MEASURED BY ICP-INDUCTABLY COUPLED PLASMA EMISSION SPECTROSCOPY); ALL OF THE PRODUCT TO PASS THROUGH A #4 US STANDARD SIEVE. MUST MEET ALL THE PERFORMANCE TESTING CRITERIA SET FORTH IN FEDERAL COMMERCIAL ITEM DESCRIPTION AA-1911 EXCEPT THAT THE FINAL TEMPERATURE OF THE CLEANER/WATER SOLUTION SHALL BE 78 TO 95 DEGREES C (INSTEAD OF 78 DEGREES C MINIMUM). PACKAGED IN 12 OZ. CONTAINERS. CERTIFICATE OF ANALYSIS (C OF A) AND/OR CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO COVER COMPOSITION, SIEVE TEST, AND PERFORMANCE TEST	UTILITY/WONDER COMSTAR INTERNATIONAL INC. NYCTA NYCTA FED. SPEC. ASTM	DRY DRAIN-A-MATIC PIRANHA II PIPE CLEANER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S CID AA1911 D514	2048	1114

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	12 OZ CTRS				
70-17-1685	CLEANER, DEGREASER FOR RAILCAR DOOR HANGERS, WATER RINSABLE, LEAVES NO RESIDUE, BIODEGRADABLE, PH 8-9, NON-VOLATILE CONTENT 48-52%, VOC FREE FOR GENERAL CLEANING CAN BE DILUTED 5-50% WITH WATER, FOR HEAVY DUTY CLEANING USE FULL STRENGTH. 16 OUNCE BOTTLE; 12 BOTTLES PER CASE. CERTIFICATE OF ANALYSIS TO INCLUDE PH, NON-VOLATILE CONTENT. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES, NITRILE GLOVES. 12 BOTTLES/CSE	CORTEC CORPORATION NYCTA NYCTA	ECOLINE CLNR DEGREASER #359035 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	201	220
70-17-2120	CLEANER, TOUCH SCREEN, SPRAYER BOTTLE, 500 ML/16.9 FLUID OUNCE, WATER BASED, 12 PER BOX	WHOOSH INC NYCTA NYCTA	MC500EN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1260	649
70-17-3030	CLEANER, HAND, LIQUID, SOLVENT FREE, NOT PETROLEUM DERIVATIVE BASED, PH BETWEEN 4.9 AND 5.3; ACTIVE INGREDIENT CONTENT BETWEEN 39-42%; VISCOSITY BETWEEN 16,000-28,000 CPS. CONTAINS PLANT/VEGETABLE MATTER SCRUBBERS (NO PUMICE), FOR REMOVING OIL, GREASE AND HEAVY GRIME FROM HANDS, PACKAGED IN 2000-ML COLLAPSIBLE PLASTIC BOTTLES, FOR USE WITH HAND CLEANER DISPENSER UNITS OBTAINABLE UNDER STOCK #61-18-2228 (PLASTIC) AND 61-18-2226 (METAL). 2000 ML BOTTLES	DEB USA INC NYCTA NYCTA	SOLOPOL CLASSIC CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4908	3367

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-3038	DETERGENT, DISHWASHING LIQUID (NON-CONCENTRATED) IN A 12.6 OZ OR 14 OZ PLASTIC BOTTLE. FOR USE IN APPLYING 3M 4-PLY MYLAR WINDOW SHIELDS. THREE TO EIGHT DROPS OF DETERGENT WILL BE ADDED TO A 32-OZ SPRAY BOTTLE FILLED WITH WATER. THE SOLUTION WILL BE SPRAYED ON THE WINDOW AND ON THE 4-PLY MYLAR SHIELD TO AID WITH THE POSITIONING OF THE FILM DURING INSTALLATION 12.6-14 OZ BOT	PROCTER & GAMBLE PROCTER & GAMBLE NYCTA NYCTA	JOY DISHWASH LIQ NON-CONC LEMO NON-ULTRA JOY LEMON CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	19252	14237
70-17-3042	CLEANER, HAND, WATERLESS, PETROLEUM DERIVATIVE BASED, PH BETWEEN 7.0 AND 9.0; 55% MINIMUM ACTIVE INGREDIENT CONTENT; MUST NOT CAUSE SKIN IRRITATION. PACKAGED IN 14 OZ. CAN. 14 OZ CAN	CRITZAS NYCTA NYCTA	GOOP HAND CLEANER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2843	1686
70-17-3050	CLEANER, HAND, LIQUID, WITH PUMICE FOR REMOVING STUBBORN INKS, RESINS, PAINTS, ADHESIVES, TAR, CARBON AND ASPHALT. ALMOND FRAGRANCE. MUST BE PACKAGED IN ONE GALLON FLAT TOP CONTAINERS. MINIMUM SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS ONE GAL CTR	ZEP MANUFACTURING COMPANY NYCTA NYCTA	ZEP REACH CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	113	50
70-17-3080	CLEANER, FOR SAFETY GLASS LENSES, SAFETY GOGGLES AND EYE GLASSES, TO COME IN A MOUNTABLE DISPENSER KIT CONSISTING OF AN 8 OZ. SPRAY BOTTLE OF CLEANER AND 760-800 LENS TISSUES. CLEANER TO HAVE ANTI-FOG PROPERTIES, PH BETWEEN 5.0 AND 7.5 MINIMUM FLASH POINT OF 80 DEGREES F. ACTIVE INGREDIENTS INCLUDE ALCOHOL. IN 2 PT KIT	CERTIFIED SAFETY MAGIC SAFETY BAUSCH & LOMB NYCTA NYCTA	CLEANSE-A-LENS STATION K335-05 LENS CLEANING STATION LC546PL SIGHT SAVERS 143060GM CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2167	1339

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-17-3084	EYEWASH, STERILE SOLUTION, IN 8 OZ. PLASTIC BOTTLE. FOR FIRST AID USE ONLY. SINGLE USE ONLY. BOTTLE SEALED TO PREVENT TAMPERING. INSTRUCTIONS AND EXPIRATION DATE TO BE PERMANENTLY AFFIXED TO BOTTLE. PACKED 12 BOTTLES PER CARTON. 8 OUNCE BOTTLE	HONEYWELL NYCTA NYCTA	32-000445 CCSS-001, REV I, 3-9-11, LABEL CCSS-063 REV E 9/11/17 RESTR S	942	1293
70-17-3086	ADDITIVE, EYE WASH, ANTI-BACTERIAL AND WATER PRESERVATIVE, MUST MEET REQUIREMENTS OF OSS SPECIFICATION E7 EXCEPT THE PRODUCT MUST BE LIQUID AND IS FOR USE IN SELF CONTAINED EMERGENCY EYE WASH STATIONS FROM 5-20 GALLONS IN CAPACITY; ADDITIVE MUST PREVENT GROWTH BACTERIA; PH TO BE BETWEEN 5.5 AND 7.5; SPECIFIC GRAVITY TO BE BETWEEN 0.98 AND 1.01; PRODUCT MUST NOT CAUSE PRECIPITATES TO FORM; DILUTION (WITH WATER) INSTRUCTIONS MUST APPEAR ON LABEL: PACKAGED IN 8 OZ. BOTTLE. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, PH, SPECIFIC GRAVITY 8 OZ BOTTLE 8 OZ BOTTLE	ENCON/MIDLAND SAFETY PRODUCTS NYCTA NYCTA	HYDROSEP 01110764 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1238	1010
70-17-3160	SANITIZER, HAND, INSTANT, ANTIBACTERIAL GEL, USED WITHOUT WATER. MUST HAVE A MINIMUM ETHYL ALCOHOL CONTENT OF 60%. SAFETY DATA SHEET MUST STATE 60% OR GREATER ETHANOL CONTENT. KILLS 99.99% OF COMMON GERMS. CONTAINS MOISTURIZER TO HELP KEEP SKIN HYDRATED; HAS A MILD FRAGRANCE. PACKED IN 8 OUNCE HAND PUMP BOTTLES OR 8-OUNCE BOTTLES WITH FLIP TOP CAPS	SAFETEC OF AMERICA, INC KIMBERLY CLARK GOJO INDUSTRIES, INC. NYCTA NYCTA	INSTANT HAND SANITIZE FRESH173 KLEENEX HAND SANITIZER 93060 PURELL ADVANCED SANITIZE 9652- CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1378	2552

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	IN 8 OZ BTL				
70-17-3162	SANITIZER, HAND, INSTANT, ANTIBACTERIAL GEL, USED WITHOUT WATER. MUST HAVE A MINIMUM ETHYL ALCOHOL CONTENT OF 60%. SAFETY DATA SHEET MUST STATE 60% OR GREATER ETHANOL CONTENT. KILLS 99.99% OF COMMON GERMS. CONTAINS MOISTURIZERS TO HELP KEEP SKIN HYDRATED; HAS A MILD FRAGRANCE. PACKAGED IN 4 OUNCE FLIP TOP BOTTLES. 4 OZ BOTTLES 4 OZ BOTTLES	SAFETEC OF AMERICA, INC GOJO INDUSTRIES, INC. TRIPLE S NYCTA NYCTA	INSTANT HAND SANITIZE FRESH173 PURELL ADVANACED SANITIZE 9651 TRIPLE S HAND SANITIZER 44154 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	540	23085
70-17-3172	SANITIZER, HAND, MINIMUM 60% ETHANOL BY WEIGHT; MINIMUM 70% ETHANOL BY VOLUME; CERTIFICATE OF ANALYSIS COVERING % ETHANOL BY WEIGHT MUST ACCOMPANY EACH BATCH SHIPPED: PACKAGED IN 500-ML BOTTLES WITH PUMP TOP	ZEP INC. NYCTA NYCTA	INSTANT HAND SANITIZER GEL 70% CCSS-001, REV I, 3-9-11 LABEL CCSS-003 REV E 9/11/17 RESTR S	18	907
70-17-3180	HAND SANITIZING SPRAY, MINIMUM 70% ETHANOL CONTENT BY WEIGHT; CERTIFICATE OF ANALYSIS COVERING ETHANOL CONTENT BY WEIGHT TO ACCOMPANY EACH BATCH SHIPPED; 32-OZ. SPRAY BOTTLE	GRIFFIN WOW NYCTA NYCTA	DERMAFRESH HAND SNTZR SPRAY 23 CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	290	263
70-17-3515	CLEANER, METAL PARTS(STEEL, ALUMINUM, BRASS); ODORLESS, LIQUID, IN 5-GALLON PAIL. MUST CONTAIN ACTIVE INGREDIENTS OF CARBONATE, BICARBONATE, SURFACTANT AND RUST PRESERVATIVES. FOR USE IN HEATED DIP/AGITATING AND SPRAY WASH TANKS. MUST NOT FOAM WHEN USED IN SPRAY WASH OR AGITATING/TURBULATING TANK HEATED 140-180F. MUST NOT LEAVE A RESIDUE ON PARTS. MUST NOT CONTAIN: CAUSTICS, ETHERS, PHOSPHATES, TERPENES, CHELATING AGENTS. PH SHOULD BE BELOW 12.0. SAFETY COMMENTS: USE PERSONAL PROTECTIVE EQUIPMENT IN ACCORDANCE WITH	GREEN POWER CHEM SCIENCES NYCTA NYCTA	HEAVY DUTY LOW FOAM 0011-HDLF CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	140	80

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	THE MSDS. WEAR CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES				
70-18-0830	CLEANER, DEGREASER, DEODORIZER, MULTI-PURPOSE, LIQUID, CONCENTRATED, HYDROGEN PEROXIDE BASED. GREEN SEAL CERTIFIED. SUPPLIED IN ONE GALLON CONTAINERS, FOUR GALLONS PER CASE. USED FOR GENERAL CLEANING AND LIGHT DEGREASING ON ALL SURFACES AND FLOORS. USED FOR CLEANING SHOP FLOORS, WALLS, RAILCAR FLOORS AND INTERIOR SURFACES, BATHROOM (BOWLS, URINALS, CHROME, SINKS, SHOWERS, TILE & OTHER FIXTURES), LOCKEROOMS, TILE AND GROUT, CLEANS MOLD AND MILDEW, ELIMINATES ODORS. USE DILUTION FOR GENERAL PURPOSE CLEANING IS 1 OUNCE OF CLEANER PER GALLON OF WATER (1:128); FOR LIGHT DUTY CLEANING 1/2 OUNCE OF CLEANER PER GALLON OF WATER (1:25 OR 1:21). SPECIFIC GRAVITY 1.00 - 1.065; PH 3.5 - 6.0 CONCENTRATED. VENDOR TO SUPPLY CERTIFICATE OR ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE). PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES FOR ALL PRODUCTS AND NITRILE OR NEOPRENE GLOVES (FOR ZEP PRODUCT), DISPOSABLE VINYL GLOVES (FOR ENVIRO SOLUTIONS PRODUCT). 4 GALLONS/CSE	CHARLOTTE PRODUCTS LTD ZEP MANUFACTURING COMPANY NYCTA NYCTA NY STATE	SUPER H2O2 CLEANER CONC ES71 ZEP VERDIZA 125423 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	5667	4105
70-18-0912	REMOVER, FLOOR FINISH AND WAX REMOVER IN 5 GALLON PAILS. USE DILUTION RATIO 16 OUNCE OF SOLUTION TO 1 GALLON OF WATER OR 64 OUNCES OF SOLUTION TO 1 GALLON OF WATER FOR HEAVY DUTY CLEANING 5 GALLON PAILS	AMERICAN CLEANING SOLUTIONS NYCTA NYCTA NY STATE	4556, FOCUS FS 22 FLOOR STRIPP CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	550	534

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-18-1000	CLEANER, WASHROOM, TO CLEAN BOWLS, URINALS, CHROMES, SINKS, TUBS, TILES, AND OTHER RESTROOM FIXTURES. IN ONE GALLON CONTAINERS, 4 GALLONS TO A CASE. 6 OZ OF CLEANER SOLUTION TO BE MIXED WITH ONE GALLON OF WATER 4 GALLONS/CSE	NATIONAL CHEMICAL LAB OF PA. HILLYARD INDUSTRIES NYCTA NYCTA NY STATE	EARTH SENSE #20 WASHROOM CLEAN GREEN SELECT CLEANER #962 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	7693	7876
70-18-1125	CLEANER, CREAM CLEANSER SCOURING COMPOUND, ONE QUART BOTTLE. GENERAL PURPOSE CLEANER FOR CLEANING TILES, SINKS, TOILETS, URINALS, PORCELAIN, CERAMIC, STAINLESS STEEL, CHROME, FIBERGLASS. REMOVES SOAP SCUM, GREASE, MILDEW STAINS, HARD WATER STAINS, RUBBER MARKS, SCUFFS, GRIME BUILDUP. GREEN SEAL OR ENVIRONMENTAL CHOICE CERTIFIED. THICK CREAM LIQUID EMULSION FORMULA CLINGS TO VERTICAL SURFACES. NON-SCRATCHING. PH 7 -10.8. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND NITRILE, NEOPRENE OR VINYL GLOVES ONE QT BOTTLE	CHARLOTTE PRODUCTS LTD SEALED AIR DIVERSEY CARE NYCTA NYCTA NY STATE	CREAM CLEANSER ES53 EMEREL PLUS #94496138 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	2139	1378
70-18-1310	CLEANER, LOW RESIDUE FOR AUTO FLOOR SCRUBBER MACHINES. ENVIRONMENTALLY PREFERRED, NEUTRAL PH DAILY FLOOR AND SURFACE CLEANER. PACKAGED IN ONE GALLON CONTAINERS. RATIO 1 OUNCE PER 1 GALLON OF COLD WATER. ITEM MUST BE ON THE NYS OGS LIST, GREEN SEAL OR ECOLOGO APPROVED. ONE GALLON CTR	JOHNSON DIVERSEY, INC MISCO PRODUCTS DIVERSEY, INC. NYCTA NYCTA NY STATE	2CXU6 E07 ALL SURFACE CLEANER STRIDE CITRIS 903904 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	2846	2459

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-18-1332	CLEANER, MULTI-PURPOSE CLEANER AND DEGREASER, CONCENTRATED, WATER BASE, CLEANS WALLS, FLOORS, CONCRETE, CERAMIC TILES AND TERRAZZO, 5 GALLON PLASTIC CAN. GREEN SEAL CERTIFIED. MUST BE DILUTED WITH WATER FOR USE ACCORDING TO LABEL INSTRUCTIONS. MAY BE USED BY HAND, THROUGH STEAM OR PRESSURE CLEANING EQUIPMENT, AND IN AUTOMATIC SCRUBBERS. NOMINAL USE DILUTION FOR MULTI-PURPOSE CLEANING IS 4 TO 8 OUNCES OF CLEANER PER GALLON OF WATER; 6 TO 10 OUNCES OF CLEANER PER GALLON OF WATER FOR CLEANING FLOORS; 6 TO 10 OUNCES OF CLEANER PER GALLON OF WATER FOR PRESSURE WASHING. SPECIFIC GRAVITY 1.02 - 1.04; PH 11 TO 12 CONCENTRATED. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE). PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND LIGHT WEIGHT NITRILE OR NEOPRENE GLOVES MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 5 GALLON CAN	ZEP MANUFACTURING COMPANY NYCTA NYCTA NY STATE	MULTI-CLEAN GREEN 124939 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	514	206
70-18-1333	CLEANER, MULTI-PURPOSE CLEANER AND DEGREASER, CONCENTRATED, WATER BASE, CLEANS WALLS, FLOORS, VINYL, RUBBER, CONCRETE. CERAMIC TILE AND TERAZZO, ONE GALLON CONTAINER. FOUR PER CASE. GREEN SEAL CERTIFIED. MUST BE DILUTED WITH WATER FOR USE ACCORDING TO LABEL INSTRUCTIONS. MAY BE USED BY HAND, THROUGH STEAM OR PRESSURE CLEANING EQUIPMENT, AND IN AUTOMATIC SCRUBBERS. NOMINAL USE DILUTION IS 1/2 OUNCE OF CLEANER PER GALLON OF WATER FOR FLOOR CLEANING; 1 OUNCE OF CLEANER PER GALLON OF WATER FOR SPRAY & WIPE CLEANING; 4 OUNCES OF CLEANER PER GALLON OF WATER FOR HEAVY DUTY CLEANING/DEGREASING (SCRUBBERS & PRESSURE WASHING). SPECIFIC GRAVITY 1.02 - 1.04; PH 10 TO	AMERICAN CLEANING SOLUTIONS NYCTA NYCTA	FOCUS MP 11 CLEANER #2101 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	74	43

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	11 CONCENTRATED. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE). PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND LIGHT WEIGHT NITRILE OR NEOPRENE GLOVES 1 GLL CTR/4 CSE				
70-18-1334	CLEANER, MULTI-PURPOSE CLEANER AND DEGREASER, CONCENTRATED, WATER BASED; CLEANS WALLS, FLOORS, CONCRETE, CERAMIC TILES AND TERRAZZO, 55-GALLON DRUM. GREEN SEAL CERTIFIED. MUST BE DILUTED WITH WATER FOR USE ACCORDING TO LABEL INSTRUCTIONS. MAY BE USE BY HAND. THROUGH STEAM OR PRESSURE CLEANING EQUIPMENT AND IN AUTOMATIC SCRUBBERS. NOMINAL USE DILUTION FOR MULTI-PURPOSE CLEANING IS 4 TO 8 OUNCES OF CLEANER PER GALLON OF WATER; 6 TO 10 OUNCES OF CLEANER PER GALLON OF WATER FOR CLEANING FLOORS; 6 TO 10 OUNCES OF CLEANER PER GALLON OF WATER FOR PRESSURE WASHING. SPECIFIC GRAVITY 1.02 - 1.04; PH 11 TO 12 CONCENTRATED. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE). PPE REQUIRED FOR USE; CHEMICAL SPLASH GOGGLES AND LIGHTWEIGHT NITRILE OR NEOPRENE GLOVES; MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS	ZEP INC. NYCTA NYCTA	MULTI-CLEAN GREEN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-18-1345	FINISH, FLOOR, ACRYLIC CO-POLYMER, NON-SKID FLOOR FINISH IN 5 GALLON CONTAINER (MUST BE GREEN SEAL OR ECOLOGO CERTIFIED OR ON THE NYS OGS LIST OF APPROVED FLOOR FINISH PRODUCTS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO ACCOMPANY SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, COLOR, % SOLIDS CONTENT. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 5 GALLON CTR	DIVERSEY, INC. AMERICAN CLEANING SOLUTIONS NYCTA NYCTA NY STATE	COMPLETE FOCUS ZF33, SEAL & FINISH #262 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV D 12/2/15 RESTR S EXECORDER 134 NY STATE COMPLIA	1334	1026
70-18-1461	CLEANER, GENERAL PURPOSE, LIQUID, CONCENTRATED; USED FOR GENERAL CLEANING AND LIGHT DEGREASING ON ALL SURFACE AND FLOORS. GREEN SEAL CERTIFIED. USED FOR CLEANING RAILCAR FLOORS & INTERIOR SURFACES, OFFICE FLOORS & WALLS, SHOP FLOORS. SUPPLIED IN 2.5 LITER/84.5 OUNCE CARTRIDGES, TWO CARTRIDGES PER CASE. USE DILUTION IS 1 PART CLEANER TO 256 PARTS WATER FOR LIGHT SOILS AND 1 PART CLEANER TO 64 PARTS WATER FOR HEAVY SOILS. CLEANER IS AUTOMATICALLY DILUTED AND DISPENSED THROUGH A HAND HELD AND/OR WALL MOUNTING DISPENSER SYSTEM. HAND HELD DISPENSER AVAILABLE UNDER COMMODITY #61-18-2347. SPECIFIC GRAVITY 0.90 - 1.02; PH 9.0 - 10. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE). PPE REQUIRED FOR USE; CHEMICAL SPLASH GOGGLES AND DISPOSABLE VINYL GLOVES 2 CRTRIDGES/CSE	SEALED AIR DIVERSEY CARE NYCTA NYCTA NY STATE	GENERAL PURPOSE CLNR15 #931726 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	1125	555

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-18-1462	CLEANER, GLASS, NON-AMMONIATED, LIQUID, CONCENTRATE; USED FOR CLEANING RAILCAR WINDOWS AND OTHER GLASS AND MIRROR SURFACES. SUPPLIED IN 2.5 LITER/84.5 OUNCE CARTRIDGES. USE DILUTION IS 1 PART CLEANER TO 40 PARTS WATER. CLEANER IS AUTOMATICALLY DILUTED AND DISPENSED THROUGH A HAND HELD AND/OR WALL MOUNTED DISPENSER SYSTEM. HAND HELD DISPENSER AVAILABLE UNDER COMMODITY #61-18-2347. GREEN SEAL CERTIFIED. SPECIFIC GRAVITY 0.98-1.02; % SOLIDS/NON-VOLATILES 4.2 - 5.2; PH 6.0 - 8.0. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, PH (CONCENTRATE), % NON-VOLATILE CONTENT; SPECIFIC GRAVITY 84.5 OZ CART	SEALED AIR DIVERSEY CARE NYCTA NYCTA NY STATE	GLANCE NA # 93172641 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	16	17
70-18-1472	GRAFFITI, REMOVER, ENVIRONMENTALLY FRIENDLY, PHOSPHATE FREE, CLEAR, CAN BE USED UNDILUTED OR DILUTED. GREEN SEAL CERTIFIED. IN QUART CONTAINERS	CLAIRE MANUFACTURING NYCTA NYCTA	CG310 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-18-1475	GRAFFITI REMOVER, LIQUID, IN ONE-GALLON CONTAINERS. REMOVES PAINT, INK, PERMANENT MARKER FROM BRICK, STONE, CONCRETE, METAL, PLASTIC, PAINTED SURFACES. CAN BE USED IN CONCENTRATED FORM OR DILUTED WITH WATER (1 PART GRAFFITI REMOVER TO 3 PARTS WATER {32 OZ. GRAFFITI REMOVER TO 1 GALLON OF WATER}). NON-FLAMMABLE (FLASH POINT > 200F); NON-CAUSTIC (PH OF CONCENTRATE = 7, 10% = 6-8); NO VOC CONTENT; SPECIFIC GRAVITY = 1.0-1.02. ECOLOGO CERTIFIED PRODUCT. VENDOR TO SUPPLY A CERTIFICATE OF CONFORMANCE AND A CERTIFICATE OF ANALYSIS WHICH INCLUDES BATCH #, DATE OF MANUFACTURE, PH @ 10%, SPECIFIC GRAVITY FOR EACH BATCH SHIPPED. APPROVED FOR BRUSH OR WIPER	ECO CONCEPTS, INC. NYCTA NYCTA NY STATE	GREEN CONCEPTS GRAF REMOVER #1 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	APPLICATION. PPE REQUIRED: CHEMICAL SPLASH GOGGLES & LATEX OR POLYETHYLENE GLOVES ONE GAL CONT				
70-18-1540	HANDSOAP, GREEN CERTIFIED FOAM HAND CLEANER, 1200ML REFILL CARTRIDGE, 2 PER CASE. FIT IN DISPENSER ALREADY IN THE SYSTEM, USE (STOCK #61-18-3134 FOR DISPENSER). MUST BE GREEN SEAL CERTIFIED 1200 ML CARTR	GOJO INDUSTRIES, INC. NYCTA NYCTA NY STATE	5665-02 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	170	85
70-18-1638	CLEANER, CONCENTRATED FOR GLASS, WINDOWS, POLYCARBONATE, PLASTIC, STAINLESS STEEL SURFACES. GREEN SEAL CERTIFIED. ONE GALLON CONTAINERS. FOUR GALLONS PER CASE. MUST BE DILUTED WITH WATER FOR USE ACCORDING TO LABEL INSTRUCTIONS. REMOVES DIRT, SMUDGES AND FINGERPRINTS WITHOUT ANY STREAKS OR HAZE. DOES NOT CONTAIN AMMONIA OR ALCOHOL. FLASH POINT ABOVE 150F. AMERICAN CLEANING SOLUTIONS "FOCUS GC 55 GLASS & WINDOW CLEANER" USE DILUTION 1:64=1 OUNCE OF CLEANER TO 64 OUNCES OF WATER, 1/2 OUNCE PER QUART OR 2 OUNCES PER GALLON. ZEP "GREEN LINK CONCENTRATED GLASS CLEANER 103623" USE DILUTION 1:32=1 OUNCE OF CLEANER TO 32 OUNCES OF WATER, 1 OUNCE PER QUART OR 4 OUNCES PER GALLON 4 GAL PER CASE	ZEP MANUFACTURING COMPANY AMERICAN CLEANING SOLUTIONS NYCTA NYCTA NY STATE	103623 GREEN LINK CONC GLASS C FOCUS GC 55 GLASS CLNR #2102 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	1107	682

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-18-1700	GRAFFITI REMOVER, TOWELETTES PRE-MOISTENED, TO BE USED TO REMOVE GRAFFITI FROM METALS: STEEL, ALUMINUM, GALVANIZED BRASS COPPER, ANODIZED ALUMINUM ZINC, GLASS: POLISH PLASTIC: FIBERGLASS, POLYETHELENE OR POLYETHELENE. COMES IN PLASTIC TUBS WITH 25 TOWELS PER TUB	GRAFFITTI REMOVAL INC. NYCTA NYCTA NY STATE	MAX-SWIPES GRAFFITI REMOVER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S EXECORDER 134 NY STATE COMPLIA	0	0
70-21-1018	DEODORIZER, AEROSOL, HYDROCARBON PROPELLANT, DRY SPRAY, USE TO FRESHEN AIR WITH NO WETNESS, NO STAINS, NO RESIDUE; MUST BE VOC COMPLIANT WITH A LEVEL OF 1.84 LBS/GAL OR 28.17% VOC CONTENT. PACKAGED IN 20 OZ. CAN WITH A NET WEIGHT OF 10 OZ. MUST HAVE A 9 MONTH MINIMUM SHELF LIFE AT TIME OF RECEIPT 20 OZ/CAN 20 OZS/CAN	ZEP MANUFACTURING COMPANY NYCTA NYCTA	MICROMIST FRESH SCENT 243 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2579	1774
70-21-1022	ODOR ELIMINATOR, LIQUID, CONCENTRATED, ONE TO TWO DROPS OF PRODUCT IS REQUIRED TO ELIMINATE ODORS. ONE-OUNCE BOTTLE. THIS IS NOT A CLEANER. THIS PRODUCT IS ONLY INTENDED TO BE USED TO ELIMIATE OBJECTIONAL ODORS. 12 BOTTLES PER CARTON. BOX SIZE 6-1/4" X 4-1/2" X 3". 100% ACTIVE INGREDIENTS; NON-WATER BASED; SPECIFIC GRAVITY IS 0.9 TO 1.0; FLASHPOINT IS 130 DEGREES F MINIMUM 12 BTLS/CTN 12 BTLS/CTN	CUSTOM ESSENCE, INC. CUSTOM ESSENCE, INC. NYCTA NYCTA	CE-162017/SPICE SPICE FRESH CE-13020 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	6205	4475

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-21-1027	ODOR ELIMINATOR, BACTERIA FREE, USED TO ELIMINATE ODORS FROM NYCT SUBWAY STATIONS. MUST UTILIZE ENZYME ACTION WHILE CONTAINING NO BACTERIA. MUST ELIMINATE ODOR CAUSING ORGANIC MATTER FROM FOOD AND BODY WASTE, IMPARTING A PLEASANT ODOR WHILE LEAVING NO VISIBLE FILM OR DRYING. MUST BE SAFE FOR USE ON TILE, CONCRETE, AGGREGATE AND OTHER FLOOR TYPES USED IN NYCT, IN ONE GALLON CONTAINERS	NATIONAL CHEMICAL LAB OF PA. NATURE PLUS NYCTA NYCTA	912 ODOR ELIMINATOR SOLUTION BACTERIA-FREE ODOR ELIMINATOR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9//11/17RESTR S	0	0
70-21-1028	ODOR ELIMINATOR, LIQUID WATER BASED, MILD PINE OR MINT ODOR, CONTAINS 25% ACTIVE INGREDIENTS (MIN.) OF WHICH 12% IS ORGANIC PERFUME; PH IS 6 TO 8; MUST NOT CONTAIN PETROLEUM DISTILLATES, CHLORINATED SOLVENTS, D'LIMONENE; USED IN SPRAY BOTTLES AND ADDED TO MOP BUCKET WATER; CAN BE DILUTED UP TO 100:1, PACKAGED IN ONE GALLON CONTAINERS. CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, PH, % ACTIVE INGREDIENT, WEIGHT % TOTAL PERFUME IN 1 GAL CTR	NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	TA514 SPRING AIR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	5699	2843
70-21-1032	ELIMINATOR, ODOR, LIQUID, STRAWBERRY/CITRUS FRAGRANCE, WATER BASED, MUST NOT CONTAIN ANY CHLORINATED SOLVENTS, PETROLEUM DISTILLATES, D'LIMONENE. MINIMUM 25 PERCENT ACTIVE INGREDIENTS AND AT LEAST 12 PERCENT MUST BE ORGANIC PERFUME (STRAWBERRY/CITRUS FRAGRANCE). PH IS 6 TO 8. USED IN SPRAY BOTTLES, ODOR MASKING DEVICES, ADDED TO MOP BUCKET WATER. CAN BE DILUTED UP TO 100:1. PACKAGED IN ONE GALLON CONTAINERS. CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR	NATIONAL CHEMICAL LAB OF PA. U.S. POLYCHEMICAL CORPORATION NYCTA NYCTA	NCL 430 STRAWBERRY/CITRUS POLYCHEM 1020 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	12897	4804

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, PH, % ACTIVE INGREDIENT, WEIGHT % TOTAL PERFUME IN 1 GAL CTR				
70-21-1036	DEODORANT, ODOR, COUNTERACTANT, BIO DEGRADABLE CONCENTRATED WATER SOLUBLE USED TO CLEAN ELEVATOR SHAFTS. TO BE SUPPLIED IN CLEARLY LABELED 1 GALLON PAILS. IN 1 GAL PAILS	FOSTER & CO. NYCTA NYCTA	DAWN TO DUSK-8380117 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-21-1054	ODOR BLOCKER, LIQUID, READY TO USE. ELIMINATES ODORS FROM GARBAGE CANS, DUMPSTERS, TRASH BINS, URINALS, RAILCARS. ELIMINATES URINE, VOMIT, AND OTHER ODORS. PH 6.0-7.0, SPECIFIC GRAVITY 0.998-1.001. SUPPLIED IN ONE-QUART BOTTLES WITH TRIGGER ACTION SPRAYERS. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND NEOPRENE OR NITRILE GLOVES. CERTIFICATE OF ANALYSIS TO BE SUPPLIED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE SPECIFIC GRAVITY AND PH. SIX BOTTLES PER CASE. IN 1 QT BTLs	ALPHA CHEMICAL SERVICES NYCTA NYCTA	ODOR OUT PLUS 5520 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1269	1005
70-21-1056	ODOR BLOCKER, LIQUID, READY TO USE. ELIMINATES ODORS FROM GARBAGE CANS, DUMPSTERS, TRASH BINS, URINALS, RAILCARS. ELIMINATES URINE, VOMIT AND OTHER ODORS. PH 6.0-7.0, SPECIFIC GRAVITY 0.998-1.001. SUPPLIED IN FIVE GALLON CONTAINER (PAIL). PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND NEOPRENE OR NITRILE GLOVES. CERTIFICATE OF ANALYSIS TO BE SUPPLIED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE SPECIFIC GRAVITY AND PH	ALPHA CHEMICAL SERVICES NYCTA NYCTA	ODOR OUT PLUS 5520 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	IN 5 GAL CTRS				
70-22-4010	FLUID, LEAK DETECTING, BUBBLE-GENERATING; FOR DETECTING LEAKS IN RAILCAR AIR SUPPLY PIPING AND JOINTS AND AIR CONDITIONING SYSTEMS; MUST GENERATE SUFFICIENT LEVEL OF BUBBLING FOR DETECTING LEAKS IN THESE AREAS. PACKAGED IN A 5-GALLON CONTAINER; PH TO BE 7.0 TO 8.5; CONTAINS MINIMUM 15% ACTIVE INGREDIENTS IN 5 GAL CTR	NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	TA901 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	30	20
70-23-1130	DISINFECTANT AND DETERGENT, QUATERNARY AMMONIA TYPE; QUATERNARY AMMONIA CONTENT TO BE 1.5% TO 1.8%; PH TO BE 10-12; MUST BE REGISTERED USEPA DISINFECTANT FOR USE AGAINST CORONA VIRUS AND NYS DEC REGISTERED; CERTIFICATE OF ANALYSIS COVERING % QUATERNARY AMMONIA CONTENT TO BE PROVIDED FOR EACH BATCH SHIPPED; PACKAGED IN 1 GALLON CONTAINERS. NOTE TO USERS: DILUTE AT 4 OZ. PER GALLON OF WATER	AMERICAN CLEANING SOLUTIONS NYCTA NYCTA	LEMON E DISINFECTANT CCSS-001 REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	395	111
70-23-1200	DISINFECTANT, SODIUM HYPOCHLORITE SOLUTION (HOUSEHOLD BLEACH), NAOCL CONTENT TO BE 5% TO 6% BY WEIGHT, % WEIGHT BY ALKALI AS NAOH TO BE 0.12% TO 0.50%; SPECIFIC GRAVITY TO BE 1.04 TO 1.10; PH TO BE 10.5 TO 12.5; CLEAR GREEN-YELLOW LIQUID TO BE FREE OF SEDIMENT OR SUSPENDED MATTER; PACKAGED IN 1-GAL PLASTIC CONTAINERS WITH PLASTIC-LINED SCREW CAPS WITH 6 CONTAINERS PER CARTON; CARTONS TO BE NEW, SEALED AND IN GOOD CONDITION; STOCK #, PO #, DATE OF MANUFACTURE, AND SCHEDULED SHIPMENT DATE TO APPEAR ON CARTONS; EPA REGISTRATION # TO APPEAR ON CONTAINER LABELS; CERTIFICATES OF ANALYSIS AND COMPLIANCE FOR EACH BATCH BEING SHIPPED TO BE SUBMITTED TO NYCT	JAMES AUSTIN CO. ROCHESTER-MIDLAND JAMES AUSTIN CO. NYC SPEC NYCTA NYCTA NYCTA	AUSTIN A-1 BLEACH COMMERCIAL CHLORGUARD 2 "5.25%" ELITE PROFESSIONAL BLEACH 5-S-26 94 TYPE B CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC	99733	68095

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	MANAGER OF INSPECTIONS & TESTING PRIOR TO DELIVERY; CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, SPECIFIC GRAVITY, PH, WEIGHT % NAOCL, ALKALINITY AS NAOH; MINIMUM SHELF LIFE AT TIME OF RECEIPT TO BE 9 MONTHS. IN 1 GAL CTR IN 1 GAL CTR				
70-23-1270	DISINFECTANT SPRAY, ANY SCENT, ACCEPTABLE, NEEDED FOR OFFICE USE AND LOCKER ROOM. TO ELIMINATE THE FOLLOWING BACTERIA= E-COLI, FUNGI=MOLD & MILDEW AND VIRUS= INFLUENZA ON HARD NON-POROUS SURFACES (19 OZ CAN AEROSOL 12 CAN PER CASE). EACH CASE MUST BE A COMPLETELY ENCLOSED CARDBOARD BOX WITH 12 CANS INSIDE 12 CANS/CSE	RECKITT BENCKISER NYCTA NYCTA	PRO LYSOL BRAND III DIS SPRAY CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	653	4109
70-29-1016	COMPOUND, EPOXY, AMINE, TWO-PART, THIXOTROPIC, FOR USE IN REPAIRING/ BONDING ARMATURES AND OTHER ELECTRICAL EQUIPMENT. PACKAGED IN 50-ML DUAL CARTRIDGES. MUST BE TACK FREE IN 20 MINUTES. MINUTES GEL TIME @ 100 DEGREES C IS 40-80 MINUTES; SHORE D HARDNESS (CURED 16-18 HOURS @ ROOM TEMPERATURE FOLLOWED BY 2 HOURS @ 65 DEGREES C) IS 84-94; VISCOSITY (BROOKFIELD SPINDLE #7 @ 20 RPMS @ 25 DEGREES C) IS 80,000-280,000 MPAS (CP); TENSILE SHEAR STRENGTH (CURED 2 HOURS @ 65 DEGREES C) IS GREATER THAN 3.47 N/MM2 (503 PSI). CERTIFICATE OF ANALYSIS AND CERTIFICATE OF COMPLIANCE/CONFORMANCE FOR EACH BATCH TO BE SUPPLIED WITH EACH SHIPMENT; CERTIFICATE OF ANALYSIS HAS TO CONTAIN VISCOSITY OF RESIN, GEL TIME, HARDNESS, TENSILE/SHEAR STRENGTH. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS	HENKEL LOCTITE CORPORATION NYCTA NYCTA	LOCTITE EAE-20NS CR50MLN23711 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	26	18

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	50 ML DUAL CART				
70-29-1017	ADHESIVE, COMPOUND, TWO-COMPONENT, ISOCYANATE BASED, POLYMERIC, FOR USE TO REPAIRING R143 CAR SEATS; PACKAGED IN 48.5 ML TWIN PACK, 12 TWIN-PACKS PER CASE; USES 3M SCOTCHWELD EPX MIXING NOZZLE (SQUARE GREEN OR HELICAL WHITE)FOR 3M SCOTHWELD EPX PLUS II APPLICATOR; ** MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 4 MONTHS ** A COPY OF CERTIFICATE OF ANALYSIS MUST ACCOMPANY THE SHIPMENT 12 PKG/CSE	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	SCOTCH WELD ADHESIVE DP-601NS CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	139	375
70-29-1020	EPOXY, TWO COMPONENT BALANCING COMPOUND, USED TO CORRECT IMBALANCES IN ELECTRIC MOTORS, CONSISTS OF PART A AND PART B, 100% SOLIDS, CAN BE AIR CURED AT 72 DEGREES FAHRENHEIT IN 24 HOURS OR HEAT CURED AT 250 DEGREES FAHRENHEIT IN 15 MINUTES. POT LIFE OF MIXED COMPONENTS IS 90-150 MIN AT 72 DEGREES FAHRENHEIT. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 4 MONTHS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE TO BE PROVIDED FOR EACH BATCH TO THE MANAGER OF INSPECTIONS AND TESTING BEFORE SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE SPECIFIC GRAVITY AND CONSISTENCY. SPECIFIC GRAVITY TO BE; 2.55-2.75 FOR PART A, 2.55-2.65 FOR PART B; CONSISTENCY TO BE: 95-145 FOR PART A, 150-200 FOR PART B, PACKAGED IN TWO POUND KITS, ONE POUND OF PART A AND ONE POUND OF PART B; 16 KITS PER CASE 16 KITS/CSE	STAR TECHNOLOGY, INC. NYCTA NYCTA	BC-22(PARTS A & B) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	12	1

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-30-1000	FILLER, LIGHTWEIGHT POLYESTER WITH CREAM HARDENER, USED FOR AUTOMOTIVE BODY AND FENDER WORK; PACKAGED IN 1 GALLON CAN, TUBE OF CREAM HARDENER MUST BE TAPED TO GALLON OF FILLER, PRODUCT MUST HAVE DRY TIME 15-20 MINUTES @ 70 DEGREES F, 80-90% OF SOLIDS BY WEIGHT; VOC 2.5 LB/GAL MAXIMUM AND TOTAL FILM BUILD SHOULD NOT EXCEED 1/4", MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS IN 1 GAL CAN	PPG INDUSTRIES NYCTA NYCTA	DF700 & DF708 CREAM HARDENER CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			48	32
70-30-1004	FILLER, BODY, LIGHTWEIGHT PASTE WITH CREAM HARDENER, USED FOR REPAIRS ON RAILCAR SEATS. PACKAGED IN 1 GALLON CANS, 4 CANS PER CASE. EACH CAN MUST BE SUPPLIED WITH TUBE OF CREAM HARDENER; MINIMUM SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	3M BONDO FILLER 7010362873 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			0	0
70-30-1560	BODY FILLER, POLYESTER RESIN FOR USE ON METAL OR PLASTIC SURFACES, PACKAGED IN ONE GALLON CANS. MINIMUM REQUIRED SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS. IN 1 GAL CANS	THE CLAUSEN COMPANY NYCTA NYCTA	"CLASSIC PLASTIC" CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			154	124
70-30-1594	FILLER, BODY, HEAVYWEIGHT PASTE WITH CREAM HARDENER USED FOR ALL TYPICAL REPAIRS; PACKAGED IN 1 GALLON CAN, 4 GALLONS TO A CASE, TUBE OF CREAM HARDENER MUST BE TAPED TO GALLON OF FILLER; PRODUCT MUST MEET ALL REQUIREMENTS UNDER NYCT SPECIFICATION 7110-FACIL-00 REV. A; MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS	QUEST AUTOMOTIVE PRODUCTS NYCTA NYCTA NYCTA	BULK, BODYFILLER WHITE #10005 7110-FACIL-00 REV. A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-30-1595	FILLER, BODY, LIGHTWEIGHT PASTE WITH CREAM HARDENER FOR SMALL REPAIRS. PACKAGED 4 GALLONS PER BOX, 1 GALLON CAN MUST BE SUPPLIED WITH TUBE OF CREAM HARDENER; PRODUCT MUST MEET ALL REQUIREMENTS UNDER NYCT SPECIFICATION 7111-FACIL-00 REV. A. MINIMUM SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS	QUEST AUTOMOTIVE PRODUCTS NYCTA NYCTA NYCTA	BC/CC EXTRA GAL(PR)#16060P 7111-FACIL-00 REV. A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-30-1596	HARDENER, CREAM/CATALYST, FOR UNSATURATED POLYMER RESIN, REINFORCED POLYESTER, VINYL OR ACRYLIC RESIN FILLERS, RED IN 2.75 OUNCE TUBES FOR FILLING COMPOUNDS UNDER COMMODITIES 70-30-1594 & 70-30-1595. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 2.75 OZ TBES	QUEST AUTOMOTIVE PRODUCTS NYCTA NYCTA NYCTA	RED CREAM HARDENER 2.75 OZ 7077-FACIL-98 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	153	73
70-30-1750	PUTTY, TWO COMPONENT EPOXY, STEEL FILLED, USED IN FILLING ROUGH OR PITTED METAL SURFACES ON SUBWAY CARS. PACKAGED IN ONE POUND CANS, MUST MEET ALL REQUIREMENTS SET UP UNDER NYCT SPECIFICATION 7099-FACIL-99. IN 1 LB CANS	ITW DEVCON NYCTA NYCTA NYCTA	PLASTIC STEEL PUTTY 10110 7099-FACIL-99 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	40	26
70-30-2151	COMPOUND, FILLING, WOOD FILLER, CELLULOSE FIBER WOOD, USED TO REPAIR WOOD SURFACES, COLOR: NATURAL, IN 4 OZ. CAN. 12 CANS PER BOX. SOLVENT BASED. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. THIS MATERIAL IS FLAMMABLE. IT MUST BE STORED IN FLAMMABLE STORAGE CABINET. MUST NOT BE USED ON OR NEAR SOURCES OF HEAT, IGNITION SOURCES, ELECTRICITY, AND/OR OPEN FLAMES INCLUDING SMOKING MATERIAL. DOORS AND WINDOWS NEED TO BE OPEN TO INCREASE AIR DILUTION 12 CANS/BOX	DAP INC. NYCTA NYCTA	PLASTICWOOD 70798 21502 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	30	22

USER-ID : RJR
PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 334
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-31-1485	POWDER, COMPOUND, FIRE EXTINGUISHER. POWDER MUST BE MULTI-PURPOSE, FOR ALL CLASS OF FIRE; A, B, & C, MONO AMMONIUM PHOSPHATE BASE, FOR DRY CHEMICAL EXTINGUISHERS. POWDER TO BE DELIVERED IN 50 LB PLASTIC PAILS. ** CERTIFICATE OF COMPLIANCE REQUIRED WITH SHIPMENT ** 50 LB PAILS	AMEREX CORP. NYCTA NYCTA NYCTA	550 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC	0	0
70-33-3557	REFRIGERANT, GAS, R438A, FOR RAILCAR AIR CONDITIONING UNITS, 25 POUND CYLINDER, COMPATIBLE WITH ALKYBENZENE, MINERAL OIL & POLYOLESTER LUBRICANTS, PPE REQUIREMENTS; WEAR CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES. PERSONNEL HANDLING THIS PRODUCT MUST POSSESS EPA CERTIFICATION, EPA APPROVED REFRIGERANT RECOVERY UNITS MUST BE USED WHEN SERVICING AIR CONDITIONING UNITS TO PREVENT THE RELEASE OF REFRIGERANT TO THE ENVIRONMENT; ADHERE TO APPLICABLE REQUIREMENTS OF THE HANDLING, STORAGE & TRANSPORTATION OF COMPRESSED & LIQUIFIED PETROLEUM GASES PI#10.7.0 IN 25 LB CYL	CHEMOURS DUPONT NYCTA NYCTA	FREON MO99 REFRIGERANT ISCEON MO99 REFRIGERANT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	19	0
70-33-3562	GAS, REFRIGERANT, R453A (RS44B), FLUOROCARBON REFRIGERANTS, IN 30 LB. DISPOSABLE CYLINDER WITH 24 LB NET WEIGHT REFRIGERANT. CERTIFICATION THAT MATERIAL MEETS THE REQUIREMENTS AHRI STANDARD 700-2004 TO BE PROVIDED WITH EACH SHIPMENT. WEAR CHEMICAL SPLASH GOGGLES AND LIGHT WEIGHT NEOPRENE GLOVES. PERSONNEL HANDLING THIS PRODUCT MUST POSSESS EPA CERTIFICATION. IT MUST BE USED WITH APPROVED REFRIGERANT RECOVERY UNITS. ADHERE TO APPLICABLE REQUIREMENTS OF THE HANDLING, STORAGE & TRANSPORTATION OF COMPRESSED & LIQUIFIED PETROLEUM GASES PI # 10.7.0	COMSTAR INTERNATIONAL INC. NYCTA NYCTA	RS44B(R453A)HFC BLEND CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	96	71

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-34-1400	SEALANT, FAST DRYING, HARD SETTING, FOR GASKET SEAL ON PERMANENT, RIGID ASSEMBLIES WITHSTANDING 5000 PSI. COLOR: REDDISH-BROWN, IN 11 OZ. TUBE. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 11 OZ TBE	PERMATEX NYCTA NYCTA MIL SPEC	1C FORM-A-GASKET#1 11 OZ #8000 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-45180D TYPE I			16	14
70-34-1410	SEALANT, SLOW DRYING, FLEXIBLE SETTING FOR GASKET SEAL ON NON-RIGID, VIBRATING, SEMI-PERMANENT AND PERMANENT ASSEMBLIES. WITHSTANDS PRESSURE TO 5000 PSI. BROOKFIELD VISCOSITY 550000-650000 MPAS. COLOR: BLACK, IN 7-11 OZ TUBE. CERTIFICATE OF ANALYSIS TO INCLUDE: VISCOSITY. MIMIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 7-11 OZ TBE	PERMATEX HENKEL CORPORATION NYCTA NYCTA	2C FORM-A-GASKET#2 SEALANT 800 LOCTITE MR GS2 SEALANT #30515 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			34	26
70-34-1420	SEALANT AND GASKET COMPOUND; EPDM (ETHYLENE PROPYLENE DIENE MONOMER) RUBBER, FOR USE ON LOCOMOTIVE DOOR FRAME GASKETS. IMPROVES GASKET SEAL IN CLOSE FITTING PARTS. SEALS AND REPAIRS CUT GASKETS AND UNEVEN FLANGE SURFACES. SEALS THREADED CONNECTIONS. PACKAGED IN 4 OZ. BRUSH JARS. CERTIFICATE OF ANALYSIS TO INCUDE VISCOSITY. MEETS REQUIREMENTS OF MILITARY SPECIFICATION MIL-S-45180D TYPE III MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. IN 4OZ JARS	PERMATEX NYCTA NYCTA MIL SPEC	AVIATION FORM-A-GASKET #3H CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-45180D TYPE 3			13	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
70-34-1430	SEALANT AND GASKET COMPOUND; FOR USE ON GE GEAR BOXES AND EPDM (ETHYLENE PROPYLENE DIENE MONOMER) RUBBER LOCOMOTIVE DOOR FRAME GASKETS. IMPROVES GASKET SEAL IN CLOSE FITTING PARTS. SEALS & REPAIRS CUT GASKETS AND UNEVEN FLANGE SURFACES. SEALS THREADED CONNECTIONS. VISCOSITY 8,000 -10,000 MPAS(BROOKFIELD RVT # 3,5 RPM @ 25OC); PACKAGED IN 16-OZ. BRUSH JARS. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS IN 16 OZ JARS	PERMATEX CO. NYCTA NYCTA	AVIATION FORM-A-GASKET #3D CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		39		13
70-34-1445	SEALANT, GASKET, HIGH TACK, 16 OZ., BRUSH TOP CAN. DRIES QUICKLY TO A HIGH TACKY FILM. SEALS OR BONDS RUBBER, CORK FELT, PAPER AND METAL GASKET. SEALS THREADED CONNECTIONS, HOSE CONNECTIONS. APPLY ONLY IN A WELL VENTILATED AREA. DO NOT USE NEAR HEAT SOURCES, IGNITION SOURCES, OPEN FLAMES INCLUDING SMOKING MATERIALS. STORE IN AN AUTHORIZED FLAMMABLE MATERIAL STORAGE CABINET. PPE REQUIRED: CHEMICAL SPLASH GOGGLES AND NITRILE GLOVES	PERMATEX, INC. NYCTA NYCTA	98D HIGH TACK GASKET SEAL #800 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/17/17 RESTR S		0		0
70-37-2201	ADHESIVE, WOOD GLUE, POLYVINYL ACETATE EMULSION, FOR BONDING WOOD JOINTS AND WOOD ASSEMBLIES, IN ONE QUART BOTTLES. 1 QT BTLS	ELMERS COMMERCIAL ITEM NYCTA NYCTA	CARPENTER'S WOOD GLUE E7040 A-A-3001 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		49		5

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1	USE YTD
70-38-2000	GROUT, CHEMICAL FOAM, SINGLE COMPONENT, LIQUID SEAL WATERPROOFING COMPOUND, HYDROPHILLIC, NON CORROSIVE. SUITABLE FOR PRESSURE INJECTION USE IN WET OR DRY CONDITIONS. PRODUCT SHALL SEAL AFTER INJECTION VIA NOZZLE INTO EXISTING CRACKS AND VOIDS BY MEANS OF POLYMERIZATION. THE GROUT SHALL BE SUPPLIED IN NON-CONDUCTIVE 5 GALLON HDPE CONTAINERS. THE CONTAINER SHALL AT MINIMUM MEET THE FOLLOWING CRITERIA: MATERIAL HDPE BLOW MOLD RESIN, CONTAINER COLOR: OPAQUE OR COLORED WITH CLEAR S17 STRIP (THE LEVEL OF THE CONTENTS IN THE CONTAINER MUST BE VISIBLE), MOUTH OPENING MINIMUM I.D. : 2-3/16, WALL THICKNESS: .055, CONTAINER HEIGHT: 14-3/4" WITH PROVISION FOR CAPPED VENT HOLE AND CARRY HANDLE, NAMPAC DRAWING #TH60022 (FOR REFERENCE ONLY). MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE (9) MONTHS. 5 GAL CTRS 5 GAL CTRS	AVANTI INTERNATIONAL FOX INDUSTRIES, INC. DE NEEF CONSTRUCTION CHEMICALS NYCTA NYCTA	AV-330 SAFEGUARD FX-1 JET SET HYDRO ACTIVE SEALFORM CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4125	4155
70-39-1265	COATING, PROTECTIVE CREAM, FOR HANDS; PROTECTS AGAINST OIL/GREASE, WATER BASED AND SOLVENT BASED PRODUCTS; SUPPLIED IN 100 ML TUBES, 12 TUBES PER CASE. PH IS 6.5 TO 7.5, ACTIVE INGREDIENT CONTENT IS 21-25%, DOES NOT CONTAIN SILICONE, VISCOSITY 20,000 TO 80,000 CPS (BROOKFIELD RVT W/SPINDLE #5 @ 5 RPM AND 25 DEGREES C). (NOTE; NOT TO BE USED IN PLACE OF GLOVES) 100 ML TUBE	S.C. JOHNSON NYCTA NYCTA	STOKODERM PROTECT PURE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	672	474

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-42-1054	COMPOUND, SILICONE, HEAT SINK, WHITE PASTE IN 5 OZ.TUBE. USE FOR HEAT SINK IN ELECTRONIC DEVICES SUCH AS DIODES AND TRANSISTORS. CERTIFICATE OF ANALYSIS TO INCLUDE WORKED PENETRATION OF COMPOUND. IN 5 OZ TBE	DOW CORNING WESTINGHOUSE VAPOR TRANSLITE NYCTA NYCTA MIL SPEC	340 HEAT SINK COMPOUND 6247D49H02 67110049 AH2668-2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-DTL-47113E	119	61
70-42-1110	COMPOUND, INSULATING, 2-PART KIT, EPOXY ADHESIVE, 4-OZ; MINIMUM SHORE "D" HARDNESS (CURE 2 HRS) TO BE 65; MINIMUM POT LIFE (100 G) TO BE 20 MIN; FOR USE ON ARC CHUTES, PLASTICS, SMALL PARTS. CERTIFICATE OF ANALYSIS TO ACCOMPANY EACH BATCH SHIPPED; CERTIFICATE OF ANALYSIS TO INCLUDE SHORE "D" HARDNESS & POT LIFE IN 2 PART KIT	HENKEL CORPORATION NYCTA NYCTA	LOCTITE EA 1C (A&B) #1373425 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1426	1050
70-42-1124	ADHESIVE, SEALANT, SILICONE RUBBER, RTV, ONE COMPONENT THIXOTROPIC PASTE, GENERAL PURPOSE SEALING AND BONDING, CLEAR/TRANSLUCENT, 4.7 OZ. TUBE. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE HARDNESS, ELONGATION, TENSILE STRENGTH, AND PEEL STRENGTH. EACH TUBE IS INDIVIDUALLY PACKED IN A BOX WITH AN APPLICATION NOZZLE 4.7 OZ TBE	DOW CORNING NYCTA NYCTA MILITARY	732 CLEAR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46106B	5972	4237
70-42-1130	SEALANT, SILICONE ELECTRONIC GRADE, APPLIED WITH A CAULKING GUN; PACKAGED IN 10.1 FL OZ. CARTRIDGES. MUST MEET REQUIREMENTS OF MILITARY SPECIFICATION MIL-A-46146B, TYPE I. CERTIFICATE OF ANALYSIS FOR EACH BATCH MUST BE PROVIDED PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS MUST INCLUDE % SOLIDS, TENSILE STRENGTH, % ELONGATION, HARDNESS, EXTRUSION/APPLICATION.	DOW CORNING NYCTA NYCTA MILITARY	738 ELECTRICAL SEALANT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46146B TYPE I	8	1

USER-ID : RJR
PROG-ID : JSBYRALL

N E W Y O R K C I T Y T R A N S I T A U T H O R I T Y
C O M M O D I T Y M A N A G E M E N T S Y S T E M

DATE 08/25/2022 PAGE : 340
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
70-42-1305	COATING, SYNTHETIC RUBBER, FOR ELECTRICAL INSULATION, 4-OZ. BRUSH-IN-CAP CAN. COLOR: BLACK. 6 CANS PER CASE. BRUSHED ON ELECTRICAL CONNECTIONS TO INSULATE AND PROTECT. USED ON L-1 REACTOR ON CONVERTER ON RAILCARS. PROVIDES EXCELLENT MOISTURE, ACID, ALKALINE, ABRASION AND DIELECTRIC RESISTANCE. WONT'T CRACK, HARDEN OR PEEL. A MINIMUM OF 2 COATS ARE REQUIRED TO ASSURE GOOD DIELECTRIC PROTECTION. DIELECTRIC STRENGTH: 1400 V/MIL (MINIMUM WITH 2 COATS); % SOLIDS 20-28 (WEIGHT %); VISCOSITY 90-110 KU(@70F); ELONGATION 430%; TENSILE STRENGTH 3500-3900 PSI 4 OZ CANS	PLASTI DIP INTERNATIONAL NYCTA NYCTA	LIQUID TAPE F-825 #LET14Z03 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 6/11/17 RESTR S	29	15
70-42-1950	INHIBITOR, CORROSION, LIQUID, FOR USE IN HIGH PRESSURE SPRAY WASHERS TO PROTECT PUMP PARTS, PIPING AND TANK INTERIOR, NON-NITRITE BASED, PH BETWEEN 7.5 AND 9.0; SPECIFIC GRAVITY BETWEEN 1.07 AND 1.10; ALKALINITY AS %KOH BETWEEN 10.5 AND 13.5; SUPPLIED IN 55 GALLON DRUMS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE: BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, PH, SPECIFIC GRAVITY, ALKALINITY AS %KOH 55 GAL DRMS	CASTROL INDUSTRIAL NYCTA NYCTA	TECHNICLEAN XHP CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	605	495

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1 -----	USE YTD -----
70-42-1996	THINNER, POT-LIFE EXTENDER, FOR VPI TANK VARNISH (AVAILABLE UNDER STOCK #70-42-1025). PACKAGED IN FIVE (5) GALLON CLOSED HEAD PAILS. MUST BE VINYL TOLUENE GRADE 50T, VT STABILIZED. MUST CONTAIN MINIMUM OF 99.2% VINYL TOLUENE (25013-15-4) BY WEIGHT; POLYMER CONTENT 15 PPM MAXIMUM, TERTIARY BUTYL CATECHOL (TBC) CONTENT 50 PPM MAXIMUM. CERTIFICATE OF ANALYSIS COVERING VINYL TOLUENE CONTENT, POLYMER AND TBC CONTENT MUST ACCOMPANY EACH SHIPMENT. MANUFACTURER'S NAME, ADDRESS AND PHONE NUMBER TO APPEAR ON CAN'S LABEL, DISTRIBUTOR/PACKAGER'S NAME, ADDRESS AND PHONE # TO APPEAR ALSO IF DISTRIBUTOR/PACKAGER IS NOT MANUFACTURER. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 5 MONTHS. MUST NOT BE USED NEAR SOURCES OF HEAT, IGNITION SOURCES, AND OPEN FLAMES. PPE RQUIRED FOR USE: CHEMICAL SPLASH GOGGLES, NEOPRENE GLOVES. 5 GAL PAILS	VON ROLL ISOLA USA, INC. DELTECH NYCTA NYCTA	774 VINYL TOLUENE VINYL TOLUENE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	160	80
70-43-0450	LUBRICANT, DRY FILM, A SUSPENSION OF SPECIAL ADDITIVES, AND MOLYBDENUM DISULFIDE IN AN ODORLESS PETROLEUM BASE STOCK; MUST CONTAIN A MINIMUM OF 10% MOLYBDENUM DISULFIDE (TECHNICAL FINE GRADE) AND MINIMUM OF 4% MINERAL THICKENER; SPECIFIC GRAVITY TO BE 0.85-0.96, MINIMUM % NON-VOLATILE = 19%. USED TO LUBRICATE RAILCAR DOOR TRACKS. PACKAGED IN 32 OZ. SCREW CAP CANS. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS WHICH INCLUDES SPECIFIC GRAVITY AND % NON-VOLATILE FOR EACH BATCH IS TO BE PROVIDED TO THE NYCT MANAGER OF INSPECTION AND TESTING PRIOR TO SHIPPING MATERIAL. 32 OZ CANS	MCGEE INDUSTRIES NYCTA NYCTA NYCTA	MCLUBE MOS2-710 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.	512	377

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-43-1000	COMPOUND, ANTI-SEIZE AND LUBRICATING GREASE CONTAINING FINE METALLIC (COPPER) AND GRAPHITE PARTICLES. FOR USE ON THREADED MACHINE PARTS, METAL FITTINGS, CONNECTORS, ETC. PACKAGED IN ONE OZ. TUBES. WORKED PENETRATION 250-380. CERTIFICATE OF ANALYSIS TO INCLUDE WORKED PENETRATION IN 1 OZ TBE	HENKEL LOCTITE CORPORATION NYCTA NYCTA MIL SPEC	C5A COPPER BASE ANTISEIZE(5100 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-907E	688			154
70-48-1015	NEUTRALIZER, COMPOUND, TO BE USED TO NEUTRALIZE ANY RESIDUE FROM THE CLEANER THAT HAS BEEN USED TO REMOVE RUST STAINS FROM RAILCAR STAINLESS STEEL SURFACES (EXTERIORS AND DOORS) SUPPLIED UNDER COMMODITY #70-17-0823 AND TO NEUTRALIZE ABSORBENT PADS USED TO CATCH RUN-OFF FROM CLEANER. ALKALINE BASED MATERIAL. MINIMUM 15% ACTIVE INGREDIENTS. FOR MANUAL APPLICATION. READY TO USE FORMULA SUPPLIED IN ONE QUART PLASTIC BOTTLES. TWELVE ALKALINE RESISTANT TRIGGER ACTION SPRAYERS SUPPLIED IN EACH CASE. APPLY TO STAINLESS STEEL SURFACES AFTER WIPING OFF CLEANER AND DIRT. RINSE THE ENTIRE AREA THOROUGHLY WITH WATER. ALSO APPLY TO ABSORBENT PADS THAT ARE PLACED AGAINST THE DOORS TO CATCH RUN-OFF FROM CLEANER IN ORDER TO NEUTRALIZE THE PADS PRIOR TO DISPOSAL. PPE REQUIRED FOR USE: CHEMICAL SPLASH GOGGLES AND LATEX/LIGHT WEIGHT NITRILE GLOVES. CERTIFICATE OF ANALYSIS TO INCLUDE % ACTIVE INGREDIENTS. TWELVE BOTTLES PER CASE 12 EA/CSE	COSCO ENTERPRISES, INC. NYCTA NYCTA	FO 3027 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			4	13

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-48-2000	NEUTRALIZER, ACID BASED, FOR NEUTRALIZING ALKALINE PARTS WASHING SOLUTIONS, CONSISTS OF 70% GLYCOLIC ACID. 55 GALLON DRUMS	THE CHEMOURS COMPANY NYCTA NYCTA	GLYCOLIC ACID 70% TECH SOLUTIO CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		220		0
70-57-1050	PRIMER, POLYSILANE BASED, CLEAR, 250 ML BOTTLE, 12 PER CASE. APPLIED TO METAL, PLASTICS, GLASS PRIOR TO USING ADHESIVE/SEALANT TO ASSIST IN BONDING. USED TO IMPROVE ADHESION OF 3M HYBRID ADHESIVE SEALANT 760 FOR FLOORING INSTALLATION ON R46 RAILCARS. PPE REQUIRED; CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES. RAILCAR WINDOWS AND DOORS ARE TO BE OPENED FOR VENTILATION DURING THE APPLICATION OF THIS PRODUCT. BLOWER FANS MAY BE USED IN THE VICINITY OF THE WORK AREA TO PROVIDE INCREASED AIR DILUTION. THIS PRODUCT MUST NOT BE USED OR STORED NEAR SOURCES OF HEAT, IGNITION SOURCES AND OPEN FLAMES. MUST BE STORED IN A FLAMMABLE MATERIALS CABINET 250 ML BTL	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	METAL PRIMER P592 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		0		0
70-58-0705	PUTTY, FIRE-RESISTANT, HAND-MOLD, USE TO FILL SMALL OPENINGS IN WALLS AND FLOORS, MEET SPECIFICATION UL1479, CAN BE EASILY FORM AND MOLDED, PACKAGED IN STICK FORM OF 10-INCH LENGTH 1-1/2 INCH WIDTH AND 1-1/2 INCH THICKNESS AND TWELVE STICKS PER BOX	RECTORSEAL CORPORATION NYCTA NYCTA	METACAULK FIRE RATED PUTTY 663 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		0		0
70-58-1010	COMPOUND, FILLING, PUTTY, ACRYLIC RESIN ELASTOMER BASED, USED FOR FILLING SMALL HOLES AND SCRATCHES IN PRIMED AUTOMOTIVE, BUS AND RAILCAR SURFACES, GREEN, 14.5 OZ. TUBE. DENSITY SHOULD BE 12.2-13.6 LBS/GAL, SOLID CONTENT 72-77%. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	ACRYL-GREEN SPOT PUTTY 05096 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		0		0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-60-0582	TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE DENSITY AND % SOLIDS. 12 TUBES PER CASE 12 TBES/CSE	ITW CHEMTRONICS, INC TECHSPRAY, L.P. GC ELECTRONICS MICROCARE CORPORATION NYCTA NYCTA	FREEZ-IT #ES1050 FREEZER 1672-10S GC FREEZE MIST #19-8410-10 MICROFREEZE CIRCUIT COOL MCC-F CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	589	255
70-60-1060	CHILLING AGENT, AEROSOL, CONTAINS 100% TETRAFLUOROETHANE, USED FOR CHECKING PROPER OPERATION OF HEATER THERMOSTAT IN RAILCARS., IN 10 OZ. CANS 10-12 CANS PER CASE 10 OZ CAN	S.C. JOHNSON NYCTA NYCTA	DEEP WOODS INSECT REPELLENT V CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	4407	3256
70-60-5007	REPELLENT, INSECT, SPRAY, MUST CONTAIN 25-30% DEET, MUST BE REGISTERED WITH EPA AND ASSIGNED A EPA NUMBER OR LISTED ON EPA APPROVED DEET INSECT REPELLENT. PACKAGED IN 6 OZ. SPRAY CAN IN 6 OZ CANS	HENKEL CORPORATION NYCTA NYCTA	LOCTITE 620 RETAIN COMP #62070 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
70-60-5010	ADHESIVE, RETAINING COMPOUND, SINGLE COMPONENT, ANAEROBIC, HIGH STRENGTH AND VISCOSITY, ROOM TEMPERATURE CURING, USED TO JOIN FITTED CYLINDRICAL PARTS, RETAINING AND MOUNTING SLEEVES, PULLEYS, GEARS, ROTORS AND FANS ON SHAFTS. COLOR: GREEN. MUST HAVE VISCOSITY 750-1750 CPS, SHEAR STRENGTH 350 PSI (MIN), BREAKAWAY TORQUE STRENGTH 240 IN-LB (MIN), GAP FILING ABILITY .015", CURE TIME 10-60 MIN, TO BE BETWEEN 36ML AND 50ML BOTTLE. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS/ CERTIFICATE OF COMPLIANCE FOR EACH BATCH SHIPPED. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY. MINIMUM SHELF LIFE RQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 36/50 ML BTL	ND INDUSTRIES PERMATEX SAF-T-LOK NYCTA	54150 HIGH STRENGTH-SLIP FIT BEARING MOUNT 50 ML 68050 R35 CCSS-001, REV I, 3-9-11, LABEL	40	19

70-60-5012	ADHESIVE, RETAINING COMPOUND, USED ON R142 CARS TO ADHERE THE BEARING ON THE CONDENSER FAN MOTOR SHAFT. URETHANE METHACRYLATE BASED ANAEROBIC, HIGH STRENGTH, LOW VISCOSITY, TOLERANT OF OIL AND OTHER CONTAMINATION. 50 ML BOTTLE. MUST HAVE VISCOSITY 100-150 MPAS (BROOKFIELD); SHEAR STRENGTH 22.5 N/MM2, (MIN); COLOR-GREEN. CERTIFICATE OF ANALYSIS/CERTIFICATE OF COMPLIANCE TO BE PROVIDED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND SHEAR STRENGTH	HENKEL CORPORATION NYCTA NYCTA	LOCTITE 603 RETAIN COMP #21441 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

70-60-5015	ADHESIVE, RETAINING COMPOUND, USED ON R142A CARS FOR SECURING THE BALANCING HARDWARE TO THE ROTOR ON TRACTION MOTORS. FOR BONDING OF CYLINDRICAL FITTING PARTS. 50 ML BOTTLE. URETHANE METHACRYLATE BASED ANAEROBIC ADHESIVE. HIGH STRENGTH, LOW VISCOSITY. VISCOSITY = 450 - 750 MPAS (CP); SHEAR STRENGTH = 3000 PSI (22 N/MM2) MINIMUM; COLOR = GREEN. MEETS REQUIREMENTS OF MILITARY SPECIFICATION MIL-R-46082B. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF	HENKEL CORPORATION NYCTA NYCTA MILITARY	640 RETAINING COMPOUND #64031 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-R-46082B	6	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	COMPLIANCE TO BE PROVIDED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND SHEAR STRENGTH. 50 ML BTL				
70-60-5020	ADHESIVE, BONDING RESIN, USED ON R142A CARS FOR HOLDING THE ENDS OF THE TOP LAYER OF INSULATION ON THE COILS AND CONNECTIONS ON THE WIRED STATOR ON THE TRACTION MOTOR BEFORE THE VPI PROCESS. FIVE GALLON PAIL. LOW TEMPERATURE, THERMOSETTING MODIFIED PHENOLIC CLEAR BONDING RESIN. VISCOSITY=800-1100 CP AT 25 DEGREES C; GEL TIME = 10-25 MINUTES; CURE=ONE HOUR AT 125 DEGREES C; SOLIDS CONTENT=18-22%; SPECIFIC GRAVITY = 0.87-0.90. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF COMPLIANCE TO BE PROVIDED FOR EACH BATCH. CERTIFICATE OF ANALYSIS TO INCLUDE % SOLIDS AND VISCOSITY.	ELANTAS PDG., INC. NYCTA NYCTA	RANVAR B553 BONDING RESIN CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-63-3100	RESIN, FIBREGLASS, WITH LIQUID HARDENER USED FOR METAL AND FIBERGLASS REPAIRS; RESIN PACKAGED IN 1 GALLON CAN AND HARDENER IN 2 OZ. TUBE; MUST MEET ALL REQUIREMENTS UNDER NYCT SPECIFICATION 7112-FACIL-00 REV. A. MINIMUM SHELF LIFE REQUIRED AT A TIME OF RECEIPT IS 9 MONTHS. USE WITH CHEMICAL SPLASH GOGGLES & NITRILE GLOVES. DO NOT USE NEAR HEAT SOURCES, IGNITION SOURCES, OPEN FLAMES INCLUDING SMOKING MATERIALS. STORE IN AN AUTHORIZED FLAMMABLE MATERIAL STORAGE CABINET IN 2 PART KIT	QUEST AUTOMOTIVE PRODUCTS NYCTA NYCTA NYCTA NYCTA	RESIN & HARD*GAL #58020 7112-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.	43	41

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
	SUBMITTED TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND TENSILE SHEAR STRENGTH MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 20 GRM TBE						
70-67-0850	SEALANT, HEAT RESISTANT, NON-SLUMPING SILICONE ELASTOMER, RED, 10.1 FL. OZ. CARTRIDGES, DESIGNED FOR SEALING AND BONDING APPLICATIONS EXPOSED TO TEMPERATURES AS HIGH AS 315 DEGREES CENTIGRADE OR 600 DEGREES FAHRENHEIT, USED TO ADHERE HEATING CABLES TO THRESHOLD PLATES ON RAILCARS; TACK FREE TIME LESS THAN 25 MINUTES; CURE TIME=24 HOURS; TENSILE STRENGTH IS GREATER THAN 220 PSI, DUROMETER HARDNESS IS GREATER THAN 20 SHORE A, ELONGATION IS GREATER THAN=350% (AFTER 72 HOURS @ 25 DEGREES CENTIGRADE AND 50% ROOM HUMIDITY). CERTIFICATE OF ANALYSIS TO INCLUDE TACK FREE TIME, HARDNESS, TENSILE STRENGTH AND ELONGATION TO BE PROVIDED FOR EACH BATCH.	DOW CORNING NYCTA NYCTA FEDERAL	736 HEAT RESISTANT SEALANT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46106A			0	0
70-67-0852	SEALANT, FAST CURE THREAD, FOR THREADED FITTINGS IN PNEUMATIC AND HYDRAULIC SYSTEMS. 50 ML TUBE. METHACRYLATE ESTER BASED. VISCOSITY 15,000-40,000 CP(BROOKFIELD); SHEAR STRENGTH > 246 PSI. CERTIFICATE OF ANALYSIS THAT INCLUDES VISCOSITY AND SHEAR STRENGTH TO BE PROVIDED FOR EACH BATCH. PPE REQUIRED: CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES	HENKEL LOCTITE CORPORATION NYCTA NYCTA	5452 THREAD SEALANT #1265769 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-67-0882	ADHESIVE, SEALANT, PERMANENT THREAD LOCKER, HIGH STRENGTH, FOR LOCKING ALL FASTENERS THAT MUST WITHSTAND HEAVY SHOCK AND VIBRATION, EXTREME CHEMICAL OR ENVIRONMENTAL CONDITIONS, FOR BOLTS RANGE 3/8" TO 1", COLOR-RED, 45-50 MIL BOTTLE. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PREVAIL LOCKING STRENGTH 45-50 MIL BTL	HENKEL CORPORATION PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL	LOCTITE 262 THREADLOCKER 26231 PERMABOND HM-118 T62 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE II GRADE 0			70	41
70-67-0884	ADHESIVE, SEALANT, LOW VISCOSITY THREAD LOCKER, WICKING GRADE, PENETRATES PRE-ASSEMBLED FASTENERS, TORQUE, FOR ADJUSTABLE POTENTIOMETERS, COLOR IS GREEN, IN 9 TO 10 ML. BOTTLES MINIMUM SHELF LIFE REQUIRED AT TIME OF SHIPMENT IS NINE MONTHS. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PREVAIL LOCKING STRENGTH.	HENKEL CORPORATION SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	LOCTITE THREADLOCKER #29021 S90 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE III GRADE R			0	0
70-67-0885	ADHESIVE, INSTANT, SUPERBONDER, HIGH VISCOSITY (400-4000 CPS), FOR BONDING METAL, PLASTIC AND VINYL PARTS, GAP FILLING ABILITY UP TO 0.010". 1.0 FLUID OUNCE NET WEIGHT BOTTLE. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY AND SHEAR STRENGTH 1.0 OZ BTL	HENKEL CORPORATION PERMABOND NYCTA NYCTA FEDERAL SPECIFICATION	LOCTITE INSTANT ADHESIVE #4165 PERMABOND 200-1 FL. OZ CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46050C, TYPE II, CLASS 3			2299	1485

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-0950	COMPOUND, ANTI-SEIZE, SILVER GRADE, HIGH TEMPERATURE, FOR USE ON DRAWBAR COMPONENTS OF R142 AND R142A; TYPICAL COEFFICIENT OF FRICTION AT @ 68F TO BE ABOUT .077; MUST PROVIDE CERTIFICATE OF ANALYSIS WHICH INCLUDES APPEARANCE, BROOKFIELD VISCOSITY OF 121,000-258,000 MPASS AND SPECIFIC GRAVITY OF 1.00-1.30. PACKAGED IN ONE LB. CAN WITH A BRUSH TOP CAP. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 10 MONTHS. IN 1 LB CAN IN 1 LB CAN	HENKEL CORPORATION NYCTA NYCTA	LOCTITE LB8150SV ANTISEIZE 767 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	426	304
70-67-1110	SEALANT, FOR COIL CONNECTIONS, PERMANENTLY SOFT, THUMBGRADE, FOR USE ON SPLIT CAM MODIFICATON FOR GE CONTROLLERS ON RAILCARS, IN ONE LB. PACKAGES, PACKED 50 LBS PER CARTON. MUST MEET REQUIREMENTS OF NYCT SPECIFICATION 7123-FACIL-00. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING CERTIFICATE OF ANALYSIS TO INCLUDE PENETRATION (UNWORKED)	SEALERS, INC. NYCTA NYCTA NYCTA	1003 SEALER 7123-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-67-1202	SEALANT, SEAM SEALANT, SYNTHETIC ELASTOMER, WATER BASED NON-SAG WHITE PASTE; USED TO REPAIR CAR BODY DAMAGE; MUST HAVE FLASH POINT OF 200F MINIMUM; % SOLIDS BY WEIGHT IS 80-87; (ASTM D2834); SAG RESISTANCE=0.5 INCHES MAXIMUM(ASTM D2202); VISCOSITY/CONE PENETRATION=235-245 MM (ASTM D217 @ 150 GM, 5 SEC, 80F); DRY TIME=60 MINUTES (1/8" FILM @ 75F, 50% HUMIDITY); HARDNESS=40 (SHORE A). CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE MUST BE PROVIDED FOR EACH BATCH IN SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY/ PENETRATION, % SOLIDS AND SAG RESISTANCE. PACKAGED IN A 10-OZ(NET WEIGHT) CARTRIDGE.	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	ALL-AROUND AUTOBODY SEALANT#85 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-1320	SEALER, EDGE, ACRYLIC/ALKYD, RESIN BASED, CLEAR, PACKAGED IN 8 OZ. CAN WITH FELT DAUBER APPLICATOR; SOLIDS CONTENT TO BE 43% TO 49%; VISCOSITY TO BE 300 TO 500 CP; FOR USE IN SEALING EDGES OF STICKERS/DECALS ON INTERIOR/ EXTERIOR RAILCAR SURFACES; VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH SHIPPED TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPMENT, CERTIFICATE OF ANALYSIS TO COVER VISCOSITY AND SOLIDS CONTENT, MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. IN 8OZ CAN	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	SCOTCHCAL BRAND EDGE SEALER 39 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	266	47
70-67-1370	RESIN, ACRYLIC, LOCKING AND SEALING COATING FOR THREADED FASTENERS. A SPECIAL BLEND OF ACRYLIC RESINS TO PREVENT FASTENERS FROM LOOSENING. NONOZONE DEPLETING AND ENVIRONMENTALLY FRIENDLY. BOTTLE SIZE: NET 1 OZ. "MUST" ADHERE TO MFG'S INSTRUCTIONS IN USE, HANDLING, & STORAGE. IN 1 OZ BTL	ND INDUSTRIES NYCTA NYCTA	VIBRA-TITE #21330 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	60	50
70-67-1425	SEALANT, GASKET AND THREAD; FOR USE IN AIR CONDITIONING EQUIPMENT; SYNTHETIC REFRIGERATION OIL BASED; MAXIMUM HELIUM LEAK RATE .05 OZ/YEAR; VISCOSITY @ 25 DEGREES C. (#1, 10 RPM) TO BE 1110 TO 1460 CPS; SPECIFIC GRAVITY TO BE .91 TO .915; POUR POINT TO BE MAXIMUM - 10 DEGREES C; CERTIFICATE OF ANALYSIS COVERING VISCOSITY, SPECIFIC GRAVITY AND POUR POINT TO ACCOMPANY EACH BATCH SHIPPED; PACKAGED IN 30-ML BOTTLE; 24 BOTTLES PER BOX; LOT # TO APPEAR ON BOX; NOTE TO USERS/PROCUREMENT, MINIMUM PURCHASE TO BE 24 BOTTLES	REFRIGERATION TECHNOLOGIES NYCTA NYCTA	NYLOG BLUE RT201B CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	39

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-1635	JOINT COMPOUND, FLEXIBLE FILLER FOR EXPANSION JOINTS, TWO-COMPONENT POLYMER CONTAINING EPOXY & URETHANE RESINS. TWO GALLON KIT: 1 GALLON PART A RESIN, 1 GALLON PART B HARDENER. MIX 1 PART A WITH PART B. 100% SOLIDS. COLOR MEDIUM GRAY. SET TO TOUCH 5-9 HOURS MAXIMUM. HARDNESS 50-60 SHORE D. FLEXURAL STRENGTH 2,700-2,800 LBS/IN, TENSILE STRENGTH 3,100-3,200 LBS/IN. VISCOSITY A=300-600 POISE: B=150-450 POISE. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS CONTAINING SET TIME & VISCOSITY. SAFETY COMMENTS: WEAR CHEMICAL SPLASH GOGGLES & NEOPRENE GLOVES	NPI FOR GARON NYCTA NYCTA	GARON JOINT GUARD 163010 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	6	6
70-67-1679	SEALANT, PIPE JOINT, FOR AIR CONDITIONING SYSTEMS; USED TO SEAL THREADED JOINTS, FLANGE JOINTS AND ALL METAL AND PLASTIC PIPING SURFACES; MUST MEET REQUIREMENTS OF NYCT SPEC. 7109-FACIL-00 REV A; PACKAGED IN 1-1/3 OZ. TUBES, 12 TUBES PER CASE. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY & SPECIFIC GRAVITY FOR EACH BATCH MUST BE PROVIDED TO NYCT MANAGER OF INSPECTION TESTING PRIOR TO SHIPMENT 12 TBES/CSE	HIGHSIDE CHEMICAL NYCTA NYCTA NYCTA	"LEAK LOCK" 7109-FACIL-00 REV A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	619	331
70-67-1680	SEALANT, PIPE JOINT, FOR AIR CONDITIONING SYSTEMS; USED TO SEAL THREADED JOINTS, FLANGE JOINTS AND ALL METAL AND PLASTIC PIPING SURFACES; MUST MEET REQUIREMENTS OF NYCT SPEC. 7109-FACIL-00, REV. A; PACKAGED IN 4 OZ BRUSH TOP JAR. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY & SPECIFIC GRAVITY FOR EACH BATCH MUST BE PROVIDED TO NYCT MANAGER OF INSPECTION TESTING PRIOR TO SHIPMENT 4 OZ PER JAR 4 OZ PER JAR	HIGHSIDE CHEMICAL NYCTA NYCTA NYCTA	LEAK LOCK 10004 7109-FACIL-00 REV A CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	262	197

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-1700	SEALANT, INSULATING, EXPANDING POLYURETHANE FOAM, TACK FREE TIME - 5 MINUTES, CUT THRU TIME- 60 MINUTES, USED TO SEAL AND INSULATE AROUND WINDOW AND DOOR FRAMES, PACKAGED IN 12 OZ. AEROSOL CANS: NOTE TO USERS: PRODUCT IS TO BE USED WITH EXPLOSION PROOF FAN AND WITHIN 20' OF FIRE EXTINGUISHER 12 OZ CAN	ICP AMERICA NYCTA NYCTA	HANDI-FOAM WINDOW & DOOR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	393	243
70-67-1702	SEALANT, INSULATING MULTI-PURPOSE, LATE FOAM, EXPANDING. TACK FREE TIME-10 MINUTES, FULL CURE TIME- 24 HOURS, FLEXIBLE AND PAINTABLE WHEN CURED. USED TO SEAL AND INSULATE AROUND WINDOW AND DOOR FRAMES, CRACKS AND GAPS AROUND PIPES, VENTS, OUTLETS. PACKAGED IN 12 OZ. AEROSOL CANS, 12 CANS IN A CASE. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS	DAP INC. NYCTA NYCTA	DAPTEX PLUS FOAM SEALANT 18836 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	22	0
70-67-1725	SEALANT, THREADLOCKER, MEDIUM STRENGTH ADHESIVE WITH INCREASED RELIABILITY TO WITHSTAND HIGH TEMPERATURE, VIBRATION, MINOR SURFACE CONTAMINATION, USED WITH FASTENERS, NUTS, BOLTS, SCREWS 1/4"-3/4", HAND TOOL REMOVABLE, COLOR: BLUE, IN 50 ML BOTTLES. SPECIFIC GRAVITY 1.07 - 1.09 @ 25C, BROOKFIELD-RVT VISCOSITY 1300-3000 MPAS @ 25C, SPINDLE 3.20 RPM. COMPRESSIVE SHEAR STRENGTH GREATER THAN 7.6 NMM2 OR 1100 PSI, VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (WHICH INCLUDES COMPRESSIVE STRENGTH AND VISCOSITY) AND CERTIFICATE OF CONFORMANCE-COMPLIANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF TESTING & INSPECTION PRIOR TO SHIPPING. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTH	NEW FLYER CO. HENKEL CORPORATION NYCTA NYCTA	081034(REF ONLY) LOCTITE 243 THREADLOCKER 13294 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	52	23

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-1802	SEALANT, SILICONE CONSTRUCTION GRADE, CLEAR; USED TO SEAL BUILDING JOINTS TO PREVENT THE PENETRATION OF RAIN, AIR AND NOISE; MUST MEET THE REQUIREMENTS OF TT-S-001543A FEDERAL SPECIFICATION; PACKED IN 10.1 OZ CARTRIDGES. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE TO NYCT MANAGER OF TESTING AND ANALYSIS PRIOR TO SHIPPING MATERIAL; CERTIFICATE OF ANALYSIS TO INCLUDE HARDNESS, TENSILE/ TEAR STRENGTH. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS 10.1 OZ CTGS	MOMENTIVE AMER IND NYCTA NYCTA	SCS 1201 12R CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	84	76
70-67-1812	SEALANT, ADHESIVE, HIGH TEMPERATURE SILICONE (POLYSILOXANE OR DIMETHTHYSILOXANE) BASED. USED FOR MAKING "FORMED-IN-PLACE" GASKETS, FOR MECHANICAL ASSEMBLIES; COLOR RED, PACKAGED IN 80ML TUBES. TACK FREE TIME IS LESS THAN 1 HOUR, CURE TIME IS ABOUT 24 HOURS. CURED ADHESIVE(7 DAYS AMBIENT) SHALL HAVE DUROMETER HARDNESS (SHORE A) 14 MINIMUM, % ELONGATION 275 MINIMUM, TENSILE STRENGTH 116 PSI MINIMUM. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE HARDNESS, % ELONGATION, TENSILE STRENGTH IN 80ML TBES	LOCTITE CORP NORTH AMER. GROUP NYCTA NYCTA	RTVSILICONE SEALANT #59630 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	219	132

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-67-1814	COMPOUND, GASKET, SILICONE, RTV, ONE COMPONENT, TO FORM GASKET SEALS IN MECHANICAL ASSEMBLIES, ULTRA BLUE PASTE, IN 70 ML. TUBE. TACK FREE TIME IS LESS THAN 1 HOUR, CURE TIME IS ABOUT 24 HOURS. EXTRUSION RATE 250 G/MIN MINIMUM, CURED ADHESIVE SHALL HAVE DUROMETER HARDNESS (SHORE A) 26 MIN, ELONGATION 340% MIN, TENSILE STRENGTH MINIMUM 1.6 N/MM2 OR 232 PSI. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING, CERTIFICATE OF ANALYSIS TO INCLUDE TACK FREE TIME (SKIN OVER TIME) AND EXTRUSION RATE. IN 70 ML TBE	HENKEL CORPORATION NYCTA NYCTA	LOCTITE SI587 RTV SILICONE 587 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			94	88
70-67-1838	SEALANT, FIRE BARRIER, ONE-COMPONENT SILICONE ELASTOMER; USED TO SEAL CRACKS OR HOLES AROUND PIPES OR IN SUBWAY FLOORS; PACKAGED IN 10.3 OZ CARTRIDGES; SHALL MEET THE FOLLOWING REQUIREMENTS; SPECIFIC GRAVITY 1.3-1.7; FLOW 0.25 INCH MAXIMUM; HARDNESS(SHORE A) 30-45; ELONGATION AT BREAK, % 150 MINIMUM; PEEL STRENGTH; PPI 15 MINIMUM; MUST PASS UL 2079 STANDARD CRITERIA FOR FIRE RESISTANCE; VENDOR TO SUPPLY CERTIFICATE OF CONFORMANCE & CERTIFICATE OF ANALYSIS TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL; CERTIFICATE OF ANALYSIS TO INCLUDE; HARDNESS, % ELONGATION, TENSILE STRENGTH, PEEL/TEAR STRENGTH "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS". 10.3OZ CTR	MINNESOTA, MINING & MANUFACTUR NYCTA NYCTA	3M FIREBARRIER 2000+ CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S			0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1 -----	USE YTD -----
70-67-1839	PUTTY, FIRESTOPPING, ONE-PART, TWO-STAGE INTUMESCENT, NON-HARDENING COMPOUND. 36 CUBIC INCH BAR PACKAGED IN 0.6 LITER TUBE. USED TO SEAL THROUGH-PENETRATIONS AS WELL AS CONSTRUCTION GAPS AND BLANK OPENINGS TO REDUCE SOUND TRANSMISSION AND INCREASE FIRE RESISTANCE. WHEN EXPOSED TO HIGH HEAT OR FLAME SHALL BE CAPABLE OF EXPANDING A MINIMUM OF FIVE TIMES. RANGE OF CONTINUING EXPANSION SHALL BE FROM 230 DEGREES F TO > 1,000 DEGREES F (110 DEGREES C TO >538 DEGREES C). THE PUTTY SHALL BE SOFT AND PLIABLE WITH AGGRESSIVE ADHESION. IT SHALL BE UL CLASSIFIED AND/OR FM SYSTEMS APPROVED AND TESTED TO THE REQUIREMENTS OF ASTM E814 (UL1479). IN 0.6 LTR TBE	SPECIFIED TECHNOLOGIES INC. NYCTA NYCTA ASTM	SPEC SEAL FIRESTOP PUTTY SSP10 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S E814	10	12
70-67-1840	SEALANT, RTV SILICONE, GRAY, FOR USE IN SEALING FLANGES AND GE GEAR UNITS; TO HAVE EXCELLENT OIL AND CHEMICAL RESISTANCE; SHORE HARDNESS MEASURED VIA ASTM D2240 DUROMETER A TO BE 45 TO 75; BREAKING ELONGATION MEASURED VIA ASTM D412 TO BE 100% OR MORE; TENSILE STRENGTH MEASURED VIA ASTM D412 TO BE 2.4 N/MM2 TO 3.8 N/MM2; TACK FREE TIME CURED @ 25 DEGREE C & 50% +/- 5% RELATIVE HUMIDITY TO BE 30 MINUTES OR LESS; PACKAGED IN 300 ML CARTRIDGES, 10 CARTRIDGES PER CASE; MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT TO BE 9 MONTHS; CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. 10 CART/CSE	HENKEL LOCTITE CORPORATION NYCTA NYCTA	LOCTITE SI 5699 GREY 18581 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	1691	569

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-1842	SEALANT, SILICONE, USED FOR FORMED-IN-PLACE GASKETING, COLOR: BLACK, PACKAGED IN 10.1 FL OZ. CARTRIDGES; MUST MEET ALL REQUIREMENTS SET UP IN NYCT SPECIFICATION 7115-FACIL-00. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE HARDNESS, % ELONGATION, TENSILE STRENGTH 10.1OZ. CART.	MOMENTIVE AMER IND NYCTA NYCTA NYCTA	RTV 1473-CRTRG 7115-FACIL-00 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	279	97
70-67-1880	SEALANT, SYNTHETIC RUBBER BASED, FOR RE-INSTALLATION OF RUBBER GASKETS ON R142 RAILCAR DOORS. REDUCES SOUND AND VAPOR TRANSMISSION. COLOR-BLACK. IN 10.3 FL. OZ. CARTRIDGES. REMAINS FLEXIBLE, RESISTANT TO CRACKS AND BLISTERING. PPE REQUIRED-CHEMICAL SPLASH GOGGLES AND NEOPRENE GLOVES. ADEQUATE VENTILATION IS REQUIRED WHEN THE PRODUCT IS USED. IT MUST NOT BE USED NEAR ANY IGNITION SOURCES. IT MUST BE STORED IN FLAMMABLE MATERIAL CABINET.	MANUS PRODUCTS, INC. NYCTA NYCTA	MANUS-BOND 52-A (BLACK) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-67-1900	SEALANT, COMPOUND, PIPE JOINT SEALANT ON THREADED METAL PIPES (NOT FOR USE ON PLASTIC PIPES), MUST MEET ALL REQUIREMENTS UNDER NYCT SPEC 7093-FACIL-99; PACKAGED IN 8 OZ. BRUSH IN CAP CONTAINERS. 8 OZ CONTAINER	HERCULES CHEMICAL NYCTA NYCTA NYCTA	PRO DOPE #15-420 7093-FACIL-99 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	104	39

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-2110	ADHESIVE, SEALANT, HIGH STRENGTH THREAD LOCKER, FOR LOCKING ALL FASTENERS UP TO 1" DIAMETER WHERE HIGH LOAD OR HIGH VIBRATION IS PRESENT, COLOR: RED, 50 ML BOTTLE; 6 TO 10 BOTTLES PER CARTON. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PREVAIL LOCKING STRENGTH. 50 ML BOTTLE	ND INDUSTRIES HENKEL CORPORATION PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	14050 HIGH STRENGTH THREADLOCK LOCTITE 271 THREADLOCKER 27131 PERMABOND HM 128-50 ML BOTTLE T70 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE I GRADE K	596	361
70-67-2135	SEALANT, GASKET ELIMINATOR, REPLACES PRE-CUT OR FORMED-IN-PLACE GASKETS, ROOM TEMPERATURE CURING, PROVIDES TOUGH RESILIENT SOLVENT AND TEMPERATURE RESISTANT SEAL, COLOR: RED, 10.15 FL. OZ. CARTRIDGE, PACKAGED 10 PER CASE. VISCOSITY IS 3,000,000-4,500,000 MPAS (BROOKFIELD, 0.5 RPM); COMPRESSIVE SHEAR/LOCKING SHEAR STRENGTH IS 725 PSI MINIMUM (24 HR CURE). "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS TEN (10) MONTHS." CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, AND COMPRESSIVE SHEAR/LOCKING SHEAR STRENGTH 10 CARTS/CSE 10.15 OZ CARTRG 10.15 OZ CARTRG	PERMATEX, INC. HENKEL CORPORATION NYCTA NYCTA	ANAEROBICGASKETMAKER 300ML 518 LOCTITE 518 GASKET ELIMINATOR CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	458	210
70-67-2139	ACTIVATOR, PRIMER TO SPEED THE CURE OF ANAEROBIC ADHESIVES AND SEALANTS, ONE COMPONENT NON-CFC SOLVENT BASED SURFACE ACTIVATOR, 4.25 - 4.5 FL. OZ. AEROSOL CAN. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS. 4.25-4.5 OZ CAN	NYCTA HENKEL CORPORATION SAF-T-LOK NYCTA	CCSS-003 REV E 9/11/17 RESTR S LOCTITE SF 7649 PRIMER 21348 PRIMER N AEROSOL CCSS-001, REV I, 3-9-11, LABEL	36	19

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
70-67-2143	ACTIVATOR/PRIMER, USED TO SPEED THE CURE OF ANAEROBIC ADHESIVES AND SEALANTS. ESPECIALLY FOR APPLICATIONS WITH PASSIVE METALS, INERT SURFACES AND WITH LARGE BOND GAPS. SPECIFICALLY USED WITH ADHESIVES USED TO SECURE PIN, GEAR AND SHAFT ASSEMBLY IN DOOR OPERATOR GEAR BOX. ACETONE BASED LIQUID. SUPPLIED IN 1.75 FL. OZ. BOTTLE. 10 BOTTLES PER CASE. NOTE: FLASH POINT REQUIREMENT OF NYCT SPECIFICATION CCSS-003 DOES NOT APPLY. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS.	HENKEL CORPORATION NYCTA NYCTA	LOCTITE SF 7471 PRIMER 19267 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	7	8
70-67-2147	SEALANT, GASKET SEALING, IN 3.5 OZ TUBE WITH NOZZLE. FOR SEALING THE END CAP TO THE HOUSING ON CONDENSER MOTOR FANS ON R142 RAILCARS. NON-SETTING, NON-HARDENING COMPOUND WITH EXCELLENT RESISTANCE TO JOINT VIBRATION, SHOCK, THERMAL EXPANSION. BLUE PASTE; SPECIFIC GRAVITY 1.13 - 1.23; VISCOSITY 240,000-260,000 MPAS. 50 TUBES PER BOX	HYLOMAR LTD/VALCO NYCTA NYCTA	HYLOMAR ADVANCEDFORMULA 710XX3 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	50	0
70-67-2151	ADHESIVE, SEALANT, THREADLOCKER; FOR SCREWS, NUTS, BOLTS LESS THAN 1/4", LOW STRENGTH, HAND TOOL REMOVABLE, COLOR: PURPLE, IN 50 ML BOTTLES. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PREVAIL LOCKING STRENGTH IN 50 ML BTLS	ND INDUSTRIES HENKEL CORPORATION PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	11150 LOW STRENGTH THREADLOCKE LOCTITE 222MS THREADLOCKER 222 PERMABOND LM 113-50ML BOTTLE T22 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE II GRADE M	98	66
70-67-2152	ADHESIVE, SEALANT, THREADLOCKER; FOR SCREWS, NUTS, BOLTS LESS THAN 1/4", LOW STRENGTH, HAND TOOL REMOVABLE, COLOR: PURPLE, IN 10 ML BOTTLES. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PROVAIL	ND INDUSTRIES HENKEL CORPORATION PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	11110 LOW STRENGTH THREADLOCKE LOCTITE 222MS THREADLOCKER 222 PERMABOND LM113-10ML BOTTLE T22 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE II GRADE M	218	194

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	LOCKING STRENGTH. MINIMUM SHELF LIFE REQUIRED IS 9 MONTHS AT TIME OF RECEIPT. IN 10 ML BTLs				
70-67-2153	ADHESIVE, SEALANT, LOW VISCOSITY, SUPER BONDER, GENERAL PURPOSE INSTANT ADHESIVE BONDS METALS, PLASTICS. FILLS GAPS UP TO .004", CAN BE USED TO BOND PRE-ASSEMBLED PARTS WITH GAPS UP TO .006", COLOR IS CLEAR, IN ONE OUNCE BOTTLES. VISCOSITY 20-60 CPS; TENSILE SHEAR STRENGTH MINIMUM OF 800 PSI. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO BE PROVIDED TO THE MANAGER OF TESTING AND ANALYSIS PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE: VISCOSITY AND TENSILE STRENGTH IN 1 OZ BTL	HENKEL CORPORATION PERMABOND NYCTA NYCTA FEDERAL SPECIFICATION	LOCTITE 495 INST ADHESIVE 4955 PERMABOND 105 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-A-46050C TYPE II CLASS 1	61	38
70-67-2170	ADHESIVE, SEALANT, THREADLOCKER, GENERAL PURPOSE, MEDIUM STRENGTH ADHESIVE FOR USE WITH FASTENERS, NUTS, BOLTS, SCREWS 1/4" AND LARGER, HAND TOOL REMOVABLE, COLOR: BLUE, IN 10ML BOTTLES. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 10 MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF TESTING & INSPECTIONS PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PREVAIL LOCKING STRENGTH IN 10 ML BTLs	HENKEL CORPORATION HERNON MFG PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	LOCTITE 242 THREADLOCKER 24221 NUTS N'BOLTS #42310 PERMABOND MM115-10ML BOTTLE T42 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A TYPE II GRADE N	2471	1567

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
70-67-2171	ADHESIVE, SEALANT, THREAD LOCKER, GENERAL PURPOSE MEDIUM STRENGTH ADHESIVE FOR USE WITH FASTENERS, NUTS, BOLTS, SCREWS 1/4" AND LARGER, HAND TOOL REMOVABLE; COLOR: BLUE, IN 50 ML BOTTLES. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY, BREAK AND PROVAIL LOCKING STRENGTH. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. IN 50 ML BTLS	HENKEL CORPORATION HERNON MFG PERMABOND SAF-T-LOK NYCTA NYCTA FEDERAL SPECIFICATION	LOCTITE 242 THREADLOCKER 24231 NUTS N'BOLTS #42330 PERMABOND MM115-50 ML BOTTLE T42 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S MIL-S-46163A, TYPE II, GRADE N	24231	676		425
70-67-2172	SEALANT, PIPE SEALANT WITH TEFLON FOR USE ON METAL PIPE THREADS, FITTINGS AND FLANGES, ESPECIALLY STAINLESS STEEL. ALSO USED ON TRACTION GEAR UNIT ASSEMBLY; NOT FOR USE ON PLASTIC PIPES. WHITE PASTE IN A 50 ML TUBE. PROVIDES IMMEDIATE LOW PRESSURE SEALING AND CURES RAPIDLY TO SECURE AND SEAL FITTINGS TO HIGH PRESSURE. ANAEROBIC COMPOUND THAT CURES WHEN CONFINED IN THE ABSENCE OF AIR AND BETWEEN CLOSE FITTING METAL SURFACES. INSTANT SEALING IS ACHIEVED UP TO 1000 PSI UPON LIMITED HAND TIGHTENING. AFTER CURE THE SEAL CAPABILITY IS UP TO THE BURST RATING OF THE TYPICAL PIPE. WITHSTANDS TEMPERATURES FROM -65F TO 350F. SEALANT IS METHACRYLATE ESTER BASED WITH POLYTETRAFLUOROETHYLENE (TEFLON). VISCOSITY IS 175,000 CPS MINIMUM; SPECIFIC GRAVITY BETWEEN 1.07 AND 1.21; BREAKAWAY TORQUE LOCKING STRENGTH 15 IN-LBS MINIMUM; SPEED OF CURE IS BETWEEN 1 AND 4 HOURS FOR FIXTURE, FULL STRENGTH WITHIN 24 HOURS. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS WHICH INCLUDES VISCOSITY, BREAKAWAY TORQUE LOCKING STRENGTH FOR EACH BATCH IS TO BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING MATERIAL. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE	PERMATEX, INC. HENKEL CORPORATION PERMABOND NYCTA NYCTA	59235 HITEMP THREAD SEALANT 50 LOCTITE 567 TB 50ML EN 2087067 PERMABOND LH-150-50ML TUBE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S		899		571

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	MONTHS				
	IN 50 ML TBE				
70-67-2173	SEALANT, PIPE, WITH TEFLON, FOR USE ON METAL PIPE THREADS, FITTINGS AND FLANGES, ESPECIALLY STAINLESS STEEL, ALSO USED ON TRACTION GEAR UNIT ASSEMBLY. NOT FOR USE ON PLASTIC PIPES, WHITE PASTE IN A 250 ML TUBE. PROVIDES IMMEDIATE LOW PRESSURE SEALING AND CURES RAPIDLY TO SECURE AND SEAL FITTINGS TO HIGH PRESSURE. ANAEROBIC COMPOUND THAT CURES WHEN CONFINED IN THE ABSENCE OF AIR AND BETWEEN CLOSE FITTING METAL SURFACES. INSTANT SEALING IS ACHIEVED UP TO 1000 PSI UPON LIMITED HAND TIGHTENING. AFTER CURE THE SEAL CAPABILITY IS UP TO THE BURST RATING OF THE TYPICAL PIPE WITHSTANDS TEMPERATURES FROM -65 F TO 350 F. SEALANT IS METHACRYLATE ESTER BASED WITH POLYTERAFLUROETHYLENE (TEFLON). VISCOSITY OF 280,000 - 800,000 MPAS; SPECIFIC GRAVITY BETWEEN 1.07 AND 1.21; BREAKAWAY TORQUE LOCKING STRENGTH 15 IN-LBS MINIMUM: SPEED OF CURE IS 1-4 HOURS FOR FIXTURE. FULL STRENGTH WITHIN 24 HOURS. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS WHICH INCLUDES VISCOSITY, BREAKAWAY LOCKING STRENGTH FOR EACH BATCH IS TO BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING MATERIAL. "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS".	HENKEL CORPORATION NYCTA NYCTA	LOCTITE 567 TB 250ML EN 208706 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	108	58
	IN 250 ML TBE				

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-2179	SEALANT, PIPE SEALANT WITH TEFLON, FOR USE ON METAL PIPE THREADS, FITTINGS AND FLANGES; ALSO USED ON GE CONTROLLER #17KC76AE2; NOT FOR USE ON PLASTIC PIPES. WHITE PASTE IN A 50 ML TUBE. PROVIDES IMMEDIATE LOW PRESSURE SEALING AND ALLOWS THE ADJUSTMENT OF FITTINGS SHORTLY AFTER ASSEMBLY (FROM 5 TO 10 HOURS); AFTER CURE THE SEAL CAPABILITY IS UP TO THE BURST RATING OF THE TYPICAL PIPE. SEALANT IS METHACRYLATE ESTER BASED WITH 5% POLYTETRAFLUOROETHYLENE (TEFLON). MINIMUM VISCOSITY 200,000 CPS; SPECIFIC GRAVITY BETWEEN 1.07 AND 1.21; LOCKING STRENGTH=PREVAIL 25 IN-LBS MINIMUM, AFTER 24 HOURS OR BREAKAWAY 50 IN-LBS. MINIMUM AFTER 24 HOURS: SPEED OF CURE IS LESS THAN 4 HOURS FOR FIXTURE. FULL STRENGTH WITHIN 72 HOURS. CERTIFICATE OF CONFORMANCE AND CERTIFICATE OF ANALYSIS WHICH INCLUDES VISCOSITY, PREVAIL OR BREAKAWAY LOCKING STRENGTH FOR EACH BATCH IS TO BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING MATERIAL. "MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS". IN 50 ML TBE	PERMABOND HENKEL CORPORATION PERMABOND NYCTA NYCTA	LH050 LOCTITE PST PIPE SEALANT 59231 PERMABOND LH-050-50ML TUBE CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	2385	1508
70-67-2300	SEALANT, ADHESIVE, ELASTOMERIC PREMIUM GRADE HIGH PERFORMANCE, MOISTURE CURED, 1 COMPONENT, POLYURETHANE BASE NON-SAG SEALANT IN 10.3 FL. OZ. CARTRIDGE. COLOR: BLACK, PACKED 24 CARTRIDGES PER CASE. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 9 MONTHS 24 CART/CSE	SIKAFLEX NYCTA NYCTA	1A BLACK CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	213	266

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-67-5170	SEALANT, PIPE, NON-HARDENING TYPE WITH TEFLON; SMOOTH PASTE; FOR USE ON THREADED METAL PIPES, FITTINGS AND FLANGES; NON-HARDENING FOR EASY DISASSEMBLY; NOT FOR USE ON PLASTIC PIPES; PACKAGED IN ONE PINT BRUSH CANS. VISCOSITY 45,000-80,000 CPS; SPECIFIC GRAVITY BETWEEN 1.06 AND 1.40; MINIMUM SHELF LIFE REQUIRED AT TIME OF SHIPMENTS IS TEN MONTHS. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS & CERTIFICATE OF CONFORMANCE FOR EACH BATCH IN SHIPMENT TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING. CERTIFICATE OF ANALYSIS TO INCLUDE VISCOSITY. IN 1 PINT CANS	HENKEL CORPORATION NYCTA NYCTA	LOCTITE 5113 THREAD SEALANT CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	496	279
70-67-7005	DETECTOR, GAS LEAK SOLUTION, NON-TOXIC, NON-FLAMMABLE, BIODEGRADABLE. FOR USE IN DETECTING GAS LEAK IN TEMPERATURE RANGE 35 TO 177 DEGREES FAHRENHEIT. PACKAGED IN ONE QUART SPRAY BOTTLE. FOR DETECTING LEAKS OF REFRIGERANT IN HVAC SYSTEMS	REFRIGERATION TECHNOLOGIES NYCTA NYCTA	BIG BLU RT100S CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	306	222
70-68-0100	COMPOUND, ELECTRICAL JOINT, CONDUCTIVE, HIGH TEMPERATURE, FOR USE IN ALUMINUM TO ALUMINUM AND/OR ALUMINUM TO COPPER CONNECTIONS, PACKAGED IN 7-OZ SQUEEZE TUBE, 10 TUBES IN A BOX. USED ON LINE SWITCH ASSEMBLY TYPE UMB-925D. A CERTIFICATE OF CONFORMANCE OF COMPOSITION ANALYSIS FOR EACH BATCH TO BE PROVIDED TO NYCT MANAGER OF TESTING & ANALYSIS PRIOR TO SHIPPING 10 TBES/BOX	ALCOA FUJIKURA LTD NYCTA NYCTA	ELECTRIC JOINT COMPOUND NO. 2 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	7	5

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-70-1000	LUBRICANT, SLIDING COMPOUND WITH SILICONE; MULTI-PURPOSE; USED FOR INSTALLING WINDOW GLASS; MINIMUM MELTING POINT 50 DEGREES C, SPECIFIC GRAVITY 0.8 TO 1.2; VISCOSITY @ 100 DEGREES C 4-25 CST; WATER CONTENT <0.1%; PACKAGED IN 1 GALLON CAN IN 1 GAL CAN	SLIPIT INDUSTRIES INC NYCTA NYCTA	SLIPIT SLIDING COMPOUND CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	30	26
70-71-1200	SOAP, MILLED TOILET CAKE, 3-OZ., MUST MEET THE PROPERTIES OF A MILLED TOILET SOAP GIVEN IN NYC SPECIFICATION 5-S-25:85, TABLES I + II, TO BE PACKAGED 200 UNWRAPPED CAKES PER CASE. EACH CASE TO HAVE MANUFACTURER'S NAME AND PART NUMBER + P.O. NUMBER PRINTED ON IT 200 CAKES/CSE	ORIGINAL BRADFORD SOAP WORKS CORCRAFT/DEPT. OF CORRECT.SERV NYC SPEC NYCTA NYCTA	LISA 3OZ HARD MILLED SOAP MILLED TOILET BAR SOAP UO15579 5-S-25:85 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	38557	22151
70-71-1525	SOAP, LEAK DETECTOR, FOR DETECTING LEAKS IN PNEUMATIC PARTS. MUST PROVIDE VISIBLE BUBBLING ACTION WHEN DILUTED AT 5:1 WITH WATER AND APPLIED TO LEAKING PNEUMATIC PARTS RUN THROUGH WITH 80 PSI AIR AND RAILCAR AIR COMPRESSORS RUN THROUGH WITH 145 PSI AIR. PH TO BE BETWEEN 7 AND 9; MINIMUM 16% ACTIVE INGREDIENTS. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE/ COMPLIANCE FOR EACH BATCH TO ACCOMPANY EACH SHIPMENT. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, PH, % ACTIVE INGREDIENT CONTENT. PACKAGED IN 55 GALLON DRUMS. IN 55 GAL DRMS	NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA	TA900 LIQUID HAND SOAP CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	715	550

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-71-1530	CLEANER, HEAVY DUTY ALKALINE. PRODUCT MUST BE NON-STREAKING, SELF RINSING, SOLUBLE IN COLD WATER, LOW FOAM, NON-TOXIC & NON-FLAMMABLE, TO BE PACKED IN 5 GAL. CONTAINERS WITH INSTRUCTIONS FOR USE AND CAUTION INSTRUCTIONS. CONTAINERS MUST BEAR LEGEND "NYCTA NOT FOR RESALE". PRODUCT MUST STATE LABEL U.S.D.A. APPROVED WITH REGISTRATION NUMBERS. IN 5 GAL CTR	NATIONWIDE CHEMICAL CO., INC. NYCTA NYCTA NYCTA	"BLOCK BUSTER" 110 (R-3) CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.	10	45
70-72-1201	CLEANER, DEGREASER, FOR REMOVAL OF GREASE, RUBBER RESIDUES, WAX, ADHESIVE. PACKAGED IN 12-16 OZ NET. WEIGHT AEROSOL CAN. CONTAINS D-LIMONENE, TECHNICAL GRADE, ALIPHATIC HYDROCARBONS, CARBON DIOXIDE PROPELLANT, FLASH POINT MUST BE ABOVE 140 DEGREES FAHRENHEIT. MUST MEET NYSDEC VOC REGULATIONS FOR AEROSOL GENERAL PURPOSE DEGREASERS WITH A MAXIMUM ALLOWABLE VOC CONTENT OF 50% BY WEIGHT. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, SIZE OF BATCH, DATE OF MANUFACTURE, & FLASHPOINT. CERTIFICATE OF CONFORMANCE/COMPLIANCE TO INCLUDE VOC CONTENT. NON-EMPTY CONTAINERS OF THIS MATERIAL OR RAGS/WIPERS USED WITH THIS MATERIAL MUST NOT NEED TO BE DISPOSED OF AS HAZARDOUS WASTE. PPE REQUIRED: CHEMICAL SPLASH GOGGLES, NEOPRENE/NITRILE GLOVES. 12-16 OZ CAN	CRC INDUSTRIES, INC. ITW CHEMTRONICS, INC NYCTA NYCTA	CITRUS DEGREASER #14170 MAX-KLEEN CITRUS HF ES2291 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	42747	21989

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-72-1202	CLEANER AND DEGREASER, USED ON R142 CARS FOR CLEANING/DEGREASING THE CONDENSER FAN MOTOR SHAFT PRIOR TO APPLYING ADHESIVE TO ADHERE BEARING. HYDROCARBON BLEND. MINIMUM FLASH POINT 188 DEGREES F., SPECIFIC GRAVITY = 0.76-0.81, PACKAGED IN 15 OZ. AEROSOL CAN. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS (C OF A) AND CERTIFICATE OF CONFORMANCE/COMPLIANCE (C OF C) FOR EACH BATCH TO NYCT MANAGER OF INSPECTIONS & TESTING PRIOR TO SHIPPING MATERIAL. CERTIFICATE OF ANALYSIS TO INCLUDE BATCH #, DATE OF MANUFACTURE, SHELF LIFE AND SPECIFIC GRAVITY. 12 CANS PER BOX. *** MINIMUM SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS ***	HENKEL CORPORATION NYCTA NYCTA	LOCKTITE ODC-FREE CLNR/DEGREAS CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-72-1711	DESICCANT, FOR KNORR AIR BRAKE DUAL CHAMBER AIR DRYER UNIT TYPE LTZ 012-H, MOLECULAR SIEVE, SODIUM ALUMINOSILICATE ADSORBENT, 8 X 12 BEADS. APPARENT DENSITY 50 LBS/FT3 MINIMUM, CRUSH STRENGTH 12 LBS MINIMUM, WATER CAPACITY @ 25 DEGREES C 19.5% WEIGHT MINIMUM, BEAD SIZE DISTRIBUTION 100% WEIGHT MINIMUM THROUGH 6 MESH SCREEN. PACKAGED IN NON-POROUS BAG WEIGHTING 5 POUNDS. BAG IS PACKED IN CARBOARD BOX WITH MATERIAL SAFETY DATA SHEET. DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. DESICCANT MUST BE UOP "MOLSIV ADSORBENTS AB 8 X 12 #F8928002". REPLACEMENT FOR COMMODITY #18-44-9818 (STU15105). DISTRIBUTORS NAME TO APPEAR ON CARBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO#, MFG. DATE, BATCH #, BEST IF USED BY DATE. VENDOR TO SUPPLY A CERTIFICATE OF COMPLIANCE/CONFORMANCE WITH EACH SHIPMENT CERTIFYING THAT THE MATERIAL BEING SUPPLIED MEETS ALL THE REQUIREMENTS OF THE PURCHASE ORDER/ ORDERING DESCRIPTION/SPECIFICATION IN 5 LB BAG IN 5 LB BAG	KNORR BRAKE CORPORATION NYCTA NYCTA	810532 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-72-1713	DESICCANT KIT, FOR KNORR AIR BRAKE DUAL CHAMBER AIR DRYER UNIT TYPE LTZ 012-H, KIT CONTAINS TWO FIVE POUND BAGS OF MOLECULAR SIEVE 8 X 12 BEAD DESICCANT, FOUR O-RINGS AND INSTRUCTION SHEET, DESICCANT MUST BE UOP "MOLSIV ABSORBENTS AB 8 X 12 #F8928002". DESICCANT IS PACKAGED IN NON-POROUS BAGS. DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. KIT SUPPLIED IN A CARDBOARD BOX. MATERIAL SAFETY DATA SHEET MUST BE PROVIDED IN EACH BOX. DISTRIBUTORS NAME TO APPEAR ON CARDBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE. VENDOR TO SUPPLY A CERTIFICATE OF COMPLIANCE/CONFORMANCE WITH EACH SHIPMENT CERTIFYING THAT THE MATERIAL BEING SUPPLIED MEETS ALL THE REQUIREMENTS OF THE PURCHASE ORDER/ORDERING DESCRIPTION/SPECIFICATION. IN 2 5 LB BAGS	KNORR BRAKE CORPORATION NYCTA	810533 CCSS-001, REV I, 3-9-11, LABEL	0	0
70-72-1715	DESICCANT, FOR KNORR AIR BRAKE AIR DRYER UNIT VV-120. MOLECULAR SIEVE, SODIUM ALUMOSILICATE ADSORBENTS, 8 X 12 BEADS. APPARENT DENSITY 50 LBS/FT3 MINIMUM, CRUSH STRENGTH 12 LBS MINIMUM, WATER CAPACITY @ 25 DEGREES C 19.5% WEIGHT MINIMUM, BEAD SIZE DISTRIBUTION 100% WEIGHT MINIMUM THROUGH 6 MESH SCREEN. PACKAGED IN NON-POROUS BAG WEIGHTING 9.7 POUNDS. BAG IS PACKED IN CARDBOARD BOX WITH MATERIAL SAFETY DATA SHEET. DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. DESICCANT MUST BE UOP "MOLSIV ADSORBENTS AB 8 X 12 #F8928002". DISTRIBUTORS NAME TO APPEAR ON CARDBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE. VENDOR TO SUPPLY A CERTIFICATE OF COMPLIANCE/CONFORMANCE WITH EACH SHIPMENT CERTIFYING THAT THE MATERIAL BEING SUPPLIED MEETS ALL THE	KNORR BRAKE CORPORATION NYCTA NYCTA NYCTA	810532/9.7 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV D 12/2/15 RESTR S CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-72-1716	<p>REQUIREMENTS OF THE PURCHASE ORDER/ ORDERING DESCRIPTION/SPECIFICATION.</p> <p>DESICCANT KIT, FOR KNORR AIR BRAKE DRYER UNIT VV-120. KIT CONTAINS TWO 9.7 POUND BAGS OF MOLECULAR SIEVE 8 X 12 BEAD DESICCANT, FOUR O-RINGS AND INSTRUCTION SHEET. DESICCANT MUST BE UOP "MOLSIV ADSORBENTS SABD 1.7-2.4 MM. DESICCANT IS PACKAGED IN NON-POROUS BAGS, DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. KIT SUPPLIED IN A CARDBOARD BOX. MATERIAL SAFETY DATA SHEET MUST BE PROVIDED IN EACH BOX. REPLACEMENT FOR COMMODITY #18-62-9956(#806544/151). DISTRIBUTOR'S NAME TO APPEAR ON CARDBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS NINE MONTHS. VENDOR TO SUPPLY A CERTIFICATE OF COMPLIANCE/ CONFORMANCE WITH EACH SHIPMENT CERTIFYING THAT THE MATERIAL BEING SUPPLIED MEETS ALL THE REQUIREMENTS OF THE PURCHASE ORDER/ORDERING DESCRIPTION/SPECIFICATION. TWO 9.7 LB BAGS</p> <p>TWO 9.7 LB BAGS</p>	<p>KNORR BRAKE CORPORATION NYCTA NYCTA</p>	<p>806544/151 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S</p>	36	5
70-72-1717	<p>DESICCANT, ABSORBENT, ACTIVATED ALUMINA(BASF-"F-200"). FOR GRAHAM WHITE AIR DRYER ASSEMBLY UNIT #995-200 USED IN RAILCAR AIR BRAKE COMPRESSOR; 1/8" BEAD DIAMETER, 3 POUNDS IN CLUTCH BAG. SEALED IN PLASTIC OR PLASTIC BAG ONLY. REPLACEMENT FOR COMMODITY #18-32-2025 (5995-038). DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. MATERIAL SAFETY DATA MUST BE PROVIDED IN EACH BOX. DISTRIBUTORS NAME TO APPEAR ON CARDBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE. BAG MUST BE LABELED WITH MANUFACTURER'S NAME, COMMODITY #, PO #,</p>	<p>GRAHAM WHITE NYCTA NYCTA</p>	<p>5995-038 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S</p>	754	245

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-72-1718	DESICCANT KIT, FOR GRAHAM WHITE AIR DRYER ASSEMBLY UNIT #995-200 USED IN RAILCAR AIR BRAKE COMPRESSORS. KIT CONTAINS A THREE POUND BAG OF ACTIVATED ALUMINA BEAD(1/8") DESICCANT, ONE 3-3/4" I.D. O-RING, TWO 11/16" O-RINGS. DESICCANT MUST BE BASF "F-200" ADSORBENT, DESICCANT IS PACKED IN CLUTCH BAG, SEALED IN PLASTIC OR PLASTIC BAG ONLY. DESICCANT MUST NOT CONTAIN QUARTZ OR SILICA. MATERIAL SAFETY DATA SHEET MUST BE PROVIDED IN EACH BOX, DISTRIBUTORS NAME TO APPEAR ON CARDBOARD BOX, ALONG WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE. BAG MUST BE LABELED WITH MANUFACTURER'S NAME, COMMODITY #, PO #, MFG. DATE, BATCH #, BEST IF USED BY DATE	GRAHAM WHITE NYCTA NYCTA	RM995-1 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
70-77-1195	TESTING COMPOUND, FLUORESCENT MAGNETIC PARTICLE PREPARED BATH; REFINED PETROLEUM DISTILLATE BASED FLUID; FLASH POINT TO BE OVER 200 DEGREES F; MAXIMUM VISCOSITY TO BE 3 CST @ 100 DEGREES F AND 5 CST @ 65 DEGREES F; FLUORESCENCE SHALL BE IN ACCORDANCE WITH SAE AMS 2641 A SECTION 3.2.3 AS MEASURED BY METHOD SECTIONS 3.2.3.1 + 3.2.3.2 OF THAT DOCUMENT; MAXIMUM PARTICLE MATTER TO BE 1.0 MG/LITER PER ASTM D2276 MAXIMUM TOTAL ACID # TO BE 0.15 MG KOH/LITER PER ASTM D3242; COLOR SHALL NOT BE DARKER THAN #2 ASTM COLOR PER ASTM D1500; SHALL BE FREE OF FOREIGN MATERIAL AND OTHER CONTAMINANTS; PACKAGED IN 5-GALLON CONTAINERS IN 5 GAL CTRS	MAGNAFLUX NYCTA NYCTA	14AM MAGNAGLO PREPARED BATH CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	300	175

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
70-77-1252	KIT, TEST, ACID, IS USED ON ALL REFRIGERATION OILS, TO DETERMINE THE LEVEL OF ACID WITHIN REFRIGERATION UNIT, BIODEGRADABLE, NON-FLAMMABLE, EACH ACID TEST KIT CONSISTS OF A CONTAINER WITH 4 GLASS VIALS TO PERFORM FOUR SEPARATE TESTS. 12 CONTAINERS/KITS PER CASE 12 KIT PER CSE	COMSTAR INTERNATIONAL INC. NYCTA NYCTA	90-311 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	39	9
71-09-1030	PAINT, LATEX, FLAT, BLACK, EXTERIOR, ACRYLIC EMULSION, IN 5 GAL. CANS. VISCOSITY 75 KU MINIMUM; 60 DEGREE SPECULAR GLOSS IS LESS THAN 10 DEGREES; DRY TO TOUCH TIME IS 1 HOUR MAXIMUM, VOC = 340 G/L (2.84 LB/GAL)MAXIUM. THIS PAINT IS USED BOTH AS AN INDUSTRIAL MAINTENANCE COATING (NYDEC REGULATION 6NYCRR PART 205) AND AS A SURFACE COATING FOR MISCELLANEOUS METAL PARTS AND PRODUCTS (6NYCRR PART 228). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE". VENDOR MUST SUBMIT DRAWDOWN SAMPLE FOR COLOR APPROVAL IN 5 GAL CANS	MERCURY PAINT CO. NYCTA NYCTA NYCTA	NYCTA TT-P-19B BLACK CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-09-1050	PAINT, ALKYD EXTERIOR ENAMEL, BLACK GLOSS IN ONE GALLON CAN. USED TO PAINT TRUCK FRAMES AND MOTORS ON SUBWAY CARS AND LOCOMOTIVE ENGINES AND ALSO SHOP DOORS AND TRIM. COLOR: NYCT FEDERAL GLOSS BLACK. MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 78 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH DRY TIME IS 4 HOURS MAX; DRY HARD	MERCURY PAINT CORP/AMSTERDAM M NYCTA NYCTA NYCTA	INDUSTL MAINT M12 BLACK CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	217	93

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. THIS PAINT IS USED BOTH AS AN INDUSTRIAL MAINTENANCE COATING (NYDEC REGULATION 6NYCRR PART 205) AND AS A SURFACE COATING FOR MISCELLANEOUS METAL PARTS AND PRODUCTS (6NYCRR PART 228). IT MUST COMPLY WITH THE MORE RESTRICTIVE VOC LIMIT FOR 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE". VENDOR MUST SUBMIT DRAWDOWN SAMPLE FOR COLOR APPROVAL IN 1 GAL CAN				
71-09-1100	PAINT, LATEX, ENAMEL, BLACK GLOSS, EXTERIOR/INTERIOR, IN ONE GALLON CAN. USED TO PAINT MOTOR FRAMES AND SHELLS. APPLIED BY SPRAY, BRUSH AND DIPPING. COLOR: NYCT LATEX BLACK. MUST MEET COMMERCIAL ITEM DESCRIPTION A-A-2246 AND FEDERAL SPECIFICATION TT-P-29K EXCEPT THAT 60 DEGREE SPECULAR GLOSS MUST BE 70 MINIMUM, VISCOSITY MUST BE 75 KU MINIMUM, SET TO TOUCH TIME MUST BE 6 HOURS MAXIMUM, DRY HARD TIME 16 HOURS MAXIMUM, DRY TO RECOAT TIME MUST BE 24 HOURS MAXIMUM. THIS PAINT IS MARKETED AS AN INDUSTRIAL MAINTENANCE COATING (NYSDEC REGULATION 6NYCRR PART 205) AND IS USED AS A SURFACE COATING FOR MISCELLANEOUS METAL PARTS AND PRODUCTS (6NYCRR PART 228). IT MUST COMPLY WITH THE MORE RESTRICTIVE VOC LIMIT FOR 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LBS/BAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR	MERCURY PAINT CO. NYCTA NYCTA NYCTA	LATENBLCK CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	946	416

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-09-1456	PROFESSIONAL USE ONLY" (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE". VENDOR MUST SUBMIT DRAWDOWN SAMPLE FOR COLOR APPROVAL IN 1 GAL CAN PAINT, LATEX, TAN, GLOSS INTERIOR/ EXTERIOR, IN ONE GALLON CANS. USED ON INTERIOR AND EXTERIOR SOP AND CLEANING BOOTH WALLS. TRISTIMULUS VALUES: L*73.06M A*7.98, B*17.29; DELTA E-2.00 MAX); MUST MEET REQUIREMENTS OF COMMERCIAL ITEM DESCRIPTION A-A-2246 EXCEPT THAT VISCOSITY MUST BE 75 KU MINIMUM, SET TO TOUCH TIME MUST BE 2 HOURS MAXIMUM, DRY HARD TIME 16 HOURS MAXIMUM, DRY TO RECOAT TIME MUST BE 24 HOURS MAXIMUM. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".	MERCURY PAINT CO. FEDERAL STD. NYCTA NYCTA NYCTA	LATEX EN LIGHT FAWN TAN AA-2246 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-09-1605	PAINT, ENAMEL, BLUE, GLOSS, AIR DRY, IN 5 GALLON CAN. USED TO PAINT SHOP WALLS AND LINES ON SHOP FLOORS TO INDICATE HARD HAT AREAS. COLOR: NYCT PENNANT BLUE (TRISTIMULUS VALUES: L* 49.23, A*-25.88, B*-19.65; DELTA E=2.00) MUST MEET REQUIREMENTS OF FEDERAL SPEC TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH IS 6 HOURS; DRY HARD TIME IS 16 HOURS. DRY TO RECOAT TIME IS 24 HOURS MAX. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205: INDUSTRIAL MAINTENANCE	MERCURY PAINT CO. NYCTA NYCTA NYCTA	IMC M12 PENNANT BLUE 71091605 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	60	25

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", (4)"NOT INTENDED FOR RESIDENTIAL USE". IN 5 GAL CAN				
71-09-1690	PAINT, ALKYD, ENAMEL, CHOCOLATE BROWN, GLOSS, IN ONE GALLON CAN. USED TO PAINT WALLS AND TRIMS. COLOR: NYCT GLOSS CHOCOBROWN ALKYD TRISTIMULUS VALUES: L* 36.03, A*5.79, B*12.44; DELTA E=1.20; REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH DRY TIME IS 2-4 HOURS. DRY HARD TIME 16 HOURS AND DRY TO RECOAT TIME 24 HOURS MAXIMUM. MUST COMPLY WITH NYSDEC REGULATION 6NYDEC PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE".	MERCURY PAINT CO. NYCTA	IND MAINT CHOCOBROWN#20099 CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-09-2310	PAINT, ALKYD, ENAMEL, BATTLESHIP GRAY FLOOR AND DECK, GLOSS, IN FIVE GALLON CAN. USED TO PAINT SHOP FLOORS. COLOR: NYCT BATTLESHIP GRAY (TRISTIMULUS VALUES: L* 48.03, A* -3.41, B* -0.61; DELTA E= 1.30). (MERCURY PAINT TRISTIMULUS VALUES: L*48.49, A*-3.25, B*-0.23, DELTA E=2.0 MAX.) SPECULAR GLOSS MUST BE 70 MINIMUM. MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-487 WITH THE EXCEPTION OF DRY TIME. SET TO TOUCH TIME IS 6 HOURS; DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE". IN 5 GAL CAN	MERCURY PAINT CO. NYCTA NYCTA NYCTA NYCTA FEDERAL SPECIFICATION	INDUSTL MAINT TTE487#16187 GRA CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC. TT-E-487	715	60
71-09-8020	PAINT, NYCT, SILVER WHITE, LATEX EXTERIOR GLOSSE, IN FIVE GALLON CAN. THE PAINT COLOR PROVIDED MUST CONFORM TO THE FOLLOWING CIELAB VALUES NYCT SILVER WHITE LATEX USING SPECIFIED(45/0 OR 0/45). STD ILLUMINANT=D65. STD OBSERVER=10 DEGREES. MERCURY L*86.01, A*=-.068, B*=7.58 AND THE DELTA E(COLOR DIFFERENCE) BASED ON THESE CIELAB VALUES AS THE REFERENCE STANDARD MERCURY DELTA E MUST NOT BE GREATER THAN 2.00 MAX. KEY CHARACTERISTICS: VISCOSITY 75 KU MIN. MERCURY DENSITY 10.00 LBS/GAL MIN. SECULAR GLOSS, 60 DEGREES MIN. TOTAL SOLIDS BY WEIGHT, 50% MINIMUM CONTRAST RATIO 0.98% MINIMUM. MERCURY DRYING TIMES: MAXIMUM 2 HR DRY TO TOUCH, DRY HARD TIME 16 HRS MAXIMUM, DRY TO HANDLE 24 HRS MAXIMUM . LEAD CONTENT 0.06% MAXIMUM BY TOTAL WEIGHT. FLASH POINT 100 DEGREES F MINIMUM. IN SERVICE TEMPERATURE,	MERCURY PAINT CO. NYCTA NYCTA NYCTA	LATEX GLOSS SLIVER WHITE #2530 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	325	150

USER-ID : RJR
PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 376
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	REQUIREMENTS -20 DEGREES F TO 180 DEGREES F. THIS PAINT MUST COMPLY WITH THE REQUIREMENTS OF FEDERAL SPECIFICATION TT-E-489J AND WITH NYSDEC REGULATION 6NYCCPART, 205 ARCHITECTURAL AND INDUSTRIAL COATING WITH MAXIMUM VOC OF (340 G/L) THE CONTAINER MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY" (2)"FOR PROFESSIONAL USE ONLY" (3)"NOT FOR RESIDENTIAL USES" OR (4)"NOT INTENDED FOR RESIDENTIAL USE". IN 5 GAL CAN				
71-09-8033	PAINT, ALKYD, ENAMEL, ANTIQUE SATIN, GLOSS, IN ONE GALLON CAN. USED TO PAINT OFFICE AND SHOP WALLS. COLOR: NYCT ANTIQUE SATIN (TRISTIMULUS VALUES: L*88.08, A*2.18, B*19.12; DELTA E=2.00 MAX; MERCURY TRISTIMULUS VALUES: L*88.83, A*2.28, B*17.41 DELTA E=2.00 MAX). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH DRY TIME IS 2-4 HOURS. DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", OR (4)"NOT INTENDED FOR RESIDENTIAL USE"	MERCURY PAINT CO. NYCTA	TT-E-489J ANTIQUE SATIN #2486 CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD	
71-09-8035	PAINT, ALKYD, ENAMEL, SNOW MIST, GLOSS, IN ONE GALLON CAN. USED TO PAINT OFFICE AND SHOP WALLS. COLOR: NYCT SNOW MIST (TRISTIMULUS VALUES:L*92.67, A*-2.68, B*5.54; DELTA E=2.00 MAX; MERCURY TRISTIMULUS VALUES: L*93.41, A*-1.65, B*5.59 DELTA E=2.00 MAX). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J. EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH DRY TIME IS 2-4 HOURS; DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".	MERCURY PAINT CO. NYCTA NYCTA FED. SPEC.	IMC M12 SNOW MIST/71-09-8035 CCSS-002 9/21 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S TT-E-489 REV. J			166		109
71-09-8200	PAINT, ALKYD, ENAMEL, MOUNTAIN MARIGOLD, SEMI-GLOSS. IN FIVE GALLON CAN. USED TO PAINT LINES ON SHOP FLOORS AND WALLS. COLOR: NYCT MOUNTAIN MARIGOLD(TRISTIMULUS VALUES; L*70.06, A*23.65, B*63.53; DELTA E=2.00 MAXIMUM). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 60 MINIMUM. SET TO TOUCH TIME IS TO BE 6 HOURS; DRY HARD TIME IS TO BE 16 HOURS; DRY TO RECOAT TIME IS TO BE 24 HOURS MAX; MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205	MERCURY PAINT CO. NYCTA NYCTA NYCTA ASTM	INDUSTLMAINT M12 MOUNTNMARIGOL CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S D 562			65		60

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE" OR (4) "NOT INTENDED FOR RESIDENTIAL USE" IN 5 GAL CAN IN 5 GAL CAN				
71-10-1180	PAINT, SPRAY, COLOR DULL ALUMINUM, INTERIOR/EXTERIOR, USED TO TOUCH UP WOOD, METAL, NET WEIGHT 12 OZ (11 OZ) 6 TO A CASE 6 11OZ CANS/CSE	KRYLON PRODUCTS GROUP NYCTA NYCTA NYCTA	METALLICS DULL ALUMINUM 1403 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	3	12
71-10-1285	PAINT, ALKYD ENAMEL, GLOSS, INTERIOR/ EXTERIOR. IN 5-GALLON CAN. USED TO PAINT INTERIOR/EXTERIOR WALLS. COLOR: NYCT MAYFAIR TAN(TRISTIMULUS VALUES: L*61.10, A*10.41, B*18.43, DE 1.40). MERCURY TRISTIMULUS VALUES: L* 61.51, A* 9.13, B*16.94 DELTA E=2.00 MAX). CERTIFY AND SUBMIT IN WRITING THE FOLLOWING INFORMATION IN ACCORDANCE WITH THE CURRENT ANSI STANDARD Z34.2, SELF CERTIFICATION BY PRODUCER OR SUPPLIER: PROOF OF VOLATILE ORGANIC CONTENT COMPLIANCE IN ACCORDANCE WITH THE CURRENT NYS ENVIRONMENTAL CONSERVATION LAW OF THE NYS OFFICIAL COMPILATION OF CODES, RULES AND REGULATIONS, TITLE 6E, PART 205, ARCHITECTURAL SURFACE COATINGS. PRODUCT LEAD (PB) CONTENT 0.06% MAXIMUM BY TOTAL WEIGHT. PRODUCT FLASH POINT 100 DEGREES F. MINIMUM BY PENSKEY MARTENS CLOSED TESTER. ADDITIONAL SPECIFICATIONS: PERFORMANCE REQUIREMENT TO FEDERAL SPECIFICATIONS TT-E 489G AND TT-E 506K. IN SERVICE TEMPERATURE LIMITATIONS -20 DEGREES F TO 180 DEGREES F. 38% TO 45% ALKYD RESIN SOLIDS NON-VOLATILE VEHICLE. 26%	MERCURY NYCTA NYCTA ASTM FEDERAL	IMC M12 MAYFAIR TAN/71-10-1285 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S D 476 TT-E 489J	50	75

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-10-1327	MINIMUM PIGMENT. 59% MINIMUM ASTM D 476 TYPE IV TITANIUM DIOXIDE. 98% MINIMUM CONTRAST RATIO AT 3 MIL DRY FILM THICKNESS, SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75-95 KREB UNITS. SET TO TOUCH DRY TIME IS 2-4 HOURS. DRY HARD TIME IS 16 HOURS; DRY TO RECOAT IN 5 GAL CAN				
71-10-1327	PAINT, ACRYLIC LATEX, ALUMINUM, HIGH GLOSS, FOR USE ON R68 RAILCAR BONNETS, IN ONE GALLON CONTAINERS, SELF PRIMING, VISCOSITY; 70-90 KU; MINIMUM 40 WEIGHT PERCENT SOLIDS; GLOSS 60 DEGREE MINIMUM; DRY TO TOUCH 3 HOURS MAX; DRY TO RECOAT 24 HOURS MAX. COMPLIES WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). CONTAINERS MUST BE LABELED AS "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".	MERCURY PAINT CO. NYCTA NYCTA NYCTA	SERIES 2150 DTM R68 BONNET GRE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	28	0
71-10-1470	PAINT, ENAMEL, ALKYD, FLAT BLACK, SPRAY CAN, 12 OZ. NET WEIGHT), 6 CANS PER CASE. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-002(GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE.] STORE IN FLAMMABLE MATERIAL STORAGE CABINET, DO NOT USE NEAR IGNITION SOURCES. VENTILATION IS REQUIRED WHEN USING THIS PRODUCT. WEAR CHEMICAL SPLASH GOGGLES AND NITRILE OR NEOPRENE GLOVES.	KRYLON PRODUCTS GROUP NYCTA NYCTA NYCTA NYCTA	COLORMAXX FLAT BLACK 5546 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.	1679	1254
	6 12 OZ CANS/CS				

USER-ID : RJR
PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 380
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-10-1475	PAINT, ENAMEL, ALKYD, GLOSS, BLACK, SPRAY CAN 12 OZ. NET WEIGHT, 6 CANS PER CASE. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-002(GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE.]STORE IN FLAMMABLE MATERIAL STORAGE CABINET. DO NOT USE NEAR IGNITION SOURCES. VENTILATON IS REQUIRED WHEN USING THIS PRODUCT. WEAR CHEMICAL SPLASH GOGGLES AND NITRILE OR NEOPRENE GLOVES. 6 12 OZ. CANS/CSE 6 11OZ CANS/CSE	KRYLON PRODUCTS GROUP NYCTA NYCTA NYCTA NYCTA	KRYLON COLORMAXX GLOSSBLACK 55 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.	5058	1971
71-10-1530	PAINT, ENAMEL, GLOSS YELLOW, 12 OUNCE NET WEIGHT SPRAY CAN. COLOR: OSHA SAFETY YELLOW. MEETS COMMERCIAL ITEM DESCRIPTION A-A-1585 WITH EXCEPTIONS TO SOLID CONTENTS AND SPECULAR GLOSS. THE SOLID CONTENTS SHOULD BE MIN 45-50G AND THE SPECULAR GLOSS 80-85 DEGREES. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-02(GENERAL REQUIREMENTS FOR PAINTS)IS NOT APPLICABLE.] STORE IN FLAMMABLE MATERIAL STORAGE CABINET. DO NOT USE NEAR IGNITION SOURCES, VENTILATION IS REQUIRED WHEN USING THIS PRODUCT. WEAR CHEMICAL SPLASH GOGGLES AND NITRILE OR NEOPRENE GLOVES. 6 12 OZ. CANS/CSE IN 16 OZ CAN	KRYLON FEDERAL SPECIFICATION NYCTA NYCTA NYCTA	KRYLON OSHA SAFETY YELLOW 1813 A-A-1585 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	1998	1536
71-10-1532	PAINT, AEROSOL, ACRYLIC LACQUER, SMOKE GRAY, 12 OUNCE NET WEIGHT IN 16-OUNCE CAN, 6 PER CASE. INTERIOR/EXTERIOR INDUSTRIAL MAINTENANCE PAINT. USED TO PAINT R142/142A VALVES AT THE CI PNEUMATIC SHOP 6 16OZ CANS/CSE	KRYLON NYCTA NYCTA NYCTA	KRYLONCOLORMAXGLOSSESMOKEGRAY55 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	65	11

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
71-10-1540	PAINT, ENAMEL, GLOSS, RED, 12 OUNCE NET WEIGHT SPRAY CAN. COLOR: OSHA SAFETY RED. MEETS COMMERCIAL ITEM DESCRIPTION A-A-1585 WITH EXCEPTIONS TO SOLID CONTENTS AND SPECULAR GLOSS. THE SOLID CONTENTS SHOULD BE MIN 45-50G AND THE SPECULAR GLOSS 80-85 DEGREES. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-02(GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE.] STORE IN FLAMMABLE MATERIAL STORAGE CABINET. DO NOT USE NEAR IGNITION SOURCES. VENTILATION IS REQUIRED WHEN USING THIS PRODUCT. WEAR CHEMICAL SPLASH GOGGLES AND NITRILE OR NEOPRENE GLOVES. 6 12 OZ CANS/CSE IN 16OZ CANS	KRYLON PRODUCTS GROUP FEDERAL SPECIFICATION NYCTA NYCTA/MABSTOA NYCTA	KRYLON OSHA SAFETY RED 2116 A-A-1585 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	229	453
71-10-1619	PAINT, EASYTHANE, BLACK, #14, COATED METAL PANEL PRODUCT REQUIREMENTS L*=7.39, A*=-1.34, B*=-0.81; GLOSS 60 DEG. +/-7 DEG., 60 DEG. GLOSS METER, WEIGHT PER GALLON: 8.50 LBS. +/-0.5 LBS., NON-VOLATILE BY WEIGHT: 35.00% +/-2.0%, VISCOSITY: 55 KREBS UNITS +/-5 KU, VOC: <340 GRAMS/LITRE, WATERBORNE, IN ONE GALLON CAN IN 1 GAL CAN	STERLING LACQUER NYCTA NYCTA NYCTA	WA1003-1 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	3
71-10-1629	PAINT, SINGLE COMPONENT, WATERBORNE, ACRYLIC, ALUMINUM, COATING FORMULATED FOR DIRECT APPLICATION TO PRE-FINISHED METAL AND FIBERGLASS SURFACES, FOR PAINTING R68 FIBERGLASS BONNETS, PACKAGED IN ONE GALLON CONTAINER. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS PLASTIC PARTS COATING LINES: COLOR TOPCOAT WITH MAXIMUM VOC OF 3.8 LB/GAL(455.34 G/L) IN 1 GAL CTR	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	B71S200 BOND PLEX ALUMINUM CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	145	16

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
71-10-5039	PAINT, ALKYD, ENAMEL, RED, GLOSS, IN ONE GALLON CAN. USED TO PAINT FIRE BOX AREAS AND FIRE EXTINGUISHER LOCATIONS. COLOR: NYCT RED GLOSS (TRISTIMULUS VALUES: L* 31.06, A* 46.14, B* 37.98: DELTA E=2.50). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J EXCEPT FOR THE VISCOSITY AND SPECULAR GLOSS AND DRY TIME REQUIREMENTS. THE UNREDUCED VISCOSITY MUST BE 75 KREB UNITS MINIMUM; SPECULAR GLOSS IS TO BE MEASURED AT 60 DEGREES (NOT 20 DEGREES) AND MUST BE 70 MINIMUM. SET TO TOUCH DRY TIME IS 2-4 HOURS; DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE". IN 1 GAL CAN	MERCURY PAINT CO. NYCTA NYCTA NYCTA FED. SPEC.	IMC ALKYD HI-GLOSS RED #11136 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S TT-E-489J			86	7
71-10-6022	PAINT, ENAMEL, GLOSSY WHITE, 16 OUNCE SPRAY CANS, NET WT. 12 OZ. MEETING COMMERCIAL ITEM DESCRIPTION A-A-1585 WITH THE EXCEPTION TO SOLID CONTENTS AND SPECULAR GLOSS. THE SOLID CONTENTS SHOULD BE 60-65 G AND THE SPECULAR GLOSS 80-85 DEGREES. FED COLOR #17875. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-002 (GENERAL REQUIREMENTS FOR PAINTS)] IS NOT APPLICABLE.] NOTE TO DCE USERS: FOR USE IN DESIGNATED SPRAY PAINT TOUCH UP AREAS AND/OR WITH TRION "AIR BOSS FUME ELIMINATOR ONLY" IN 16 OZ CAN	KRYLON FEDERAL SPECIFICATION NYCTA NYCTA NYCTA	KRYLON COLORMAX GLOSS WHITE 55 A-A-1585 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S			861	719

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1 -----	USE YTD -----
71-10-6030	PAINT, 100% ACRYLIC WATER EMULSION, TRAFFIC AND AIRFIELD MARKING WHITE IN FIVE GALLON CAN. USED TO PAINT TRIP COCKS, WHEEL AXLE AND INSPECTION LINES. COLOR: NYCT WHITE LATEX TRAFFIC MARKING PAINT WHITE (TRISTIMULUS VALUES:L*92.76, A*-0.75, B*2.88; DELTA E=1.50; MERCURY PAINT TRISTIMULUS VALUES: L*95.33, A*-0.79, B*2.28, DELTA E=1.50). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-P-1952E WITH THE EXCEPTION OF VISCOSITY/, % SOLIDS AND DRYING TIME. VISCOSITY/CONSISTENCY MUST BE BETWEEN 80 AND 105 KREBS UNITS. % SOLIDS MUST BE A MINIMUM OF 50% BY WEIGHT. DRY TO TOUCH TIME MUST BE 30 MINUTES MAXIMUM. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATING MAXIMUM VOC LIMIT OF 2.84 LB/GAL (340 G/L). [NOTE PART 228; SURFACE COATING FOR MISCELLANEOUS METAL PARTS AND PRODUCTS DOES NOT APPLY SINCE THIS PAINT IS APPLIED TO RAIL CART PARTS BY BRUSH.] THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY"(2)"FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4)"NOT INTENDED FOR RESIDENTIAL USE". IN 5 GAL CAN	BENJAMIN MOORE PAINTS MERCURY PAINT CO. NYCTA NYCTA NYCTA NYCTA FED. SPEC.	GT 56210 NYCTA WHT LX TRAF PNT LEAD FREE FAST DRY TRAFFIC PAI CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC. TT-P-1952E	340	85
71-10-6031	PAINT, ENAMEL, ALKYD, GLOSS SWEET CREAM, SPRAY CAN 12 OZ. NET WEIGHT, 6 CANS PER CASE. USED TO PAINT VALVES IN THE MOTORMAN'S CAB AND BRAKE VALVES IN THE CONEY ISLAND PNEUMATIC SHOP. SOLIDS CONTENT MINIMUM 14.2 AND SPECULAR GLOSS 80-85 DEGREES. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-002(GENERAL REQUIREMENTS FOR PAINTS)IS NOT APPLICABLE.] STORE IN FLAMMABLE MATERIAL STORAGE CABINET. DO NOT USE NEAR IGNITION SOURCES. VENTILATION IS REQUIRED WHEN USING THIS PRODUCT. WEAR CHEMICAL SPLASH GOGGLES	KRYLON PRODUCTS GROUP NYCTA NYCTA NYCTA	COLORMAXX GLOSS SWEET CREAM 55 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	38	4

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
----------	------------------	----------	-------------	---------	---------

71-10-6035	PAINT, 100% ACRYLIC WATER EMULSION, TRAFFIC AND AIRFIELD MARKING WHITE IN ONE GALLON CAN. USED TO PAINT TRIP COCKS, WHEEL AXLE AND INSPECTION LINES. COLOR: NYCT WHITE LATEX TRAFFIC MARKING PAINT WHITE (TRISTIMULUS VALUES: L*92.76, A*0.79, B*2.28, DELTA E=1.50; MERCURY PAINT TRISTIMULUS VALUES: L* 95.33, A*0.79, B*2.28, DELTA E-1.50). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-P-1952E WITH THE EXCEPTION OF VISCOSITY/CONSISTENCY, % SOLIDS AND DRYING TIME, VISCOSITY/CONSISTENCY MUST BE BETWEEN 80 AND 105 KREBS UNITS, % SOLIDS MUST BE MINIMUM OF 50% BY WEIGHT, DRY TO TOUCH TIME MUST BE 30 MINUTES MAXIMUM. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATING MAXIMUM VOC LIMIT OF 2.84 LB/G/L). [NOTE PART 228: SURFACE COATING FOR MISCELLANEOUS METAL PARTS AND PRODUCTS DOES NOT APPLY SINCE THIS PAINT IS APPLIED TO RAIL CAR PARTS BY BRUSH.] THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE". IN 1 GAL CAN	MERCURY PAINT CO. NYCTA NYCTA NYCTA FEDERAL SPECIFICATION	LEAD FREE FAST DRY TRAFFIC PAI CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S TT-P-1952E	111	57
------------	---	---	--	-----	----

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	DRY TIME IS 6 HOURS, DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. THIS PAINT IS USED BOTH AS AN INDUSTRIAL MAINTENANCE COATING (NYSDEC REGULATION 6NYCRR PART 205) AND AS A SURFACE COATING MISCELLANEOUS METAL PARTS AND PRODUCTS(6NYCRR PART 228). IT MUST COMPLY WITH THE MORE RESTRICTIVE VOC LIMIT FOR 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) " FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4)"NOT INTENDED FOR RESIDENTIAL USE".				
	IN 1 GAL CAN				
71-10-7030	PAINT, LATEX COLOR: TRAFFIC YELLOW. IN FIVE GALLON CAN, PER NYCT SPEC STA-7030-0609	AMSTERDAM PAINT MERCURY PAINT CO. NYCTA NYCTA NYCTA NYCTA NYCTA	TT-P-1952 REV B TYPE II TZWBYEL CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC. STA-7030-0609	1925	1375
	IN 5 GAL CAN				
71-11-9020	PAINT, ALKYD, ENAMEL, WHITE, GLOSS IN ONE GALLON CANS. USE TO PAINT OFFICE WALLS AND SHOP PITS. COLOR, NYCT SUPER WHITE (TRISTIMULUS VALUES; L* 94.90, A* -1.81, B* 8.56; DELTA E=1.70 MAX). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-P-102E WITH THE EXCEPTION THAT THE SPECULAR GLOSS MUST BE 70 MINIMUM. SET TO TOUCH TIME IS 6 HOURS; DRY HARD TIME IS 16 HOURS; DRY TO RECOAT TIME IS 24 HOURS MAX. MUST COMPLY WITH NYSDEC 6NYCRR PART 205 "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4)"NOT INTENDED	MERCURY PAINT CO. NYCTA NYCTA	IMC TTP 102-E WHITE/71-11-9020 CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	FOR RESIDENTIAL USE".				
71-14-2900	PAINT, BRIGHT SILVER ALUMINUM, ENAMEL, IN 16 OZ. SPRAY CANS, NET WT. 11 OZ., MEETING COMMERCIAL ITEM DESCRIPTION A-A-1585 WITH EXCEPTIONS TO THE SOLID CONTENTS AND SPECULAR GLOSS. THE SOLID CONTENTS SHOULD BE 25-30G AND THE SPECULAR GLOSS OF 80-85 DEGREES, FED COLOR #17178. [NOTE: FLASHPOINT REQUIREMENT OF NCYTA SPECIFICATION CCSS-002(GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE.] IN 16 OZ CANS	KRYLON FEDERAL SPECIFICATION NYCTA NYCTA NYCTA	METALLICS BRIGHT SILVER 1401 A-A-1585 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	378	232
71-14-7320	PAINT, WATER BASED ACRYLIC ENAMEL, JOHN DEERE GREEN, ONE GALLON CAN, HIGH GLOSS. VOC LESS THAN 250 G/L (2.08 LBS/GAL). SOLID CONTENT BY WEIGHT 36-49%; DENSITY 8.7-10 LBS/GAL; FLASH POINT > 200F; DRY TIMES: 1-2 HOURS TACK FREE, 2-4 HOURS HANDLE; 1-3 HOURS RECOAT. USE IN WELL VENTILATED AREAS: OPEN DOORS, WINDOWS AND USE BLOWER FANS IN THE VICINITY OF THE WORK AREA TO INCREASE AIR DILUTION. PPE REQUIRED; CHEMICAL SPLASH GOGGLES, LIGHT WEIGHT NEOPRENE/NITRILE GLOVES. IN 1 GAL CAN	RUST-OLEUM NYCTA NYCTA	INDUSTRIAL CHOICE DTM #5234402 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 REV E 9/11/17 RESTR S	0	0
71-19-8300	PAINT, ALKYD, ENAMEL, SEMI-GLOSS WHITE. IN ONE GALLON CANS. USED TO PAINT EXTERIOR WALLS AT SHOPS. COLOR NYCT OIL BASED ALKYD WHITE (TRISTIMULUS VALUES: L*95.01, A*-1.47, B*9.20, DELTA E=2.0 MAXIMUM) MUST MEET REQUIREMENTS OF COMMERCIAL ITEM DESCRIPTION A-A-3067. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE	MERCURY PAINT CO. COMMERICAL NYCTA NYCTA NYCTA	TTP-102 TYPE II ASG WHITE A-A-3067 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-19-9600	<p>FOLLOWING STATEMENTS: (1) FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".</p> <p>PAINT, PRESERVATIVE, RED, STEEL, ITEM C #6073, AIR DRY IN ONE GALLON CAN, USED FOR METAL, USED TO PAINT STEEL BEAMS, COLUMNS AND PLATES. COLOR: NYCT RED STEEL PRESERVATIVE #6073 KEY CHARACTERISTIC: VISCOSITY 75 KREB UNITS. TOTAL SOLIDS BY WEIGHT 67.2, MINIMUM DRYING TIMES: MAXIMUM 6 HRS DRY TO TOUCH, MAXIMUM 16 HRS TO DRY HARD, MAXIMUM 24 HRS DRY TO RECOAT. LEAD CONTENT 0.06% MAXIMUM BY TOTAL WEIGHT. FLASH POINT 100 DEGREES F MINIMUM. MUST COMPLY WITH NYSDEC REGULATION 6NYCCR PART 205 ARCHITECTURAL AND INDUSTRIAL COATING WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L) THE CONTAINER MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS.(1) "FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY" (3) "NOT FOR RESIDENTIAL USE" OR (4) "NOT INTENDED FOR RESIDENTIAL USE ONLY" IN 1 GAL CAN</p>	<p>MERCURY PAINT CO. NYCTA NYCTA NYCTA NYCTA</p>	<p>#6073 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S PALLET SPEC.</p>	564	126
71-22-0001	<p>PAINT KIT, SAFETY YELLOW, TWO COMPONENT URETHANE, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS. GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER AND SPRAY APPLICATION; COLOR: NYCT POLYLON SAFETY YELLOW (TRISTIMULUS VALUES: L* 74.81, A* 14.70, B* 43.08 DELTA E=1.80), SPECULAR GLOSS OF 85+5 (@ 60 DEGREES) BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS; PART A RESIN IN A FULL GALLON CAN AND PART B CATALYST IN A HALF GALLON CAN. PART A AND PART B COMBINE TO MAKE 1-1/2 GALLON OF PAINT. VENDOR TO SUPPLY MANUFACTURER'S</p>	<p>SHERWIN-WILLIAMS NYCTA NYCTA NYCTA</p>	<p>HP POLYURETHANE B 65W525 YELLO CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
	<p>CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY OF PART A, PART B, GLOSS, VOC WITH EACH SHIPMENT VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT, VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 2.8 LB/GAL (340 G/L).</p> <p>2 EA/KIT</p>						
71-22-0002	<p>PAINT KIT, SAFETY YELLOW, TWO COMPONENT URETHANE, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS. GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER AND SPRAY APPLICATION. COLOR: NYCT POLYON SAFETY YELLOW (TRISTIMULUS VALUES; L*76.28, A*16.17, B* 97.25 DELTA E=1.80), SPECULAR GLOSS OF 90 MINIMUM. BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. QUART SIZE PAINT KIT CONSISTS OF TWO PARTS: 1-1/2 PINTS OF PART A RESIN IN A 1 QUART CAN AND 1/2 PINT OF PART B CATALYST IN A 1/2 PINT CAN. PART A AND PART B COMBINE TO MAKE 1 QUART OF PAINT. DENSITY OF PART A IS 9.2 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.4 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 3 TO 1 BY VOLUME) IS 30 TO 50 SECONDS AS MEASURED BY #3 ZAHN CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL(419.39 G/L)</p>	<p>SHERWIN-WILLIAMS NYCTA/MABSTOA NYCTA NYCTA</p>	<p>POLY-LON 1441-88 LOCOMOT CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>			0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
71-22-0004	PAINT KIT, BIEGE, TWO COMPONENT URETHANE, INTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER AND SPRAY APPLICATION. COLOR: NYCT POLYLON BEIGE (TRISTIMULUS VALUES: L* 72.81, A* 4.51, B* 22.91, DELTA E=1.30), SPECULAR GLOSS OF 90 MINIMUM. BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. QUART SIZE PAINT KIT CONSISTS OF TWO PARTS: 1-1/2 PINTS OF PART A RESIN IN A QUART CAN AND 1/2 PINT OF PART B CATALYST IN A 1/2 PINT CAN. PART A AND PART B COMBINE TO MAKE 1 QUART OF PAINT. DENSITY OF PART A IS 9.2+/-0.3 LBS/ GAL, DENSITY OF PART B IS 9.4 +/- 0.3 LBS/GAL. VISCOSITY OF PART A AND PART B COMBINED (MIXED 3 TO 1 VOLUME) IS 30 TO 50 SECONDS AS MEASURED BY #3 ZAHN CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L).	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA NYCTA	POLY-LON 514-87 BEIGE 1075-C-86 REV.J MARCH 1990 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-22-0006	PAINT KIT, BEIGE, TWO COMPONENT URETHANE, INTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER AND SPRAY APPLICATION. COLOR: NYCT POLYLON BEIGE (TRISTIMULUS VALUES: L*70.55, A*2.88, B*14.29, DELTA E = 1.00). SPECULAR GLOSS OF 85+5 (@ 60 DEGREES) MINIMUM. BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. GALLON SIZE PAINT KIT CONSISTS OF TWO PARTS: PART A RESIN IN A FULL 1 GALLON CAN AND PART B CATALYST IN A HALF GALLON CAN. PART A	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	BW65W525 BEIGE & B65V525 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	4	6

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1 -----	USE YTD -----
	AND PART B COMBINE TO MAKE 1-1/2 GALLON OF PAINT. VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY OF PART A AND OF PART B, VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT, COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 2.80 LB/GAL (340 G/L)				
	2 PART/KIT				
71-22-0018	PAINT KIT, TWO COMPONENT URETHANE; WHITE, INTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER & SPRAY APPLICATION. COLOR: NYCT POLY WHITE (TRISTIMULUS VALUES: L*92.4, A*-1.15, B*0.86, DELTA E=1.00), SPECULAR GLOSS OF 85+5 (@ 60 DEGREES). BASED ON MOBAY "DESMODUR" ALPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. GALLON SIZE PAINT KIT CONSISTS OF TWO PARTS; PART A RESIN IN A FULL ONE GALLON CAN AND PART B CATALYST IN A HALF GALLON CAN. PART A AND PART B COMBINE TO MAKE 1-1/2 GALLON OF PAINT. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY OF PART A AND OF PART B)UP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B, VISCOSITY (MIXED), GLOSS WITH EACH SHIPMENT VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT, MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 2.8 LB/GAL(340G/L)	SHERWIN WILLIAMS NYCTA NYCTA NYCTA NYCTA	HP POLYURETHANE B 65W525 WHITE 1075-C-86 REV.J, MAR. 1990 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-22-0028	PAINT KIT, TWO-COMPONENT POLYURETHANE PRIMER SURFACER, LIGHT GRAY, FOR FILLING PINHOLES AND ROUGH SURFACES OF FIBERGLASS SURFACES OR REWORK SURFACES. EACH KIT SHALL CONTAIN 3/4 GALLON OF PRIMER, 1 PINT OF CATALYST AND 1 PINT OF REDUCER IN A SEPARATE CONTAINER. PRODUCT IS EXEMPT FROM FLASH POINT REQUIREMENT OF CCSS-002 REV E. AND HAS BEEN APPROVED BY OSS FOR USE IN DESIGNATED PAINT BOOTH.	DEFT, INC. NYCTA NYCTA NYCTA	09GY024, 80X040 & IS300 CCSS-001, REV I, 3-9-11, LABEL CCSS-003 06/16/00 RESTRICTED S CCSS-003 REV E 9/11/17 RESTR S	0	0
	2 PARTS/KIT				
71-22-0033	PAINT KIT, GRAY, TWO COMPONENT URETHANE, INTERIOR FULL GLOSS TOPCOAT FOR RAILCARS; GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER, AND SPRAY APPLICATION, COLOR: NYCT POLYLON GRAY (TRISTIMULUS VALUES: L* 25.88, A* -2.32, B* -0.55, DELTA E=1.10), SPECULAR GLOSS OF 90 MINIMUM. BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. QUART SIZE PAINT KIT CONSISTS OF TWO PARTS: 1-1/2 PINTS OF PART A RESIN IN A 1 QUART CAN AND 1/2 PINT OF PART B CATALYST IN A 1/2 PINT CAN. PART A AND PART B COMBINE TO MAKE 1 QUART OF PAINT. DENSITY OF PART A IS 9.2 +/- 0.3 LBS/GAL, DENSITY OF PART B IS 9.4 +/- 0.3 LBS/GAL. VISCOSITY OF PART A AND B COMBINED(MIXED 3 TO 1 BY VOLUME) IS 30 TO50 SECONDS AS MEASURED BY #3 ZAHN CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OFF PART A AND OF PART B). VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS PLASTIC PARTS COATING LINES: COLOR TOPCOAT WITH MAXIMUM VOX OF 3.8 LB/GAL(455.34 G/L)	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA NYCTA NYCTA	POLY-LON 876-87 GRAY 1075-C-86 REV.J, MAR. 1990 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 6/16/00 RESTRICTED SU CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-22-0034	PAINT KIT, GRAY, TWO COMPONENT URETHANE, EXTERIOR/INTERIOR FULL GLOSS TOPCOAT FOR RAILCARS; GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER, AND SPRAY APPLICATION, COLOR: NYCT: POLYLON GRAY (TRISTIMULUS VALUES: L* 29.91, A* -1.15, B* -0.86, DELTA E= 1.00), SPECULAR GLOSS OF 85 + 5(@ 60 DEGREES) BASED ON MOBAY "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. GALLON SIZE PAINT KIT CONSISTS OF TWO PARTS; PART A RESIN IN FULL ONE GALLON CAN AND PART B CATALYST IN A HALF GALLON CAN. PART A AND B COMBINE TO MAKE 1-1/2 GALLON OF PAINT. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY OF PART A AND OF PART B. VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT VOC CERTIFICATION MUST ACCOMPANY WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS PLASTIC PARTS COATING LINES: COLOR TOPCOAT WITH MAXIMUM VOC OF 2.8 LB/GAL(340 G/L) IN 2 PART KIT	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	HP POLYURETHANE B 65W525 GRAY CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-22-0037	ACCELERATOR, FOR POLYURETHANE PAINTS. THIS PRODUCT IS EXEMPT FROM THE FLASH POINT REQUIREMENTS OF CCSS-002, REV. D AND HAS BEEN APPROVED BY OSS FOR USE IN THE DESIGNATED PAINT BOOTH AREAS. PACKAGED IN ONE PINT CONTAINERS	PPG INDUSTRIES NYCTA NYCTA NYCTA	MX195 CCSS-001, REV I, 3-9-11 LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	6	37
71-22-0090	KIT, TOUCH-UP, BLUE ACRYLIC TOPCOAT, CONSISTING OF 2 COMPONENTS(BASE AND CATALYST) FOR USE BY DOB IN PAINT SPRAY BOOTH. ZERO VOC COATING. MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS SIX MONTHS. THIRD PARTY ANALYSIS LIMITS SHALL BE USED WHEN INSPECTING THE FOLLOWING PROPERTIES: WEIGHT PER GALLON (MIXED) ASTM D-1475, PERCENT WEIGHT SOLID (MIXED) ASTM D-2369, DRY TO TAPE	PPG INDUSTRIES NYCTA NYCTA NYCTA	BLUE 36BLO15E-T/36X194CAT CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	121	95

USER-ID : RJR
PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 394
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
	TIME (TAPE TIME) MIL-PRF-85285D, WEIGHT PER GALLON (BASE ONLY) ASTM D-1475 AND PERCENT WEIGHT SOLID (BASE ONLY) ASTM D-2369 IN 2 PART KIT						
71-22-0092	KIT, TOUCH-UP, BLACK ACRYLIC TOPCOAT, CONSISTING OF 2 COMPONENTS(BASE AND CATALYST) FOR USE BY DOB IN PAINT SPRAY BOOTH, ZERO VOC COATING MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS SIX MONTHS. THIRD PARTY ANALYSIS LIMITS SHALL BE USED WHEN INSPECTING THE FOLLOWING PROPERTIES: WEIGHT PER GALLON (MIXED) ASTM D-1475, PERCENT WEIGHT SOLID (MIXED) ASTM D-2369, DRY TO TAPE (TAPE TIME) MIL-PRF-85285D. WEIGHT PER GALLON (BASE ONLY) ASTM D-1475 AND PERCENT WEIGHT SOLID (BASE ONLY) ASTM D-2369 IN 2 PART KIT	PPG INDUSTRIES NYCTA NYCTA NYCTA	BLACK 36BK001E-T/36X194CAT CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	128		108	
71-22-0094	KIT, TOUCH-UP, GREY PRIMER/SURFACER CONSISTING OF 2 COMPONENTS (BASE AND CATALYST) FOR USE BY DOB IN PAINT SPRAY BOOTH. ZERO VOC COATING MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS SIX MONTHS. THIRD PARTY ANALYSIS LIMITS SHALL BE USED WHEN INSPECTING THE FOLLOWING PROPERTIES: WEIGHT PER GALLON (MIXED) ASTM D-1475, PERCENT WEIGHT SOLID (MIXED) ASTM D-2369. DRY TO TAPE TIME (TAPE TIME) MIL-PRF-85285D, WEIGHT PER GALLON (BASE ONLY) ASTM D-1475 AND PERCENT WEIGHT SOLID (BASE ONLY) ASTM D-2369 IN 2 PART KIT	PPG INDUSTRIES NYCTA NYCTA NYCTA	GRAY 09GY007E-T/36X194CAT CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	3		0	

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1	USE YTD
71-22-0096	KIT, TOUCH-UP, WHITE ACRYLIC TOPCOAT, CONSISTING OF 2 COMPONENTS(BASE AND CATALYST)FOR USE BY DOB IN PAINT SPRAY BOOTH. ZERO VOC COATING MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS SIX MONTHS. THIRD PARTY ANALYSIS LIMITS SHALL BE USED WHEN INSPECTING THE FOLLOWING PROPERTIES: WEIGHT PER GALLON (MIXED) ASTM-D-1475, PERCENT WEIGHT SOLID (MIXED) ASTM-D-2369. DRY TO TAPE TIME (TAPE TIME) MIL-PRF-85285D, WEIGHT PER GALLON (BASE ONLY) ASTM D-1475 AND PERCENT WEIGHT SOLID(BASE ONLY) ASTM-D-2369 IN 2 PART KIT	PPG INDUSTRIES NYCTA NYCTA NYCTA	WHITE 36W021E-T/36X194CAT CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	185	121
71-22-0126	PAINT KIT, TWO COMPONENT URETHANE, SEAT BLUE, INTERIOR FULL GLOSS TOPCOAT FOR R142, R142A & R143 RAILCAR SEATS, GRAFFITI REMOVER RESISTANT FOR BRUSH; ROLLER AND SPRAY APPLICATION. COLOR: NYCT SEAT BLUE, (TRISTIMULUS VALUES: L*50.53, A*-1.40, B*-15.10, DELTA E=1.30), SPECULAR GLOSS 90 MINIMUM. BASED ON MOBAY'S "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT TO BE PACKAGED INDIVIDUALLY. QUART SIZE PAINT KIT CONSISTS OF TWO PARTS: 1-1/2 PINTS OF PART A RESIN IN A 1 QUART CAN AND 1/2 PINT OF PART B CATALYST IN A 1/2 PINT CAN. PART A AND PART B COMBINE TO MAKE 1 QUART OF PAINT. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OF PART A AND PART B), VISCOSITY(MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS IN 2 PART KIT	DEFT, INC. NYCTA NYCTA NYCTA	BLUE(36BL047)& CATALYST(80XO22 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
71-22-0128	PAINT KIT, TWO COMPONENT URETHANE, SEAT BLUE, INTERIOR FULL GLOSS TOPCOAT FOR R160 RAILCAR SEATS, GRAFFITI REMOVER RESISTANT; FOR BRUSH, ROLLER AND SPRAY APPLICATION. COLOR: NYCT SEAT BLUE, (TRISTIMULUS VALUES: L*=50.95, A*=0.37, B*=-17.26, DELTA E=1.30), SPECULAR GLOSS 90 MINIMUM. BASED ON MOBAY'S "DESMODUR" ALIPHATIC POLYURETHANE RESIN SYSTEM OR EQUIVALENT. EACH PAINT KIT TO BE PACKAGED INDIVIDUALLY. QUART SIZE PAINT KIT CONSISTS OF TWO PARTS: 1-1/2 PINTS OF PART A RESIN IN A 1 QUART CAN AND 1/2 PINT OF PART B CATALYST IN A 1/2 PINT CAN. PART A AND PART B COMBINE TO MAKE 1 QUART OF PAINT. FLASHPOINT REQUIREMENT OF NYCT SPECIFICATION CCSS-002 GENERAL REQUIREMENTS FOR PAINT IS NOT APPLICABLE. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY OF PART A AND PART B, VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT, MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS IN 2 PART KIT	PPG INDUSTRIES NYCTA NYCTA NYCTA	36BL051E & 36X194CATCURING CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S			42	22
71-22-0129	PAINT KIT, THREE COMPONENT URETHANE, SEAT BLUE, INTERIOR FULL GLOSS TOPCOAT FOR R160 RAILCAR SEATS, GRAFFITI REMOVER RESISTANT FOR BRUSH; ROLLER AND SPRAY APPLICATION. COLOR: NYCT SEAT BLUE, (L*54.66, A*-0.28, B* -13.17, DELTA E<2), SPECULAR GLOSS 90 MINIMUM. EACH PAINT KIT TO BE PACKAGED INDIVIDUALLY. 1 GALLON SIZE PAINT KIT CONSISTS OF THREE PARTS: 3/4 GALLON OF PART A RESIN IN A 1 GALLON CAN; 1 PINT HARDENER IN A 1 PINT CAN;; AND 1 PINT ACTIVATOR IN A 1 PINT CAN. ALL THREE PARTS COMBINE TO MAKE 1 GALLON OF PAINT. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OFF ALL THREE PARTS), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE	PPG INDUSTRIES NYCTA NYCTA NYCTA	BLUEESSS989473,ESH200,ESX510 CCSS-001, REV I, 3-9-11 LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S			0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1	USE YTD
	COATINGS IN 3 PART KIT				
71-22-0150	PAINT KIT, TWO COMPONENT URETHANE, STAINLESS STEEL, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITI REMOVER RESISTANT, FOR BRUSH, ROLLER & SPRAY APPLICATION. COLOR: OEM WHITE (TRISTMULUS VALUES: L* 88.9, A* -1.3, B* 1.1, DELTA E<2), SPECULAR GLOSS OF 90 MINIMUM @ 60 DEGREES F. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS; 4 GALLONS OF PART A RESIN IN A 5 GALLON CAN AND 1 GALLON OF PART B HARDENER IN A 1 GALLON CAN. PART A AND PART B COMBINE TO MAKE 5 GALLONS OF PAINT. DENSITY OF PART A IS 9.93 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.18 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B COMBINED (MIXED 4 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B), VISOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L)	PPG INDUSTRIES NYCTA NYCTA NYCTA	OEM N0006 WHITE CCA976469 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-22-0152	PAINT KIT, TWO COMPONENT URETHANE, STAINLESS STEEL, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITTI REMOVER RESISTANT, FOR BRUSH, ROLLER & SPRAY APPLICATION. COLOR: OEM YELLOW (TRISTIMULUS VALUES; L*59.1, A*-33.3, B*17.8, DELTA E<2), SPECULAR GLOSS OF 90 MINIMUM @ 60 DEGREES F. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS; 4 GALLONS OF PART A RESIN IN A 5 GALLON CAN AND 1 GALLON OF PART B HARDENER IN A 1 GALLON CAN. PART A AND PART B COMBINE TO MAKE 5 GALLONS OF PAINT.	PPG INDUSTRIES NYCTA NYCTA NYCTA	OEM SAFETY YELLOW CCA976425 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----
	DENSITY OF PART A IS 9.01 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.18 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B COMBINED (MIXED 4 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L)				
71-22-0154	PAINT KIT, TWO COMPONENT URETHANE, STAINLESS STEEL, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITTI REMOVER RESISTANT, FOR BRUSH, ROLLER & SPRAY APPLICATION. COLOR: OEM BLACK (TRISTIMULUS VALUES: L*23.7, A* -0.2, B* -0.9, DELTA E <2), SPECULAR GLOSS OF 8 MINIMUM @ 60 DEGREES F. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS: 4 GALLONS OF PART A RESIN IN A 5 GALLON CAN AND 1 GALLON OF PART B HARDENER IN A 1 GALLON CAN. PART A AND PART B COMBINE TO MAKE 5 GALLONS OF PAINT. DENSITY OF PART A IS 8.68 +/- 0.3 LBS/GAL, DENSITY OF PART B IS 9.18 +/- LBS/GAL. VISCOSITY OF PART A AND PART B COMBINED(MIXED 4 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B). VISCOSITY(MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L)	PPG INDUSTRIES NYCTA NYCTA NYCTA	OEM NYCT LG BLACK CCA950368 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-22-0156	PAINT, KIT, TWO COMPONENT URETHANE, STAINLESS STEEL, EXTERIOR FULL GLOSS TOPCOAT FOR RAILCARS, GRAFFITTI REMOVER RESISTANT, FOR BRUSH, ROLLER & SPRAY APPLICATION. COLOR: OEM GREEN (TRISTIMULUS VALUES: L*66.6, A*21.2, B*62.1, DELTA E<2), SPECULAR GLOSS OF 90 MINIMUM @ 60 DEGREES F. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS: 4 GALLONS OF PART A RESIN IN A 5 GALLON CAN AND 1 GALLON OF PART B HARDENER IN A 1 GALLON CAN. PART A AND PART B COMBINE TO MAKE 5 GALLONS OF PAINT. DENSITY OF PART A IS 9.85 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.18 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B COMBINED (MIXED 4 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L)	PPG INDUSTRIES NYCTA NYCTA NYCTA	OEM SAFETY GREEN CCA911742 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-24-2000	PAINT, PRESERVATIVE, TIRE, BLACK FLAT, READY MIX. 1 GALLON CANS IN 1 GAL CAN	CONVENTRY COATINGS NYCTA NYCTA NYCTA	SA-70083 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	104	8
71-26-8000	PAINT, ALKYD, WHITE, SATIN FINISH IN 5 GALLON CAN. USED TO PAINT SHOP AND OFFICE WALLS. TRIP COCK AND CONTROL RAIL MATERIALS. COLOR: NYCT WHITE SATIN FINISH ALKYD (TRISTIMULUS VALUES; L*86.76, A*-1.06, B*6.94; DELTA E=1.50). (MERCURY PAINT TRISTIMULUS VALUES: L*87.29, A*=-0.66, B*=8.73; DELTA E=1.50 MAX). MUST MEET REQUIREMENTS OF FEDERAL SPEC. TT-E-489, REVISION J WITH THE EXCEPTION FINENESS OF GRIND, SPECULAR GLOSS, VISCOSITY AND DRY TIME	MERCURY PAINT CO. NYCTA NYCTA NYCTA FEDERAL SPECIFICATION	IMC M12 SATFIN SILV WH(T489MOD CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S TT-489J	185	75

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	<p>REQUIREMENTS. FINENESS OF GRIND MUST BE 5 OR GREATER; SPECULAR GLOSS MUST BE IN THE RANGE OF 15-35; THE UNREDUCED VISCOSITY MUST BE 78-88 KREB UNITS. SET TO TOUCH DRY TIME IS 6 HOURS MAXIMUM. MUST COMPLY WITH THE NYSDEC REGULATION 6NYCRR PART 205: INDUSTRIAL MAINTENANCE COATING WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). NOTE PART 228: SURFACE COATINGS FOR MISCELLANEOUS METAL PARTS AND PRODUCTS DOES NOT APPLY SINCE THIS PAINT IS APPLIED TO RAILCAR PARTS BY BRUSH). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING "WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY", (2)"FOR PROFESSIONAL USE ONLY", (3)NOT FOR RESIDENTIAL USE", (4)"NOT INTENDED FOR RESIDENTIAL USE".</p> <p>IN 5 GAL CAN</p>				
71-28-3010	<p>PAINT, EXTERIOR, SILVER BRITE ALUMINUM, HIGH TEMPERATURE MAINTENANCE COATING, GLOSS TOPCOAT FOR CAR BONNETS, READY MIXED, FOR BRUSH AND ROLLER APPLICATION, IN ONE GALLON CANS. MUST COMPLY WITH NYSDEC REGULATIONS 6NYCRR PART 228 SURFACE COATING LINES. HIGH TEMPERATURE COATING WITH VOC 600G/L OR 5.01 LB/GAL. DENSITY IS 7.61-7.91 LBS/GAL; VISCOSITY 22-26 FORD CUP SEC #4; DRY TO TOUCH TIME 15-30 MINUTES; DRY TACK FREE TIME 4-6 HOURS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY, VISCOSITY, DRY TO TOUCH AND TACK FREE TIME AND DRAWDOWN SAMPLES WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE".</p> <p>IN 1 GAL CAN</p>	SHERWIN WILLIAMS/DIVERSIFIED NYCTA/MABSTOA NYCTA/MABSTOA NYCTA	SILVR-BRITE ALUMINUM PAINT B59 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	42	17

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-30-5060	PAINT, KIT, FOR FLOORS, TWO COMPONENT WATER BASED EPOXY AMINE TYPE, RED - FEDERAL COLOR STANDARD(595A) #10076, GLOSS. EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN AND 1 GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). DENSITY OF PART A IS 11.2+/-0.3 LBS/GAL, DENSITY OF PART B IS 9.0+/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 1 TO 1 BY VOLUME) IS 85 TO 105 KREB UNITS. HAS A SPECULAR GLOSS OF 70 DEGREES MINIMUM. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B), VISCOSITY (MIXED, GLOSS, VOC AND DRAWDOWN SAMPLES, WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FORRESIDENTIAL USE". IN 2 PART KIT	SHERWIN WILLIAMS NYCTA NYCTA NYCTA	FL-PLX RED 10076 #B70RB6&CL710 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	79	49
71-30-5065	PAINT, KIT, FOR FLOORS, TWO COMPONENT WATER BASED EPOXY AMINE TYPE, GRAY - FEDERAL COLOR STANDARD (595A) #16251, GLOSS. EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN AND 1 GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). DENSITY OF PART A IS 10.9+/-0.3 LBS./GAL, DENSITY OF PART B IS 9.0+/-0.3 LBS./GAL. VISCOSITY OF PART A AND PART B(MIXED 1	SHERWIN WILLIAMS NYCTA NYCTA NYCTA	FL-PLX QUARRYGRAY#CL7105&CL710 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	70	298

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	<p>TO 1 BY VOLUME) IS 85 TO 105 KREB UNITS. HAS A SPECULAR GLOSS OF 70 DEGREES MINIMUM. VENDOR MUST SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B). VISCOSITY (MIXED), GLOSS, VOC AND DRAWDOWN SAMPLES WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".</p> <p>IN 2 PART KIT</p>				
71-30-5070	<p>PAINT KIT, FOR FLOORS, ANTI-SKID, TWO COMPONENT WATER BASED EPOXY AMINE, RED-FEDERAL COLOR STANDARD (595A) #10076, GLOSS. MUST CONTAIN APPROXIMATELY 4 LBS. OF ALUMINUM OXIDE ANTI-SKID GRIT (APPROXIMATELY 70 MESH SIZE). EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN AND ALUMINUM OXIDE GRIT IN A 1 GALLON CAN AND 1 GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL((340 G/L). DENSITY OF PART A IS 13.7 +/- 0.3 LBS/GAL, DENSITY OF PART B IS 9.0 +/- 0.3 LBS/GAL. VISCOSITY OF PART A AND PART B(MIXED 1 TO 1 BY VOLUME) IS 98 TO 120 KREB UNITS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OFF PART A AND OF PART B), VISCOSITY(MIXED), GLOSS, VOC AND DRAWDOWN SAMPLES WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4)</p>	<p>SHERWIN WILLIAMS NYCTA NYCTA NYCTA</p>	<p>FL-PLX NAVRED #CL1657-92&CL710 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	76	35

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
	"NOT INTENDED FOR RESIDENTIAL USE". IN 2 PART KIT						
71-30-5075	PAINT KIT, FOR FLOORS, ANTI-SKID, TWO COMPONENT WATER BASED EPOXY AMINE TYPE, BLUE-FEDERAL COLOR STANDARD (595A) #15065, GLOSS. MUST CONTAIN APPROXIMATELY 4 LBS. OF ALUMINUM OXIDE ANTI-SKID GRIT(APPROXIMATELY 70 MESH SIZE). EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS; 1 GALLON OF PART A RESIN AND ALUMINUM OXIDE GRIT IN A 1 GALLON CAN AND 1 GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). DENSITY OF PART A IS 12.4 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.0 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B(MIXED 1 TO 1 BY VOLUME) IS 85 TO 105 KREB UNITS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC AND DRAWDOWN SAMPLES WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS:(1) "FOR INDUSTRIAL USE ONLY",(2)"FOR PROFESSIONAL USE ONLY",(3)"NOT FOR RESIDENTIAL USE", OR(4)"NOT INTENDED FOR RESIDENTIAL USE".	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	FL-PLX 1653-92 SKD RES BLUE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		0	0	
71-30-5080	PAINT KIT, FOR FLOORS, SAFETY-YELLOW-FEDERAL COLOR STANDARD (595A) #13538, GLOSS. ANTI-SKID, TWO COMPONENT WATER BASED EPOXY AMINE TYPE. MUST CONTAIN APPROXIMATELY 4 LBS. OF ALUMINUM OXIDE ANTI-SKID GRIT (APPROXIMATELY 70 MESH SIZE). EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS; 1 GALLON OF PART A RESIN AND ALUMINUM OXIDE GRIT IN A 1 GALLON CAN AND 1	SHERWIN WILLIAMS NYCTA NYCTA NYCTA	FL-PLX YELLOW #CL1655-92&CL710 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		265		145

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). DENSITY OF PART A IS 12.2 +/-0.3 LBS/GAL, DENSITY OF PART B IS 9.0 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 1 TO 1 BY VOLUME) IS 89 TO 120 KREB UNITS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND OF PART B), VISCOSITY (MIXED), GLOSS, VOC AND DRAWDOWN SAMPLES WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE". IN 2 PART KIT				
71-30-5085	PAINT KIT, FOR FLOORS, ANTI-SKID, TWO COMPONENT WATER BASED EPOXY AMINE TYPE, GRAY- FEDERAL COLOR STANDARD(595A) #16251, GLOSS. MUST CONTAIN APPROXIMATELY 4 LBS. OF ALUMINUM OXIDE ANTI-SKID GRIT (APPROXIMATELY 70 MESH SIZE). EACH KIT IS TO BE PACKAGED INDIVIDUALLY AND CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN AND ALUMINUM OXIDE GRIT IN A 1 GALLON CAN AND 1 GALLON OF PART B CATALYST IN A 1 GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). DENSITY OF PART A IS 13.4 +/-0.3 LBS/ GAL. DENSITY OF PART B IS 9.0 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 1 TO 1 BY VOLUME) IS 98 TO 120 KREB UNITS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY(OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC AND DRAWDOWN SAMPLES WITH EACH SHIPMENT.	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	FL-PLX B70AW1 SKD RES GRAY 162 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	394	15

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS:(1) "FOR INDUSTRIAL USE ONLY"(2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE". IN 2 PART KIT				
71-30-5110	ADDITIVE, ANTI-SLIP, FOR EPOXY BASED FLOOR COATINGS. PROVIDES TRACTION ENCHANCEMENT, ALUMINUM OXIDE BASED, PACKAGED AS FIVE POUNDS IN A ONE-QUART CAN. COVERAGE IS 100 SQUARE FOOT PER POUND. [SAFETY COMMENTS: WEAR SAFETY GLASSES & NITRILE GLOVES. EXERCISE CAUTION WHEN POURING TO MINIMIZE DUST EXPOSURE]	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GRIT 240 #32601 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-30-5200	COATING, FOR FLOORS, TWO COMPONENT EPOXY, ADMIRAL BLUE, GLOSS, HIGH SOLIDS (91%). EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONRY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). ASTM TEST METHOD D1475 DENSITY OF PART A IS 11.95 +/-0.5 LBS/GAL @ 70F, DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @ 70F WHEN TESTED USING A WEIGHT-PER GALLON CUP. IN ACCORDANCE WITH METHOD A, PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A & PART B (MIXED 2:1 BY VOLUME) IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523, SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS)>70 @ 60 DEGREES. IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS(AT 20 MILS WET)@ 70F. POT LIFE(150 GRAMS MIXED)= 45-190 MINUTES @	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GUARD 80117 ADMIRAL BLUE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
	70F. COLOR TRISTIMULUS VALUES(L*36.15, A* -5.91, B* -3.07, DELTA E <6). VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY (PART A & PART B), GLOSS, DRY TIME. PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO ITS SPEC'S AND SUBMIT GLOSS, VISCOSITY, DENSITY AND COLOR TEST RESULTS TO NYCT INSPECTION & TESTING FOR ABOVE CITED ASTM TEST METHODS USING AN INDEPENDENT ACCREDITED LAB CERTIFIED TO ISO 17025 FOR EACH BATCH PRODUCED.						
71-30-5202	COATING, FOR FLOORS, TWO COMPONENT EPOXY, TILE RED, GLOSS, HIGH SOLIDS(93%). EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONRY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). ASTM TEST METHOD D1475 DENSITY OF PART A IS 12.50 +/-0.5 LBS/GAL @ 70F. DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @ 70F WHEN TESTED USING A WEIGHT-PER-GALLON CUP. IN ACCORDANCE WITH METHOD A, PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A & PART B (MIXED 2:1 BY VOLUME) IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523, SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS)> 70 @ 60 DEGREES. IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS (AT 20 MILS WET) @ 70F. POT LIFE (150 GRAMS MIXED) = 45-190 MINUTES @ 70F. COLOR TRISTIMULUS VALUES (L*21.90, A* 32.81, B*26.09, DELTA E <6). VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY (PART A & PART B). GLOSS, DRY TIME, PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO ITS	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GUARD 80117 TILE RED CCSS 001, REV I, 3-9-11, LABEL CCSS 002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0		0	

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-30-5206	COATING, FOR FLOORS, TWO COMPONENT EPOXY, CHARCOAL GRAY, GLOSS, HIGH SOLIDS(93%). EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONRY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). ASTM TEST METHD D1475 DENSITY OF PART A IS 12.20 +/-0.5 LBS/GAL @ 70G, DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @ 70F WHEN TESTED USING A WEIGHT-PER GALLON CUP. IN ACCORDANCE WITH METHOD A, PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A & PART B (MIXED 2:1 BY VOLUME) IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523 SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS)> 70 @ 60 DEGREES IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS (AT 20 MILS WET) @ 70F. POT LIFE(150 GRAMS MIXED)= 45-190 MINUTES @ 70F. COLOR TRISTIMULUS VALUES (L*33.91, A*0.45, B*0.41, DELTA E <6). VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY (PART A & PART B), GLOSS, DRY TIME PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO ITS SPEC'S AND SUBMIT GLOSS, VISCOSITY, DENSITY AND COLOR TEST RESULTS TO NYCT INSPECTION & TESTING FOR ABOVE CITED ASTM TEST METHODS USING AN INDEPENDENT ACCREDITED LAB CERTIFIED TO ISO 17025 FOR EACH BATCH PRODUCED	NYCTA NYCTA NYCTA NPI FOR GARON	CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S GARON GUARD 80117 CHARCOAL GRA	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD	
-----	-----	-----	-----	-----	-----	-----	-----	
71-30-5208	COATING, FOR FLOORS, TWO COMPONENT EPOXY, DARK GRAY, GLOSS, HIGH SOLIDS (93%). EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONRY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L). ASTM TEST METHOD D1475 DENSITY OF PART A IS 12.20 +/-0.5 LBS/GAL @ 70F, DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @ 70F WHEN TESTED USING A WEIGHT-PER GALLON CUP. IN ACCORDANCE WITH METHOD A. PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A AND PART B (MIXED 2 TO 1 BY VOLUME) IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523, SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS) >70 @ 60 DEGREES. IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS (AT 20 MILS WET)@ 70F. POT LIFE (150 GRAMS MIXED)=45-190 MINUTES @70F. COLOR TRISTIMULUS VALUES (L*49.47,A*0.65,B*1.71 DELTA E<6). VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY(PART A & PART B). GLOSS DRY TIME. PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO ITS SPEC'S AND SUBMIT GLOSS, VISCOSITY, DENSITY AND COLOR TEST RESULTS TO NYCT INSPECTION AND TESTING FOR ABOVE CITED ASTM TEST METHODS USING AN INDEPENDENT ACCREDITED LAB CERTIFIED TO ISO 17025 FOR EACH BATCH PRODUCED	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GUARD 80117 DARK GRAY CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S				0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
71-30-5210	COATING, FOR FLOORS, TWO COMPONENT EPOXY, TRAFFIC YELLOW, GLOSS, HIGH SOLIDS (93%). EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PART A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONARY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). ASTM TEST METHOD D1475 DENSITY OF PART A IS 12.00 +/-0.5 LBS/GAL @ 70F, DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @70F WHEN TESTED USING A WEIGHT-PER GALLON CUP, IN ACCORDANCE WITH METHOD A, PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A & PART B (MIXED 2.1 BY VOLUME) IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523, SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS)>70 @ 60 DEGREES. IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS (AT 20 MILS WET) @ 70F. POT LIFE (150 GRAMS MIXED)=45-190 MINUTES @ 70F. COLOR TRISTIMULUS VALUES(L*72.15,A* 23.92, B*76.43, DELTA E<6.)VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY(PART A & PART B). GLOSS, DRY TIME. PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO IT'S SPECS AND SUBMIT GLOSS, VISCOSITY, DENSITY AND COLOR TEST RESULTS TO NYCT INSPECTION & TESTING FOR ABOVE CITED ASTM TEST METHODS USING AN INDEPENDENT ACCREDITED LAB CERTIFIED TO ISO 17025 FOR EACH BATCH PRODUCED.	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GUARD 80117 TRAFFIC YELL CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		0		0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-30-5212	COATING, FOR FLOORS, TWO COMPONENT EPOXY, WHITE, GLOSS, HIGH SOLIDS (93%), EACH KIT CONSISTS OF TWO PARTS: 1 GALLON OF PAR A RESIN IN A 1 GALLON CAN & 1/2 GALLON OF PART B CATALYST IN A 1/2 GALLON CAN. PROTECTIVE COATING FOR CONCRETE & MASONRY. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL(340 G/L). ASTM TEST METHOD D1475 DENSITY OF PART A IS 12.50 +/-0.5 LBS/GAL @ 70F, DENSITY OF PART B IS 8.31 +/-0.5 LBS/GAL @ 70F WHEN TESTED USING A WEIGHT-PER GALLON CUP. IN ACCORDANCE WITH METHOD A, PROCEDURE A OF ASTM TEST METHOD D562 VISCOSITY OF PART A & PART B (MIXED 2:1 BY VOLUME)IS 60-80 KU @ 70F TESTED WITHIN 3 MINUTES AFTER MIXING. IN ACCORDANCE WITH ASTM D523 SECTION 8.1, USING PRACTICE E PER ASTM TEST METHOD 823 SPECULAR GLOSS (AT 20 MILS WET AFTER 24 HOURS)>70 @ 60 DEGREES. IN ACCORDANCE WITH ASTM D1640 DRY TO TOUCH IS 6-10 HOURS (AT 20 MILS WET) @ 70F. POT LIFE(150 GRAMS MIXED)= 45-190 MINUTES @ 70F. COLOR TRISTIMULUS VALUES (L*94.77, A*-0.83, B* 2.88, DELTA E <6). VENDOR TO SUPPLY C OF A FOR EACH BATCH SHOWING THE VISCOSITY (PART A & PART B), GLOSS, DRY TIME. PRIOR TO VENDOR'S REQUEST FOR INSPECTION TO NYCT INSPECTION & TESTING VENDOR MUST SHOW CONFORMANCE TO ITS SPEC'S AND SUBMIT GLOSS, VISCOSITY, DENSITY AND COLOR TEST RESULTS TO NYCT INSPECTION & TESTING FOR ABOVE CITED ASTM TEST METHODS USING AN INDEPENDENT ACCREDITED LAB CERTIFIED TO ISO 17025 FOR EACH BATCH PRODUCED	NPI FOR GARON NYCTA NYCTA NYCTA	GARON GUARD 80117 WHITE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-31-0900	PAINT, TRAFFIC YELLOW, SIGNALOCK WATERBORNE IN ONE QUART CAN. THE PAINT MUST CONFORM TO THE FOLLOWING: WEIGHT PERCENT SOLID 50% MIN; WEIGHT PER GALLON - 10.00 LBS/GAL. MIN; VOC- 340 GMS/LTR MAX. GRIND - 4 HEGMAN UNITS MIN. VISCOSITY - 70 KU MIN. COLOR- L*83.77, A*8.04, B*66.42, DELTA E-2.00 MAX. GLOSS - 5 DEGREES - 15 DEGREES. CONTRAST RATIO-N/A. DRYING TIME TO TOUCH MAX HOURS-6 HOURS MAX. TO DRY HARD MAX HRS - 16 HRS. MAX. TO RECOAT MAX HRS - 24 HRS MAX IN 1 QT CAN	AMSTERDAM PAINT NYCTA NYCTA NYCTA	A1372 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	1428	1000
71-31-0915	PAINT, BLACK, ACRYLIC COPOLYMER, WATERBOURNE IN ONE GALLON CAN. THE PAINT MUST CONFORM TO THE FOLLOWING: WEIGHT PERCENT SOLIDS 50% MIN: VOC/1 HOUR @ 110 DEG. C INDUSTRIAL MAINTENANCE COATING, EXEMPT FROM NYS DEC PART 205 SINCE THIS PAINT IS APPLIED BY BRUSH. VISCOSITY 70 KU MIN; COLOR-VISUAL NO L.A.B. READING IS REQUIRED; GLOSS LESS THAN 10 DEG. @ 60 DEG. DRYING TIME: TO TOUCH 6 HR MAX; DRY HARD: 16 HRS MAX. TO RECOAT: 24 HOURS MAX IN 1 GAL CAN	MERCURY PAINT CORP/AMSTERDAM M NYCTA NYCTA NYCTA	HIGH DIELECTRIC 71-31-0915 BLK CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	60
71-31-1000	PAINT, EASYTHANE, #10 WHITE, CODE WA-3787 WHITE, COATED METAL PANEL PRODUCT REQUIREMENTS. GLOSS 54 DEG., +/-7 DEG., 60 DEG. GLOSS METER, WEIGHT PER GALLON: 10.50 LBS, +/-0.5 LBS., NON-VOLATILE BY WEIGHT: 48.00% +/-2.0%, NON-VOLATILE BY VOLUME: 34.00% +/-2.0% VISCOSITY: 35 SEC. #4 FORD CUP +/-5, VOC: 142 GRAMS/LITRE, THEORETICAL COVERAGE: 556 SQ FT PER GAL @ 1 MIL DRY, RECOMMENDED FILM THICKNESS: 0.7 - 1.5 MILS DRY, THINNER: WATER. 1 GALLON CAN	STERLING LACQUER NYCTA NYCTA NYCTA	WA-3787 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
71-31-1005	PAINT, EASYTHANE, BLUE #12, COATED METAL PANEL PRODUCT REQUIREMENTS. GLOSS 60 DEG. +/-7 DEG., 60 DEG. GLOSS METER, WEIGHT PER GALLON: 8.80 LBS., +/-0.5 LBS., NON-VOLATILE BY WEIGHT: 36.05% +/-3.0%, NON-VOLATILE BY VOLUME; 30.72% +/-2.0% VISCOSITY: 12 SEC., #3 ZAHN +/-5. VOC: <340 GRAMS/LTRE, THEORETICAL COVERAGE: 493 SQ FT PER GAL @ 1 MIL DRY. RECOMMENDED FILM THICKNESS: 0.7-1.5 MILS DRY, THINNER: WATER 1 GALLON CAN	STERLING LACQUER NYCTA NYCTA NYCTA	WA-3816 EASYTHANE #12 BLUE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		4		0
71-31-1010	PAINT, WHITE, FOR TOUCH-UP OF TRANSIT AUTHORITY BUS EXTERIOR COATINGS. 12 OUNCE NET WEIGHT IN A 16 OUNCE SPRAY CAN IN 16 OZ CAN	SEYMOUR OF SYCAMORE INC. NYCTA NYCTA NYCTA	NT-1010 WHITE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		1694		624
71-31-1015	PAINT, BLUE, FOR TOUCH-UP OF TRANSIT AUTHORITY BUS EXTERIOR COATINGS. 12 OUNCE NET WEIGHT IN A 16 OUNCE SPRAY CAN IN 16 OZ CAN	SEYMOUR OF SYCAMORE INC. NYCTA NYCTA NYCTA	NT-1015 BLUE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		362		91
71-31-1020	PAINT, EASYTHANE, #20 CHARCOAL GRAY, CODE WA-3977, COATED METAL PANEL PRODUCT REQUIREMENTS, GLOSS 33 DEG. +/-7 DEG., 60 DEG, GLOSS METER, WEIGHT PER GALLON 8.80 LBS, +/-0.5 LBS, NON-VOLATILE BY WEIGHT; 37.00% +/-2.0%, NON-VOLATILE BY VOLUME; 31.00% +/-2.0% VISCOSITY; 55 KREBS UNITS +/-5. VOC; <340 GRAMS/LITRE, THEORETICAL COVERAGE; 507 SQ. FT PER GAL. @ 1 MIL DRY, RECOMMENDED FILM THICKNESS: 0.7 - 1.5 MIL DRY, THINNER; WATER, 1 GALLON CAN IN 1 GAL CAN	STERLING LACQUER NYCTA NYCTA NYCTA	WA-3977 EASYTHANE #20 CHAR GRY CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S		41		38

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD

71-32-1010	PRIMER, ONE-COMPONENT, ACRYLIC LOW VOC, OFF-WHITE, USED TO PRIME THE SURFACES OF SUBWAY CARS; MUST PROVIDE EXCELLENT HIDING AND CORROSION RESISTANCE WHEN APPLIED OVER STEEL, ALUMINUM AND FIBERGLASS, PACKAGED IN ONE-GALLON CAN. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATING WITH MAXIMUM VOC OF 3.5 LB/GAL(419.39 G/L). GLOSS AT 60 DEGREES IS 5-15; DENSITY IS 10-11 LBS/GAL; VISCOSITY IS 75-95 KU. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE VISCOSITY AND DENSITY WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE" IN 1 GAL CAN IN 1 GAL CAN	SHERWIN-WILLIAMS NYCTA NYCTA NYCTA	PRO-CRYL PRIMER B66W310 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0			20
71-32-1020	PRIMER, TWO COMPONENT WATER BASED EPOXY SEALER/PRIMER, 54% SOLIDS, CLEAR FOR COATING CONCRETE OR MASONRY. MIX ONE GALLON OF PART A RESIN WITH 1/2 GALLON OF PART B CATALYST. PACKAGED AS THREE GALLON KIT CONSISTING OF TWO 1-GALLON CANS OF PART A & TWO 1/2 GALLON CANS OF PART B. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340 G/L), DENSITY OF PART A IS 8.55 +/-0.3 LBS/GAL, DENSITY OF PART B IS 11.30 +/-0.3 LBS/GAL. VISCOSITY OF PART A & PART B (MIXED) IS 70-75 KREB UNITS @ 70F. SPECULAR GLOSS OF 30-40 DEGREES @ 60F. DRY TO TOUCH IS 4-8 HOURS @ 70F, POT LIFE IS 1 HOUR @ 70F. VENDOR TO SUPPLY CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A & OF PART B),	NPI FOR GARON NYCTA NYCTA NYCTA	GARON TIGERPRIME A&B #18603 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0			0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	VISCOSITY (MIXED A & B), GLOSS, DRY TIME. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING "WITH ONE OR MOR OF THE FOLLOWING STATEMENTS: (1)"FOR INDUSTRIAL USE ONLY" (2)"FOR PROFESSIONAL USE ONLY", (3)"NOT FOR RESIDENTIAL USE", OR (4)"NOT INTENDED FOR RESIDENTIAL USE". [SAFETY COMMENTS: WEAR CHEMICAL SPLASH GOGGLES & NEOPRENE GLOVES.]				
71-32-1030	PRIMER, TWO COMPONENT WHITE EPOXY PRIMER. EACH KIT IS TO BE PACKAGED INDIVIDUALLY. KIT CONSISTS OF TWO PARTS; 1 GALLON OF PART A RESIN AND 2 QUARTS OF PART B HARDENER. DENSITY OF PART A IS 12.27 +/-0.3 LBS/GAL, DENSITY OF PART B IS 8.1 +/-0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 2 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL (419.39 G/L)	PPG INDUSTRIES NYCTA NYCTA NYCTA	CRE-121 2.1 VOC WHITEEPOXYPRIM CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0
71-32-1032	PRIMER, TWO COMPONENT GRAY EPOXY PRIMER. EACH KIT IS TO BE PACKAGED INDIVIDUALLY. KIT CONSISTS OF TWO PARTS; 1 GALLON OF PART A RESIN AND 2 QUARTS OF PART B HARDENER. DENSITY OF PART A IS 12.02 +/- 0.3 LBS/GAL, DENSITY OF PART B IS 8.1 +/- 0.3 LBS/GAL. VISCOSITY OF PART A AND PART B (MIXED 2 TO 1 BY VOLUME) IS 10 TO 15 SECONDS AS MEASURED BY ZAHN #3 CUP. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE DENSITY (OF PART A AND PART B), VISCOSITY (MIXED), GLOSS, VOC WITH EACH SHIPMENT. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228	PPG INDUSTRIES NYCTA NYCTA NYCTA	CRE321 2.1 VOC GRAY EPOXY PRIM CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
71-32-2000	<p>SURFACE COATINGS: COATING LINES FOR MISCELLANEOUS METAL PARTS AND PRODUCTS EXTREME PERFORMANCE COATINGS WITH MAXIMUM VOC OF 3.5 LB/GAL(419.39 G/L)</p> <p>PAINT, TWO-COMPONENT, WHITE PRIMER, USED TO PRIME THE SURFACES OF SUBWAY CARS; MUST PROVIDE EXCELLENT HIDING AND CORROSION RESISTANCE WHEN APPLIED OVER STEEL, ALUMINUM AND FIBERGLASS, EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY, PAINT KIT CONSISTS OF TWO PARTS: 1 GALLON OF PRIMER AND 1 QUART OF HARDENER MIXED IN A 4:1 RATIO. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS METAL PARTS AND PRODUCTS EXTREME PERFORMANCE COATING WITH MAXIMUM VOC OF 2.1 LB/GAL (251.64 G/L). DENSITY IS 11-12 LBS/GAL; VISCOSITY EZ-ZAHN CUP #2 ACCEPTABLE RANGE = 23 TO 27 SECONDS VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE VISCOSITY AND DENSITY WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE",</p>	<p>PPG INDUSTRIES NYCTA NYCTA NYCTA</p>	<p>ESU481(PRIMER); ESU489(HARDENE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV 3 9/11/17 RESTR S</p>	0	0
71-32-2005	<p>PAINT, TWO-COMPONENT, GRAY PRIMER, USED TO PRIME THE SURFACES OF SUBWAY CARS; MUST PROVIDE EXCELLENT HIDING AND CORROSION RESISTANCE WHEN APPLIED OVER STEEL, ALUMINUM AND FIBERGLASS. EACH PAINT KIT IS TO BE PACKAGED INDIVIDUALLY. PAINT KIT CONSISTS OF TWO PARTS: 1 GALLON OF PRIMER AND 1 QUART OF HARDENER MIXED IN A 4:1 RATIO. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 228 SURFACE COATINGS: MISCELLANEOUS METAL PARTS AND PRODUCTS: EXTREME PERFORMANCE COATING WITH MAXIMUM VOC OF 2.1 LB/GAL (251.64 G/L).</p>	<p>PPG INDUSTRIES NYCTA NYCTA NYCTA</p>	<p>ESU480(PRIMER); ESU489(HARDENE CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	<p>DENSITY IS 11-12 LBS/GAL; SPRAY VISCOSITY #2 EZ-ZAHN 25 SECONDS. VENDOR TO SUPPLY MANUFACTURER'S CERTIFICATE OF ANALYSIS FOR EACH BATCH SHOWING THE VISCOSITY AND DENSITY WITH EACH SHIPMENT. THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY", (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", (4) "NOT INTENDED FOR RESIDENTIAL USE"</p>				
71-32-3251	<p>PRIMER, WHITE PIGMENTED, WATER BASED STAIN KILLER IN ONE GALLON CAN. FOR USE AS AN INTERIOR BONDING PRIMER. COLOR: NYCT WHITE PRIMER, STAINKILLER. MUST HAVE FLASH POINT 100 DEGREES F MINIMUM, VISCOSITY 85 KU; MUST HAVE DRYING TIME TO RE-COAT 2 HOURS MINIMUM AND COVERAGE UP TO 500 SQ. FT/GAL @ 1MIL. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 ARCHITECTURAL & INDUSTRIAL MAINTENANCE COATINGS: SPECIALTY PRIMERS, SEALERS AND UNDERCOATERS WITH MAXIMUM VOC OF 2.92 LB/GAL (350 G/L). THE CONTAINERS MUST BE LABELED WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR BLOCKING STAINS:", (2) "FOR FIRE DAMAGED SUBSTRATES", (3) "FOR SMOKE DAMAGED SUBSTRATES", (4) "FOR WATER DAMAGED SUBSTRATES", OR (5) "FOR EXCESSIVELY CHALKY SUBSTRATES". IN 1 GAL CAN</p>	<p>MERCURY PAINT CO. NYCTA NYCTA NYCTA</p>	<p>AQUAZOOM ACRYL STAINKILLER WHI CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	0	0
71-33-7400	<p>PRIMER, PAINT, OIL BASED, RED/BROWN PIGMENT. USED AS RUST INHIBITING PRIMER ON METAL STRUCTURAL SURFACES; PACKED IN ONE GALLON CAN. SOLIDS CONTENT -73-77% WEIGHT, VISCOSITY 80-90 KU; DRY TO TOUCH TIME 2-4 HOURS, TACK FREE DRY TIME 4-6 HURS. USED BOTH AS AN INDUSTRIAL MAINTENANCE COATING AND AS A RUST PREVENTIVE COATING (NYDEC REGULATION 6NYCRR PART 205). IT MUST</p>	<p>SHERWIN WILLIAMS NYCTA/MABSTOA NYCTA NYCTA</p>	<p>E41 N1 KROMIK METAL PRIMER CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R.PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	<p>COMPLY WITH THE MORE RESTRICTIVE VOC LIMIT FOR 6NYCRR PART 205 INDUSTRIAL MAINTENANCE COATINGS WITH MAXIMUM VOC OF 2.84 LB/GAL (340G/L). THE CONTAINERS MUST BE LABELED "INDUSTRIAL MAINTENANCE COATING" WITH ONE OR MORE OF THE FOLLOWING STATEMENTS: (1) "FOR INDUSTRIAL USE ONLY" (2) "FOR PROFESSIONAL USE ONLY", (3) "NOT FOR RESIDENTIAL USE", OR (4) "NOT INTENDED FOR RESIDENTIAL USE".</p> <p>1 GAL CAN</p>				
71-34-7300	<p>PRIMER, SEALER, RUDDY BROWN, SPRAY CAN 12 OZ/CAN 12 OZ/CAN</p>	<p>KRYLON NYCTA NYCTA NYCTA</p>	<p>RUST TOUGH RUDDY BROWN (RTA920 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	997	429
71-50-2999	<p>PAINT, LACQUER, CRYSTAL CLEAR, ACRYLIC, 16 OZ. SPRAY CANS, NET WT. 12 OZ. , MEETING COMMERCIAL ITEM DESCRIPTION A-A-1585 WITH EXCEPTIONS TO SOLID CONTENTS AND SPECULAR GLOSS. THE SOLID CONTENTS SHOULD BE MIN 20-25G AND THE SPECULAR GLOSS 85-90 DEGREES MIL-TT-L50 COLOR. [NOTE: FLASHPOINT REQUIREMENT OF NYCTA SPECIFICATION CCSS-002(GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE.] NOTE TO DCE USERS: APPROVED FOR USE ONLY AT DESIGNATED SPRAY ROOM AT 207 ST ELECTRIC COMPONENT SHOP IN 16 OZ CAN IN 16 OZ CAN</p>	<p>KRYLON FEDERAL SPECIFICATION NYCTA NYCTA NYCTA</p>	<p>CLRMSRW/CVMXTECACRCRYCLRGLS513 A-A-1585 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S</p>	135	120

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
71-63-0100	PRIMER AND RUST CONVERTER, WATER BASED ACRYLIC EMULSION; MUST CONTAIN MINIMUM OF 34 PERCENT OF RESIN SOLID BY WEIGHT; VISCOSITY=15-28 SECS. PACKAGED IN ONE GALLON CONTAINERS. MINIMUM SHELF LIFE AT TIME OF RECEIPT IS 9 MONTHS. MUST COMPLY WITH THE VOC LIMIT FOR NYSDEC REGULATION 6NYCRR PART 205 ARCHITECTURAL & INDUSTRIAL MAINTENANCE COATINGS: PRIMERS, SEALERS AND UNDERCOATERS WITH MAXIMUM VOC OF 1.67 LB/GAL (220 G/L). IN 1 GAL CTRS	PROTEK PAINT LTD NYCTA NYCTA NYCTA NYCTA	BLUE STEEL PRIMER 7137-FACIL-01 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	145		123	
71-65-0010	COATING, UNDERCOAT AND PRIMER; WATER BASED RUBBERIZED ACRYLIC COATING; FOR SEALING ROOFS, WALLS AND DECKS; ESPECIALLY FOR USE ON RAILCAR ROOFS; USED IN CONJUNCTION WITH MOBILE COAT MC5. THICK LIGHT GRAY; 34% SOLIDS BY VOLUME; SPECIFIC GRAVITY 1.12 TO 1.20; PH 8.5-9.9, NOMINAL WEIGHT APPROXIMATELY 9.37-9.97 LBS/GAL; FLEXIBLE AND DURABLE OVER A WIDE TEMPERATURE RANGE; BONDS EASILY TO MOST SURFACES. PACKAGED IN 5 GALLON PAIL. USED IN CONJUNCTION WITH #71-65-0012 COATING. MUST COMPLY WITH NYSDEC REGULATION 6NYCRR PART 205 ARCHITECTURAL & INDUSTRIAL MAINTENANCE COATINGS: WATERPROOFING SEALERS WITH MAXIMUM VOC OF 2.09 LB/GAL (250 G/L). IN 5 GAL PAIL	KST COATINGS MANUFACTURING INC NYCTA NYCTA NYCTA	ELASTO-SEAL KST 0000ES-20 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0		0	
71-65-0012	COATING, RUBBERIZED, MODIFIED ACRYLIC; PROTECTIVE; FOR WATERPROOFING, MAINTAINING AND REPAIRING RAILCAR ROOFS; CREAMY WHITE LIQUID; 32% SOLIDS BY VOLUME; 25% RESIN BY WEIGHT, 28% PIGMENT BY WEIGHT; SPECIFIC GRAVITY 1.21 TO 1.28; PH 8.5 TO 9.9; NOMINAL WEIGHT APPROXIMATELY 10.08-10.68 LBS/GAL; FLEXIBLE AND DURABLE OVER A WIDE TEMPERATURE RANGE; REFLECTS SUNS RAYS (85%); 5 GALLON PAIL USED IN CONJUNCTION WITH #71-65-0010	KST COATINGS MANUFACTURING INC NYCTA NYCTA NYCTA	MOBILE COAT KST0000MC-20 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 1/05 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0		0	

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO -----	LONG DESCRIPTION -----	MFG NAME -----	MFG PART NO -----	USE PY1 -----	USE YTD -----
	(ASTM D115 USING A COPPER SUBSTRATE AFTER 24 HOURS IMMERSION IN DISTILLED WATER) SHALL BE 1500 VPM(DRY) AND 350 VPM (WET). VISCOSITY (ASTM D2393 @ 25 DEG. C, BROOKFIELD) SHALL BE 175-350 CPS. SOLIDS CONTENT (ASTM D1644) SHALL BE 38-52% BY WEIGHT. SHALL BE TACK FREE (ASTM D1640) WITHIN ONE HOUR. MINIMUM FLASH POINT (ASTM D93) OF 70 DEG. F. MAXIMUM VOC (ASTM D396) OF 4.9. SPECIFIC GRAVITY (ASTM D1963 @ 25 DEG. C) BETWEEN 0.91 AND 1.01. NOTE: FLASH POINT AND VOC REQUIREMENT OF NYCT SPECIFICATION CCSS-002 (GENERAL REQUIREMENTS FOR PAINTS) IS NOT APPLICABLE. SINCE THIS MATERIAL IS APPLIED BY BRUSH TO TRAIN PARTS IT IS EXEMPT FROM THE VOC REQUIREMENTS. SINCE THIS MATERIAL IS ONLY APPLIED BY BRUSH TO TRAIN PARTS IT IS EXEMPT FROM NYSDEC REGULATION 6NYCRR PART 205 ARCHITECTURAL & INDUSTRIAL MAINTENANCE COATINGS AND PART 228 SURFACE COATING PROCESSES. IN 1 GAL CANS				
71-86-3553	VARNISH, RESIN AND WATER BASED, CLEAR, HIGH GLOSS INSULATING, AIR DRYING; FOR USE AS A DIELECTRIC INSULATING COATING FOR RAILCAR SHOE BEAMS AND ELECTRICAL EQUIPMENT. PACKAGED IN BLACK PLASTIC QUART-SIZED CONTAINER. MUST HAVE EXCELLENT OIL AND MOISTURE RESISTANCE, AND HEAT RESISTANCE UP TO 125 DEG. C. MUST BE HOMOGENEOUS AND FREE OF SEDIMENT AND SUSPENDED MATTER. DIELECTRIC STRENGTH (ASTM D115 USING A COPPER SUBSTRATE AFTER 24 HOURS IMMERSION IN DISTILLED WATER) SHALL BE A MINIMUM OF 1500 VPM (DRY) AND 350 VPM (WET). VISCOSITY (ASTM D2393 @ 25 DEG. C, STORMER) SHALL BE 72-78 KU. SOLIDS CONTENT (ASTM D1644) SHALL BE 27% BY WEIGHT MINIMUM. SHALL BE TACK FREE (ASTM D1640) WITHIN THREE HOUR. MINIMUM FLASH POINT (ASTM D93) OF 70 DEG. F. SPECIFIC GRAVITY (ASTM D1963) @ 25 DEG C BETWEEN 1.00 AND 1.10. MUST COMPLY	GLYPTAL NYCTA NYCTA NYCTA	1202E SPECIAL SAMPLE B HI GLOS CCSS-001 REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	733	518

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD

	WITH NYSDEC REGULATION 6 NYCRR PART 205 ARCHITECHTURAL & INDUSTRIAL MAINTENANCE COATINGS AND PART 228 SURFACE COATING PROCESS.				
71-86-3995	VARNISH, RED AEROSOL DIELECTRIC INSULATING; POLYURETHANE BASED; MUST HAVE DIELECTRIC STRENGTHS AS MEASURED BY ASTM D115 MINIMUM 1770 VOLTS/MIL (DRY) AND MINIMUM 1,140 VOLTS/MIL(WET); MUST DRY TO TOUCH WITHIN 60 MINUTES; PACKAGED IN A 20 FL. OZ. AEROSOL CAN; (NET WT IS 15.6 OZ.) MUST CONTAIN SUFFICIENT PROPELLANT SO THAT LARGE QUANTITIES OF VARNISH DO NOT REMAIN IN CAN AFTER ALL PROPELLANT IS EXPELLED; VARNISH MUST BE ABLE TO BE SPRAYED FREELY FROM CAN WITHOUT CLOGGING; FLASHPOINT REQUIREMENT OF NYCT SPEC CCSS-002 IS NOT APPLICABLE. CERTIFICATE OF ANALYSIS AND CERTIFICATE OF CONFORMANCE FOR EACH BATCH TO BE SUPPLIED TO NYCT MANAGER OF INSPECTIONS AND TESTING PRIOR TO SHIPPING MATERIAL. THE MANUFACTURER (J.C. DOLPH) WILL PROVIDE THE TECHNICAL DATA ON DRY AND WET DIELECTRIC STRENGTHS. IN 20 OZ CANS	JOHN C. DOLPH NYCTA NYCTA NYCTA ASTM NYCTA	ER-44 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S D115 PALLET SPEC.	358	176
71-86-3998	VARNISH, ALKYD, RESIN AND SOLVENT BASED, RED, INSULATING, AIR DRYING; FOR USE AS A DIELECTRIC INSULATING COATING FOR RAIL CAR ELECTRICAL EQUIPMENT. PACKAGED IN 1-QUART CANS. MUST BE FAST DRYING, HAVE EXCELLENT OIL, MOISTURE AND ACID RESISTANCE AND HEAT RESISTANCE UP TO 145 DEG. C. MUST BE HOMOGENEOUS, CLEAR AND FREE OF SEDIMENT, MOISTURE AND SUSPENDED MATTER. DIELECTRIC STRENGTH(ASTM D115 USING A COPPER SUBSTRATE AFTER 24 HOURS IMMERSION IN DISTILLED WATER)SHALL BE 1400-2900 VPM(DRY)AND 350-1400 VPM(WET). VISCOSITY(ASTM D3794@ 25 DEG. C. ZAHN CUP # 3)SHALL BE 35-55 SEC. SOLIDS	GLYPTAL NYCTA NYCTA NYCTA	1201 CCSS-001, REV I, 3-9-11, LABEL CCSS-002 9/21 G.R. PAINTS REV. CCSS-003 REV E 9/11/17 RESTR S	0	0

USER-ID : RJR
 PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
 COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 427
 CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
-----	-----	-----	-----	-----	-----	-----	-----
72-15-1128	TEST STRIP, EXTENDED LIFE COOLANT, USED TO CHECK INHIBITOR LEVEL OF EXTENDED LIFE COOLANT (70-07-2015, 70-07-2022 OR 70-07-2023), MINIMUM SHELF LIFE REQUIRED AT TIME OF RECEIPT IS 24 MONTHS, 25 STRIPS PER BOTTLE	OLD WORLD INDUSTRIES	FXATK3		3		5
74-11-8000	BRAKE BLOCK, FRONT STANDARD, MATERIAL MUST CONFORM TO FMSI 4228 FD	NEW FLYER CO. ABEX	6305671 MC4228FD		2		0
74-11-8001	BRAKE BLOCK, FRONT, 1/16" OVERSIZE, MATERIAL MUST CONFORM TO FMSI 4228 FDX	ORION ABEX NYCTA	A0102507RB MC4228FDX PALLET SPEC		0		0
74-11-8500	BRAKE BLOCK, REAR STANDARD, MATERIAL MUST CONFORM TO FMSI 4592 AD	ORION ABEX NYCTA	A0202519PC MC4592AD PALLET SPEC.		0		0
74-11-8501	BRAKE BLOCK, REAR, 1/16" OVERSIZE, MATERIAL MUST CONFORM TO FMSI 4592 ADX	ORION ABEX	A0202519PD MC4592ADX		0		0
74-43-8002	BRAKE BLOCK, FRONT, STANDARD NON-SYMMETRICAL, FOR THIRD GENERATION DESIGN, MATERIAL MUST CONFORM TO FMSI 4690D	ABEX CORP.	MC4690D		0		0
74-43-8003	BRAKE BLOCK, FRONT, 1/16" OVERSIZE, NON-SYMMETRICAL, FOR THIRD GENERATION DESIGN, MATERIAL MUST CONFORM TO FMSI 4690DX	ABEX CORP	MC4690DX		0		0
74-43-8502	BRAKE BLOCK, REAR, STANDARD, NON-SYMMETRICAL, FOR THIRD GENERATION DESIGN, MATERIAL MUST CONFORM TO FMSI 4691D	ABEX CORP.	MC4691D		0		0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
80-83-0003	CAMSHAFT, RH	MCI MERITOR HEAVY VEHICLE SYSTEMS	2099860 2210-W-5535			0	0
80-83-0004	CAMSHAFT, LH	MCI MERITOR HEAVY VEHICLE SYSTEMS	15526041 2210-X-5536			0	0
80-87-0105	CAMSHAFT, FRONT, LEFT HAND ROTATION	MERITOR HEAVY VEHICLE SYSTEMS NEW FLYER CO. ORION	2210-Z-8398 6329815 F0102519AB			419	142
80-87-0106	CAMSHAFT, FRONT, RIGHT HAND ROTATION	MERITOR HEAVY VEHICLE SYSTEMS ORION	2210-Y-8397 F0102519AD			422	142
82-37-0028	PLATE, LOCK UP CLUTCH, INTERNAL SPLINED	ALLISON TRANSMISSION	23048511			0	0
82-37-0218	PLATE, SECOND CLUTCH, EXTERNAL TANGED	ALLISON TRANSMISSION	6834488			0	0
82-43-0159	KIT, POWER TAKE OFF, DRIVE, V731 AND V731RH TRANSMISSION.	ALLISON TRANSMISSION	29502597			0	0
84-55-0600	PEDAL ASSEMBLY, ACCELERATOR, ELECTRONIC	ORION WILLIAMS AIR CONTROL NEW FLYER CO. NOVA BUS INC.	051219526 403662 6367555 G1017868			1	2
85-11-1028	DRUM, REAR BRAKE, MATERIAL MUST BE GREY CAST IRON WHICH CONFORMS TO SAE J431 - GRADE G11H20B. NOTE: THE DRUMS ARE NOT TO BE STACKED NO MORE THAN 3 HIGH PER PALLET	WEBB WHEEL PRODUCTS NYCTA	64115J BRAKEDRUMS PALLET SPEC.			8	1

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE	PY1	USE	YTD
85-19-0014	CAMSHAFT, LH	MERITOR HEAVY VEHICLE SYSTEMS ORION	2210V8628 G0202509AB		420		130
85-19-0015	CAMSHAFT, RH	MERITOR HEAVY VEHICLE SYSTEMS ORION	2210U8627 G0202509AC		413		134
85-43-0089	HUB ASSEMBLY, REAR WHEEL	NOVA BUS INC. MERITOR HEAVY VEHICLE SYSTEMS	621170 HRSF00T9		0		0
85-61-0107	SPIDER ASSEMBLY, REAR BRAKE, RIGHT HAND	NOVA BUS INC. MERITOR HEAVY VEHICLE SYSTEMS TRUCK TRAILER	2041841 A-3211-H-3414 T-4143		0		0
85-65-0090	CAMSHAFT, BRAKE, LEFT HAND	MERITOR HEAVY VEHICLE SYSTEMS MCI	2210-Z-8294 T04-1126		1		0
85-65-0091	CAMSHAFT, BRAKE, RIGHT HAND	MERITOR HEAVY VEHICLE SYSTEMS MCI	2210-Y-8293 T04-1127		1		0
85-67-0059	CAMSHAFT, REAR STREET SIDE, NOVA S-CAM BRAKES	MERITOR HEAVY VEHICLE SYSTEMS NOVA BUS INC.	2210H8432 G1092180		0		0
85-67-0060	CAMSHAFT, REAR CURBSIDE, NOVA S-CAM BRAKES	MERITOR HEAVY VEHICLE SYSTEMS NOVA BUS INC.	2210G8431 G1092181		0		0
85-75-0014	DRUM, BRAKE, HEAVY DUTY, REAR AXLE. MATERIAL MUST BE GREY CAST IRON WHICH CONFORMS TO SAE J431-GRADE G11H20B. NOTE: THE DRUMS ARE NOT TO BE STACKED MORE THAN 3 HIGH PER PALLET	MCI WEBB NYCTA	15L-3-57 64125B BRAKEDRUMS PALLET SPEC.		36		4

USER-ID : RJR
 PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
 COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 432
 CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
85-75-0027	DRUM, BRAKE, HEAVY DUTY, TAG AXLE, MATERIAL MUST BE GREY CAST IRON WHICH CONFORMS TO SAE J431-GRADE G11H20B. NOTE: THE DRUMS ARE NOT TO BE STACKED MORE THAN 3 HIGH PER PALLET	MCI WEBB NYCTA	15L-3-44 65153B BRAKE DRUM PALLET	56	14
85-83-0004	CAMSHAFT, LH	MOHAWK MFG. SUPPLY MERITOR HEAVY VEHICLE SYSTEMS MUNCIE RECLAMATION	2032431 2210-Q-4905 MR3358	0	0
85-83-0005	CAMSHAFT, RIGHT HAND	MOHAWK MFG. SUPPLY MERITOR HEAVY VEHICLE SYSTEMS NEW FLYER CO.	2032432 2210-R-4906 5960314	0	0
85-87-0065	DRUM, BRAKE, REAR. MATERIAL MUST BE GREY CAST IRON WHICH CONFORMS TO SAE J431 - GRADE G11H20B. NOTE: THE DRUMS ARE NOT TO BE STACKED MORE THAN 3 HIGH PER PALLET.	WEBB NYCTA	64051J BRAKEDRUMS PALLET SPEC.	1011	392
86-43-0002	CHAMBER ASSEMBLY, FRONT WEDGE BRAKES	NOVA BUS INC. MERITOR HEAVY VEHICLE SYSTEMS TRUCK TRAILER NYCTA	2055505 M27-3276-L-12 T-0021A PALLET SPEC.	0	0
86-43-6700	BLADE ASSEMBLY, 26", WINDSHIELD WIPER, NOTE; WINDSHIELD WIPERS SHALL BE MADE IN ACCORDANCE TO SAE J 198 STANDARDS AND FMVSS 104; ELEMENT SHALL BE NATURAL OR SYNTHETIC RUBBER. ALL SUB COMPONENTS THAT MAKE UP WINDSHIELD WIPER FRAME SHALL BE CORROSION RESISTANT. ENTIRE BLADE SHALL BE PAINTED BLACK WITH SPECULAR GLOSS THAT COMPLIES WITH ASTM D-523. BLADE MUST BE SECURED WITH TWO RETAINING CLIPS THAT ARE CORROSION RESISTANT, ONE AT EACH END (OR EQUAL/IMPROVED DESIGN). FRAME RIVETS SHALL NOT AT ANY TIME, BREAK OR DISASSEMBLE DURING NORMAL WINDSHIELD WIPING OPERATIONS. A LEGIBLE MANUFACTURERS LOGO SHALL BE STAMPED/MARKED ON THE WINDSHIELD WIPER	MCI ANCO NEW FLYER CO. ORION SPRAGUE	3J-34-5 (REF ONLY) 52-27 8112552 (REF ONLY) C1201501AH (REF ONLY) S-1137-7	10687	8296

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
	FRAME FOR IDENTIFICATION. NECESSARY ADAPTERS AND MOUNTING INSTRUCTIONS SHALL BE FURNISHED WITH EACH BLADE. WIPER BLADE ELEMENT MUST NOT BE ABLE TO DETACH FROM ITS LOCKING CLIP/MECHANISM, OR SLIDE DOWN FROM EITHER END OF THE WIPER, UNLESS ITS ELEMENT IS DESIGNED TO DO SO AND REMAIN TOTALLY SECURED AT ALL TIMES				
88-07-8101	COMPUTER, ON BOARD-VEHICLE LOGIC UNIT, USED WITH THE DIGITAL INFORMATION SCREENS(DIS)	STRATEGIC MAPPING	OBU3210	0	0
88-07-8102	MONITOR, 24" LCD PANEL, USED FOR THE DIGITAL INFORMATION SCREENS (DIS) SYSTEM	STRATEGIC MAPPING	LCD24SP	0	0
88-07-8104	MONITOR, 37" WIDE SCREEN DISPLAY, USED FOR THE DIGITAL INFORMATION SCREENS (DIS) SYSTEM	STRATEGIC MAPPING	DE37SS	0	0
88-29-0963	MONITOR, PRIMARY, 24" DISPLAY KIT, ALL IN ONE - 24" LED BACKLIT LCD PANEL, MEDIA PLAYER, SSD ENCLOSURE CONFIGURATION AND ON BOARD SOFTWARE, DIGITAL INFORMATION SCREENS (DIS) SYSTEM	CLEVER DEVICES	141-300-0001	0	0
88-29-0964	MONITOR, SECONDARY, 24" DISPLAY, USED FOR THE DIGITAL INFORMATION SCREENS (DIS)SYSTEM	CLEVER DEVICES	3843	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
88-29-0966	MONITOR, PRIMARY, 37" DISPLAY KIT, ALL IN ONE - 37" LED BACKLIT LCD PANEL MEDIA PLAYER, SSD, ENCLOSURE CONFIGURATION AND ON BOARD SOFTWARE, DIGITAL INFORMATION SCREENS (DIS) SYSTEM	CLEVER DEVICES	141-300-0008	0	0
88-29-0967	MONITOR, SECONDARY, 37" DISPLAY, USED FOR THE DIGITAL INFORMATION SCREENS (DIS) SYSTEM	CLEVER DEVICES NEW FLYER CO.	4196 695062	0	0
88-33-0821	COMPUTER, INFOTAINMENT SERVER MS-700 INCL SW. USED WITH THE DIGITAL INFORMATION SCREENS (DIS)SYSTEM	VIANOVA TECHNOLOGIES	MS-700-NYCT-01	0	0
88-33-0822	MONITOR, 18.6" COLOR RAL 7035 DOUBLE DISPLAY MODULE, USED FOR THE DIGITAL INFORMATION SCREENS (DIS) SYSTEM	VIANOVA TECHNOLOGIES	IDM-18-D-AX-02	0	0
88-61-0610	ALTERNATOR REPAIR KIT	DELCO	10514967	36	21
91-43-4183	KIT, REAR DOOR CYLINDER	VAPOR CORP.	58220750	0	0
92-86-5493	KIT, ELEMENT, ORION SERIES 50 ENGINE, OIL SEPARATOR, CONSISTING OF 2 EACH, MINI COALESCENT ELEMENT AND 1 EACH, WATER FILTER ELEMENT	AIR & POWER TRANSMISSION	5094RK-KIT	44	27
92-88-8886	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM, CONTAINS: ONE INFOTAINMENT SERVER AND TWO 18.6" DOUBLE DISPLAY MODULES, COLOR RAL 7035	VIANOVA TECHNOLOGIES	VP-BUS-40-NYCT-01	0	0

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
92-88-8888	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM, CONTAINS: ONE 37" PRIMARY MONITOR AND ONE 37" SECONDARY MONITOR	CLEVER DEVICES	141-311-0003	0	0
92-88-8890	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM, CONTAINS: ONE INFOTAINMENT SERVER AND FOUR 18.5" SCREENS FOR PREVOST BUSES	VIANOVA TECHNOLOGIES	BUS-NY-COACH-01	0	0
92-88-8892	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM CONTAINS: ONE INFOTAINMENT SERVER AND FOUR 20" SCREENS FOR PREVOST BUSES	CLEVER DEVICES	100-311-0023	0	0
92-88-8893	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM, CONTAINS: ONE 37" PRIMARY DISPLAY, ONE 37" SECONDARY DISPLAY AND ONE 29" SECONDARY DISPLAY FOR NEW FLYER AND NOVA ARTICULATED BUSES	CLEVER DEVICES	100-311-0022	0	0
92-88-8896	KIT, DIGITAL INFORMATION SCREENS (DIS) SYSTEM, CONTAINS: ONE INFOTAINMENT SERVER, TWO 18.5" DOUBLE SCREENS AND ONE 28.6" (32:9 STRETCH) SCREEN FOR NEW FLYER AND NOVA ARTICULATED BUSES	VIANOVA TECHNOLOGIES	BUS-NY-ARTIC-02	0	0
97-24-5016	LIFT, PORTABLE, HYDRAULIC, WHEEL ENGAGING MOBILE BUS LIFT SYSTEM, 18,000 LBS MINIMUM. ALL PORTABLE BUS LIFTS SHALL BE QUALIFIED IN RELATIONSHIP TO THE TERMS AND CONDITIONS OF NYCT DEPARTMENT OF BUSES FACILITIES DEPARTMENT SPECIFICATION 11BC "PORTABLE BUS LIFT" DATED 7/8/2016	ROTARY LIFT CO. STERTIL KONI	MCH418D100 ST-1085 RSA NYT2	0	0

USER-ID : RJR
PROG-ID : JSBYRALL

NEW YORK CITY TRANSIT AUTHORITY
COMMODITY MANAGEMENT SYSTEM

DATE 08/25/2022 PAGE : 436
CURRENT VERSION : 1.10.00

QUALIFIED PRODUCTS LISTING

SURFACE TRANSIT PROCUREMENT SUBDIVISION UNIT (400) RPT

STOCK NO	LONG DESCRIPTION	MFG NAME	MFG PART NO	USE PY1	USE YTD
-----	-----	-----	-----	-----	-----

TOTAL PROCESSING TIME = 00 HRS, 04 MINS.

TOTAL RECORDS READ : 386,812

TOTAL RECORDS PRINTED : 18,127

**** FILES USED ****

MMS --> Y T D 86

MMS --> USAGE 85

CTF --> LONG DESCRIPTION

VXF --> MFG PART NO

MFG --> MFG NAME

ITEM --> U/M

PROGRAM LOCATED : IN ON